

MSDS

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 643

IDENTITY: GRAFFITI WIZARD +6/40

Revision Date: 01/25/2007

Section I

Manufacturer's Name: BLUE STAR MAINTENANCE SUPPLY A
Address: P.O. BOX 291

WENONAH
State: NJ Zip Code: 08090

Telephone Numbers:
Emergency:
800/255-3924
Information:
856/848-4236

HMS CODES: REACTIVITY: 0 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
DIMETHYL ADIPATE	627-93-0	NE	NE		
DIMETHYL GLUTARATE	1119-40-0	NE	NE		
DIMETHYL SUCCINATE	106-65-0	NA	NA		
N-METHYL PYRROLIDONE	872-50-4	NOT ESTAB	NOT ESTAB	10 MG/M3 100 PPM	

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	N/A	Specific Gravity (water=1)	1.08
Vapor Pressure(mm Hg)	N/A	Melting Point:	N/A
Vapor Density(AIR=1)	N/A	Evaporation Rate:	N/A
Solubility in water:	NEGLIG	(Butyl Acetate=1)	

Appearance and odor: PURPLE CLOTH IMPREGNATED WITH CLEAR LIQUID, MILD ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): >200 TCC Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL.
Special Fire Fighting Procedures: COOL EXPOSED CONTAINERS WITH WATER FOG.
FULL PROTECTIVE GEAR INCLUDING SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: NONE.

MSDS

Section V: REACTIVITY DATA

PRODUCT NUMBER: 643

Stability: Unstable: Conditions to avoid: EXCESS HEAT, OPEN FLAME.

Stable: X

Incompatibility (Materials to Avoid): OXIDIZERS, STRONG ACIDS, AND ALKALIS.

Hazardous Decomposition or Byproducts: OXIDES OF CARBON

Hazardous Polymerization: May Occur: Will Not Occur: X

Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards (Acute and Chronic):

INHALATION: IRRITATION TO UPPER RESPIRATORY TRACT. EYES: MILD IRRITATION AND REDNESS. SKIN: REDNESS, DRYNESS AND IRRITATION WITH REPEATED OR PROLONGED EXPOSURE. INGESTION: STOMACH IRRITATION, NAUSEA, CRAMPS, VOMITING.

Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: YES

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE VICTIM TO FRESH AIR
SKIN: WASH WITH SOAP AND WATER. SEE PHYSICIAN IF IRRITATION PERSISTS. EYES:
FLUSH WITH WATER FOR 15 MINUTES. SEE PHYSICIAN IF IRRITATION PERSISTS.
INGESTION: DO NOT INDUCE VOMITING. DRINK WATER. CONTACT PHYSICIAN IMMEDIATELY

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: SOAK UP SPILLED MATERIAL WITH INERT ABSORBENT MATERIAL AND PLACE IN PROPERLY LABELED CLOSED CONTAINER FOR DISPOSAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Precautions to be Taken in Handling and Storing: STORE IN A COOL, DRY PLACE KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

Other Precautions: AVOID PROLONGED OR REPEATED INHALATION OF MIST OR VAPOR AND CONTACT WITH SKIN. KEEP OUT OF REACH OF CHILDREN.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE WITH ADEQUATE VENTILATION.

Ventilation: Local Exhaust: RECOMMENDED

Mechanical: NOT REQUIRED Special: N/A

Other: N/A

Protective Gloves: CHEMICAL RESISTANT GLOVES RECOMMENDED.

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

N/A

Work/Hygienic Practices:

WASH HANDS AFTER USE.