

Window Replacement Specifications

Required materials:

- i) Storefront frames: U.S. Aluminum (or equivalent), IT 451 2" inch x 4.5" inch thermally broken framing, clear anodized aluminum, center glazed, break shapes 040 clear anodized aluminum.
- ii) Glass: 1" OA 1/4" inch solar ban tempered over 1/4" inch clear tempered glass.
- iii) Awning windows: U.S. Aluminum (or equivalent) 7400 series awning windows with 1" inch glass pocket/glazed with same glass as specified in line ii. above. Include removable stops, NO wet glazing.
- iv) Caulking: Dow Corning 795

Windows should be installed per the materials list above and Division #8 of the District Standards found at the link below.

<https://www.beaverton.k12.or.us/departments/facilities-development/technical-standards>

Room	# of windows	Width	Height	# of panes / sashes	awning window?	mullions?
Principles Office	3	36	69	2	one	yes
Wrk Rm #2	1	34	70	2	no	no
A100	6	48	112	4	one	yes
A102	6	48	112	4	one	yes
A104	6	48	112	4	one	yes
A106	6	48	112	4	one	yes
A108	6	48	112	4	one	yes
A116	7	44	112	4	one	yes
A118	7	44	112	4	one	yes
A120	7	44	112	4	one	yes
A122	7	44	112	4	one	yes
B108	2	36	69	2	one	yes
B110	2	36	69	2	one	yes