

Window Replacement Specifications

Required materials:

- i) Storefront frames: U.S. Aluminum (or equivalent), IT 451 2" inch x 4.5" inch thermally broken framing, clear anodized aluminum, center glazed, break shapes 040 clear anodized aluminum.
- ii) Glass: 1" OA 1/4" inch solar ban tempered over 1/4" inch clear tempered glass.
- iii) Awning windows: U.S. Aluminum (or equivalent) 7400 series awning windows with 1" inch glass pocket/glazed with same glass as specified in line ii. above. Include removable stops, NO wet glazing.
- iv) Caulking: Dow Corning 795

Windows should be installed per the materials list above and Division #8 of the District Standards found at the link below.

<https://www.beaverton.k12.or.us/departments/facilities-development/technical-standards>

Room	# of windows	Width (in.)	Height (in.)	# of panes	awning window?	mullions?
MAIN PROJECT						
Main Office	5	54	96	3	no	yes
Principles Office	3	52	96	3	yes	yes
Classroom 7	8	54	96	4	yes	yes
Classroom 8	5	48	96	4	yes	yes
Classroom 9	6	48	96	4	yes	yes
Classroom 10	6	48	96	4	yes	yes
Classroom 11	6	48	96	4	yes	yes
Classroom 12	6	48	96	4	yes	yes
Classroom 13	7	52	96	4	yes	yes
Classroom 13	1	23	28	1	no	no
ADD ALTERNATE						
Classroom 4	3	44	60	1	yes	no
	3	46	40	1	no	no
Classroom 5	3	60	60	1	yes	no
	3	44	54	1	no	no
	1	60	48	1	yes	no
Classroom 2	3	20	48	1	yes	no