

**SCHOOL DISTRICT NO. 25
Bannock County
Pocatello, Idaho**

Administration Offices
3115 Poleline Road
Pocatello, Idaho

ADDENDUM #1
Dated: March 12, 2015

**CARPET AND COVE BASE / INDOOR/OUTDOOR ENTRANCE TILE AND COVE
BASE
FOR VARIOUS DISTRICT BUILDINGS**

This Addendum forms a part of the Contract Documents and modifies the original Bidding Specifications, as noted on the next page. All other elements of the original bidding specifications remain intact.

Wilcox Elementary Media Center Only – Carpet will be Carpet/Tile.

Bid Opening:

**March 18, 2015
11:30 A.M.**

2. Carpeting / VCT/ Indoor/Outdoor Entrance tile must meet or exceed all the following minimum specifications. Shipment may consist of one or two color selection dye lot.

► **MATERIAL SPECIFICATIONS CARPET/CARPET TILE:**

Manufacturer/Style Name:

- Mannington Gametime 111 Integra HP
- Mohawk Nauvoov Life Lock Laminate
- Mannington Gametime 111 Carpet Tile with Standard Infinity Backing
- Mohawk Nauvoov Carpet Tile with Standard Infinity Backing

(The afore-mentioned carpets/carpet tile will be the only acceptable carpet/carpet tile to be bid for our projects, (no exceptions).

Traffic Class: Heavy Duty
Construction: Tufted
Fiber - Face Yarn: Cationic Type 6.6 Nylon, *(no exceptions)*
Dye Method: Solution or Majority Solution Dyed
Primary Backing: Polypropylene (Unibond®)
Secondary Backing: Thermoplastic (EPBL) or (Unibond Flex Block)
Min. Tuft Bind Test (lbs.): 20 lbs.
Yarn Weight (oz./sq. yds.): 26 ozs. per yd. minimum
Density (oz./Cu. Yd.): 6455 minimum
Gauge: 1/8
Width: 12'
Stitches per inch: 8.3 minimum
Finished Pile Thickness: .145 average
Electrostatic Propensity: less than 3.5 KV permanent conductive fiber
ASTM E 648 Flammability Standard: Class I
ASTM E 662 Smoke Chamber: less than 450
Warranty: Lifetime as specified in warranty section
Floor Patching Compound: Ardex Feather Finish

MATERIAL SPECIFICATIONS VCT TILE:

Manufacturer:	Mohawk or equal
Style Name:	Congoleum Commercial Floor Tile
Ramp areas:	Commercial VCT traction face surface.
Traffic Class:	Commercial VCT Tile
Construction:	Commercial VCT Tile
Size:	12" x 12" (305mmx305mm)
Gauge:	1/8" (3.2mm)
ASTM F 1066, Composition 1:	Class 2
Warranty:	Five (5) years as specified in warranty section