

**POCATELLO/CHUBBUCK
SCHOOL DISTRICT NO. 25
Bannock County, Idaho**

March 27, 2019

Addendum No. 2

RE: 2019 Suspended Ceiling
 School District No. 25
 Pocatello, Idaho 83201

FROM: Renaë Bentley
 Business Services
 3115 Pole Line Road
 Pocatello, Idaho 83201
 (208) 235-3220
 bentlere@sd25.us

This Addendum becomes a part of the Contract Documents and modifies the original Bidding Specifications, as noted below. **Acknowledge receipt of Addendums 1 and 2 on the original Bid Sheet.** Failure to do so may subject the Bidder to disqualification.

CLARIFICATION for the acoustical panel, manufacturer specifications attached.

Strike out and **replace** the following for the bid specification and bidding purposes.

2.3 MANUFACTURERS – ACCOUSTICAL UNITS

- A. ~~Armstrong, Word Industries, Inc.~~
- B. USG Interiors, Inc.

2.4 ACOUSTICAL UNIT MATERIALS

- A. ~~Acoustical Tile: Armstrong Armatuff~~
 Replace with: USG Radar Basic Acoustical Panel, Class A, Item No. 2310

No other changes are made to the original bidding specifications.

NO OTHER CHANGES

END OF ADDENDUM No.1 – 3/27/2019 rlb

USG RADAR™ BASIC ACOUSTICAL PANELS



USG Radar™ Basic Acoustical
Panels/USG Donn® Brand
DX®/DXL™ Acoustical
Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Nondirectional pattern with a fresh, clean appearance offers fast, efficient installation.
- Economical, all-purpose ceiling pattern offered in many sizes.
- Optional Firecode® product designed to meet life-safety codes.
- USDA Certified Biobased Product.⁸

APPLICATIONS

- Schools
- Corridors
- Offices
- Retail stores

SUBSTRATE

- Wet-formed mineral fiber

Lightly Textured Panel



USG RADAR™ BASIC ACOUSTICAL PANELS


ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818



UL Classified

Edge	Panel Size Imperial Metric (mm)	Fire Rating ²	Item No. Imperial Metric (mm)	NRC	CAC Min.	LR ³	Color ⁶	Grid Options	VOC Emissions	Recycled Content ¹	Panel Cost
SQ 	2'x2'x5/8" 600x600x15		2110 ME2110	0.55	33	0.83	White	A,B	Low	25%	\$
	2'x2'x5/8"		2115	0.55	35	0.83	White	A	Low	48-51%	\$
	2'x4'x5/8" 600x1200x15	Class A	2310 ME2310	0.55	35	0.83	White	A,B	Low	25%	\$
	2'x4'x5/8"		2315	0.55	35	0.83	White	A	Low	48-51%	\$
	2'x5'x5/8"	Class A	2619	0.55	35	0.83	White	A,B	Low	25%	\$
	20"x60"x5/8" 500x1500x15	Class A	2617 ME2617	0.55	35	0.83	White	A,B	Low	25%	\$
	30"x60"x3/4"	Class A	2618	0.60	35	0.83	White	A,B	Low	25%	\$
SLT 	2'x2'x5/8" 600x600x15	Class A	2120 ME2120	0.55	33	0.83	White	C	Low	25%	\$
	2'x2'x5/8"		2125	0.55	35	0.83	White	C	Low	51-59% ⁷	\$
	2'x4'x5/8"	Class A	2320	0.55	35	0.83	White	C	Low	25%	\$
	20"x60"x5/8"	Class A	2627	0.55	35	0.83	White	C	Low	25%	\$
FLB 	2'x2'x5/8"	Class A	2130	0.55	33	0.83	White	D,E,F,G	Low	25%	\$
BESK 	12"x12"x5/8"	Class A	2990	0.50 ⁵	40 ⁵	0.83	White	H	Low	44%	\$\$\$
SLT 	2'x4'x3/4"	Class A	2742	0.55	35	0.83	White	C	Low	25-26%	\$\$

USG RADAR™
BASIC PANEL

USG RADAR™ BASIC TILE^{4,5}

USG RADAR™ ILLUSION
BASIC TWO/24 PANEL

PATTERNS

Illusion™ Two/24



The look of 2'x2' panels

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.



GRID PROFILE OPTIONS

A USG DX*/DXL™	B USG DXW™	C USG DX*/DXL™	D USG Centricitee™ DXT™	E USG Fineline® DXF™	F USG Fineline® 1/8 DXFF™	G USG Identitee® DXI™	H USG DX*/DXL™ Concealed

PHYSICAL DATA/
FOOTNOTES

Product literature
Data sheet: SC2288

ASTM E1264 classification
Type III, Form 2, Pattern C, E
and C, E, K

ASTM E84 and CAN/ULC S102
surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

UL Type
FR-83

Weight
0.61-1.15 lb./sq. ft.

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance
R-1.4 (Class A, 5/8" panels and tile)
R-1.7 (Class A, 3/4" panels)
R-1.4 (Class A, 15 mm panels)
R-1.6 (Firecode®, 5/8" panels)

Maximum backloading
See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Metric sizes available
Contact sales for minimum quantities and lead times.

Notes

- For details, see LEED report tool at usgdesignstudio.com or cgcdesignstudio.com.
- Fire-rated items: see UL design details.
- LR values are shown as averages.
- Contact USG for adhesive recommendation for 12"x12" glue-up applications.
- Not UL Classified for acoustics.
- No Flat Black or 'Deeptones' are available on any reveal edge or USG Radar™ Firecode® panel.
- Recycled content not available at all plants.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2288/rev. 8-18
© 2018 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, FIRECODE, IDENTITEE, RADAR, IT'S YOUR WORLD, BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

