



Larson & Darby Group

Architecture Engineering Interiors

PROJECT MANUAL

ROOF ALTERATIONS

WEST MIDDLE SCHOOL

1900 N. ROCKTON AVE, ROCKFORD, IL 61103

ROCKFORD PUBLIC SCHOOLS 205

ROCKFORD, ILLINOIS

PROJECT MANUAL

FOR

ROOF ALTERATIONS – RPS PROJECT 2239
WEST MIDDLE SCHOOL
1900 N. ROCKTON AVE, ROCKFORD, IL 61103
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

RPS IFB 22-45

LDG PROJECT NO. 31029-03

DATE: April 21, 2022

LARSON & DARBY GROUP
4949 HARRISON AVENUE, SUITE 100
Illinois Design Firm Registration Number: 184-000280

ARCHITECTURE-ENGINEERING-INTERIORS
ROCKFORD, ILLINOIS 61108

Andrew Macklin
Licensed Architect
LIC. EXPIRES: 11/30/2022

Date

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

TABLE OF CONTENTS

PROCUREMENT AND CONTRACTING DOCUMENTS

DIVISION 00 - PROCUREMENT AND CONTRACTING REQUIREMENTS BY RPS

- Bid Offer Form – Roof Alterations
- 00 11 16 Bid Submission Instructions
- 00 73 00 Supplementary Conditions

SPECIFICATIONS

DIVISION 01 - GENERAL REQUIREMENTS

- 01 10 00 Summary
- 01 20 00 Price and Payment Procedures
- 01 22 00 Unit Prices
- 01 23 00 Alternates
- 01 30 00 Administrative Requirements
- 01 50 00 Temporary Facilities and Controls
- 01 60 00 Product Requirements
- 01 70 00 Execution and Closeout Requirements
- 01 78 23 Operation and Maintenance Data
- 01 78 39 Project Record Documents

DIVISION 02 - EXISTING CONDITIONS

- 02 41 19 Selective Demolition

DIVISION 06 - WOOD, PLASTICS, AND COMPOSITES

- 06 10 53 Miscellaneous Rough Carpentry
- 06 16 00 Sheathing

DIVISION 07 - THERMAL AND MOISTURE PROTECTION

- 07 01 50.19 Preparation For Reroofing
- 07 54 23 EPDM Roofing
- 07 62 00 Sheet Metal Flashing And Trim
- 07 72 00 Roof Accessories
- 07 84 13 Penetration Firestopping
- 07 92 00 Joint Sealants

DIVISION 08 - OPENINGS

- 08 63 00 Metal-framed Skylights
- 08 80 00 Glazing

END TABLE OF CONTENTS

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

DOCUMENT 007300 – SUPPLEMENTARY CONDITIONS

1. CHANGE ORDER MARK-UPS: Add the following to provisions regarding Change Order markups in the Conditions of the Contract:
 - A. The combined overhead and profit included in the total cost to the Owner for a change in the Work shall be based on the following schedule:
 - .1 For the Contractor, for Work performed by the Contractor's own forces, twelve percent (12%) of the cost.
 - .2 For the Contractor, for Work performed by the Contractor's Subcontractors, five percent (5%) of the amount due the Subcontractors.
 - .3 For each Subcontractor involved, for Work performed by that Subcontractor's own forces, twelve percent (12%) of the cost.
 - .4 For each Subcontractor involved, for Work performed by the Subcontractor's Subcontractors, five percent (5%) of the amount due the Sub-subcontractor.
 - .5 In order to facilitate checking of quotations for extras or credits, all proposals, except those so minor that their propriety can be seen by inspection, shall be accompanied by a complete itemization of costs including labor, materials and Subcontracts. Labor and materials shall be itemized in the manner prescribed above. Where major cost items are Subcontracts, they shall be itemized also.

END OF DOCUMENT 007300

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

SECTION 01 10 00 - SUMMARY

PART 1 - GENERAL

1.1 SUMMARY OF WORK

A. Projects:

- a Roof ALTERATIONS at West Middle School.

B. Owner: Rockford Public Schools District 205.

C. Work Under Other Contracts:

1. General: Cooperate fully with separate contractors so work on those contracts may be carried out smoothly, without interfering with or delaying work under this Contract or other contracts. Coordinate the Work of this Contract with work performed under separate contracts.

1.2 WORK RESTRICTIONS

A. Contractor's Use of Premises: During construction, Contractor will have limited use of site and building indicated.

1. Owner will occupy premises during construction. Perform construction during normal working hours (7 AM to 4 PM Monday thru Friday, other than holidays), unless otherwise agreed to in advance by Owner. Clean up work areas and return to a useable condition at the end of each work period.

PART 2 - PRODUCTS (Not Applicable)

PART 3 - EXECUTION (Not Applicable)

END OF SECTION 01 10 00

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

SECTION 01 20 00 - PRICE AND PAYMENT PROCEDURES

PART 1 - GENERAL

1.1 ALLOWANCES

- A. Allowances shall include cost to Contractor of specific products and materials ordered by Owner under allowance and shall include taxes, freight, and delivery to Project site. Allowances are specified in the Bid Form.
- B. Obtain three proposals for each allowance and submit to Architect with recommendations. Purchase products and systems selected by Owner.
- C. Advise Architect of the date when selection and purchase of each product or system described by an allowance must be completed to avoid delaying the Work.
- D. Submit invoices to show cost of products furnished under each allowance. Reconciliation of Allowance amounts with actual costs will be by Change Order.

1.2 ALTERNATES

- A. An alternate is an amount proposed by bidder for certain work that may be added to or deducted from the Base Bid amount if Owner accepts the Alternate. The cost or credit for each alternate is the net addition to or deduction from the Contract Sum to incorporate the Alternate into the Work. No other adjustments are made to the Contract Sum. B. Alternates are specified in the Bid Form.

1.3 UNIT PRICES

- A. A unit price is an amount proposed by bidders and stated on the Bid Form as a price per unit of measurement for work added to or deducted from the Contract Sum by appropriate modification, if estimated quantities of Work required by the Contract Documents are increased or decreased. Unit prices are specified in the Bid Form.
- B. Unit prices include all necessary material, plus cost for delivery, installation, insurance, overhead, and profit.

PART 2 - PRODUCTS (Not Applicable)

PART 3 - EXECUTION (Not Applicable)

END OF SECTION 01 20 00

ROOF ALTERATION
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

Copyright 2018 by The American Institute of Architects (AIA)

Exclusively published and distributed by Deltek, Inc. for the AIA

SECTION 01 22 00 - UNIT PRICES

Revise this Section by deleting and inserting text to meet Project-specific requirements.

Much of this Section consists of Project-specific data. Examples in the Evaluations were chosen to illustrate possible Section content. Use these sample paragraphs as models to develop text for specific Project requirements, or delete them if they do not apply. See the Evaluations.

Verify that Section titles referenced in this Section are correct for this Project's Specification; Section titles may have changed.

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes administrative and procedural requirements for unit prices.
- B. Related Requirements:

Retain subparagraph below to cross-reference requirements Contractor might expect to find in this Section but are specified in other Sections.

- 1. Section 01 21 00 "Allowances" for procedures for using unit prices to adjust quantity allowances.

1.2 DEFINITIONS

Retain terms below that remain after this Section has been edited for a project.

Definition in this article expands that contained in AIA Document A701 and revises the definition for the Contract.

- A. Unit price is an amount incorporated into the Agreement, applicable during the duration of the Work as a price per unit of measurement for materials, equipment, or services, or a portion of the Work, added to or deducted from the Contract Sum by appropriate modification, if the scope of Work or estimated quantities of Work required by the Contract Documents are increased or decreased.

1.3 PROCEDURES

Retain first paragraph below unless the Supplementary Conditions include similar requirements. EJCDC Document C-700 stipulates that unit prices include overhead and profit; AIA Document A201 does not.

- A. Unit prices include all necessary material, plus cost for delivery, installation, insurance, overhead, and profit.

Usually retain "Measurement and Payment" Paragraph below. It will suffice for all but the most complex projects. Revise below if many unit prices are anticipated and if methods for measuring work-in-place are

ROOF ALTERATION
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

complex. A special article or additional paragraphs outlining procedures for measurement and payment might be needed to define responsibilities for complex situations.

Usually first retain paragraph below with AIA Document A201. It protects Owner in case of dispute. Revise below if using EJCDC Document C-700. EJCDC Document C-700 gives Engineer authority to determine actual quantity of work. Revise to suit Owner's requirements.

- B. Owner reserves the right to reject Contractor's measurement of work-in-place that involves use of established unit prices and to have this work measured, at Owner's expense, by an independent surveyor acceptable to Contractor.

Retain "List of Unit Prices" Paragraph below and revise to suit Project.

- C. List of Unit Prices: A schedule of unit prices is included in Part 3. Specification Sections referenced in the schedule contain requirements for materials described under each unit price.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3.1 SCHEDULE OF UNIT PRICES

Copy and re-edit "Unit Price No. (Insert unit-price number) - (Insert unit-price item)" Paragraph below for each unit price required for Project. See samples of unit-price descriptions in the Evaluations.

- A. Unit Price No. 1: Removal and disposal of broken stone coping units and replacement with new stone coping units.
 - 1. Description: Reinforced EPDM roof flashing membrane fully installed over a 12" curb
 - 2. Unit of Measurement: Lineal foot

"Quantity Allowance" Subparagraph below addresses relationship to quantity allowance. Retain below if coordination is required with a corresponding quantity allowance. Revise to suit Project.

- B. Unit Price No. 2: installation of new aluminum skylight.
 - 1. Description: Labor and material for complete installation of new aluminum skylight over existing roof curb with new flashings and all associated trim per specification section 086300.
 - 2. Unit of Measurement: per skylight.
- C. Unit Price No. 3: Installation of roof hatch.
 - 1. Description: Labor and material to fully install new roof hatch with access ladder to floor below.
 - 2. Unit of Measure: per hatch.

"Quantity Allowance" Subparagraph below addresses relationship to quantity allowance. Retain below if coordination is required with a corresponding quantity allowance. Revise to suit Project.

END OF SECTION 01 22 00

ROOF REPLACEMENT & HVAC SYSTEM UPGRADES
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

SECTION 01 23 00 - ALTERNATES

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes administrative and procedural requirements for alternates.

1.2 DEFINITIONS

- A. Alternate: An amount proposed by bidders and stated on the Bid Form for certain work defined in the bidding requirements that may be added to or deducted from the base bid amount if the Owner decides to accept a corresponding change either in the amount of construction to be completed or in the products, materials, equipment, systems, or installation methods described in the Contract Documents.
 - 1. Alternates described in this Section are part of the Work only if enumerated in the Agreement.
 - 2. The cost or credit for each alternate is the net addition to or deduction from the Contract Sum to incorporate alternates into the Work. No other adjustments are made to the Contract Sum.

1.3 PROCEDURES

- A. Coordination: Revise or adjust affected adjacent work as necessary to completely integrate work of the alternate into Project.
 - 1. Include as part of each alternate, miscellaneous devices, accessory objects, and similar items incidental to or required for a complete installation whether or not indicated as part of alternate.
- B. Execute accepted alternates under the same conditions as other work of the Contract.
- C. Schedule: A schedule of alternates is included at the end of this Section. Specification Sections referenced in schedule contain requirements for materials necessary to achieve the work described under each alternate.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3.1 SCHEDULE OF ALTERNATES

NONE

END OF SECTION 01 23 00

SECTION 01 30 00 - ADMINISTRATIVE REQUIREMENTS

PART 1 - GENERAL

1.1 PROJECT MANAGEMENT AND COORDINATION

- A. Coordinate construction to ensure efficient and orderly installation of each part of the Work.
- B. Schedule and conduct progress meetings at Project site at regular intervals. Notify Owner and Architect of meeting dates and times. Require attendance of each subcontractor or other entity concerned with current progress or involved with planning or coordination of future activities.
 - 1. Record minutes and distribute to everyone concerned, including Owner and Architect.

1.2 SUBMITTAL PROCEDURES

- A. Coordinate each submittal with fabrication, purchasing, testing, delivery, other submittals, and related activities that require sequential activity.
 - 1. No extension of the Contract Time will be authorized because of failure to transmit submittals enough in advance of the Work to permit processing, including resubmittals.
 - 2. Prepare submittals as PDF packages and transmit to Architect by email.
 - 1 Email Address: DocumentAdmin@Larsondarby.com.
 - 2 Architect will annotate PDF submittal and return.
 - 3. Architect will return submittals, without review, received from sources other than Contractor.
- B. Place a permanent label or title block on each submittal for identification. Provide a space approximately 6 by 8 inches on label or beside title block to record Contractor's review and approval markings and action taken by Architect. Include the following information on the label:
 - 1. Project name.
 - 2. Date.
 - 3. Name and address of Contractor.
 - 4. Name and address of subcontractor or supplier.
 - 5. Number and title of appropriate Specification Section.
- C. Identify deviations from the Contract Documents on submittals.
- D. Contractor's Construction Schedule Submittal Procedure: Submit two copies of schedule within 10 working days after date established for Commencement of the Work.

PART 2 - PRODUCTS

2.1 ACTION SUBMITTALS

- A. Product Data: Mark each copy to show applicable products and options. Include the following:
 - 1. Manufacturer's written recommendations, product specifications, and installation instructions.
 - 2. Testing by recognized testing agency.
 - 3. Compliance with specified standards and requirements.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Shop Drawings: Prepare Project-specific information, drawn accurately to scale. Do not base Shop Drawings on reproductions of the Contract Documents or standard printed data. Submit on sheets at least 8-1/2 by 11 inches but no larger than 30 by 42 inches. Include the following:
 - 1. Dimensions and identification of products.
 - 2. Fabrication and installation drawings and roughing-in and setting diagrams.
- C. Samples: Submit Samples for review of kind, color, pattern, and texture and for a comparison of these characteristics between submittal and actual component as delivered and installed. Include name of manufacturer and product name on label.
 - 1. If variation is inherent in material or product, submit at least three sets of paired units that show variations.

2.2 INFORMATION SUBMITTALS

- A. Qualification Data: Include lists of completed projects with project names and addresses, names and addresses of architects and owners, and other information specified.
- B. Product Certificates: Prepare written statements on manufacturer's letterhead certifying that product complies with requirements in the Contract Documents.

2.3 DELEGATED DESIGN

- A. Performance and Design Criteria: Where professional design services or certifications by a design professional are specifically required of Contractor by the Contract Documents, provide products and systems complying with specific performance and design criteria indicated.
 - 1. If criteria indicated are not sufficient to perform services or certification required, submit a written request for additional information to Architect.
- B. Delegated-Design Submittal: In addition to Shop Drawings, Product Data, and other required submittals, submit three copies of a statement, signed and sealed by the responsible design professional, for each product and system specifically assigned to Contractor to be designed or certified by a design professional.
 - 1. Indicate that products and systems comply with performance and design criteria in the Contract Documents. Include list of codes, loads, and other factors used in performing these services.

2.4 CONTRACTOR'S CONSTRUCTION SCHEDULE

- A. Gantt-Chart Schedule: Submit a comprehensive, fully developed, horizontal Gantt-chart-type schedule within 10 days of date established for the Notice of Award.
- B. Preparation: Indicate each significant construction activity separately. Identify first workday of each week with a continuous vertical line.

PART 3 - EXECUTION

3.1 SUBMITTAL REVIEW

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- A. Review each submittal and check for coordination with other Work of the Contract and for compliance with the Contract Documents. Note corrections and field dimensions. Mark with approval stamp before submitting to Architect.
- B. Architect will review each action submittal, make marks to indicate corrections or modifications required, stamp and mark as appropriate to indicate action taken, and return.

3.2 CONTRACTOR'S CONSTRUCTION SCHEDULE

- A. Distribute copies of approved schedule to Owner, Architect, subcontractors, testing and inspecting agencies, and parties identified by Contractor with a need-to-know schedule responsibility. When revisions are made, distribute updated schedules to the same parties.
- B. Updating: At monthly intervals, update schedule to reflect actual construction progress and activities.
 - 1. As the Work progresses, indicate Actual Completion percentage for each activity.

END OF SECTION 01 30 00

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

SECTION 01 50 00 - TEMPORARY FACILITIES AND CONTROLS

PART 1 - GENERAL

1.1 SECTION REQUIREMENTS

- A. Use Charges: Cost or use charges for temporary facilities shall be included in the Contract Sum.
- B. Use water and electric power from Owner's existing system without metering and without payment of use charges.
- C. Electrical Service: Comply with NEMA, NECA, and UL standards and regulations for temporary electric service. Install service to comply with NFPA 70.

PART 2 - PRODUCTS (Not Applicable)

PART 3 - EXECUTION

3.1 TEMPORARY UTILITIES

- A. Sanitary Facilities: Contractor may use existing toilets when the building is not occupied by students.

3.2 TEMPORARY SUPPORT FACILITIES

- A. Provide waste-collection containers in sizes adequate to handle waste from construction operations. Collect waste daily and, when containers are full, legally dispose of waste off-site. Comply with requirements of authorities having jurisdiction.
- B. Install project identification and other signs in locations approved by Owner to inform the public and persons seeking entrance to Project.

3.3 TEMPORARY SECURITY AND PROTECTION FACILITIES

- A. Provide temporary environmental protection, operate temporary facilities, and conduct construction in ways and by methods that comply with environmental regulations and that minimize possible air, waterway, and subsoil contamination or pollution or other undesirable effects.
- B. Comply with requirements of authorities having jurisdiction for erecting structurally adequate barricades, including warning signs and lighting.

END OF SECTION 01 50 00

SECTION 01 60 00 - PRODUCT REQUIREMENTS

PART 1 - GENERAL

1.1 SECTION REQUIREMENTS

- A. The term "product" includes the terms "material," "equipment," "system," and terms of similar intent.
- B. Product Substitutions: Substitutions include changes in products, materials, equipment, and methods of construction from those required by the Contract Documents and proposed by Contractor after award of the Contract.
 - 1. Submit three copies of each request for product substitution.
 - 2. Submit requests within ten days after the Notice of Award.
 - 3. Do not submit unapproved substitutions on Shop Drawings or other submittals.
 - 4. Identify product to be replaced and show compliance with requirements for substitutions. Include a detailed comparison of significant qualities of proposed substitution with those of the Work specified, a list of changes needed to other parts of the Work required to accommodate proposed substitution, and any proposed changes in the Contract Sum or the Contract Time should the substitution be accepted.
 - 5. Architect will review the proposed substitution and notify Contractor of its acceptance or rejection.
- C. Comparable Product Requests:
 - 1. Submit three copies of each request for comparable product. Do not submit unapproved products on Shop Drawings or other submittals.
 - 2. Identify product to be replaced and show compliance with requirements for comparable product requests. Include a detailed comparison of significant qualities of proposed substitution with those of the Work specified.
 - 3. Architect will review the proposed product and notify Contractor of its acceptance or rejection.
- D. Deliver, store, and handle products using means and methods that will prevent damage, deterioration, and loss, including theft. Comply with manufacturer's written instructions.
 - 1. Schedule delivery to minimize long-term storage at Project site and to prevent overcrowding of construction spaces.
 - 2. Deliver products to Project site in manufacturer's original sealed container or packaging, complete with labels and instructions for handling, storing, unpacking, protecting, and installing.
 - 3. Inspect products on delivery to ensure compliance with the Contract Documents and to ensure that products are undamaged and properly protected.
 - 4. Store materials in a manner that will not endanger Project structure.
 - 5. Store products that are subject to damage by the elements, under cover in a weathertight enclosure above ground, with ventilation adequate to prevent condensation.
- E. Warranties specified in other Sections shall be in addition to, and run concurrent with, other warranties required by the Contract Documents. Manufacturer's disclaimers and limitations on product warranties do not relieve Contractor of obligations under requirements of the Contract Documents.

PART 2 - PRODUCTS

2.1 PRODUCT OPTIONS

- A. Provide products that comply with the Contract Documents, are undamaged, and are new at the time of installation.
 - 1. Provide products complete with accessories, trim, finish, and other devices and components needed for a complete installation and the intended use and effect.
 - 2. Descriptive, performance, and reference standard requirements in the Specifications establish "salient characteristics" of products.

- B. Product Selection Procedures:
 - 1. Where Specifications name a single product or manufacturer, provide the item indicated that complies with requirements, or Owner-approved equal.
 - 2. Where Specifications include a list of names of products or manufacturers, provide one of the items indicated that complies with requirements, or Owner-approved equal.
 - 3. Where Specifications include a list of names of products or manufacturers, accompanied by the term "available products" or "available manufacturers," provide one of the named items that complies with requirements, or Owner-approved equal. Comply with provisions for "comparable product requests" for consideration of an unnamed product.
 - 4. Where Specifications name a product as the "basis-of-design" and include a list of manufacturers, provide the named product, or Owner-approved equal. Comply with provisions for "comparable product requests" for consideration of an unnamed product by the other named manufacturers.
 - 5. Where Specifications name a single product as the "basis-of-design" and no other manufacturers are named, provide the named product or Owner-approved equal. Comply with provisions for "comparable product requests" for consideration of an unnamed product by another manufacturer.

- C. Unless otherwise indicated, Architect will select color, pattern, and texture of each product from manufacturer's full range of options that includes both standard and premium items.

PART 3 - EXECUTION (Not Applicable)

END OF SECTION 01 60 00

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

SECTION 01 70 00 - EXECUTION AND CLOSEOUT REQUIREMENTS

PART 1 - GENERAL

1.1 CLOSEOUT SUBMITTALS

- A. Record Drawings: Maintain a set of prints of the Contract Drawings as Record Drawings. Mark to show actual installation where installation varies from that shown originally.
 - 1. Identify and date each Record Drawing; include the designation "PROJECT RECORD DRAWING" in a prominent location.
- B. Operation and Maintenance Data: Submit one copy of manual. Organize data into three-ring binders with identification on front and spine of each binder, and envelopes for folded drawings. Include the following:
 - 1. Manufacturer's operation and maintenance documentation.
 - 2. Video on CD or flashdrive of training seminar for Owner use.
 - 3. Maintenance and service schedules.
 - 4. Maintenance service contracts.
 - 5. Emergency instructions.
 - 6. Spare parts list.
 - 7. Copies of warranties.

PART 2 - PRODUCTS (Not Applicable)

PART 3 - EXECUTION

3.1 EXAMINATION AND PREPARATION

- A. Examine substrates and conditions for compliance with manufacturer's written requirements including, but not limited to, surfaces that are sound, level, plumb, smooth, clean, and free of deleterious substances; substrates within installation tolerances; and application conditions within environmental limits. Proceed with installation only after unsatisfactory conditions have been corrected.
- B. Before proceeding to lay out the Work, verify layout information shown on Drawings.
- C. Take field measurements as required to fit the Work properly. Where fabricated products are to be fitted to other construction, verify dimensions by field measurement before fabrication and, when possible, allow for fitting and trimming during installation.

3.2 CUTTING AND PATCHING

- A. Cutting and Patching: Comply with requirements for and limitations on cutting and patching of construction elements.
 - 1. Structural Elements: When cutting and patching structural elements, notify Architect of locations and details of cutting and await directions from Architect before proceeding. Shore, brace, and support structural elements during cutting and patching. Do not cut and patch structural elements in a manner that could change their load-carrying capacity or increase deflection.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

2. Operational Elements: Do not cut and patch operating elements and related components in a manner that results in reducing their capacity to perform as intended or that results in increased maintenance or decreased operational life or safety.
 3. Other Construction Elements: Do not cut and patch other construction elements or components in a manner that could change their load-carrying capacity, that results in reducing their capacity to perform as intended, or that results in increased maintenance or decreased operational life or safety.
 4. Visual Elements: Do not cut and patch construction in a manner that results in visual evidence of cutting and patching. Do not cut and patch exposed construction in a manner that would, in Architect's opinion, reduce the building's aesthetic qualities. Remove and replace construction that has been cut and patched in a visually unsatisfactory manner.
- B. Cutting and Patching, General: Employ skilled workers to perform cutting and patching. Proceed with cutting and patching at the earliest feasible time, and complete without delay.
1. Cut in-place construction to provide for installation of other components or performance of other construction, and subsequently patch as required to restore surfaces to their original condition.
- C. Protection: Protect in-place construction during cutting and patching to prevent damage. Provide protection from adverse weather conditions for portions of Project that might be exposed during cutting and patching operations.
- D. Cutting: Cut in-place construction by sawing, drilling, breaking, chipping, grinding, and similar operations, using methods least likely to damage elements retained or adjoining construction. .
1. In general, use hand or small power tools designed for sawing and grinding, not hammering and chopping. Cut holes and slots neatly to minimum size required, and with minimum disturbance of adjacent surfaces. Temporarily cover openings when not in use.
 2. Finished Surfaces: Cut or drill from the exposed or finished side into concealed surfaces.
 3. Concrete and Masonry: Cut using a cutting machine, such as an abrasive saw or a diamond-core drill.
 4. Mechanical and Electrical Services: Cut off pipe or conduit in walls or partitions to be removed. Cap, valve, or plug and seal remaining portion of pipe or conduit to prevent entrance of moisture or other foreign matter after cutting.
 5. Proceed with patching after construction operations requiring cutting are complete.
- E. Patching: Patch construction by filling, repairing, refinishing, closing up, and similar operations following performance of other work. Patch with durable seams that are as invisible as practicable. Provide materials and comply with installation requirements specified in other Sections, where applicable.
1. Exposed Finishes: Restore exposed finishes of patched areas and extend finish restoration into retained adjoining construction in a manner that will minimize evidence of patching and refinishing.
 2. Floors and Walls: Where walls or partitions that are removed extend one finished area into another, patch and repair floor and wall surfaces in the new space. Provide an even surface of uniform finish, color, texture, and appearance. Remove in-place floor and wall coverings and replace with new materials, if necessary, to achieve uniform color and appearance.
 3. Ceilings: Patch, repair, or rehang in-place ceilings as necessary to provide an even-plane surface of uniform appearance.
 4. Exterior Building Enclosure: Patch components in a manner that restores enclosure to a weathertight condition and ensures thermal and moisture integrity of building enclosure.

3.3 INSTALLATION

- A. Instruct Owner's personnel in operation, adjustment, and maintenance of products, equipment,

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

and systems.

- B. Comply with manufacturer's written instructions for installation. Anchor each product securely in place, accurately located and aligned with other portions of the Work. Clean exposed surfaces and protect from damage.
- C. Clean Project site and work areas daily, including common areas.

3.4 FINAL CLEANING

- A. Complete the following cleaning operations before requesting inspection for certification of Substantial Completion:
 - 1. Remove labels that are not permanent.
 - 2. Clean exposed finishes to a dust-free condition, free of stains, films, and foreign substances. Sweep concrete floors broom clean.
 - 3. Vacuum clean floors in areas of Work.
 - 4. Wipe surfaces of mechanical and electrical equipment. Remove excess lubrication. Clean plumbing fixtures. Clean light fixtures, lamps, globes, and reflectors.
 - 5. Clean Project site, yard, and grounds, in areas disturbed by construction activities. Sweep paved areas; remove stains, spills, and foreign deposits. Rake grounds to a smooth, even-textured surface.

3.5 CLOSEOUT PROCEDURES

- A. Substantial Completion: Before requesting Substantial Completion inspection, complete the following:
 - 1. Prepare a list of items to be completed and corrected (punch list), the value of items on the list, and reasons why the Work is not complete.
 - 2. Advise Owner of pending insurance changeover requirements.
 - 3. Submit specific warranties, maintenance service agreements, and similar documents.
 - 4. Obtain and submit releases permitting Owner unrestricted use of the Work and access to services and utilities. Include occupancy permits, operating certificates, and similar releases.
 - 5. Submit Record Drawings and Specifications, operation and maintenance manuals, and Similar final record information.
 - 6. Deliver tools, spare parts, extra materials, and similar items.
 - 7. Complete final cleaning requirements.
 - 8. Touch up and otherwise repair and restore marred exposed finishes to eliminate visual defects.
- B. Submit a written request for inspection for Substantial Completion. On receipt of request, Architect will proceed with inspection or advise Contractor of unfulfilled requirements. Architect will prepare the Certificate of Substantial Completion after inspection or will advise Contractor of items that must be completed or corrected before certificate will be issued. C. Request inspection for Final Completion, once the following are complete:
 - 1. Submit a copy of Substantial Completion inspection list stating that each item has been completed or otherwise resolved for acceptance.
- C. Request re-inspection when the Work identified in previous inspections as incomplete is completed or corrected.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- D. Submit a written request for final inspection for acceptance. On receipt of request, Architect will proceed with inspection or advise Contractor of unfulfilled requirements. Architect will prepare final Certificate for Payment after inspection or will advise Contractor of items that must be completed or corrected before certificate will be issued.

3.6 DEMONSTRATION AND TRAINING

- A. Engage qualified instructors to instruct Owner's personnel to adjust, operate, and maintain systems, subsystems, and equipment not part of a system. Include a detailed review of the following:
 - 1. Include instruction for basis of system design and operational requirements, review of documentation, emergency procedures, operations, adjustments, troubleshooting, maintenance, and repairs.

END OF SECTION 01 70 00

SECTION 01 78 23 - OPERATION AND MAINTENANCE DATA

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes administrative and procedural requirements for preparing operation and maintenance manuals, including the following:
 - 1. Operation and maintenance documentation directory.
 - 2. Emergency manuals.
 - 3. Operation manuals for systems, subsystems, and equipment.
 - 4. Product maintenance manuals.

1.2 CLOSEOUT SUBMITTALS

- A. Manual Content: Operations and maintenance manual content is specified in individual Specification Sections to be reviewed at the time of Section submittals. Submit reviewed manual content formatted and organized as required by this Section.
 - 1. Where applicable, clarify and update reviewed manual content to correspond to revisions and field conditions.
- B. Format: Submit operations and maintenance manuals in the following format:
 - 1. PDF electronic file. Assemble each manual into a composite electronically indexed file. Submit on digital media acceptable to Owner.
 - a. Name each indexed document file in composite electronic index with applicable item name. Include a complete electronically linked operation and maintenance directory.
 - b. Enable inserted reviewer comments on draft submittals.
 - 2. Three paper copies. Include a complete operation and maintenance directory. Enclose title pages and directories in clear plastic sleeves. Owner will return two copies.
- C. Manual Submittal: Submit each manual in final form prior to requesting inspection for Substantial Completion and at least 15 days before commencing demonstration and training. Owner will return copy with comments.
 - 1. Correct or revise each manual to comply with Owner's comments. Submit copies of each corrected manual within 15 days of receipt of Owner's comments and prior to commencing demonstration and training.

PART 2 - PRODUCTS

2.1 REQUIREMENTS FOR EMERGENCY, OPERATION, AND MAINTENANCE MANUALS

- A. Directory: Prepare a single, comprehensive directory of emergency, operation, and maintenance data and materials, listing items and their location to facilitate ready access to desired information.
- B. Organization: Unless otherwise indicated, organize each manual into a separate section for each system and subsystem, and a separate section for each piece of equipment not part of a system. Each manual shall contain the following materials, in the order listed:
 - 1. Title page.
 - 2. Table of contents.
 - 3. Manual contents.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- C. Title Page: Include the following information:
1. Subject matter included in manual.
 2. Name and address of Project.
 3. Name and address of Owner.
 4. Date of submittal.
 5. Name and contact information for Contractor.
 6. Name and contact information for Architect.
 7. Names and contact information for major consultants to the Owner that designed the systems contained in the manuals.
 8. Cross-reference to related systems in other operation and maintenance manuals.
- D. Table of Contents: List each product included in manual, identified by product name, indexed to the content of the volume, and cross-referenced to Specification Section number in Project Manual.
- E. Manual Contents: Organize into sets of manageable size. Arrange contents alphabetically by system, subsystem, and equipment. If possible, assemble instructions for subsystems, equipment, and components of one system into a single binder.
- F. Manuals, Electronic Files: Submit manuals in the form of a multiple file composite electronic PDF file for each manual type required.
1. Electronic Files: Use electronic files prepared by manufacturer where available. Where scanning of paper documents is required, configure scanned file for minimum readable file size.
 2. File Names and Bookmarks: Enable bookmarking of individual documents based on file names. Name document files to correspond to system, subsystem, and equipment names used in manual directory and table of contents. Group documents for each system and subsystem into individual composite bookmarked files, then create composite manual, so that resulting bookmarks reflect the system, subsystem, and equipment names in a readily navigated file tree. Configure electronic manual to display bookmark panel on opening file.
- G. Manuals, Paper Copy: Submit manuals in the form of hard copy, bound and labeled volumes.
1. Binders: Heavy-duty, three-ring, vinyl-covered, loose-leaf binders, in thickness necessary to accommodate contents, sized to hold 8-1/2-by-11-inch paper; with clear plastic sleeve on spine to hold label describing contents and with pockets inside covers to hold folded oversize sheets.
 - a. Identify each binder on front and spine, with printed title "OPERATION AND MAINTENANCE MANUAL," Project title or name, and subject matter of contents. Indicate volume number for multiple-volume sets.
 2. Dividers: Heavy-paper dividers with plastic-covered tabs for each section of the manual. Mark each tab to indicate contents. Include typed list of products and major components of equipment included in the section on each divider, cross-referenced to Specification Section number and title of Project Manual.
 3. Protective Plastic Sleeves: Transparent plastic sleeves designed to enclose diagnostic software storage media for computerized electronic equipment.
 4. Drawings: Attach reinforced, punched binder tabs on drawings and bind with text.
 - a. If oversize drawings are necessary, fold drawings to same size as text pages and use as foldouts.
 - b. If drawings are too large to be used as foldouts, fold and place drawings in labeled envelopes and bind envelopes in rear of manual. At appropriate locations in manual, insert typewritten pages indicating drawing titles, descriptions of contents, and drawing locations.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

2.2 EMERGENCY MANUALS

- A. Content: Organize manual into a separate section for each of the following:
 - 1. Type of emergency.
 - 2. Emergency instructions.
 - 3. Emergency procedures.

- B. Type of Emergency: Where applicable for each type of emergency indicated below, include instructions and procedures for each system, subsystem, piece of equipment, and component:
 - 1. Fire.
 - 2. Flood.
 - 3. Gas leak.
 - 4. Water leak.
 - 5. Power failure.
 - 6. Water outage.
 - 7. System, subsystem, or equipment failure.
 - 8. Chemical release or spill.

- C. Emergency Instructions: Describe and explain warnings, trouble indications, error messages, and similar codes and signals. Include responsibilities of Owner's operating personnel for notification of Installer, supplier, and manufacturer to maintain warranties.

- D. Emergency Procedures: Include the following, as applicable:
 - 1. Instructions on stopping.
 - 2. Shutdown instructions for each type of emergency.
 - 3. Operating instructions for conditions outside normal operating limits.
 - 4. Required sequences for electric or electronic systems.
 - 5. Special operating instructions and procedures.

2.3 OPERATION MANUALS

- A. Content: In addition to requirements in this Section, include operation data required in individual Specification Sections and the following information:
 - 1. System, subsystem, and equipment descriptions. Use designations for systems and equipment indicated on Contract Documents.
 - 2. Performance and design criteria if Contractor is delegated design responsibility.
 - 3. Operating standards.
 - 4. Operating procedures.
 - 5. Operating logs.
 - 6. Wiring diagrams.
 - 7. Control diagrams.
 - 8. Piped system diagrams.
 - 9. Precautions against improper use.
 - 10. License requirements including inspection and renewal dates.

- B. Descriptions: Include the following:
 - 1. Product name and model number. Use designations for products indicated on Contract Documents.
 - 2. Manufacturer's name.
 - 3. Equipment identification with serial number of each component.
 - 4. Equipment function.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

5. Operating characteristics.
 6. Limiting conditions.
 7. Performance curves.
 8. Engineering data and tests.
 9. Complete nomenclature and number of replacement parts.
- C. Operating Procedures: Include the following, as applicable:
1. Startup procedures.
 2. Equipment or system break-in procedures.
 3. Routine and normal operating instructions.
 4. Regulation and control procedures.
 5. Instructions on stopping.
 6. Normal shutdown instructions.
 7. Seasonal and weekend operating instructions.
 8. Required sequences for electric or electronic systems.
 9. Special operating instructions and procedures.
- D. Systems and Equipment Controls: Describe the sequence of operation, and diagram controls as installed.
- E. Piped Systems: Diagram piping as installed, and identify color-coding where required for identification.

2.4 PRODUCT MAINTENANCE MANUALS

- A. Content: Organize manual into a separate section for each product, material, and finish. Include source information, product information, maintenance procedures, repair materials and sources, and warranties and bonds, as described below.
- B. Source Information: List each product included in manual, identified by product name and arranged to match manual's table of contents. For each product, list name, address, and telephone number of Installer or supplier and maintenance service agent, and cross-reference Specification Section number and title in Project Manual.
- C. Product Information: Include the following, as applicable:
1. Product name and model number.
 2. Manufacturer's name.
 3. Color, pattern, and texture.
 4. Material and chemical composition.
 5. Reordering information for specially manufactured products.
- D. Maintenance Procedures: Include manufacturer's written recommendations and the following:
1. Inspection procedures.
 2. Types of cleaning agents to be used and methods of cleaning.
 3. List of cleaning agents and methods of cleaning detrimental to product.
 4. Schedule for routine cleaning and maintenance.
 5. Repair instructions.
- E. Repair Materials and Sources: Include lists of materials and local sources of materials and related services.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- F. Warranties and Bonds: Include copies of warranties and bonds and lists of circumstances and conditions that would affect validity of warranties or bonds.

2.5 SYSTEMS AND EQUIPMENT MAINTENANCE MANUALS

- A. Content: For each system, subsystem, and piece of equipment not part of a system, include source information, manufacturers' maintenance documentation, maintenance procedures, maintenance and service schedules, spare parts list and source information, maintenance service contracts, and warranty and bond information, as described below.
- B. Source Information: List each system, subsystem, and piece of equipment included in manual, identified by product name and arranged to match manual's table of contents. For each product, list name, address, and telephone number of Installer or supplier and maintenance service agent, and cross-reference Specification Section number and title in Project Manual.
- C. Manufacturers' Maintenance Documentation: Manufacturers' maintenance documentation including the following information for each component part or piece of equipment:
 - 1. Standard maintenance instructions and bulletins.
 - 2. Drawings, diagrams, and instructions required for maintenance, including disassembly and component removal, replacement, and assembly.
 - 3. Identification and nomenclature of parts and components.
 - 4. List of items recommended to be stocked as spare parts.
- D. Maintenance Procedures: Include the following information and items that detail essential maintenance procedures:
 - 1. Test and inspection instructions.
 - 2. Troubleshooting guide.
 - 3. Precautions against improper maintenance.
 - 4. Disassembly; component removal, repair, and replacement; and reassembly instructions.
 - 5. Aligning, adjusting, and checking instructions.
 - 6. Demonstration and training video recording, if available.
- E. Maintenance and Service Schedules: Include service and lubrication requirements, list of required lubricants for equipment, and separate schedules for preventive and routine maintenance and service with standard time allotment. Spare Parts List and Source Information: Include lists of replacement and repair parts, with parts identified and cross-referenced to manufacturers' maintenance documentation and local sources of maintenance materials and related services.
- F. Maintenance Service Contracts: Include copies of maintenance agreements with name and telephone number of service agent.
- G. Warranties and Bonds: Include copies of warranties and bonds and lists of circumstances and conditions that would affect validity of warranties or bonds.

PART 3 - EXECUTION

3.1 MANUAL PREPARATION

- A. Emergency Manual: Assemble a complete set of emergency information indicating procedures for use by emergency personnel and by Owner's operating personnel for types of emergencies indicated.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Product Maintenance Manual: Assemble a complete set of maintenance data indicating care and maintenance of each product, material, and finish incorporated into the Work.
- C. Operation and Maintenance Manuals: Assemble a complete set of operation and maintenance data indicating operation and maintenance of each system, subsystem, and piece of equipment not part of a system.
- D. Manufacturers' Data: Where manuals contain manufacturers' standard printed data, include only sheets pertinent to product or component installed. Mark each sheet to identify each product or component incorporated into the Work. If data include more than one item in a tabular format, identify each item using appropriate references from the Contract Documents. Identify data applicable to the Work and delete references to information not applicable.
- E. Drawings: Prepare drawings supplementing manufacturers' printed data to illustrate the relationship of component parts of equipment and systems and to illustrate control sequence and flow diagrams. Coordinate these drawings with information contained in record Drawings to ensure correct illustration of completed installation.
 - 1. Do not use original project record documents as part of operation and maintenance manuals.

END OF SECTION 017823

SECTION 01 78 39 - PROJECT RECORD DOCUMENTS

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes administrative and procedural requirements for project record documents, including the following:
 - 1. Record Drawings.
 - 2. Record Specifications.
 - 3. Record Product Data.
- B. Related Requirements:
 - 1. Section 01 78 23 "Operation and Maintenance Data" for operation and maintenance manual requirements.

1.2 CLOSEOUT SUBMITTALS

- A. Record Drawings: Comply with the following:
 - 1. Number of Copies: Submit copies of record Drawings as follows:
 - a. Initial Submittal:
 - 1) Submit PDF electronic files of scanned record prints and one set(s) of file prints.
 - 2) Owner will indicate whether general scope of changes, additional information recorded, and quality of drafting are acceptable.
 - b. Final Submittal:
 - 1) Submit PDF electronic files of scanned record prints and one set(s) of prints.
 - 2) Print each drawing, whether or not changes and additional information were recorded.
- B. Record Specifications: Submit one paper copy and annotated PDF electronic files of Project's Specifications, including addenda and contract modifications.
- C. Record Product Data: Submit one paper copy and annotated PDF electronic files and directories of each submittal.

PART 2 - PRODUCTS

2.1 RECORD DRAWINGS

- A. Record Prints: Maintain one set of marked-up paper copies of the Contract Drawings and Shop Drawings, incorporating new and revised Drawings as modifications are issued.
 - 1. Preparation: Mark record prints to show the actual installation where installation varies from that shown originally. Require individual or entity who obtained record data, whether individual or entity is Installer, subcontractor, or similar entity, to provide information for preparation of corresponding marked-up record prints.
 - a. Give particular attention to information on concealed elements that would be difficult to identify or measure and record later.
 - b. Record data as soon as possible after obtaining it.
 - c. Record and check the markup before enclosing concealed installations.
 - 2. Mark the Contract Drawings and Shop Drawings completely and accurately. Use personnel proficient at recording graphic information in production of marked-up record prints.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

3. Mark record sets with erasable, red-colored pencil. Use other colors to distinguish between changes for different categories of the Work at same location.
 4. Note Construction Change Directive numbers, alternate numbers, Change Order numbers, and similar identification, where applicable.
- B. Record Digital Data Files: Immediately before inspection for Certificate of Substantial Completion, review marked-up record prints with Owner. When authorized, prepare a full set of corrected digital data files of the Contract Drawings, as follows:
1. Format: Annotated PDF electronic file with comment function enabled.
 2. Incorporate changes and additional information previously marked on record prints. Delete, redraw, and add details and notations where applicable.
 3. Refer instances of uncertainty to Owner for resolution.
- C. Format: Identify and date each record Drawing; include the designation "PROJECT RECORD DRAWING" in a prominent location.
1. Record Prints: Organize record prints and newly prepared record Drawings into manageable sets. Bind each set with durable paper cover sheets. Include identification on cover sheets.
 2. Format: Annotated PDF electronic file with comment function enabled.
 3. Record Digital Data Files: Organize digital data information into separate electronic files that correspond to each sheet of the Contract Drawings. Name each file with the sheet identification. Include identification in each digital data file.
 4. Identification: As follows:
 - a. Project name.
 - b. Date.
 - c. Designation "PROJECT RECORD DRAWINGS."
 - d. Name of Owner.
 - e. Name of Contractor.

2.2 RECORD SPECIFICATIONS

- A. Preparation: Mark Specifications to indicate the actual product installation where installation varies from that indicated in Specifications, addenda, and contract modifications.
1. Give particular attention to information on concealed products and installations that cannot be readily identified and recorded later.
 2. Mark copy with the proprietary name and model number of products, materials, and equipment furnished, including substitutions and product options selected.
 3. Record the name of manufacturer, supplier, Installer, and other information necessary to provide a record of selections made.
 4. Note related Change Orders, record Product Data, and record Drawings where applicable.
- B. Format: Submit record Specifications as annotated PDF electronic file.

2.3 RECORD PRODUCT DATA

- A. Preparation: Mark Product Data to indicate the actual product installation where installation varies substantially from that indicated in Product Data submittal.
1. Give particular attention to information on concealed products and installations that cannot be readily identified and recorded later.
 2. Include significant changes in the product delivered to Project site and changes in manufacturer's written instructions for installation.
 3. Note related Change Orders, record Specifications, and record Drawings where applicable.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Format: Submit record Product Data as annotated PDF electronic file.

2.4 MISCELLANEOUS RECORD SUBMITTALS

- A. Assemble miscellaneous records required by other Specification Sections for miscellaneous record keeping and submittal in connection with actual performance of the Work. Bind or file miscellaneous records and identify each, ready for continued use and reference.
- B. Format: Submit miscellaneous record submittals as PDF electronic file.

PART 3 - EXECUTION

3.1 RECORDING AND MAINTENANCE

- A. Recording: Maintain one copy of each submittal during the construction period for project record document purposes. Post changes and revisions to project record documents as they occur; do not wait until end of Project.
- B. Maintenance of Record Documents and Samples: Store record documents and Samples in the field office apart from the Contract Documents used for construction. Do not use project record documents for construction purposes. Maintain record documents in good order and in a clean, dry, legible condition, protected from deterioration and loss. Provide access to project record documents for Owner's reference during normal working hours.

END OF SECTION 01 78 39

SECTION 02 41 19 - SELECTIVE DEMOLITION

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Demolition and removal of selected portions of building or structure.
 - 2. Salvage of existing items to be reused or recycled.

1.2 DEFINITIONS

- A. Remove: Detach items from existing construction and dispose of them off-site unless indicated to be salvaged or reinstalled.
- B. Remove and Salvage: Detach items from existing construction, in a manner to prevent damage, and store where directed by Owner.
- C. Remove and Reinstall: Detach items from existing construction, in a manner to prevent damage, prepare for reuse, and reinstall where indicated.
- D. Existing to Remain: Leave existing items that are not to be removed and that are not otherwise indicated to be salvaged or reinstalled.
- E. Dismantle: To remove by disassembling or detaching an item from a surface, using gentle methods and equipment to prevent damage to the item and surfaces; disposing of items unless indicated to be salvaged or reinstalled.

1.3 MATERIALS OWNERSHIP

- A. Unless otherwise indicated, demolition waste becomes property of Contractor.
- B. Historic items, relics, antiques, and similar objects including, but not limited to, cornerstones and their contents, commemorative plaques and tablets, and other items of interest or value to Owner that may be uncovered during demolition remain the property of Owner.
 - 1. Carefully salvage in a manner to prevent damage and promptly return to Owner.

1.4 PREINSTALLATION MEETINGS

- A. Pre-demolition Conference: Conduct conference at Project site.
 - 1. Inspect and discuss condition of construction to be selectively demolished.
 - 2. Review structural load limitations of existing structure.
 - 3. Review and finalize selective demolition schedule and verify availability of materials, demolition personnel, equipment, and facilities needed to make progress and avoid delays.
 - 4. Review requirements of work performed by other trades that rely on substrates exposed by selective demolition operations.
 - 5. Review areas where existing construction is to remain and requires protection.

1.5 INFORMATIONAL SUBMITTALS

- A. Engineering Survey: Submit engineering survey of condition of building.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Proposed Protection Measures: Submit report, including Drawings, that indicates the measures proposed for protecting individuals and property, for dust control and, for noise control. Indicate proposed locations and construction of barriers.
- C. Schedule of Selective Demolition Activities: Indicate the following:
 - 1. Detailed sequence of selective demolition and removal work, with starting and ending dates for each activity. Ensure Owner's on-site operations are uninterrupted.
 - 2. Interruption of utility services. Indicate how long utility services will be interrupted.
 - 3. Coordination for shutoff, capping, and continuation of utility services.
 - 4. Use of elevator and stairs.
 - 5. Coordination of Owner's continuing occupancy of portions of existing building and of Owner's partial occupancy of completed Work.
- D. Pre-demolition Photographs or Video: Show existing conditions of adjoining construction, including finish surfaces, that might be misconstrued as damage caused by salvage and demolition operations.
- E. Warranties: Documentation indicating that existing warranties are still in effect after completion of selective demolition.

1.6 CLOSEOUT SUBMITTALS

- A. Inventory: Submit a list of items that have been removed and salvaged.

1.7 FIELD CONDITIONS

- A. Owner will occupy portions of building immediately adjacent to selective demolition area. Conduct selective demolition so Owner's operations will not be disrupted.
- B. Conditions existing at time of inspection for bidding purpose will be maintained by Owner as far as practical.
- C. Notify Architect of discrepancies between existing conditions and Drawings before proceeding with selective demolition.
- D. Hazardous Materials: Present in buildings and structures to be selectively demolished. A report on the presence of hazardous materials is on file for review and use. Examine report to become aware of locations where hazardous materials are present.
 - 1. Hazardous material remediation, if necessary, will be performed under separate contract by Owner.
 - 2. Do not disturb hazardous materials or items suspected of containing hazardous materials except under procedures specified elsewhere in the Contract Documents.
- E. Storage or sale of removed items or materials on-site is not permitted.
- F. Utility Service: Maintain existing utilities indicated to remain in service and protect them against damage during selective demolition operations.
 - 1. Maintain fire-protection facilities in service during selective demolition operations.

1.8 WARRANTY

- A. Existing Warranties: Remove, replace, patch, and repair materials and surfaces cut or damaged during selective demolition, by methods and with materials and using approved contractors so as not to void existing warranties.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Notify warrantor on completion of selective demolition, and obtain documentation verifying that existing system has been inspected and warranty remains in effect. Submit documentation at Project closeout.

1.9 COORDINATION

- A. Arrange selective demolition schedule so as not to interfere with Owner's operations.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Regulatory Requirements: Comply with governing EPA notification regulations before beginning selective demolition. Comply with hauling and disposal regulations of authorities having jurisdiction.
- B. Standards: Comply with ANSI/ASSP A10.6 and NFPA 241.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Verify that utilities have been disconnected and capped before starting selective demolition operations.
- B. Review Project Record Documents of existing construction or other existing condition and hazardous material information provided by Owner. Owner does not guarantee that existing conditions are same as those indicated in Project Record Documents.
- C. Perform an engineering survey of condition of building to determine whether removing any element might result in structural deficiency or unplanned collapse of any portion of structure or adjacent structures during selective building demolition operations.
 - 1. Perform surveys as the Work progresses to detect hazards resulting from selective demolition activities.
- D. Verify that hazardous materials have been remediated before proceeding with building demolition operations.
- E. Survey of Existing Conditions: Record existing conditions by use of measured drawings, preconstruction photographs, or video and templates.
 - 1. Inventory and record the condition of items to be removed and salvaged.
 - 2. Before selective demolition or removal of existing building elements that will be reproduced or duplicated in final Work, make permanent record of measurements, materials, and construction details required to make exact reproduction.

3.2 UTILITY SERVICES AND MECHANICAL/ELECTRICAL SYSTEMS

- A. Existing Services/Systems to Remain: Maintain services/systems indicated to remain and protect them against damage.
- B. Existing Services/Systems to Be Removed, Relocated, or Abandoned: Locate, identify, disconnect, and seal or cap off utility services and mechanical/electrical systems serving areas to be selectively demolished.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

1. Owner will arrange to shut off indicated services/systems when requested by Contractor.
2. If services/systems are required to be removed, relocated, or abandoned, provide temporary services/systems that bypass area of selective demolition and that maintain continuity of services/systems to other parts of building.
3. Disconnect, demolish, and remove fire-suppression systems, plumbing, and HVAC systems, equipment, and components indicated on Drawings to be removed.
 - a. Piping to Be Removed: Remove portion of piping indicated to be removed and cap or plug remaining piping with same or compatible piping material.
 - b. Piping to Be Abandoned in Place: Drain piping and cap or plug piping with same or compatible piping material and leave in place.
 - c. Equipment to Be Removed: Disconnect and cap services and remove equipment.
 - d. Equipment to Be Removed and Reinstalled: Disconnect and cap services and remove, clean, and store equipment; when appropriate, reinstall, reconnect, and make equipment operational.
 - e. Equipment to Be Removed and Salvaged: Disconnect and cap services and remove equipment and deliver to Owner.
 - f. Ducts to Be Removed: Remove portion of ducts indicated to be removed and plug remaining ducts with same or compatible ductwork material.
 - g. Ducts to Be Abandoned in Place: Cap or plug ducts with same or compatible ductwork material and leave in place.

3.3 PROTECTION

- A. Temporary Protection: Provide temporary barricades and other protection required to prevent injury to people and damage to adjacent buildings and facilities to remain.
 1. Provide protection to ensure safe passage of people around selective demolition area and to and from occupied portions of building.
 2. Provide temporary weather protection, during interval between selective demolition of existing construction on exterior surfaces and new construction, to prevent water leakage and damage to structure and interior areas.
 3. Protect walls, ceilings, floors, and other existing finish work that are to remain or that are exposed during selective demolition operations.
 4. Cover and protect furniture, furnishings, and equipment that have not been removed.
 5. Comply with requirements for temporary enclosures, dust control, heating, and cooling specified in Section 01 50 00 "Temporary Facilities and Controls."
- B. Temporary Shoring: Design, provide, and maintain shoring, bracing, and structural supports as required to preserve stability and prevent movement, settlement, or collapse of construction and finishes to remain, and to prevent unexpected or uncontrolled movement or collapse of construction being demolished.
 1. Strengthen or add new supports when required during progress of selective demolition.
- C. Remove temporary barricades and protections where hazards no longer exist.

3.4 SELECTIVE DEMOLITION, GENERAL

- A. General: Demolish and remove existing construction only to the extent required by new construction and as indicated. Use methods required to complete the Work within limitations of governing regulations and as follows:
 1. Proceed with selective demolition systematically, from higher to lower level. Complete selective demolition operations above each floor or tier before disturbing supporting members on the next lower level.
 2. Neatly cut openings and holes plumb, square, and true to dimensions required. Use cutting methods least likely to damage construction to remain or adjoining construction.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- Use hand tools or small power tools designed for sawing or grinding, not hammering and chopping. Temporarily cover openings to remain.
3. Cut or drill from the exposed or finished side into concealed surfaces to avoid marring existing finished surfaces.
 4. Do not use cutting torches until work area is cleared of flammable materials. At concealed spaces, such as duct and pipe interiors, verify condition and contents of hidden space before starting flame-cutting operations. Maintain portable fire-suppression devices during flame-cutting operations.
 5. Maintain fire watch during and after flame-cutting operations.
 6. Maintain adequate ventilation when using cutting torches.
 7. Remove decayed, vermin-infested, or otherwise dangerous or unsuitable materials and promptly dispose of off-site.
 8. Remove structural framing members and lower to ground by method suitable to avoid free fall and to prevent ground impact or dust generation.
 9. Locate selective demolition equipment and remove debris and materials so as not to impose excessive loads on supporting walls, floors, or framing.
 10. Dispose of demolished items and materials promptly.
- B. Site Access and Temporary Controls: Conduct selective demolition and debris-removal operations to ensure minimum interference with roads, streets, walks, walkways, and other adjacent occupied and used facilities.
- C. Removed and Salvaged Items:
1. Clean salvaged items.
 2. Pack or crate items after cleaning. Identify contents of containers.
 3. Store items in a secure area until delivery to Owner.
 4. Transport items to Owner's storage area designated by Owner.
 5. Protect items from damage during transport and storage.
- D. Removed and Reinstalled Items:
1. Clean and repair items to functional condition adequate for intended reuse.
 2. Pack or crate items after cleaning and repairing. Identify contents of containers.
 3. Protect items from damage during transport and storage.
 4. Reinstall items in locations indicated. Comply with installation requirements for new materials and equipment. Provide connections, supports, and miscellaneous materials necessary to make item functional for use indicated.
- E. Existing Items to Remain: Protect construction indicated to remain against damage and soiling during selective demolition. When permitted by Architect, items may be removed to a suitable, protected storage location during selective demolition[**and cleaned**] and reinstalled in their original locations after selective demolition operations are complete.
- 3.5 SELECTIVE DEMOLITION PROCEDURES FOR SPECIFIC MATERIALS
- A. Masonry: Demolish in small sections. Cut masonry at junctures with construction to remain, using power-driven saw, and then remove masonry between saw cuts.
- B. Roofing: Remove no more existing roofing than what can be covered in one day by new roofing and so that building interior remains watertight and weathertight. See Section 07 54 23 – TPO Roofing for new roofing requirements.
1. Remove existing roof membrane, flashings, copings, and roof accessories.
 2. Remove existing roofing system down to substrate.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

3.6 DISPOSAL OF DEMOLISHED MATERIALS

- A. Remove demolition waste materials from Project site and dispose of them in an EPA-approved construction and demolition waste landfill acceptable to authorities having jurisdiction.
 - 1. Do not allow demolished materials to accumulate on-site.
 - 2. Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
 - 3. Remove debris from elevated portions of building by chute, hoist, or other device that will convey debris to grade level in a controlled descent.
- B. Burning: Do not burn demolished materials.

3.7 CLEANING

- A. Clean adjacent structures and improvements of dust, dirt, and debris caused by selective demolition operations. Return adjacent areas to condition existing before selective demolition operations began.

END OF SECTION 02 41 19

SECTION 06 10 53 - MISCELLANEOUS ROUGH CARPENTRY

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
1. Wood blocking and nailers.
 2. Plywood backing panels.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of process and factory-fabricated product.

PART 2 - PRODUCTS

2.1 WOOD PRODUCTS, GENERAL

- A. Lumber: DOC PS 20 and applicable rules of grading agencies indicated. If no grading agency is indicated, provide lumber that complies with the applicable rules of any rules-writing agency certified by the ALSC Board of Review. Provide lumber graded by an agency certified by the ALSC Board of Review to inspect and grade lumber under the rules indicated.
1. Factory mark each piece of lumber with grade stamp of grading agency.
 2. Dress lumber, S4S, unless otherwise indicated.
- B. Maximum Moisture Content of Lumber: 15 percent unless otherwise indicated.

2.2 WOOD-PRESERVATIVE-TREATED MATERIALS

- A. Preservative Treatment by Pressure Process: AWPA U1; Use Category UC2.
1. Preservative Chemicals: Acceptable to authorities having jurisdiction and containing no arsenic or chromium.
- B. Kiln-dry lumber after treatment to a maximum moisture content of 19 percent. Do not use material that is warped or does not comply with requirements for untreated material.
- C. Mark lumber with treatment quality mark of an inspection agency approved by the ALSC Board of Review.
- D. Application: Treat items indicated on Drawings, and the following:
1. Wood nailers, blocking, and similar members in connection with roofing.

2.3 FIRE-RETARDANT-TREATED MATERIALS

- A. Fire-Retardant-Treated Lumber and Plywood by Pressure Process: Products with a flame-spread index of 25 or less when tested according to ASTM E 84, and with no evidence of significant progressive combustion when the test is extended an additional 20 minutes, and with the flame front not extending more than 10.5 feet beyond the centerline of the burners at any time during the test.
1. Interior Type A: Treated materials shall have a moisture content of 28 percent or less when tested according to ASTM D 3201 at 92 percent relative humidity. Use where exterior type is not indicated.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Kiln-dry lumber after treatment to a maximum moisture content of 19 percent. Kiln-dry plywood after treatment to a maximum moisture content of 15 percent.
- C. Identify fire-retardant-treated wood with appropriate classification marking of qualified testing agency.
- D. Application: Treat items indicated on Drawings, and the following:
 - 1. Concealed blocking.
 - 2. Plywood backing panels.

2.4 PLYWOOD BACKING PANELS

- A. Equipment Backing Panels: Plywood, DOC PS 1, Exposure 1, C-D Plugged, fire-retardant treated, in thickness indicated or, if not indicated, not less than 3/4-inch nominal thickness.

2.5 FASTENERS

- A. General: Provide fasteners of size and type indicated that comply with requirements specified in this article for material and manufacture.
 - 1. Where carpentry is exposed to weather, in ground contact, pressure-preservative treated, or in area of high relative humidity, provide fasteners with hot-dip zinc coating complying with ASTM A 153/A 153M.
- B. Power-Driven Fasteners: Fastener systems with an evaluation report acceptable to authorities having jurisdiction, based on ICC-ES AC70.

PART 3 - EXECUTION

3.1 INSTALLATION, GENERAL

- A. Framing Standard: Comply with AF&PA's WCD 1, "Details for Conventional Wood Frame Construction," unless otherwise indicated.
- B. Set carpentry to required levels and lines, with members plumb, true to line, cut, and fitted. Fit carpentry accurately to other construction. Locate nailers, blocking,,and similar supports to comply with requirements for attaching other construction.
- C. Install plywood backing panels by fastening to substrate; coordinate locations with utilities requiring backing panels. Install fire-retardant-treated plywood backing panels with classification marking of testing agency exposed to view.
- D. Comply with AWWA M4 for applying field treatment to cut surfaces of preservative-treated lumber.
- E. Securely attach carpentry work to substrates.

END OF SECTION 06 10 53

SECTION 06 16 00 - SHEATHING

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
1. Parapet & curb sheathing.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of process and factory-fabricated product.

PART 2 - PRODUCTS

2.1 PARAPET SHEATHING

- A. Glass-Mat Gypsum Parapet and curb Sheathing: ASTM C1177/C1177M.
1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Certainteed; SAINT-GOBAIN.
 - b. National Gypsum Company.
 - c. USG Corporation.
 2. Type and Thickness: Regular, 1/2 inch thick.

2.2 FASTENERS

- A. General: Provide fasteners of size and type indicated that comply with requirements specified in this article for material and manufacture.
1. For parapet sheathing, provide fasteners with hot-dip zinc coating complying with ASTM A153/A153M.

2.3 SHEATHING JOINT-AND-PENETRATION TREATMENT MATERIALS

- A. Sealant for Glass-Mat Gypsum Sheathing: Silicone emulsion sealant complying with ASTM C834, compatible with sheathing tape and sheathing and recommended by tape and sheathing manufacturers for use with glass-fiber sheathing tape and for covering exposed fasteners.
1. Sheathing Tape: Self-adhering glass-fiber tape, minimum 2 inches wide, 10 by 10 or 10 by 20 threads/inch, of type recommended by sheathing and tape manufacturers for use with silicone emulsion sealant in sealing joints in glass-mat gypsum sheathing and with a history of successful in-service use.

PART 3 - EXECUTION

3.1 INSTALLATION, GENERAL

- A. Do not use materials with defects that impair quality of sheathing or pieces that are too small to use with minimum number of joints or optimum joint arrangement. Arrange joints so that pieces do not span between fewer than three support members.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Cut panels at penetrations, edges, and other obstructions of work; fit tightly against abutting construction unless otherwise indicated.
- C. Do not bridge building expansion joints; cut and space edges of panels to match spacing of structural support elements.

3.2 GYPSUM SHEATHING INSTALLATION

- A. Comply with GA-253 and with manufacturer's written instructions.
 - 1. Fasten gypsum sheathing to masonry substrates with screws.
 - 2. Install panels with a 3/8-inch gap where non-load-bearing construction abuts structural elements.
- B. Seal sheathing joints according to sheathing manufacturer's written instructions.
 - 1. Apply glass-fiber sheathing tape to glass-mat gypsum sheathing joints and apply and trowel sealant to embed entire face of tape in sealant. Apply sealant to exposed fasteners with a trowel so fasteners are completely covered. Seal other penetrations and openings.

END OF SECTION 06 16 00

SECTION 07 54 23 – EPDM ROOFING

PART 1 - GENERAL

1.1 SUMMARY

A. Section Includes:

1. Adhered EPDM roofing system.
2. Accessory roofing materials.
3. Roof insulation.
4. Insulation accessories.
5. Walkways.

B. Related Requirements:

1. Section 06 10 53 "Miscellaneous Rough Carpentry" for wood nailers and blocking.
2. Section 07 62 00 "Sheet Metal Flashing and Trim" for metal roof flashings and counterflashings.
3. Section 07 92 00 "Joint Sealants" for joint sealants, joint fillers, and joint preparation.

1.2 DEFINITIONS

- A. Roofing Terminology: Definitions in ASTM D1079 and glossary in NRCA's "The NRCA Roofing Manual: Membrane Roof Systems" apply to Work of this Section.

1.3 PREINSTALLATION MEETINGS

A. Preinstallation Roofing Conference: Conduct conference at Project site.

1. Meet with Owner, Architect, Owner's insurer if applicable, testing and inspecting agency representative, roofing Installer, roofing system manufacturer's representative, and installers whose work interfaces with or affects roofing, including installers of roof accessories and roof-mounted equipment.
2. Review methods and procedures related to roofing installation, including manufacturer's written instructions.
3. Review and finalize construction schedule, and verify availability of materials, Installer's personnel, equipment, and facilities needed to make progress and avoid delays.
4. Examine deck substrate conditions and finishes for compliance with requirements, including flatness and fastening.
5. Review structural loading limitations of roof deck during and after roofing.
6. Review base flashings, special roofing details, roof drainage, roof penetrations, equipment curbs, and condition of other construction that affects roofing system.
7. Review governing regulations and requirements for insurance and certificates if applicable.
8. Review temporary protection requirements for roofing system during and after installation.
9. Review roof observation and repair procedures after roofing installation.

1.4 ACTION SUBMITTALS

A. Product Data: For each type of product.

1. For insulation and roof system component fasteners, include copy of SPRI's Directory of Roof Assemblies listing.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Shop Drawings: Include roof plans, sections, details, and attachments to other work, including the following:
 - 1. Layout and thickness of insulation.
 - 2. Base flashings and membrane termination details.
 - 3. Flashing details at penetrations.
 - 4. Tapered insulation layout, thickness, and slopes.
 - 5. Insulation fastening patterns for corner, perimeter, and field-of-roof locations.
- C. Samples for Verification: For the following products:
 - 1. Roof membrane and flashings, of color required.
 - 2. Walkway pads or rolls, of color required.
- D. Wind Uplift Resistance Submittal: For roofing system, indicating compliance with wind uplift performance requirements.

1.5 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For Installer and manufacturer.
- B. Manufacturer Certificates:
 - 1. Performance Requirement Certificate: Signed by roof membrane manufacturer, certifying that roofing system complies with requirements specified in "Performance Requirements" Article.
 - a. Submit evidence of compliance with performance requirements.
 - 2. Special Warranty Certificate: Signed by roof membrane manufacturer, certifying that all materials supplied under this Section are acceptable for special warranty.
- C. Product Test Reports: For roof membrane and insulation, for tests performed by a qualified testing agency, indicating compliance with specified requirements.
- D. Field quality-control reports.
- E. Sample Warranties: For manufacturer's special warranties.

1.6 CLOSEOUT SUBMITTALS

- A. Maintenance Data: For roofing system to include in maintenance manuals.

1.7 QUALITY ASSURANCE

- A. Qualifications:
 - 1. Manufacturers: A qualified manufacturer that is listed in SPRI's Directory of Roof Assemblies for roofing system identical to that used for this Project.
 - 2. Installers: A qualified firm that is approved, authorized, or licensed by roofing system manufacturer to install manufacturer's product and that is eligible to receive manufacturer's special warranty.

1.8 DELIVERY, STORAGE, AND HANDLING

- A. Deliver roofing materials to Project site in original containers with seals unbroken and labeled with manufacturer's name, product brand name and type, date of manufacture, approval or listing agency markings, and directions for storing and mixing with other components.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Store liquid materials in their original undamaged containers in a clean, dry, protected location and within the temperature range required by roofing system manufacturer. Protect stored liquid material from direct sunlight.
 - 1. Discard and legally dispose of liquid material that cannot be applied within its stated shelf life.
- C. Protect roof insulation materials from physical damage and from deterioration by sunlight, moisture, soiling, and other sources. Store in a dry location. Comply with insulation manufacturer's written instructions for handling, storing, and protecting during installation.
- D. Handle and store roofing materials, and place equipment in a manner to avoid permanent deflection of deck.

1.9 FIELD CONDITIONS

- A. Weather Limitations: Proceed with installation only when existing and forecasted weather conditions permit roofing system to be installed according to manufacturer's written instructions and warranty requirements.

1.10 WARRANTY

- A. Special Warranty: Manufacturer agrees to repair or replace components of roofing system that fail in materials or workmanship within specified warranty period.
 - 1. Special warranty includes roof membrane, base flashings, roof insulation, cover boards, and other components of roofing system.
 - 2. Warranty Period: 20 years from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. General Performance: Installed roofing system and flashings to withstand specified uplift pressures, thermally induced movement, and exposure to weather without failure due to defective manufacture, fabrication, installation, or other defects in construction. Roof system and flashings to remain watertight.
 - 1. Accelerated Weathering: Roof to withstand 2000 hours of exposure when tested according to ASTM G152, ASTM G154, or ASTM G155.
 - 2. Impact Resistance: Roof membrane to resist impact damage when tested according to ASTM D3746, ASTM D4272, or the "Resistance to Foot Traffic Test" in FM Approvals 4470.
- B. Material Compatibility: Roofing materials to be compatible with one another and adjacent materials under conditions of service and application required, as demonstrated by roof membrane manufacturer based on testing and field experience.
- C. Wind Uplift Resistance: Design roofing system to resist the following wind uplift pressures when tested according to FM Approvals 4474, UL 580, or UL 1897:
 - 1. Zone 1 (Roof Area Field): 33.9 lbf/sq. ft..
 - 2. Zone 2 (Roof Area Perimeter): 56.9 lbf/sq. ft..
 - a. Location: From roof edge to 14.2 ft. inside roof edge.
 - 3. Zone 3 (Roof Area Corners): 85.5 lbf/sq. ft..
 - a. Location: 14.2 ft. in each direction from each building corner.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- D. Exterior Fire-Test Exposure: ASTM E108 or UL 790, Class A; for application and roof slopes indicated; testing by a qualified testing agency. Identify products with appropriate markings of applicable testing agency.
- E. Fire-Resistance Ratings: Comply with fire-resistance-rated assembly designs indicated. Identify products with appropriate markings of applicable testing agency.

2.2 EPDM ROOFING MEMBRANE

- A. EPDM Roofing Membrane: ASTM D 4637, Type I, nonreinforced uniform, flexible sheet made from EPDM, and as follows:
 - 1. Manufacturers: Subject to compliance with requirements, provide products by the manufacturers specified.
 - a. Carlisle SynTec Incorporated.
 - b. Firestone Building Products Company.
 - c. Johns Manville International, Inc.
 - d. Versico.
 - 2. Thickness: 60 mils, nominal.
 - 3. Exposed Face Color: Black.

2.3 AUXILIARY MATERIALS

- A. General: Auxiliary materials recommended by roofing system manufacturer for intended use and compatible with membrane roofing.
- B. Sheet Flashing: 60-mil- thick EPDM, partially cured or cured, according to application.
- C. Bonding Adhesive: Manufacturer's standard bonding adhesive.
- D. Seaming Material: Manufacturer's standard synthetic-rubber polymer primer and 3-inch- wide minimum, butyl splice tape with release film.
- E. Fasteners: Factory-coated steel fasteners and metal or plastic plates meeting corrosion-resistance provisions in FMG 4470, designed for fastening membrane to substrate, and acceptable to membrane roofing system manufacturer.
- F. Miscellaneous Accessories: Provide lap sealant, water cutoff mastic, metal termination bars, metal battens, pourable sealers, preformed cone and vent sheet flashings, preformed inside and outside corner sheet flashings, T-joint covers, in-seam sealants, termination reglets, cover strips, and other accessories.

2.4 ROOF INSULATION

- A. General: Preformed roof insulation boards manufactured or approved by roof membrane manufacturer.
- B. Polyisocyanurate Board Insulation: ASTM C1289, Type II, Class 1, Grade 3, felt or glass-fiber mat facer on both major surfaces.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Atlas Polyiso Roof and Wall Insulation.
 - b. Carlisle Syntec Systems.
 - c. Certainteed; SAINT-GOBAIN.
 - d. Firestone Building Products.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- e. GAF.
 - f. Hunter Panels.
 - g. Insulfoam; Carlisle Construction Materials Company.
 - h. Johns Manville; a Berkshire Hathaway company.
2. Compressive Strength: 25 psi.

- C. Tapered Insulation: Provide factory-tapered insulation boards.
- 1. Material: Match roof insulation.
 - 2. Minimum Thickness: 1/4 inch.
 - 3. Slope:
 - a. Roof Field: 1/4 inch per foot unless otherwise indicated on Drawings.
 - b. Saddles and Crickets: 1/2 inch per foot unless otherwise indicated on Drawings.

2.5 INSULATION ACCESSORIES AND COVER BOARD

- A. General: Roof insulation accessories recommended by insulation manufacturer for intended use and compatibility with other roofing system components.
- B. Fasteners: Factory-coated steel fasteners with metal or plastic plates complying with corrosion-resistance provisions in FM Approvals 4470, designed for fastening roof insulation to substrate, and acceptable to roofing system manufacturer.
- C. Insulation Adhesive: Insulation manufacturer's recommended adhesive formulated to attach roof insulation to substrate or to another insulation layer.:

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, with Installer present, for compliance with requirements and other conditions affecting performance of the Work.
- 1. Verify that roof openings and penetrations are in place, curbs are set and braced, and roof-drain bodies are securely clamped in place.
 - 2. Verify that wood blocking, curbs, and nailers are securely anchored to roof deck at penetrations and terminations and that nailers match thicknesses of insulation.
 - 3. Verify that concrete substrate is visibly dry and free of moisture, and that minimum concrete internal relative humidity is not more than 75 percent, or as recommended by roofing system manufacturer, when tested according to ASTM F2170.
 - a. Test Frequency: One test probe per each 1000 sq. ft., or portion thereof, of roof deck, with not less than three test probes.
 - b. Submit test reports within 24 hours after performing tests.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Clean substrate of dust, debris, moisture, and other substances detrimental to roofing system installation according to roofing system manufacturer's written instructions. Remove sharp projections.
- B. Prevent materials from entering and clogging roof drains and conductors and from spilling or migrating onto surfaces of other construction. Remove roof-drain plugs when no work is taking place or when rain is forecast.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

3.3 INSTALLATION OF ROOFING, GENERAL

- A. Install roofing system according to roofing system manufacturer's written instructions, SPRI's Directory of Roof Assemblies listed roof assembly requirements, and FM Global Property Loss Prevention Data Sheet 1-29.
- B. Complete terminations and base flashings and provide temporary seals to prevent water from entering completed sections of roofing system at end of workday or when rain is forecast. Remove and discard temporary seals before beginning Work on adjoining roofing.

3.4 INSTALLATION OF INSULATION

- A. Coordinate installing roofing system components so insulation is not exposed to precipitation or left exposed at end of workday.
- B. Comply with roofing system and roof insulation manufacturer's written instructions for installing roof insulation.
- C. Installation Over Metal Decking:
 - 1. Install base layer of insulation with joints staggered in adjacent rows.
 - a. Locate end joints over crests of decking.
 - b. Make joints between adjacent insulation boards not more than 1/4 inch in width.
 - c. Fill gaps exceeding 1/4 inch with insulation.
 - d. Cut and fit insulation within 1/4 inch of nailers, projections, and penetrations.
 - e. Mechanically attach base layer of insulation using mechanical fasteners specifically designed and sized for fastening specified board-type roof insulation to metal decks.
 - 1) Fasten insulation to resist specified uplift pressure at corners, perimeter, and field of roof.
 - 2. Install upper layers of insulation and tapered insulation with joints of each layer offset from previous layer of insulation.
 - a. Trim insulation neatly to fit around penetrations and projections, and to fit tight to intersecting sloping roof decks.
 - b. Make joints between adjacent insulation boards not more than 1/4 inch in width.
 - c. At internal roof drains, slope insulation to create a square drain sump with each side equal to the diameter of the drain bowl plus 24 inches.
 - 1) Trim insulation so that water flow is unrestricted.
 - d. Fill gaps exceeding 1/4 inch with insulation.
 - e. Cut and fit insulation within 1/4 inch of nailers, projections, and penetrations.
 - f. Adhere upper layers of insulation to substrate using adhesive according to SPRI's Directory of Roof Assemblies listed roof assembly requirements for specified Wind Uplift Load Capacity and FM Global Property Loss Prevention Data Sheet 1-29.
- D. Installation Over Concrete Decks:
 - 1. Install base layer of insulation with joints staggered in adjacent rows.
 - a. Trim insulation neatly to fit around penetrations and projections, and to fit tight to intersecting sloping roof decks.
 - b. Make joints between adjacent insulation boards not more than 1/4 inch in width.
 - c. At internal roof drains, slope insulation to create a square drain sump with each side equal to the diameter of the drain bowl plus 24 inches.
 - 1) Trim insulation so that water flow is unrestricted.
 - d. Fill gaps exceeding 1/4 inch with insulation.
 - e. Cut and fit insulation within 1/4 inch of nailers, projections, and penetrations.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- f. Adhere base layer of insulation to concrete roof deck according to SPRI's Directory of Roof Assemblies listed roof assembly requirements for specified Wind Uplift Load Capacity and FM Global Property Loss Prevention Data Sheet 1-29.
2. Install upper layers of insulation and tapered insulation with joints of each layer offset from previous layer of insulation.
 - a. Staggered end joints within each layer in adjacent rows.
 - b. Install with long joints continuous and with end joints staggered in adjacent rows.
 - c. Trim insulation neatly to fit around penetrations and projections, and to fit tight to intersecting sloping roof decks.
 - d. Make joints between adjacent insulation boards not more than 1/4 inch in width.
 - e. At internal roof drains, slope insulation to create a square drain sump with each side equal to the diameter of the drain bowl plus 24 inches.
 - 1) Trim insulation so that water flow is unrestricted.
 - f. Fill gaps exceeding 1/4 inch with insulation.
 - g. Cut and fit insulation within 1/4 inch of nailers, projections, and penetrations.
 - h. Adhere each layer of insulation to substrate using adhesive according to SPRI's Directory of Roof Assemblies listed roof assembly requirements for specified Wind Uplift Load Capacity and FM Global Property Loss Prevention Data Sheet 1-29.

3.5 INSTALLATION OF ADHERED ROOF MEMBRANE

- A. Adhere roof membrane over area to receive roofing according to roofing system manufacturer's written instructions.
- B. Unroll roof membrane and allow to relax before installing.
- C. Start installation of roofing in presence of roofing system manufacturer's technical personnel.
- D. Accurately align roof membrane, and maintain uniform side and end laps of minimum dimensions required by manufacturer. Stagger end laps.
- E. Bonding Adhesive: Apply to substrate and underside of roof membrane at rate required by manufacturer, and allow to partially dry before installing roof membrane. Do not apply to splice area of roof membrane.
- F. In addition to adhering, mechanically fasten roof membrane securely at terminations, penetrations, and perimeter of roofing.
- G. Apply roof membrane with side laps shingled with slope of roof deck where possible.
- H. Seams: Clean seam areas, overlap roof membrane, and hot-air weld side and end laps of roof membrane and sheet flashings, to ensure a watertight seam installation.
 1. Test lap edges with probe to verify seam weld continuity. Apply lap sealant to seal cut edges of roof membrane and sheet flashings.
 2. Verify field strength of seams a minimum of twice daily, and repair seam sample areas.
 3. Repair tears, voids, and lapped seams in roof membrane that do not comply with requirements.
- I. Spread sealant bed over deck-drain flange at roof drains, and securely seal roof membrane in place with clamping ring.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

3.6 INSTALLATION OF BASE FLASHING

- A. Install sheet flashings and preformed flashing accessories, and adhere to substrates according to roofing system manufacturer's written instructions.
- B. Apply bonding adhesive to substrate and underside of sheet flashing at required rate, and allow to partially dry. Do not apply to seam area of flashing.
- C. Flash penetrations and field-formed inside and outside corners with cured or uncured sheet flashing.
- D. Clean seam areas, overlap, and firmly roll sheet flashings into the adhesive. Hot-air weld side and end laps to ensure a watertight seam installation.
- E. Terminate and seal top of sheet flashings and mechanically anchor to substrate through termination bars.

3.7 FIELD QUALITY CONTROL

- A. Final Roof Inspection: Arrange for roofing system manufacturer's technical personnel to inspect roofing installation on completion, in presence of Architect, and to prepare inspection report.
- B. Repair or remove and replace components of roofing system where inspections indicate that they do not comply with specified requirements.
- C. Additional testing and inspecting, at Contractor's expense, will be performed to determine if replaced or additional work complies with specified requirements.

3.8 PROTECTING AND CLEANING

- A. Protect roofing system from damage and wear during remainder of construction period. When remaining construction does not affect or endanger roofing system, inspect roofing system for deterioration and damage, describing its nature and extent in a written report, with copies to Architect and Owner.
- B. Correct deficiencies in or remove roofing system that does not comply with requirements, repair substrates, and repair or reinstall roofing system to a condition free of damage and deterioration at time of Substantial Completion and according to warranty requirements.
- C. Clean overspray and spillage from adjacent construction using cleaning agents and procedures recommended by manufacturer of affected construction.

END OF SECTION 07 54 23

Copyright 2018 by The American Institute of Architects (AIA)

Exclusively published and distributed by Deltek, Inc. for the AIA

SECTION 07 62 00 - SHEET METAL FLASHING AND TRIM

Revise this Section by deleting and inserting text to meet Project-specific requirements.

This Section uses the term "Architect." Change this term to match that used to identify the design professional as defined in the General and Supplementary Conditions.

Verify that Section titles referenced in this Section are correct for this Project's Specifications; Section titles may have changed.

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes but is not limited to:
1. Formed counterflashing.
 2. Parapet through-wall flashing.
 3. Formed roof-drainage sheet metal fabrications.
 4. Formed low-slope roof sheet metal fabrications.
 5. Formed wall sheet metal fabrications.

1.2 ACTION SUBMITTALS

- A. Product Data: For each of the following
1. Underlayment materials.
 2. Elastomeric sealant.
 3. Butyl sealant.
 4. Epoxy seam sealer.
- B. Shop Drawings: For sheet metal flashing and trim.
1. Include plans, elevations, sections, and attachment details.
 2. Detail fabrication and installation layouts, expansion-joint locations, and keyed details. Distinguish between shop- and field-assembled Work.
 3. Include identification of material, thickness, weight, and finish for each item and location in Project.
 4. Include details for forming, including profiles, shapes, seams, and dimensions.
 5. Include details for joining, supporting, and securing, including layout and spacing of fasteners, cleats, clips, and other attachments. Include pattern of seams.
 6. Include details of termination points and assemblies.
 7. Include details of edge conditions, including crickets, flashings, and counterflashings.
 8. Include details of special conditions.
 9. Include details of connections to adjoining work.
- C. Samples: For each exposed product and for each color and texture specified, 12 inches long by actual width.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

1.3 QUALITY ASSURANCE

- A. Fabricator Qualifications: Employs skilled workers who custom fabricate sheet metal flashing and trim similar to that required for this Project and whose products have a record of successful in-service performance.

Retain subparagraph below if Project is governed by the IBC, or if requirements in ANSI/SPRI/FM 4435/ES-1 set a minimum quality standard.

1. For copings and roof edge flashings that are ANSI/SPRI/FM 4435/ES-1 tested, shop shall be listed as able to fabricate required details as tested and approved.

PART 2 - PRODUCTS

Manufacturers and products listed in SpecAgent and MasterWorks Paragraph Builder are neither recommended nor endorsed by the AIA or Deltek. Before inserting names, verify that manufacturers and products listed there comply with requirements retained or revised in descriptions and are both available and suitable for the intended applications. For definitions of terms and requirements for Contractor's product selection, see Section 01 60 00 "Product Requirements."

2.1 PERFORMANCE REQUIREMENTS

- A. Sheet metal flashing and trim assemblies, including cleats, anchors, and fasteners, shall withstand wind loads, structural movement, thermally induced movement, and exposure to weather without failure due to defective manufacture, fabrication, installation, or other defects in construction. Completed sheet metal flashing and trim shall not rattle, leak, or loosen, and shall remain watertight.
- B. Sheet Metal Standard for Flashing and Trim: Comply with NRCA's "The NRCA Roofing Manual: Architectural Metal Flashing, Condensation and Air Leakage Control, and Reroofing" and SMACNA's "Architectural Sheet Metal Manual" requirements for dimensions and profiles shown unless more stringent requirements are indicated.

Retain "Sheet Metal Standard for Copper" Paragraph below if applicable. NRCA has a testing program and authorized fabricators for particular NRCA copper-sheet metal details. CDA does not have a testing program or authorized fabricators for its details.

- C. Sheet Metal Standard for Copper: Comply with CDA's "Copper in Architecture Handbook." Conform to dimensions and profiles shown unless more stringent requirements are indicated.

Retain "SPRI Wind Design Standard" Paragraph below if Project is governed by the IBC or if ANSI/SPRI/FM 4435/ES-1 testing sets a minimum quality standard. Coordinate ANSI/SPRI/FM 4435/ES-1 requirements with other Section requirements. Verify availability of copings or roof edge flashings that have these requirements. NRCA has a testing program and authorized fabricators for particular NRCA zinc-coated (galvanized) steel sheet, aluminum, and copper details. SMACNA has limited details that have successfully been tested for compliance with ANSI/SPRI/FM 4435/ES-1. CDA does not have a testing program or authorized fabricators for its details.

- D. SPRI Wind Design Standard: Manufacture and install roof edge flashings tested in accordance with ANSI/SPRI/FM 4435/ES-1 and capable of resisting the following design pressure:

Indicate wind design pressure on Drawings or in "Design Pressure" Subparagraph below. Design pressure is determined by formulas in the IBC or ANSI/SPRI/FM 4435/ES-1, as applicable, that account for basic wind speed, exposure factor, building height, building importance factor, and pressure coefficient that combines a gust factor.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

1. Design Pressure:
 - a. Roof Edge Perimeter, Vertical Load Direction: 56.9 psf.
 - b. Wall Edge Perimeter, Horizontal Load Direction: 36.8 psf.

Retain "FM Approvals Listing" Paragraph below if Project is FM Global insured or if FM Approvals' requirements set a minimum quality standard. Coordinate requirements of FM Approvals' classification with other requirements in this Section. Verify availability of copings or roof edge flashings that have these classifications. NRCA has a testing program and authorized fabricators for particular NRCA zinc-coated (galvanized) steel sheet and aluminum details.

- E. Thermal Movements: Allow for thermal movements from ambient and surface temperature changes to prevent buckling, opening of joints, overstressing of components, failure of joint sealants, failure of connections, and other detrimental effects. Base calculations on surface temperatures of materials due to both solar heat gain and nighttime-sky heat loss.

Differential values in "Temperature Change" Subparagraph below (for aluminum in particular) are suitable for most of the United States.

1. Temperature Change: 120 deg F, ambient; 180 deg F, material surfaces.

Insert additional performance requirements here; verify system compliance with manufacturers.

2.2 SHEET METALS

Finishes for sheet metals are specified with materials in this article rather than in a separate "Finishes" Article.

- A. Protect mechanical and other finishes on exposed surfaces from damage by applying strippable, temporary protective film before shipping.
- B. Copper Sheet: ASTM B370, cold-rolled copper sheet, H00 or H01 temper.
 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Hussey Copper Ltd.
 - b. Revere Copper Products, Inc.

Retain "Nonpatinated, Exposed Finish" or "Prepatinated Copper-Sheet Finish" Subparagraph below. Retain first subparagraph for natural-color copper finish that weathers and changes color naturally over time. If retaining more than one finish, indicate locations of each on Drawings.

2. Nonpatinated, Exposed Finish: Mill.

Retain "Prepatinated Copper-Sheet Finish" Subparagraph below for prepatinated finishes, which reduce nonuniform weathering of exposed copper sheet. Verdigris is the ultimate, light-green color of aged copper.

Second option in "Aluminum Sheet" Paragraph below may diminish oil-canning effect.

- C. Aluminum Sheet: ASTM B209, alloy as standard with manufacturer for finish required, with temper as required to suit forming operations and performance required; with smooth, flat surface.

Retain "As-Milled Finish"; "Alclad Finish"; "Factory Prime Coating"; "Clear Anodic Finish, Coil Coated"; "Color Anodic Finish, Coil Coated"; or "Exposed Coil-Coated Finish" Subparagraph below. If retaining more than one, indicate location of each on Drawings or by inserts.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

Retain "Alclad Finish" Subparagraph below if required; delete for coil-coated finishes.

Retain "Factory Prime Coating" Subparagraph below for field painting aluminum sheet. Field painting is specified in Section 09 91 13 "Exterior Painting."

Retain "Exposed Coil-Coated Finish" Subparagraph below for factory-coil-coated finish.

1. Exposed Coil-Coated Finish:

Retain "Two-Coat Fluoropolymer," "Three-Coat Fluoropolymer," or "Siliconized Polyester" Subparagraph below.

- a. Two-Coat Fluoropolymer: AAMA 2605. Fluoropolymer finish containing not less than 70 percent polyvinylidene fluoride (PVDF) resin by weight in color coat. Prepare, pretreat, and apply coating to exposed metal surfaces to comply with coating and resin manufacturers' written instructions.

Retain "Color" Subparagraph below for factory-coil-coated finish.

2. Color: As selected by Architect from manufacturer's full range.

Finish in "Concealed Finish" Subparagraph below is often retained as a factory finish for interior surfaces of coil-coated sheet. Usually delete for other finishes.

Consider including ASTM A666 stainless steel in "Stainless Steel Sheet" Paragraph below if permitted by authorities having jurisdiction. The IBC requires ASTM A240/A240M, Series 300 alloys for stainless steel roof covering but does not state a specific alloy for flashing and trim. Last option may diminish oil-canning effect.

- D. Stainless Steel Sheet: ASTM A240/A240M, Type 304, dead soft, fully annealed; with smooth, flat surface.
 1. Finish: ASTM A480/A480M, No. 2D (dull, cold rolled).

2.3 UNDERLAYMENT MATERIALS

Retain applicable paragraphs in this article for sheet metal flashing and trim applied directly over metal deck, solid sheathing, dissimilar metals, or corrosive substrates. Rosin-sized building paper is used as a slip sheet over other types of underlayment materials.

- A. Felt: ASTM D226/D226M, Type II (No. 30), asphalt-saturated organic felt; nonperforated.

Before retaining "Synthetic Underlayment" Paragraph below, verify that it is acceptable to authorities having jurisdiction; revise to suit Project.

Underlayment in "Self-Adhering, High-Temperature Sheet Underlayment" Paragraph below is suitable for higher temperatures associated with exposed sheet metal flashing and trim. This underlayment is used to resist leaks from roof areas where ice dams may form. Revise if high-temperature underlayment is not required. Slopes are typically limited to not less than 2:12 in accordance with manufacturers' published literature. Verify, with underlayment manufacturer, acceptability of use on shallower slopes.

- B. Self-Adhering, High-Temperature Sheet Underlayment: Minimum 30 mils thick, consisting of a slip-resistant polyethylene- or polypropylene-film top surface laminated to a layer of butyl- or SBS-modified asphalt adhesive, with release-paper backing; specifically designed to withstand high metal temperatures beneath metal flashing. Provide primer in accordance with underlayment manufacturer's written instructions.
 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- a. Carlisle WIP Products; a brand of Carlisle Construction Materials.
 - b. GCP Applied Technologies Inc.
 - c. Henry Company.
 - d. Polyglass U.S.A., Inc.
 - e. Protecto Wrap Company.
2. Low-Temperature Flexibility: ASTM D1970/D1970M; passes after testing at minus 20 deg F or lower.

Retain "Slip Sheet" Paragraph below for separating sheet metal from underlayment. Heavier rosin-sized paper is generally unavailable. See the Evaluations and consult sheet metal manufacturer.

2.4 MISCELLANEOUS MATERIALS

- A. Provide materials and types of fasteners, protective coatings, sealants, and other miscellaneous items as required for complete sheet metal flashing and trim installation and as recommended by manufacturer of primary sheet metal or manufactured item unless otherwise indicated.
- B. Fasteners: Wood screws, annular threaded nails, self-tapping screws, self-locking rivets and bolts, and other suitable fasteners designed to withstand design loads and recommended by manufacturer of primary sheet metal or manufactured item.
 1. General: Blind fasteners or self-drilling screws, gasketed, with hex-washer head.
 - a. Exposed Fasteners: Heads matching color of sheet metal using plastic caps or factory-applied coating. Provide metal-backed EPDM or PVC sealing washers under heads of exposed fasteners bearing on weather side of metal.
 - b. Blind Fasteners: High-strength aluminum or stainless steel rivets suitable for metal being fastened.

Retain applicable fastener subparagraph(s) below.

2. Fasteners for Copper Sheet: Copper, hardware bronze or passivated Series 300 stainless steel.
 3. Fasteners for Stainless Steel Sheet: Series 300 stainless steel.
- C. Sealant Tape: Pressure-sensitive, 100 percent solids, polyisobutylene compound sealant tape with release-paper backing. Provide permanently elastic, nonsag, nontoxic, nonstaining tape 1/2 inch wide and 1/8 inch thick.

Revise "Elastomeric Sealant" Paragraph below if sealant of specific type, grade, class, and use is required.

- D. Elastomeric Sealant: ASTM C920, elastomeric silicone polymer sealant; of type, grade, class, and use classifications required to seal joints in sheet metal flashing and trim and remain watertight.

Retain "Butyl Sealant" Paragraph below for expansion joints with limited movement.

- E. Butyl Sealant: ASTM C1311, single-component, solvent-release butyl rubber sealant; polyisobutylene plasticized; heavy bodied for hooked-type expansion joints with limited movement.

Retain "Epoxy Seam Sealer" Paragraph below if required for aluminum sheet without painted or coated finish.

- F. Epoxy Seam Sealer: Two-part, noncorrosive, aluminum seam-cementing compound, recommended by aluminum manufacturer for exterior nonmoving joints, including riveted joints.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

2.5 FABRICATION, GENERAL

- A. Custom fabricate sheet metal flashing and trim to comply with details indicated and recommendations in cited sheet metal standard that apply to design, dimensions, geometry, metal thickness, and other characteristics of item required.
1. Fabricate sheet metal flashing and trim in shop to greatest extent possible.
 2. Fabricate sheet metal flashing and trim in thickness or weight needed to comply with performance requirements, but not less than that specified for each application and metal.
 3. Verify shapes and dimensions of surfaces to be covered and obtain field measurements for accurate fit before shop fabrication.
 4. Form sheet metal flashing and trim to fit substrates without excessive oil-canning, buckling, and tool marks; true to line, levels, and slopes; and with exposed edges folded back to form hems.
 5. Conceal fasteners and expansion provisions where possible. Do not use exposed fasteners on faces exposed to view.

B. Fabrication Tolerances:

Consider retaining one of two subparagraphs below to control fabrication tolerances. Retain first for sophisticated or highly finished sheet metal assemblies. Second has more lenient tolerances suitable for residential installation.

1. Fabricate sheet metal flashing and trim that is capable of installation to a tolerance of 1/4 inch in 20 feet on slope and location lines indicated on Drawings and within 1/8-inch offset of adjoining faces and of alignment of matching profiles.

C. Expansion Provisions: Form metal for thermal expansion of exposed flashing and trim.

Revise both subparagraphs below to suit Project.

1. Form expansion joints of intermeshing hooked flanges, not less than 1 inch deep, filled with butyl sealant concealed within joints.

D. Sealant Joints: Where movable, nonexpansion-type joints are required, form metal in accordance with cited sheet metal standard to provide for proper installation of elastomeric sealant.

E. Fabricate cleats and attachment devices from same material as accessory being anchored or from compatible, noncorrosive metal.

Retain option in first paragraph below if Project is FM Global insured or if FM Global requirements set a minimum installation standard. FM Global states that cleats (hook strips) for fasciae "should be at least one gauge heavier than the fascia metal."

F. Fabricate cleats and attachment devices of sizes as recommended by cited sheet metal standard for application, but not less than thickness of metal being secured.

G. Seams:

Retain one of three subparagraphs below; revise to suit Project. Retain first for metals being soldered. Soldering requires removal of painted, coated, or lacquered finishes.

1. Copper: Fabricate nonmoving seams with flat-lock seams. Tin edges to be seamed, form seams, and solder.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

Retain first subparagraph below for aluminum sheet and metals with painted, coated, or lacquered finishes. If required, retain option for sheet aluminum.

2. Aluminum: Fabricate nonmoving seams with flat-lock seams. Form seams and seal with elastomeric sealant unless otherwise recommended by sealant manufacturer for intended use.

Retain "Seams for Aluminum" Subparagraph below only for aluminum sheet without painted or coated finish. If required, retain option.

2.6 ROOF-DRAINAGE SHEET METAL FABRICATIONS

Retain formed items required in this article. Although the most common fabrications are included, insert descriptions of others if required.

- A. Hanging Gutters:
 1. Fabricate to cross section required, complete with end pieces, outlet tubes, and other accessories as required.
 2. Fabricate in minimum 96-inch-long sections.
 3. Furnish flat-stock gutter brackets and flat-stock gutter spacers and straps fabricated from same metal as gutters, of size recommended by cited sheet metal standard, but with thickness not less than twice the gutter thickness.
 4. Fabricate expansion joints, expansion-joint covers, and gutter accessories from same metal as gutters.
 5. Gutters with Girth up to 15 Inches: Fabricate from the following materials:
 - a. Aluminum: 0.032 inch thick.
- B. Downspouts: Fabricate rectangular downspouts to dimensions indicated on Drawings, complete with mitered elbows. Furnish with metal hangers from same material as downspouts and anchors. Shop fabricate elbows.
 1. Fabricate from the following materials:
 - a. Aluminum: 0.024 inch thick.

Parapet scuppers, installed in parapet wall, discharge into conductor heads or, as overflow scuppers, merely project through parapet. Scuppers combined with roof edge flashing (gravel stop) or fascia caps, discharging into hanging gutters or conductor heads, are specified in "Low-Slope Roof Sheet Metal Fabrications" Article.

- C. Parapet Scuppers: Fabricate scuppers to dimensions required, with closure flange trim to exterior, 4-inch-wide wall flanges to interior, and base extending 4 inches beyond cant or tapered strip into field of roof. Fabricate from the following materials:
 1. Copper: 16 oz./sq. ft..
- D. Conductor Heads: Fabricate conductor heads with flanged back and stiffened top edge and of dimensions and shape required, complete with outlet tubes, exterior flange trim,. Fabricate from the following materials:
 1. Copper: 16 oz./sq. ft..

2.7 LOW-SLOPE ROOF SHEET METAL FABRICATIONS

Retain formed items required in this article. Although the most common fabrications are included, insert descriptions of others if required.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

NRCA, SMACNA, and FM Global offer recommendations for profiles, thicknesses, fastenings, and installation of low-slope roof sheet metal fabrications. Base-metal thicknesses cited for copper sheets, for copper-clad stainless steel sheet, and for zinc sheet are from manufacturer's literature.

- A. Roof Edge Flashing (Gravel Stop) and Fascia Cap: Fabricate in minimum 96-inch-long, but not exceeding 12-foot-long sections. Furnish with 6-inch-wide, joint cover plates. Shop fabricate interior and exterior corners.
1. Fabricate from the following materials:

Retain material and thickness of roof edge components that suit wind performance and testing requirements if any. NRCA has a testing program and authorized fabricators for particular NRCA zinc-coated (galvanized) steel sheet and aluminum details. SMACNA and CDA do not have testing programs or authorized fabricators for their details.

- a. Aluminum: 0.050 inch thick.

- B. Copings: Fabricate in minimum 96-inch-long, but not exceeding 12-foot-long, sections. Fabricate joint plates of same thickness as copings. Furnish with continuous cleats to support edge of external leg and drill elongated holes for fasteners on interior leg. Miter corners, fasten and seal watertight. Shop fabricate interior and exterior corners.
1. Fabricate from the following materials:

Retain material and thickness of copings that suit wind performance requirements if any. NRCA has a testing program and authorized fabricators for particular NRCA zinc-coated (galvanized) steel sheet and aluminum details. SMACNA and CDA do not have testing programs or authorized fabricators for their details.

- a. Aluminum: 0.050 inch thick.

- C. Roof-Penetration Flashing: Fabricate from the following materials:
1. Stainless Steel: 0.0188 inch thick.

Retain "Opening Flashings in Frame Construction" Paragraph below for nonmasonry-clad wood or cold-formed steel-framed walls. Claddings may include exterior insulation and finish systems (EIFS), siding, wood shingles, or shakes. Flashing is usually required to surround wall-opening components such as windows, doors, and louvers.

PART 3 - EXECUTION

3.1 INSTALLATION OF UNDERLAYMENT

Retain "Felt Underlayment"; "Synthetic Underlayment"; or "Self-Adhering, High-Temperature Sheet Underlayment" Paragraph below based on products retained in Part 2.

- A. Self-Adhering, High-Temperature Sheet Underlayment:
1. Install self-adhering, high-temperature sheet underlayment; wrinkle free.
 2. Prime substrate if recommended by underlayment manufacturer.
 3. Comply with temperature restrictions of underlayment manufacturer for installation; use primer for installing underlayment at low temperatures.
 4. Apply in shingle fashion to shed water, with end laps of not less than 6 inches staggered 24 inches between courses.
 5. Overlap side edges not less than 3-1/2 inches. Roll laps and edges with roller.
 6. Roll laps and edges with roller.
 7. Cover underlayment within 14 days.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

3.2 INSTALLATION, GENERAL

- A. Install sheet metal flashing and trim to comply with details indicated and recommendations of cited sheet metal standard that apply to installation characteristics required unless otherwise indicated on Drawings.
1. Install fasteners, solder, protective coatings, separators, sealants, and other miscellaneous items as required to complete sheet metal flashing and trim system.
 2. Install sheet metal flashing and trim true to line, levels, and slopes. Provide uniform, neat seams with minimum exposure of sealant.
 3. Anchor sheet metal flashing and trim and other components of the Work securely in place, with provisions for thermal and structural movement.
 4. Install sheet metal flashing and trim to fit substrates and to result in watertight performance.

Retain one or both of first two subparagraphs to suit Project.

5. Install continuous cleats with fasteners spaced not more than 12 inches o.c.
 6. Space individual cleats not more than 12 inches apart. Attach each cleat with at least two fasteners. Bend tabs over fasteners.
 7. Install exposed sheet metal flashing and trim with limited oil-canning, and free of buckling and tool marks.
 8. Do not field cut sheet metal flashing and trim by torch.
- B. Metal Protection: Where dissimilar metals contact each other, or where metal contacts pressure-treated wood or other corrosive substrates, protect against galvanic action or corrosion by painting contact surfaces with bituminous coating or by other permanent separation as recommended by sheet metal manufacturer or cited sheet metal standard.
1. Coat concealed side of stainless steel sheet metal flashing and trim with bituminous coating where flashing and trim contact wood, ferrous metal, or cementitious construction.
 2. Underlayment: Where installing sheet metal flashing and trim directly on cementitious or wood substrates, install underlayment and cover with slip sheet.
- C. Expansion Provisions: Provide for thermal expansion of exposed flashing and trim.
1. Space movement joints at maximum of 10 feet with no joints within 24 inches of corner or intersection.

Revise both subparagraphs below to suit Project.

2. Form expansion joints of intermeshing hooked flanges, not less than 1 inch deep, filled with sealant concealed within joints.
- D. Fasteners: Use fastener sizes that penetrate substrate not less than recommended by fastener manufacturer to achieve maximum pull-out resistance.
- E. Conceal fasteners and expansion provisions where possible in exposed work and locate to minimize possibility of leakage. Cover and seal fasteners and anchors as required for a tight installation.
- F. Seal joints as required for watertight construction.
1. Use sealant-filled joints unless otherwise indicated.

Retain first subparagraph below when fabrications with hooked flanges are specified.

- a. Embed hooked flanges of joint members not less than 1 inch into sealant.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- b. Form joints to completely conceal sealant.
 - c. When ambient temperature at time of installation is between 40 and 70 deg F, set joint members for 50 percent movement each way.
 - d. Adjust setting proportionately for installation at higher ambient temperatures.
 - 1) Do not install sealant-type joints at temperatures below 40 deg F.
2. Prepare joints and apply sealants to comply with requirements in Section 07 92 00 "Joint Sealants."

Retain "Rivets" Paragraph below if required for aluminum or zinc sheet.

3.3 INSTALLATION OF ROOF-DRAINAGE SYSTEM

- A. Install sheet metal roof-drainage items to produce complete roof-drainage system in accordance with cited sheet metal standard unless otherwise indicated. Coordinate installation of roof perimeter flashing with installation of roof-drainage system.
- B. Hanging Gutters:
1. Join sections with joints sealed with sealant.
 2. Provide for thermal expansion.
 3. Attach gutters at eave or fascia to firmly anchor them in position.
 4. Provide end closures and seal watertight with sealant.
 5. Slope to downspouts.
- C. Downspouts:
1. Join sections with 1-1/2-inch telescoping joints.
 2. Provide hangers with fasteners designed to hold downspouts securely to walls.
 3. Locate hangers at top and bottom and at approximately 60 inches o.c.

Retain one of two subparagraphs below; delete both if indicated on Drawings.

4. Provide elbows at base of downspout to direct water away from building.

Retain "Splash Pans" Paragraph below for metal splash pans.

- D. Parapet Scuppers:
1. Continuously support scupper, set to correct elevation, and seal flanges to interior wall face, over cants or tapered edge strips, and under roofing membrane.

Retain first subparagraph below if scupper terminates at exterior wall. Retain second subparagraph, with first, if scupper discharges into conductor head set immediately below base elevation of scupper. Retain third subparagraph if scupper discharges directly into back of conductor head.

2. Anchor scupper closure trim flange to exterior wall and seal with elastomeric sealant to scupper.

3.4 INSTALLATION OF ROOF FLASHINGS

Retain this article for low-slope and steep-slope roof flashing. Coordinate steep-slope roof flashing requirements with applicable steep-slope roofing Section. Revise the Section Text if fastener spacings are indicated on Drawings.

Retain option in first paragraph below if manufactured reglets are required.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- A. Install sheet metal flashing and trim to comply with performance requirements, sheet metal manufacturer's written installation instructions, and cited sheet metal standard.
 - 1. Provide concealed fasteners where possible, and set units true to line, levels, and slopes.
 - 2. Install work with laps, joints, and seams that are permanently watertight and weather resistant.

B. Roof Edge Flashing:

Retain one of three subparagraphs below; revise to suit Project. Retain first if Project is governed by the IBC or if ANSI/SPRI/FM 4435/ES-1 testing sets a minimum quality standard. Retain second if Project is FM Global insured or if FM Global requirements set minimum installation standard. FM Global requirements depend on specific roof edge and flashing configurations.

- 1. Install roof edge flashings in accordance with ANSI/SPRI/FM 4435/ES-1.

C. Copings:

Retain one of three subparagraphs below; revise to suit Project. Retain first if Project is governed by the IBC or if ANSI/SPRI/FM 4435/ES-1 testing sets a minimum quality standard. Retain second if Project is FM Global insured or if FM Global requirements set minimum installation standard. FM Global requirements depend on specific coping material, thickness, and configuration.

- 1. Install roof edge flashings in accordance with ANSI/SPRI/FM 4435/ES-1.

- D. Pipe or Post Counterflashing: Install counterflashing umbrella with close-fitting collar with top edge flared for elastomeric sealant, extending minimum of 4 inches over base flashing. Install stainless steel draw band and tighten.

- E. Counterflashing: Coordinate installation of counterflashing with installation of base flashing.

- 1. Insert counterflashing in reglets or receivers and fit tightly to base flashing.
- 2. Extend counterflashing 4 inches over base flashing.
- 3. Lap counterflashing joints minimum of 4 inches.

3.5 INSTALLATION OF WALL FLASHINGS

- A. Install sheet metal wall flashing to intercept and exclude penetrating moisture in accordance with cited sheet metal standard unless otherwise indicated. Coordinate installation of wall flashing with installation of roofing system.

3.6 INSTALLATION TOLERANCES

- A. Installation Tolerances: Shim and align sheet metal flashing and trim within installed tolerance of 1/4 inch in 20 feet on slope and location lines indicated on Drawings and within 1/8-inch offset of adjoining faces and of alignment of matching profiles.

3.7 CLEANING

Retain first paragraph below for metal surfaces unless metal is painted, coated, or lacquered.

- A. Clean exposed metal surfaces of substances that interfere with uniform oxidation and weathering.

Retain first paragraph below for soldered joints.

- B. Clean and neutralize flux materials. Clean off excess solder.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- C. Clean off excess sealants.

3.8 PROTECTION

- A. Remove temporary protective coverings and strippable films as sheet metal flashing and trim are installed unless otherwise indicated in manufacturer's written installation instructions.
- B. Replace sheet metal flashing and trim that have been damaged or that have deteriorated beyond successful repair by finish touchup or similar minor repair procedures, as determined by Architect.

END OF SECTION 07 62 00

SECTION 07 72 00 - ROOF ACCESSORIES

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
1. Roof hatches.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of roof accessory.

1.3 INFORMATIONAL SUBMITTALS

- A. Sample warranties.

1.4 CLOSEOUT SUBMITTALS

- A. Operation and maintenance data.

PART 2 - PRODUCTS

2.1 ROOF HATCHES

- A. Roof Hatches: Metal roof-hatch units with lids and insulated double-walled curbs, welded or mechanically fastened and sealed corner joints, continuous lid-to-curb counterflashing and weathertight perimeter gasketing, straight sides, and integrally formed deck-mounting flange at perimeter bottom.
1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. BILCO Company (The).
 - b. Babcock-Davis.
 - c. Milcor; Hart & Cooley, Inc.
 - d. Nystrom, Inc.
 - e. Pate Company (The).
 2. Type and Size: Single-leaf lid, size as indicated on Drawings.
 3. Loads: Minimum 40-lbf/sq. ft. external live load and 30-lbf/sq. ft. internal uplift load.
 - a. When release is actuated, lid shall open against 10-lbf/sq. ft. snow or wind load and lock in position.
 - b. Hatch-Lid Glazing: Minimum 40-lbf/sq. ft. external live load and 20-lbf/sq. ft. internal uplift load.
 4. Curb, Framing, and Lid Material: Aluminum sheet.
 - a. Thickness: Manufacturer's standard thickness for hatch size indicated.
 - b. Finish: Mill.
 5. Construction:
 - a. Insulation: 1-inch-thick, glass-fiber board.
 - 1) R-Value: 4.3 according to ASTM C1363.
 - b. Nailer: Factory-installed wood nailer continuous around hatch perimeter.
 - c. Hatch Lid: Glazed, insulated, and double walled, with manufacturer's standard metal liner of same material and finish as outer metal lid.
 - d. Exterior Curb Liner: Manufacturer's standard, of same material and finish as metal curb.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- e. Fabricate curbs to minimum height of 12 inches above roofing surface unless otherwise indicated.
 6. Hatch-Lid Glazing: Double polycarbonate glazing of thickness capable of resisting indicated loads; colorless, transparent.
 7. Hardware: Manufacturer's standard corrosion resistant; with hinges, hold-open devices, and independent manual-release devices for inside and outside operation of lids.
- B. Safety Railing System: Roof-hatch manufacturer's standard system including rails, clamps, fasteners, safety barrier at railing opening, and accessories required for a complete installation; attached to roof hatch and complying with 29 CFR 1910.23 requirements and authorities having jurisdiction.
1. Height: 42 inches above finished roof deck.
 2. Posts and Rails: Galvanized-steel pipe, 1-1/4 inches in diameter or galvanized-steel tube, 1-5/8 inches in diameter.
 3. Maximum Opening Size: System constructed to prevent passage of a sphere 21 inches in diameter.
 4. Self-Latching Gate: Fabricated of same materials and rail spacing as safety railing system. Provide manufacturer's standard hinges and self-latching mechanism.
 5. Post and Rail Tops and Ends: Weather resistant, closed or plugged with prefabricated end fittings.
 6. Provide weep holes or another means to drain entrapped water in hollow sections of handrail and railing members.
 7. Fabricate joints exposed to weather to be watertight.
 8. Fasteners: Manufacturer's standard, finished to match railing system.
 9. Finish: Manufacturer's standard.
- C. Ladder-Assist Post: Roof-hatch manufacturer's standard device for attachment to roof-access ladder.
1. Operation: Post locks in place on full extension; release mechanism returns post to closed position.
 2. Height: 42 inches above finished roof deck.
 3. Material: Steel tube.
 4. Post: 1-5/8-inch- diameter pipe.
 5. Finish: Manufacturer's standard baked enamel or powder coat.

2.2 METAL MATERIALS

- A. Aluminum Sheet: ASTM B209, manufacturer's standard alloy for finish required, with temper to suit forming operations and performance required.
 1. Mill Finish: As manufactured.
- B. Aluminum Extrusions and Tubes: ASTM B221, manufacturer's standard alloy and temper for type of use, finished to match assembly where used; otherwise mill finished.
- C. Stainless Steel Sheet and Shapes: ASTM A240/A240M or ASTM A666, Type 304.
- D. Steel Shapes: ASTM A36/A36M, hot-dip galvanized according to ASTM A123/A123M unless otherwise indicated.
- E. Steel Tube: ASTM A500/A500M, round tube.
- F. Galvanized-Steel Tube: ASTM A500/A500M, round tube, hot-dip galvanized according to ASTM A123/A123M.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- G. Steel Pipe: ASTM A53/A53M, galvanized.

2.3 MISCELLANEOUS MATERIALS

- A. Provide materials and types of fasteners, protective coatings, sealants, and other miscellaneous items required by manufacturer for a complete installation.
- B. Polycarbonate Glazing: Thermoformable, monolithic polycarbonate sheets manufactured by extrusion process, burglar-resistance rated according to UL 972 with an average impact strength of 12 to 16 ft-lbf/in. of width when tested according to ASTM D256, Method A (Izod).
- C. Glass-Fiber Board Insulation: ASTM C726, nominal density of 3 lb/cu. ft., thermal resistivity of 4.3 deg F x h x sq. ft./Btu x in. at 75 deg F, thickness as indicated.
- D. Wood Nailers: Softwood lumber, pressure treated with waterborne preservatives for aboveground use, acceptable to authorities having jurisdiction, and complying with AWPA C2; not less than 1-1/2 inches thick.
- E. Underlayment:
 - 1. Self-Adhering, High-Temperature Sheet: Minimum 30 to 40 mils thick, consisting of slip-resisting polyethylene-film top surface laminated to layer of butyl or SBS-modified asphalt adhesive, with release-paper backing; cold applied. Provide primer when recommended by underlayment manufacturer.
- F. Fasteners: Roof accessory manufacturer's recommended fasteners suitable for application and metals being fastened. Match finish of exposed fasteners with finish of material being fastened. Provide nonremovable fastener heads to exterior exposed fasteners. Furnish the following unless otherwise indicated:
- G. Gaskets: Manufacturer's standard tubular or fingered design of neoprene, EPDM, PVC, or silicone or a flat design of foam rubber, sponge neoprene, or cork.
- H. Elastomeric Sealant: ASTM C920, elastomeric polymer sealant as recommended by roof accessory manufacturer for installation indicated; low modulus; of type, grade, class, and use classifications required to seal joints and remain watertight.
- I. Butyl Sealant: ASTM C1311, single-component, solvent-release butyl rubber sealant; polyisobutylene plasticized; heavy bodied for expansion joints with limited movement.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Verify dimensions of roof openings for roof accessories. Install roof accessories according to manufacturer's written instructions.
 - 1. Install roof accessories level; plumb; true to line and elevation; and without warping, jogs in alignment, buckling, or tool marks.
 - 2. Anchor roof accessories securely in place so they are capable of resisting indicated loads.
 - 3. Use fasteners, separators, sealants, and other miscellaneous items as required to complete installation of roof accessories and fit them to substrates.
 - 4. Install roof accessories to resist exposure to weather without failing, rattling, leaking, or loosening of fasteners and seals.
 - 5. Attach safety railing system to roof-hatch curb.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

6. Attach ladder-assist post according to manufacturer's written instructions.

B. Metal Protection: Protect metals against galvanic action by separating dissimilar metals from contact with each other or with corrosive substrates by painting contact surfaces with bituminous coating or by other permanent separation as recommended by manufacturer.

1. Coat concealed side of uncoated aluminum roof accessories with bituminous coating where in contact with wood, ferrous metal, or cementitious construction.
2. Underlayment: Where installing roof accessories directly on cementitious or wood substrates, install a course of underlayment and cover with manufacturer's recommended slip sheet.

C. Seal joints with elastomeric sealant as required by roof accessory manufacturer.

3.2 REPAIR AND CLEANING

A. Clean exposed surfaces according to manufacturer's written instructions.

B. Replace roof accessories that have been damaged or that cannot be successfully repaired by finish touchup or similar minor repair procedures.

END OF SECTION 07 72 00

ROOF ALTERATION
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

Copyright 2019 by The American Institute of Architects (AIA)

Exclusively published and distributed by Deltek, Inc. for the AIA

SECTION 07 84 13 - PENETRATION FIRESTOPPING

Revise this Section by deleting and inserting text to meet Project-specific requirements.

Verify that Section titles referenced in this Section are correct for this Project's Specifications; Section titles may have changed.

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Penetration firestopping systems for the following applications:
 - a. Penetrations in fire-resistance-rated walls.
 - b. Penetrations in horizontal assemblies.
 - c. Penetrations in smoke barriers.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Product Schedule: For each penetration firestopping system. Include location, illustration of firestopping system, and design designation of qualified testing and inspecting agency.

Retain "Engineering Judgments" Subparagraph below only after verifying that authorities having jurisdiction will accept modifications handled by method in subparagraph.

- 1. Engineering Judgments: Where Project conditions require modification to a qualified testing and inspecting agency's illustration for a particular penetration firestopping system, submit illustration, with modifications marked, approved by penetration firestopping system manufacturer's fire-protection engineer as an engineering judgment or equivalent fire-resistance-rated assembly. Obtain approval of authorities having jurisdiction prior to submittal.

1.3 CLOSEOUT SUBMITTALS

- A. Installer Certificates: From Installer indicating that penetration firestopping systems have been installed in compliance with requirements and manufacturer's written instructions.

PART 2 - PRODUCTS

Manufacturers and products listed in SpecAgent and MasterWorks Paragraph Builder are neither recommended nor endorsed by the AIA or Deltek. Before inserting names, verify that manufacturers and products listed there comply with requirements retained or revised in descriptions and are both available and suitable for the intended applications. For definitions of terms and requirements for Contractor's product selection, see Section 01 60 00 "Product Requirements."

2.1 PERFORMANCE REQUIREMENTS

- A. Fire-Test-Response Characteristics:
1. Perform penetration firestopping system tests by a qualified testing agency acceptable to authorities having jurisdiction.
 2. Test per testing standards referenced in "Penetration Firestopping Systems" Article. Provide rated systems complying with the following requirements:
 - a. Penetration firestopping systems shall bear classification marking of a qualified testing agency.

Retain only those subparagraphs below that reference the directories of testing and inspecting agency or agencies approved by authorities having jurisdiction.

- 1) UL in its "Fire Resistance Directory."
- 2) Intertek Group in its "Directory of Listed Building Products."
- 3) FM Approval in its "Approval Guide."

2.2 PENETRATION FIRESTOPPING SYSTEMS

- A. Penetration Firestopping Systems: Systems that resist spread of fire, passage of smoke and other gases, and maintain original fire-resistance rating of construction penetrated. Penetration firestopping systems shall be compatible with one another, with the substrates forming openings, and with penetrating items if any.
1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. 3M Fire Protection Products.
 - b. Hilti, Inc.
 - c. Specified Technologies, Inc.
- B. Penetrations in Fire-Resistance-Rated Walls: Penetration firestopping systems with ratings determined per ASTM E814 or UL 1479, based on testing at a positive pressure differential of 0.01-inch wg.

Rating in "F-Rating" Subparagraph below indicates resistance to flame spread.

1. F-Rating: Not less than the fire-resistance rating of constructions penetrated.

- C. Penetrations in Horizontal Assemblies: Penetration firestopping systems with ratings determined per ASTM E814 or UL 1479, based on testing at a positive pressure differential of 0.01-inch wg.

Ratings in "F-Rating" Subparagraph below indicate resistance to flame spread.

1. F-Rating: At least one hour, but not less than the fire-resistance rating of constructions penetrated.

Ratings in "T-Rating" Subparagraph below indicate resistance to excessive thermal transmission.

2. T-Rating: At least one hour, but not less than the fire-resistance rating of constructions penetrated except for floor penetrations within the cavity of a wall.

Ratings in "W-Rating" Subparagraph below indicate resistance to water leakage. W-ratings are not required by the IBC but may be needed if water leakage is a concern.

3. W-Rating: Provide penetration firestopping systems showing no evidence of water leakage when tested according to UL 1479.

ROOF ALTERATION
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

Retain "Penetrations in Smoke Barriers" Paragraph below if smoke barriers are included in Project, and indicate locations on Drawings.

- D. Penetrations in Smoke Barriers: Penetration firestopping systems with ratings determined per UL 1479, based on testing at a positive pressure differential of 0.30-inch wg.

Ratings in "L-Rating" Subparagraph below indicate resistance to air leakage.

- 1. L-Rating: Not exceeding 5.0 cfm/sq. ft. of penetration opening at and no more than 50-cfm cumulative total for any 100 sq. ft. at both ambient and elevated temperatures.
- E. Exposed Penetration Firestopping Systems: Flame-spread and smoke-developed indexes of less than 25 and 450, respectively, per ASTM E84.
- F. Accessories: Provide components for each penetration firestopping system that are needed to install fill materials and to maintain ratings required. Use only those components specified by penetration firestopping system manufacturer and approved by qualified testing and inspecting agency for conditions indicated.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Examine substrates and conditions, with Installer present, for compliance with requirements for opening configurations, penetrating items, substrates, and other conditions affecting performance of the Work.
- B. General: Install penetration firestopping systems to comply with manufacturer's written installation instructions and published drawings for products and applications.
- C. Install forming materials and other accessories of types required to support fill materials during their application and in the position needed to produce cross-sectional shapes and depths required to achieve fire ratings.
 - 1. After installing fill materials and allowing them to fully cure, remove combustible forming materials and other accessories not forming permanent components of firestopping.
- D. Install fill materials by proven techniques to produce the following results:
 - 1. Fill voids and cavities formed by openings, forming materials, accessories and penetrating items to achieve required fire-resistance ratings.
 - 2. Apply materials so they contact and adhere to substrates formed by openings and penetrating items.
 - 3. For fill materials that will remain exposed after completing the Work, finish to produce smooth, uniform surfaces that are flush with adjoining finishes.

3.2 IDENTIFICATION

- A. Wall Identification: Permanently label walls containing penetration firestopping systems with the words "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS," using lettering not less than 3 inches high and with minimum 0.375-inch strokes.
 - 1. Locate in accessible concealed floor, floor-ceiling, or attic space at 15 feet from end of wall and at intervals not exceeding 30 feet.

Retain "Penetration Identification" Paragraph below if required. Individual joint penetration labeling may not be required by authorities having jurisdiction if wall is identified, but labeling is useful if penetration firestopping systems must be replaced.

ROOF ALTERATION
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Penetration Identification: Identify each penetration firestopping system with legible metal or plastic labels. Attach labels permanently to surfaces adjacent to and within 6 inches of penetration firestopping system edge so labels are visible to anyone seeking to remove penetrating items or firestopping systems. Use mechanical fasteners or self-adhering-type labels with adhesives capable of permanently bonding labels to surfaces on which labels are placed. Include the following information on labels:
1. The words "Warning - Penetration Firestopping - Do Not Disturb. Notify Building Management of Any Damage."
 2. Contractor's name, address, and phone number.
 3. Designation of applicable testing and inspecting agency.
 4. Date of installation.
 5. Manufacturer's name.
 6. Installer's name.

3.3 FIELD QUALITY CONTROL

If required, inspection of penetration firestopping systems in this article is performed according to ASTM E2174, "On-Site Inspection of Installed Fire Stops." To prevent conflicts of interest, ASTM E2174 precludes making Contractor responsible for engaging the testing agency. Inspectors may verify compliance by destructive examination of some completed installations.

- A. Owner reserves the right to engage a qualified testing agency to perform tests and inspections according to ASTM E2174.
- B. Where deficiencies are found or penetration firestopping system is damaged or removed because of testing, repair or replace penetration firestopping system to comply with requirements.
- C. Proceed with enclosing penetration firestopping systems with other construction only after inspection reports are issued and installations comply with requirements.

END OF SECTION 07 84 13

SECTION 07 92 00 - JOINT SEALANTS

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Joint sealant systems.

1.2 ACTION SUBMITTALS

- A. Product data.
- B. Samples: Manufacturer's standard color charts consisting of strips of cured sealants showing the full range of colors available for each product exposed to view.
- C. Joint-sealant schedule.

PART 2 - PRODUCTS

2.1 JOINT SEALANTS, GENERAL

- A. Compatibility: Provide joint sealants, backings, and other related materials that are compatible with one another and with joint substrates under conditions of service and application, as demonstrated by joint-sealant manufacturer, based on testing and field experience.
- B. Colors of Exposed Joint Sealants: As selected by Architect from manufacturer's full range.

2.2 NONSTAINING SILICONE JOINT SEALANTS

- A. Nonstaining Joint Sealants: No staining of substrates when tested in accordance with ASTM C1248.
- B. Silicone, Nonstaining, S, NS, 100/50, NT: Nonstaining, single-component, nonsag, plus 100 percent and minus 50 percent movement capability, nontraffic-use, neutral-curing silicone joint sealant; ASTM C920, Type S, Grade NS, Class 100/50, Use NT.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Pecora Corporation.
 - b. Sika Corporation.
 - c. Tremco Incorporated.
- C. Silicone, Nonstaining, S, NS, 50, NT: Nonstaining, single-component, nonsag, plus 50 percent and minus 50 percent movement capability, nontraffic-use, neutral-curing silicone joint sealant; ASTM C920, Type S, Grade NS, Class 50, Use NT.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. GE Construction Sealants; Momentive Performance Materials Inc.
 - b. Pecora Corporation.
 - c. Sika Corporation.
 - d. The Dow Chemical Company.
 - e. Tremco Incorporated.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

2.3 URETHANE JOINT SEALANTS

- A. Urethane, S, NS, 25, NT: Single-component, nonsag, nontraffic-use, plus 25 percent and minus 25 percent movement capability, urethane joint sealant; ASTM C920, Type S, Grade NS, Class 25, Use NT.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Everkem Diversified Products, Inc.
 - b. Master Builders Solutions.
 - c. Pecora Corporation.
 - d. Polymeric Systems, Inc.
 - e. Sherwin-Williams Company (The).
 - f. Sika Corporation.
 - g. Tremco Incorporated.

2.4 MILDEW-RESISTANT JOINT SEALANTS

- A. Mildew-Resistant Joint Sealants: Formulated for prolonged exposure to humidity with fungicide to prevent mold and mildew growth.
- B. Silicone, Mildew Resistant, Acid Curing, S, NS, 25, NT: Mildew-resistant, single-component, nonsag, plus 25 percent and minus 25 percent movement capability, nontraffic-use, acid-curing silicone joint sealant; ASTM C920, Type S, Grade NS, Class 25, Use NT.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. GE Construction Sealants; Momentive Performance Materials Inc.
 - b. Pecora Corporation.
 - c. The Dow Chemical Company.
 - d. Tremco Incorporated.

2.5 LATEX JOINT SEALANTS

- A. Acrylic Latex: Acrylic latex or siliconized acrylic latex, ASTM C834, Type OP, Grade NF.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Everkem Diversified Products, Inc.
 - b. Franklin International.
 - c. Pecora Corporation.
 - d. Sherwin-Williams Company (The).
 - e. Tremco Incorporated.

2.6 JOINT-SEALANT BACKING

- A. Sealant Backing Material, General: Nonstaining; compatible with joint substrates, sealants, primers, and other joint fillers; and approved for applications indicated by sealant manufacturer based on field experience and laboratory testing.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Alcot Plastics Ltd.
 - b. Master Builders Solutions.
- B. Cylindrical Sealant Backings: ASTM C1330, Type C (closed-cell material with a surface skin), and of size and density to control sealant depth and otherwise contribute to producing optimum sealant performance.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- C. Bond-Breaker Tape: Polyethylene tape or other plastic tape recommended by sealant manufacturer for preventing sealant from adhering to rigid, inflexible joint-filler materials or joint surfaces at back of joint. Provide self-adhesive tape where applicable.

2.7 MISCELLANEOUS MATERIALS

- A. Primer: Material recommended by joint-sealant manufacturer where required for adhesion of sealant to joint substrates indicated, as determined from preconstruction joint-sealant-substrate tests and field tests.
- B. Cleaners for Nonporous Surfaces: Chemical cleaners acceptable to manufacturers of sealants and sealant backing materials, free of oily residues or other substances capable of staining or harming joint substrates and adjacent nonporous surfaces in any way, and formulated to promote optimum adhesion of sealants to joint substrates.
- C. Masking Tape: Nonstaining, nonabsorbent material compatible with joint sealants and surfaces adjacent to joints.

PART 3 - EXECUTION

3.1 PREPARATION

- A. Surface Cleaning of Joints: Clean out joints immediately before installing joint sealants to comply with joint-sealant manufacturer's written instructions and the following requirements:
 - 1. Remove all foreign material from joint substrates that could interfere with adhesion of joint sealant, including dust, paints (except for permanent, protective coatings tested and approved for sealant adhesion and compatibility by sealant manufacturer), old joint sealants, oil, grease, waterproofing, water repellents, water, surface dirt, and frost.
 - 2. Clean porous joint substrate surfaces by brushing, grinding, mechanical abrading, or a combination of these methods to produce a clean, sound substrate capable of developing optimum bond with joint sealants. Remove loose particles remaining after cleaning operations above by vacuuming or blowing out joints with oil-free compressed air. Porous joint substrates include the following:
 - a. Concrete.
 - b. Masonry.
 - 3. Clean nonporous joint substrate surfaces with chemical cleaners or other means that do not stain, harm substrates, or leave residues capable of interfering with adhesion of joint sealants. Nonporous joint substrates include the following:
 - a. Metal.
- B. Joint Priming: Prime joint substrates where recommended by joint-sealant manufacturer or as indicated by preconstruction joint-sealant-substrate tests or prior experience. Apply primer to comply with joint-sealant manufacturer's written instructions. Confine primers to areas of joint-sealant bond; do not allow spillage or migration onto adjoining surfaces.
- C. Masking Tape: Use masking tape where required to prevent contact of sealant or primer with adjoining surfaces that otherwise would be permanently stained or damaged by such contact or by cleaning methods required to remove sealant smears. Remove tape immediately after tooling without disturbing joint seal.

3.2 INSTALLATION OF JOINT SEALANTS

- A. General: Comply with joint-sealant manufacturer's written installation instructions for products and applications indicated, unless more stringent requirements apply.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Sealant Installation Standard: Comply with recommendations in ASTM C1193 for use of joint sealants as applicable to materials, applications, and conditions indicated.
- C. Install sealant backings of type indicated to support sealants during application and at position required to produce cross-sectional shapes and depths of installed sealants relative to joint widths that allow optimum sealant movement capability.
 - 1. Do not leave gaps between ends of sealant backings.
 - 2. Do not stretch, twist, puncture, or tear sealant backings.
 - 3. Remove absorbent sealant backings that have become wet before sealant application, and replace them with dry materials.
- D. Install bond-breaker tape behind sealants where sealant backings are not used between sealants and backs of joints.
- E. Install sealants using proven techniques that comply with the following and at the same time backings are installed:
 - 1. Place sealants so they directly contact and fully wet joint substrates.
 - 2. Completely fill recesses in each joint configuration.
 - 3. Produce uniform, cross-sectional shapes and depths relative to joint widths that allow optimum sealant movement capability.
- F. Tooling of Nonsag Sealants: Immediately after sealant application and before skinning or curing begins, tool sealants according to requirements specified in subparagraphs below to form smooth, uniform beads of configuration indicated; to eliminate air pockets; and to ensure contact and adhesion of sealant with sides of joint.
 - 1. Remove excess sealant from surfaces adjacent to joints.
 - 2. Use tooling agents that are approved in writing by sealant manufacturer and that do not discolor sealants or adjacent surfaces.
 - 3. Provide concave joint profile in accordance with Figure 8A in ASTM C1193 unless otherwise indicated.
- G. Clean off excess sealant or sealant smears adjacent to joints as the Work progresses by methods and with cleaning materials approved in writing by manufacturers of joint sealants and of products in which joints occur.
- H. Protect joint sealants during and after curing period from contact with contaminating substances and from damage resulting from construction operations or other causes so sealants are without deterioration or damage at time of Substantial Completion. If, despite such protection, damage or deterioration occurs, cut out, remove, and repair damaged or deteriorated joint sealants immediately so installations with repaired areas are indistinguishable from original work.

3.3 JOINT-SEALANT SCHEDULE

- A. Exterior joints in vertical surfaces and horizontal nontraffic surfaces:
 - 1. Joint Locations including but not limited to the following:
 - a. Joints between stone parapet coping units.
 - b. Control and expansion joints in unit masonry.
 - c. Other joints as indicated on Drawings.
 - 2. Joint Sealant: Silicone, nonstaining, S, NS, 50, NT.
- B. Interior joints in vertical surfaces and horizontal nontraffic surfaces:
 - 1. Joint Sealant: Urethane, S, NS, 25, NT.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- C. Interior joints in vertical surfaces and horizontal nontraffic surfaces not subject to significant movement:
 - 1. Joint Sealant: Acrylic latex.

- D. Mildew-resistant interior joints in vertical surfaces and horizontal nontraffic surfaces:
 - 1. Joint Locations include but are not limited to:
 - a. Joints in food service preparation areas.
 - b. Other joints as indicated on Drawings.
 - 2. Joint Sealant: Silicone, mildew resistant, acid curing, S, NS, 25, NT.

END OF SECTION 07 92 00

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

Copyright 2021 by The American Institute of Architects (AIA)

Exclusively published and distributed by Deltek, Inc. for the AIA

SECTION 08 63 00 - METAL-FRAMED SKYLIGHTS

Revise this Section by deleting and inserting text to meet Project-specific requirements.

MasterSpec includes provisions for LEED 2009, LEED v4, IgCC, and Green Globes. Sustainable design requirements may be inserted in the Section Text using the hypertext links.

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes metal-framed skylights.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Shop Drawings: For metal-framed skylights. Include plans, elevations, sections, and attachment details.
- C. Samples: For each type of exposed finish required, in manufacturer's standard sizes.

1.3 INFORMATIONAL SUBMITTALS

- A. Sample warranties.

1.4 WARRANTY

- A. Manufacturer's Warranty: Manufacturer agrees to repair or replace components of metal-framed skylights that fail in materials or workmanship within specified warranty period.

Verify available warranties and warranty periods for assemblies with manufacturers listed in Part 2.

- 1. Warranty Period: Two years from date of Substantial Completion.
- B. Special Finish Warranty, Anodized Finishes: Standard form in which manufacturer agrees to repair finishes or replace aluminum that shows evidence of deterioration of anodized finishes within specified warranty period.

Coordinate "Warranty Period" Subparagraph below with "Aluminum Finishes" Article. Five years is standard for Class I anodized finishes. Class II anodized finishes often carry less than a five-year warranty. Verify available warranties and warranty periods for finishes.

- 1. Warranty Period: 5 years from date of Substantial Completion.

PART 2 - PRODUCTS

Manufacturers and products listed in this Section are neither recommended nor endorsed by the AIA or Deltek. Before selecting manufacturers and products, verify availability, suitability for intended

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

applications, and compliance with minimum performance requirements. For definitions of terms and requirements for Contractor's product selection, see Section 01 60 00 "Product Requirements."

Product options commonly available from manufacturers are included in square brackets throughout the Section Text. Not every manufacturer listed can provide every option offered; verify availability with manufacturers. For definitions of terms and requirements for Contractor's product selection, see Section 01 60 00 "Product Requirements."

2.1 PERFORMANCE REQUIREMENTS

- A. Structural Loads: As required by Code.
- B. Deflection of Framing Members: At design wind pressure, as follows:

Depending on Project conditions, more stringent deflection criteria than specified in "Deflection Normal to Glazing Plane" and "Deflection Parallel to Glazing Plane" subparagraphs below may be required; see "Seismic Loads" Article in the Evaluations. First option in first subparagraph is based on recommendations in the IBC for framing members supporting glass. Second option is based on recommendations in AAMA TIR-A11.

- 1. Deflection Normal to Glazing Plane: Limited to edge of glass in a direction perpendicular to glass plane not exceeding $L/175$ of the glass edge length for each individual glazing lite or an amount that restricts edge deflection of individual glazing lites to $3/4$ inch, whichever is less.

First option in "Deflection Parallel to Glazing Plane" Subparagraph below is based on typical deflection criteria for glass. Second option is based on GANA's "Glazing Manual."

- 2. Deflection Parallel to Glazing Plane: Limited to $L/360$ of clear span or $1/8$ inch, whichever is smaller.

Usually retain "Lateral Bracing of Framing Members" Paragraph below. AAMA SDGS-1, "Structural Design Guidelines for Aluminum Framed Skylights," states that manufacturers sometimes assume glazing material provides continuous lateral bracing and base their designs on unbraced lengths equal to zero.

- C. Lateral Bracing of Framing Members: Compression flanges of flexural members are laterally braced by cross members with minimum depth equal to 50 percent of flexural member that is braced. Glazing does not provide lateral support.
- D. Structural-Test Performance: Metal-framed skylights tested in accordance with ASTM E330, as follows:
 - 1. When tested at positive and negative wind-load design pressures, assemblies do not evidence deflection exceeding specified deflection limits.
 - 2. When tested at 150 percent of positive and negative wind-load design pressures, assemblies, including anchorage, do not evidence material failures, structural distress, and permanent deformation of main framing members exceeding 0.2 percent of span.
 - 3. Test Durations: As required by design wind velocity, but not less than 10 seconds.

Retain "Windborne-Debris Impact Resistance" Paragraph below to suit Project. The IBC establishes criteria for buildings in hurricane-prone locations. In paragraph, "enhanced" option applies to essential facilities and has additional requirements. Verify requirements of authorities having jurisdiction. Verify which manufacturers have tested products and can demonstrate compliance.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

Usually retain "Air Leakage" Paragraph below. ASTM E283 requires using a static-air-pressure difference of 1.57 lbf/sq. ft. (75 Pa) unless otherwise indicated, which is equivalent to a 25-mph (40-km/h) wind. Static-air-pressure difference of 6.24 lbf/sq. ft. (300 Pa) is equivalent to a 50-mph (80-km/h) wind.

- E. Air Leakage: Metal-framed skylights with maximum air leakage through fixed glazing and framing areas of 0.06 cfm/sq. ft. of when tested in accordance with ASTM E283 at a minimum static-air-pressure difference of 6.24 lbf/sq. ft..

Usually retain "Water Penetration under Static Pressure" Paragraph below. For water-penetration under static pressure tests, air-pressure difference of 20 percent of wind-load design pressure provides satisfactory performance in most parts of the U.S. Locations where high winds and heavy rains frequently occur simultaneously require higher test-pressure differences. Lower test-pressure differences are acceptable for some locations. Revise paragraph to suit Project.

- F. Water Penetration under Static Pressure: Metal-framed skylights that do not evidence water penetration through fixed glazing and framing areas when tested in accordance with ASTM E331 at a minimum static-air-pressure difference of 20 percent of positive wind-load design pressure, but not less than 6.24 lbf/sq. ft..
- G. Thermal Movements: Allow for thermal movements from ambient and surface temperature changes.

Differential values in "Temperature Change" Subparagraph below (for aluminum in particular) are suitable for most of the U.S.

- 1. Temperature Change: 120 deg F, ambient; 180 deg F, material surfaces.

Retain "Condensation Resistance" Paragraph below if required and insert condensation-resistance factor (CRF) needed for Project; options are examples only.

- H. Condensation Resistance: Metal-framed skylights with fixed glazing and framing areas having condensation-resistance factor (CRF) of not less than 45 when tested in accordance with AAMA 1503.

Retain "Haze Factor" Subparagraph below if required to diffuse direct sunlight.

Retain "Energy Performance" Paragraph below if required and insert U-factor and solar heat gain coefficient needed for Project; options are examples only.

- I. Energy Performance: Provide metal-framed skylights with performance properties specified, as indicated in manufacturer's published test data, based on procedures indicated below:
 - 1. Thermal Transmittance (U-Factor): Fixed glazing and framing areas have U-factor of not more than 0.28 Btu/sq. ft. x h x deg F as determined in accordance with NFRC 100.
 - 2. Solar Heat Gain Coefficient: Fixed glazing and framing areas have a solar heat gain coefficient of no greater than 0.25 as determined in accordance with NFRC 200.

2.2 METAL-FRAMED SKYLIGHTS

- A. Metal-Framed Skylights: Glazed skylight assemblies supported by aluminum framing.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. CPI Daylighting, Inc.
 - b. Kawneer Company, Inc.; Arconic Corporation.
 - c. Linel; Mestek, Inc.
 - d. Oldcastle BuildingEnvelope (OBE); CRH Americas, Inc.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- e. Super Sky Products Enterprises, LLC.
- B. Aluminum Framing Systems: Manufacturer's standard extruded-aluminum members of thickness required and reinforced as required to support imposed loads.
- C. Aluminum: Alloy and temper as recommended in writing by manufacturer for type of use and finish indicated.
 - 1. Sheet and Plate: ASTM B209.
 - 2. Extruded Bars, Rods, Profiles, and Tubes: ASTM B221.
 - 3. Extruded Structural Pipe and Tubes: ASTM B429/B429M.
 - 4. Structural Profiles: ASTM B308/B308M.
- D. Pressure Caps: Manufacturer's standard aluminum components that mechanically retain glazing.
 - 1. Include snap-on aluminum trim that conceals fasteners.
- E. Brackets and Reinforcements: Manufacturer's standard high-strength aluminum with nonstaining, nonferrous shims for aligning skylight components.
- F. Fasteners and Accessories: Manufacturer's standard, corrosion-resistant, nonstaining, nonbleeding fasteners and accessories compatible with adjacent materials.
- G. Concealed Flashing: Manufacturer's standard, corrosion-resistant, nonstaining, nonbleeding flashing compatible with adjacent materials.
- H. Exposed Flashing and Closures: Manufacturer's standard aluminum components not less than 0.040 inch thick.
- I. Framing Sealants: As recommended in writing by manufacturer.
- J. Corrosion-Resistant Coating: Cold-applied asphalt mastic.

2.3 GLAZING

- A. Glazing: As specified in Section 08 80 00 "Glazing."
- B. Glazing Gaskets: Manufacturer's standard sealed-corner pressure-glazing system of black, resilient elastomeric glazing gaskets, setting blocks, and shims or spacers.
- C. Spacers and Setting Blocks: Manufacturer's standard elastomeric types.
- D. Glazing Sealants: As recommended in writing by manufacturer.

2.4 FABRICATION

- A. Fabricate aluminum components that, when assembled, have the following characteristics:
 - 1. Profiles that are sharp, straight, and free of defects or deformations.
 - 2. Accurately fitted joints with ends coped or mitered.
 - 3. Physical and thermal isolation of glazing from framing members.
 - 4. Accommodations for thermal and mechanical movements of glazing and framing to maintain required glazing edge clearances.
- B. Fabricate aluminum sill closures with weep holes and for installation as continuous component.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- C. Reinforce aluminum components as required to receive fastener threads.

Retain "Factory-Glazed, Metal-Framed Skylights" Paragraph below for factory-glazed, metal-framed skylights. Many manufacturers factory assemble and glaze metal-framed skylights in whole or in part, then ship them to the site as a complete assembly or as partially assembled components.

- D. After fabrication, clearly mark components to identify their locations in Project in accordance with Shop Drawings.

2.5 ALUMINUM FINISHES

Retain finishes in this article to suit Project. If retaining more than one, indicate location of each on Drawings or by inserts.

Retain one of two options in "Clear Anodic Finish" Paragraph below. Verify availability with manufacturers.

- A. Clear Anodic Finish: AAMA 611, AA-M12C22A41, Class I, 0.018 mm or thicker.

Retain one of two options in "Color Anodic Finish" Paragraph below. Verify availability with manufacturers.

"Baked-Enamel or Powder-Coat Finish" Paragraph below references AAMA standard for pigmented organic coating on aluminum extrusions and panels.

Retain "High-Performance Organic Finish, Two-Coat PVDF," "Superior-Performance Organic Finish, Three-Coat PVDF," "Superior-Performance Organic Finish, Four-Coat PVDF," "Superior-Performance Organic Finish, Single-Coat FEVE," or "Superior-Performance Organic Finish, Two-Coat FEVE" Paragraph below; if more than one finish is required, indicate location of each system on Drawings, in schedules, or by inserts. Coordinate finish system selected with special finish warranty period specified in Part 1 "Warranty" Article.

In "High-Performance Organic Finish, Two-Coat PVDF" Paragraph below, retain AAMA 2604 with 50 percent resin content by weight in color coat or AAMA 2605 with 70 percent resin content by weight in color coat for high-performance organic coatings on extrusions and panels. If specific products are required, name coating manufacturers and products.

"Superior-Performance Organic Finish, Single-Coat FEVE" Paragraph below is not suitable for seacoast and severe environments.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. General: Comply with manufacturer's written instructions.
 1. Do not install damaged components.
 2. Fit joints between aluminum components to produce hairline joints free of burrs and distortion.
 3. Rigidly secure nonmovement joints.
 4. Install anchors with separators and isolators to prevent metal corrosion and electrolytic deterioration and to prevent impeding movement of moving joints.
 5. Seal joints watertight unless otherwise indicated.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- B. Metal Protection: Where aluminum will contact dissimilar materials, protect against galvanic action by painting contact surfaces with protective coating or by installing nonconductive spacers as recommended in writing by manufacturer for this purpose.
- C. Install continuous aluminum sill closure with weatherproof expansion joints and locked and sealed or welded corners. Locate weep holes at rafters.
- D. Install components to drain water passing joints, and moisture migrating within skylight to exterior.
- E. Install components plumb and true in alignment with established lines and elevations.
- F. Glazing: Install glazing as specified in Section 08 80 00 "Glazing."
- G. Erection Tolerances: Install metal-framed skylights to comply with the following maximum tolerances:

Erection tolerances in "Alignment" and "Location and Plane" subparagraphs below are examples only and are based on manufacturers' literature. Coordinate with tolerances for support systems and revise to suit Project.

- 1. Alignment: Limit offset from true alignment to 1/32 inch where surfaces abut in line, edge to edge, at corners, or where a reveal or protruding element separates aligned surfaces by less than 3 inches; otherwise, limit offset to 1/8 inch.
- 2. Location and Plane: Limit variation from true location and plane to 1/8 inch in 12 feet but no greater than 1/2 inch over total length.

3.2 FIELD QUALITY CONTROL

Retain "Testing Agency" Paragraph below to identify who performs tests and inspections. If retaining second option in paragraph, retain "Field quality-control reports" Paragraph in "Informational Submittals" Article.

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections.

Generally retain inexpensive test in "Water-Spray Test" Subparagraph below to check skylights' resistance to water penetration. Insert test area requirements to suit Project.

- 1. Water-Spray Test: Skylights shall be tested in accordance with AAMA 501.2 and shall not evidence water penetration.
- B. Repair or remove work where test results and inspections indicate that it does not comply with specified requirements.
- C. Additional testing and inspecting, at Contractor's expense, will be performed to determine compliance of replaced or additional work with specified requirements.
- D. Prepare test and inspection reports.

END OF SECTION 08 63 00

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

Copyright 2020 by The American Institute of Architects (AIA)

Exclusively published and distributed by Deltek, Inc. for the AIA

SECTION 08 80 00 - GLAZING

Revise this Section by deleting and inserting text to meet Project-specific requirements.

MasterSpec includes provisions for LEED 2009, LEED v4, IgCC, and Green Globes. Sustainable design requirements may be inserted in the Section Text using the hypertext links.

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Skylight glass and glazing.

1.2 COORDINATION

- A. Coordinate glazing channel dimensions to provide necessary bite on glass, minimum edge and face clearances, and adequate sealant thicknesses, with reasonable tolerances to achieve proper safety margins for glazing retention under each design load case, load case combination, and service condition.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Glass Samples: For each type of glass product other than clear monolithic vision glass; 12 inches square.

Retain "Delegated Design Submittal" Paragraph below if design services have been delegated to Contractor.

- C. Delegated Design Submittal: For glass indicated to comply with performance requirements and design criteria, including analysis data signed and sealed by qualified professional engineer responsible for their preparation.

1.4 INFORMATIONAL SUBMITTALS

- A. Product Certificates: For glass.
- B. Sample warranties.

1.5 WARRANTY

"Manufacturer's Special Warranty for Coated-Glass Products," "Manufacturer's Special Warranty for Laminated Glass," and "Manufacturer's Special Warranty for Insulating Glass" paragraphs below are examples only.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- A. Manufacturer's Special Warranty for Laminated Glass: Manufacturer agrees to replace laminated-glass units that deteriorate within specified warranty period. Deterioration of laminated glass is defined as defects developed from normal use that are not attributed to glass breakage or to maintaining and cleaning laminated glass contrary to manufacturer's written instructions. Defects include edge separation, delamination materially obstructing vision through glass, and blemishes exceeding those allowed by referenced laminated-glass standard.

Verify available warranties and warranty periods with manufacturers listed in Part 2 articles. Revise "Warranty Period" Subparagraph below if glass manufacturers insist on warranty beginning on date of manufacture. See the Evaluations.

1. Warranty Period: 10 years from date of Substantial Completion.

- B. Manufacturer's Special Warranty for Insulating Glass: Manufacturer agrees to replace insulating-glass units that deteriorate within specified warranty period. Deterioration of insulating glass is defined as failure of hermetic seal under normal use that is not attributed to glass breakage or to maintaining and cleaning insulating glass contrary to manufacturer's written instructions. Evidence of failure is obstruction of vision by dust, moisture, or film on interior surfaces of glass.

Verify available warranties and warranty periods with manufacturers listed in Part 2 articles. Revise "Warranty Period" Subparagraph below if glass manufacturers insist on warranty beginning on date of manufacture. See the Evaluations.

1. Warranty Period: 10 years from date of Substantial Completion.

Possibly insert glazier's warranty covering labor to replace insulating-glass units or, as an alternative, a maintenance contract that incorporates unit prices for replacement labor.

PART 2 - PRODUCTS

Manufacturers and products listed in this Section are neither recommended nor endorsed by the AIA or Deltek. Before selecting manufacturers and products, verify availability, suitability for intended applications, and compliance with minimum performance requirements. For definitions of terms and requirements for Contractor's product selection, see Section 01 60 00 "Product Requirements."

Product options commonly available from manufacturers are included in square brackets throughout the Section Text. Not every manufacturer listed can provide every option offered; verify availability with manufacturers. For definitions of terms and requirements for Contractor's product selection, see Section 01 60 00 "Product Requirements."

2.1 PERFORMANCE REQUIREMENTS

Retain "Delegated Design" Paragraph below if Contractor is required to assume responsibility for design.

- A. Structural Performance: Glazing shall withstand the following design loads within limits and under conditions indicated determined in accordance with the IBC and ASTM E1300:

Retain "Design Wind Pressures" Subparagraph below. The IBC requires that design wind pressures used for design of exterior components and cladding not designed by the registered design professional be indicated on the Construction Documents.

1. Design Wind Pressures: As required by Code.

Retain "Design Snow Loads" Subparagraph below if sloped glazing is exposed to snow loads. The IBC requires that flat-roof snow load be indicated on the Construction Documents if ground snow load exceeds 10 lbf/sq. ft. (0.479 kN/sq. m).

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

2. Design Snow Loads: As required by Code.

"Thermal Loads" Subparagraph below applies primarily to tinted and spandrel glass because of its heat-absorbing properties. ASTM E1300 and the IBC do not address this concern.

3. Thermal Loads: Design glazing to resist thermal stress breakage induced by differential temperature conditions and limited air circulation within individual glass lites and insulated glazing units.

Retain "Windborne-Debris-Impact Resistance" Paragraph below to suit Project. The IBC establishes criteria for buildings in hurricane-prone locations. In paragraph, "enhanced" option applies to essential facilities and has additional requirements. Verify requirements of authorities having jurisdiction. Verify which manufacturers have tested products and can demonstrate compliance.

- B. Safety Glazing: Provide glazing that complies with 16 CFR 1201, Category II.
- C. Thermal and Optical Performance Properties: Provide glass with performance properties specified, as indicated in manufacturer's published test data, based on procedures indicated below:
 1. U-Factors: Center-of-glazing values, in accordance with NFRC 100 and based on most current non-beta version of LBL's WINDOW computer program, expressed as Btu/sq. ft. x h x deg F.
 2. SHGC and Visible Transmittance: Center-of-glazing values, in accordance with NFRC 200 and based on most current non-beta version of LBL's WINDOW computer program.
 3. Visible Reflectance: Center-of-glazing values, in accordance with NFRC 300.

Retain "Acoustic Performance" Paragraph below to suit Project.

2.2 GLASS PRODUCTS, GENERAL

- A. Glazing Publications: Comply with published recommendations of glass product manufacturers and organizations below unless more stringent requirements are indicated. See these publications for glazing terms not otherwise defined in this Section or in referenced standards.

Retain "NGA Publications," "AAMA Publications," "IGMA Publication for Sloped Glazing," and "IGMA Publication for Insulating Glass" subparagraphs below that apply to glass products specified.

1. NGA Publications: "Laminated Glazing Reference Manual" and "Glazing Manual."
2. AAMA Publications: AAMA GDSG-1, "Glass Design for Sloped Glazing," and AAMA TIR A7, "Sloped Glazing Guidelines."
3. IGMA Publication for Sloped Glazing: IGMA TB-3001, "Guidelines for Sloped Glazing."
4. IGMA Publication for Insulating Glass: SIGMA TM-3000, "North American Glazing Guidelines for Sealed Insulating Glass Units for Commercial and Residential Use."

Retain "Safety Glazing Labeling" Paragraph below if applicable and if labeling is required. Not all manufacturers participate in third-party testing programs.

- B. Safety Glazing Labeling: Permanently mark glazing with certification label of the SGCC or another certification agency acceptable to authorities having jurisdiction. Label shall indicate manufacturer's name, type of glass, thickness, and safety glazing standard with which glass complies.

Delete "Insulating-Glass Certification Program" Paragraph below if no insulating glass. Not all manufacturers participate in program; see the IGCC directory for participants. Verify that types of units required are certified.

- C. Insulating-Glass Certification Program: Permanently marked either on spacers or on at least one component lite of units with appropriate certification label of the IGCC.
- D. Thickness: Where glass thickness is indicated, it is a minimum.[Provide glass that complies with performance requirements and is not less than thickness indicated.]

2.3 GLASS PRODUCTS

Retain paragraphs in this article that apply to monolithic-, laminated-, and insulating-glass types specified.

Retain "Clear Annealed Float Glass" Paragraph below even if plain, clear float glass is not required; other paragraphs in this article and in glass types articles depend on below for definition of "clear float glass."

Retain option in "Low-Iron Annealed Float Glass" Paragraph below if required for passive solar design.

Retain "Fully Tempered Float Glass" Paragraph below even if plain, tempered float glass is not required; other paragraphs in this article and glass types articles depend on below for definition of "fully tempered float glass." Always retain paragraph if Contractor is responsible for determining glass thickness and strength.

- A. Fully Tempered Float Glass: ASTM C1048, Kind FT (fully tempered), Condition A (uncoated) unless otherwise indicated, Type I, Class 1 (clear) or Class 2 (tinted) as indicated, Quality-Q3.

Retain "Heat-Strengthened Float Glass" Paragraph below even if plain, heat-strengthened float glass is not required but other paragraphs in this article and glass types articles depend on below for definition of "heat-strengthened float glass." Always retain paragraph if Contractor is responsible for determining glass thickness and strength.

In "Silicone-Coated Spandrel Glass" Paragraph below, coating is an elastomeric paint and is less expensive than ceramic coating. Silicone coating is typically more uneven than ceramic coating and frequently contains pinholes; however, these irregularities are generally not visible from typical viewing distances because of lack of illumination in the space behind spandrel glass. Silicone coating is more readily available in custom colors and may provide fallout resistance.

Retain "Windborne-Debris-Impact-Resistant Laminated Glass" Paragraph below if retaining "Windborne-Debris-Impact Resistance" Paragraph in "Performance Requirements" Article.

2.4 INSULATING GLASS

- A. Insulating-Glass Units: Factory-assembled units consisting of sealed lites of glass separated by a dehydrated interspace, qualified in accordance with ASTM E2190.

Retain one of five options in "Sealing System" Subparagraph below or insert other combinations; coordinate with manufacturers and products.

1. Sealing System: Dual seal, with manufacturer's standard primary and secondary sealants.

If retaining a specific spacer material, coordinate options in "Perimeter Spacer" Subparagraph below with manufacturers and products.

2. Perimeter Spacer: Manufacturer's standard spacer material and construction.

Revise "Desiccant" Subparagraph below if a specific type of desiccant is required.

3. Desiccant: Molecular sieve or silica gel, or a blend of both.

PART 3 - EXECUTION

3.1 GLAZING, GENERAL

- A. Comply with combined written instructions of manufacturers of glass, sealants, gaskets, and other glazing materials, unless more stringent requirements are indicated, including those in referenced glazing publications.
- B. Protect glass edges from damage during handling and installation. Remove damaged glass from Project site and legally dispose of off Project site. Damaged glass includes glass with edge damage or other imperfections that, when installed, could weaken glass, impair performance, or impair appearance.
- C. Apply primers to joint surfaces where required for adhesion of sealants, as determined by preconstruction testing.
- D. Install setting blocks in sill rabbets, sized and located to comply with referenced glazing publications, unless otherwise required by glass manufacturer. Set blocks in thin course of compatible sealant suitable for heel bead.
- E. Do not exceed edge pressures stipulated by glass manufacturers for installing glass lites.
- F. Provide spacers for glass lites where length plus width is larger than 50 inches.
- G. Provide edge blocking where needed to prevent glass lites from moving sideways in glazing channel, as recommended in writing by glass manufacturer and in accordance with requirements in referenced glazing publications.

3.2 GASKET GLAZING (DRY)

- A. Cut compression gaskets to lengths recommended by gasket manufacturer to fit openings exactly, with allowance for stretch during installation.
- B. Insert soft compression gasket between glass and frame or fixed stop so it is securely in place with joints miter cut and bonded together at corners.
- C. Installation with Drive-in Wedge Gaskets: Center glass lites in openings on setting blocks, and press firmly against soft compression gasket by inserting dense compression gaskets formed and installed to lock in place against faces of removable stops. Start gasket applications at corners and work toward centers of openings. Compress gaskets to produce a weathertight seal without developing bending stresses in glass. Seal gasket joints with sealant recommended in writing by gasket manufacturer.
- D. Installation with Pressure-Glazing Stops: Center glass lites in openings on setting blocks, and press firmly against soft compression gasket. Install dense compression gaskets and pressure-glazing stops, applying pressure uniformly to compression gaskets. Compress gaskets to produce a weathertight seal without developing bending stresses in glass. Seal gasket joints with sealant recommended in writing by gasket manufacturer.

ROOF ALTERATIONS
WEST MIDDLE SCHOOL
ROCKFORD PUBLIC SCHOOLS 205
ROCKFORD, ILLINOIS

- E. Install gaskets so they protrude past face of glazing stops.

3.3 CLEANING AND PROTECTION

- A. Immediately after installation, remove nonpermanent labels and clean surfaces.
- B. Protect glass from contact with contaminating substances resulting from construction operations. Examine glass surfaces adjacent to or below exterior concrete and other masonry surfaces at frequent intervals during construction, but not less than once a month, for buildup of dirt, scum, alkaline deposits, or stains.
 - 1. If, despite such protection, contaminating substances do contact with glass, remove substances immediately as recommended in writing by glass manufacturer. Remove and replace glass that cannot be cleaned without damage to coatings.
- C. Remove and replace glass that is damaged during construction period.

3.4 INSULATING-LAMINATED-GLASS SCHEDULE

Glass types in this article are primarily for sloped glazing and glazing that is required to be windborne-debris-impact resistant.

Copy paragraphs below and re-edit for each product.

Insert drawing designation. Use these designations on Drawings to identify each product.

If thickness designations are indicated on Drawings or are determined solely by compliance with "Performance Requirements" Article, delete "Minimum Thickness of Outdoor Lite" and "Minimum Thickness of Each Glass Ply" subparagraphs below.

- A. Translucent Insulating Laminated Glass:

Retain "Basis-of-Design Product" Subparagraph below to require a specific product.

- 1. Overall Unit Thickness: 1 inch.
- 2. Minimum Thickness of Outdoor Lite: 6 mm.
- 3. Outdoor Lite: Clear fully tempered float glass.
- 4. Interspace Content: Air.
- 5. Indoor Lite: Clear laminated glass with two plies of fully tempered float glass.
 - a. Minimum Thickness of Each Glass Ply: 6 mm.
 - b. Interlayer Thickness: 0.060 inch.
 - c. Interlayer color: Translucent white.

Retain subparagraph below if required.

- 6. Safety glazing required.

END OF SECTION 08 80 00