

# SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover**  
**880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : Renown® Heavy Duty Carpet Spot Remover

Material number : A00173

### Manufacturer or supplier's details

Company : Interline Brands

Address : 701 San Marco Blvd.  
Jacksonville, FL 32207

Telephone : 1-866-412-6726

### Emergency telephone numbers

**For SDS Information** : 1-866-412-6726

**For a Medical Emergency** : 1-800-424-9300

**For a Transportation  
Emergency** : Chemtrec 1-800-424-9300

## SECTION 2. HAZARDS IDENTIFICATION

### Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

### GHS Classification

Flammable aerosols : Category 2  
Gases under pressure : Liquefied gas  
Eye irritation : Category 2A

### GHS Label element

Hazard pictograms :



Signal word : Warning

Hazard statements : H223 Flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P264 Wash skin thoroughly after handling.  
P280 Wear eye protection/ face protection.  
**Response:**

# SAFETY DATA SHEET

## Renown® Heavy Duty Carpet Spot Remover 880266)

(REN05009-AM /

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Potential Health Effects

#### Carcinogenicity:

##### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

##### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

##### OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

##### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical Name	CAS-No.	Concentration [%]
butane	106-97-8	>= 5 - < 10
propan-2-ol	67-63-0	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 5 - < 10
acetone	67-64-1	>= 1 - < 5
D-Glucopyranose, oligomers, decyl octyl glycosides	68515-73-1	>= 1 - < 5
1-phenoxypropan-2-ol	770-35-4	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
D-Glucopyranose, oligomeric, C10-16-alkyl glycosides	110615-47-9	>= 1 - < 5

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
If unconscious place in recovery position and seek medical advice.

# SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover**  
**880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

- In case of skin contact : In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash contaminated clothing before re-use.  
Call a physician if irritation develops or persists.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Remove contact lenses.  
If eye irritation persists, consult a specialist.
- If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.

# SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover  
880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Always replace cap after use.  
Dispose of rinse water in accordance with local and national regulations.  
Do not breathe vapours or spray mist.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Keep in a dry, cool and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	800 ppm 1,900 mg/m <sup>3</sup>	OSHA P0
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm	NIOSH REL

**SAFETY DATA SHEET**

**Renown® Heavy Duty Carpet Spot Remover  
880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

			980 mg/m3	
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

**Biological occupational exposure limits**

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to the workstation location.  
Safety glasses

## SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover  
880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

- Skin and body protection : impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Colour : clear
- Odour : characteristic
- Odour Threshold : no data available
- pH : no data available
- Melting point/freezing point : no data available
- Boiling point : no data available
- Flash point :  
not applicable
- Evaporation rate : 1
- Flammability (solid, gas) : The product is not flammable.
- Upper explosion limit : no data available
- Lower explosion limit : no data available
- Vapour pressure : 4,136 hPa (21 °C)
- Relative vapour density : no data available
- Density : 0.985 g/cm<sup>3</sup>
- Solubility(ies)
- Water solubility : soluble
- Partition coefficient: n-octanol/water : no data available
- Auto-ignition temperature : not determined
- Thermal decomposition : no data available
- Viscosity
- Viscosity, kinematic : no data available
- Heat of combustion : 10.46 kJ/g

# SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover  
880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ) Carbon monoxide Nitrogen oxides (NO <sub>x</sub> )

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

#### Product:

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

#### Components:

##### **butane:**

Acute inhalation toxicity	: LC50 mouse: 1,237 mg/l Exposure time: 2 h  LC50 rat: 1,355 mg/l
---------------------------	--

##### **propan-2-ol:**

Acute oral toxicity	: LD50 Oral rat: 4,396 mg/kg Method: Calculation method
---------------------	--

##### **acetone:**

Acute oral toxicity	: LD50 rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 rat: 132 mg/l Exposure time: 3 h  LC50 rat: 50.1 mg/l

# SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover  
880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

Acute dermal toxicity : LD50 guinea pig: > 7,426 mg/kg

LD50 rabbit: > 7,426 mg/kg

**propane:**

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l  
Exposure time: 2 h

LC50 rat: 658 mg/l  
Exposure time: 4 h

LC50 rat: 1,355 mg/l

## Skin corrosion/irritation

**Product:**

Remarks: May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

**Product:**

Remarks: Eye irritation

## Respiratory or skin sensitisation

no data available

## Germ cell mutagenicity

no data available

## Carcinogenicity

no data available

## Reproductive toxicity

no data available

**butane:**

**propan-2-ol:**

**2-(2-butoxyethoxy)ethanol:**

**acetone:**

**D-Glucopyranose, oligomers, decyl octyl glycosides:**

**1-phenoxypropan-2-ol:**

**propane:**

**D-Glucopyranose, oligomeric, C10-16-alkyl glycosides:**

## STOT - single exposure

no data available

## STOT - repeated exposure

no data available

## Aspiration toxicity

no data available

## Further information



# SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover  
880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

**Product:**

Remarks: no data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

no data available

### Persistence and degradability

no data available

### Bioaccumulative potential

**Product:**

Partition coefficient: n- octanol/water : Remarks: no data available

**Components:**

**butane :**

Partition coefficient: n- octanol/water : Pow: 2.89

**2-(2-butoxyethoxy)ethanol :**

Partition coefficient: n- octanol/water : Pow: 1

**D-Glucopyranose, oligomeric, C10-16-alkyl glycosides :**

Partition coefficient: n- octanol/water : Pow: 0.07

### Mobility in soil

no data available

### Other adverse effects

no data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : no data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

# SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover  
880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

- Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, 2.1, - Limited quantity

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard  
Sudden Release of Pressure Hazard

**SARA 302** : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

# SAFETY DATA SHEET

## Renown® Heavy Duty Carpet Spot Remover 880266)

(REN05009-AM /

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

### SARA 313

: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### California Prop 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

methanol

67-56-1

### The components of this product are reported in the following inventories:

#### TSCA

On TSCA Inventory

#### DSL

This product contains one or several components that are not on the Canadian DSL nor NDSL.

#### AICS

Not in compliance with the inventory

#### NZIoC

Not in compliance with the inventory

#### PICCS

Not in compliance with the inventory

#### IECSC

Not in compliance with the inventory


### Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>2</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Warning:**

Hazard statements

: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation.

Precautionary statements

:

## SAFETY DATA SHEET

**Renown® Heavy Duty Carpet Spot Remover  
880266)**

**(REN05009-AM /**

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

---

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear eye protection/ face protection.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

---

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

1027072