

# 09 64 66 – Wood Athletic Flooring

## DIVISION 9 - Finishes



### STATEMENT OF PURPOSE & BACKGROUND

- Scope:
  - Selection, installation and substrate preparation of anchored resilient vented wood athletic floor.
- Statement of goals: See 09 60 00 – Floor Finishes.
- Revision history of section:
  - 11/17/15
  - 02/08/18

### MAINTENANCE & CLEANING PROCEDURES

- Daily
  - Daily sweeping to remove loose dirt and debris.
- Periodically
  - Do not wet mop. Apply a professional wood cleaning product.
- Long Term Renewal
  - Stripping and refinishing with polyurethane.

### END OF LIFE RECLAMATION / DISPOSAL

- Product is entirely reclaimable. Contact manufacturer.

### OUTLINE SPECIFICATION

- Part 1 General
- Part 2 Products / WD-2
  - System consisting of:
    - Moisture Barrier
    - CDX plywood subfloor panels supported with resilient pads
    - MFMA Northern Hard Maple random length continuous tongue and groove flooring; finger jointed construction not accepted.
    - Fasteners and anchors designed for system
    - Finish: two coats of sealer, game lines, two coats of finish.
- Reference Manufacturer and systems:
  - Conner – Anchored Rezill Sleeper Din
  - Robbins, Inc – Eclipse SB
  - Tarkett – Clutchcourt Performance Anchor
- Part 3 Execution
  - Per Consultant and / or manufacturer specification.
  - Post Installation
    - Per manufacturer's recommendations.

End of Section