

09 65 13 – Resilient Base

DIVISION 9 - Finishes



STATEMENT OF PURPOSE & BACKGROUND

- Scope:
 - Selection of color-integrated vinyl or rubber wall base.
- Statement of goals: See 09 60 00 – Floor Finishes.
- Revision history of section:
 - 03/01/13
 - 10/24/18
 - 01/13/21

SELECTION AND APPLICATION CRITERIA

- 4" vinyl or rubber wall base shall be standard for resilient base applications, except provide rubber sanitary base or flash cove base at food service areas where rubber flooring is used, and where required by authorities having jurisdiction.
- 6" resilient wall base may be required in specific situations or locations; for example, to cover poor wall conditions or irregularities in finished surfaces in existing buildings.
- Install coved base at resilient or hard surface flooring; straight base at carpet.

MAINTENANCE & CLEANING PROCEDURES

- Daily
 - Not needed.
- Periodically
 - Wash with a neutral detergent solution diluted to 3 to 4 ounces per gallon in water, using a sponge or clean cloth.
- Long Term Renewal
 - Apply 2 coats of a high-quality commercial floor polish.

END OF LIFE RECLAMATION / DISPOSAL

- Product is entirely reclaimable. Contact manufacturer.

OUTLINE SPECIFICATION

- Part 1 General
 - Extra Materials
 - Contractor to turn over open boxes to Owner. Contractor shall not supply any additional attic stock unless directed otherwise by Owner.
- Part 2 Products – VB-1 (See 09 60 00 – Flooring Matrix)
 - Acceptable Manufacturer(s):
 - Armstrong color-integrated vinyl base
 - Tarkett/Johnsonite for vinyl or rubber base
 - Nora for rubber base
 - Equivalent manufacturers **approved, in writing, in advance, by the Architect**, may be substituted in accordance with the provisions of the Contract.
- Part 3 Execution
 - Per Consultant and / or manufacturer specification.

End of Section