

11 52 13 – Projection Screens

DIVISION 11 - Equipment



STATEMENT OF PURPOSE & BACKGROUND

- Scope:
 - Selection and installation of front-projection screens and controls.
- Statement of goals:
 - Provide consistent, high quality materials that:
 - Meet quality standards for intended purpose;
 - Are easily maintained.
- Revision history of section:
 - 12/7/18 (date of adoption)

OUTLINE SPECIFICATION

- Part 1 General
 - Sizes, quantities and locations of projection screens to be as shown on Drawings.
- Part 2 Products
 - Projection Screens – recessed or suspended:
 - Electrically operated, front-projection.
 - Manufacturer's standard units consisting of metal case, screen, motor, controls, mounting accessories, and other necessary components.
 - Controls – remote, key-operated, 3-position switch installed in recessed device box.
 - Motor in roller – Instant-reversing motor of size and capacity recommended for screen.
 - Tab Tensioning: Provide tensioning cord on each side of screen to pull screen flat horizontally.
 - Provide units without ceiling closure, with bottom of case entirely or partially open under screen compartment.
 - If recessed, provide trim flange on case to receive ceiling finish.
 - Screen to be matte white, vinyl sheet, pearlescent finish with black masking borders and 12 inch black drop standard.
 - Acceptable Manufacturers:
 - Da-Lite Screen Company
 - Draper Inc.
 - Stewart Filmscreen Corp.
 - Equivalent manufacturers **approved, in writing, in advance, by the Architect**, may be substituted in accordance with the provisions of the Contract.
- Part 3 Execution
 - Per Consultant and / or manufacturer specification.

End of Section