

M

FLINN SCIENTIFIC, INC.

Safety Data Sheet (SDS)

SDS #: 468.00

Revision Date: March 21, 2014

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Magnesium

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Signal Word **DANGER**

Pictograms



SECTION 2 — HAZARDS IDENTIFICATION

Hazard class: Flammable solids (Category 1). Flammable solid (H228). Keep away from heat, sparks, open flames, and hot surfaces. No smoking (P210).

SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

| Component Name | CAS Number | Formula | Formula Weight | Concentration |
|----------------|------------|---------|----------------|---------------|
| Magnesium | 7439-95-4 | Mg | 24.31 | |

SECTION 4 — FIRST AID MEASURES

Call a POISON CENTER or physician if you feel unwell.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing.

If on skin: Wash with plenty of water.

If swallowed: Rinse mouth. Call a POISON CENTER or physician if you feel unwell.

SECTION 5 — FIRE FIGHTING MEASURES

Flammable solid.

Water reactive metal; avoid contact with acids or water. When heated to decomposition, may emit toxic fumes.

In case of fire: Use a Class D or dry sand as a fire extinguisher. Avoid water contact, violent reaction with water.

NFPA CODE

H-0

F-1

R-1

No Water

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Remove all ignition sources and water. Sweep up the spill, place in a sealed bag or container, and dispose. Ventilate area and wash spill site after material pickup is complete. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Inorganic #1. Store with metals and metal hydrides.
Store in a Flinn Saf-Stor™ can.

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective gloves, protective clothing, and eye protection. Wash hands thoroughly after handling.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Silvery-white metal turnings or ribbon. Odorless.
Soluble: Acids. Insoluble in water.

Melting point: 651 °C
Specific gravity: 1.74

SECTION 10 — STABILITY AND REACTIVITY

Avoid contact with water, acids, acid chlorides, strong oxidizers, halogens, and chlorinated solvents.
Shelf life: Indefinite, if stored properly.

SECTION 11 — TOXICOLOGICAL INFORMATION

Acute effects: Irritating dust.
Chronic effects: N.A.
Target organs: N.A.

ORL-RAT LD₅₀: N.A.
IHL-RAT LC₅₀: N.A.
SKN-RBT LD₅₀: N.A.

N.A. = Not available, not all health aspects of this substance have been fully investigated.

SECTION 12 — ECOLOGICAL INFORMATION

Data not yet available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.
Flinn Suggested Disposal Method #26a is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Magnesium. Hazard class: 4.1, Flammable solid. UN number: UN1869.

N/A = Not applicable

SECTION 15 — REGULATORY INFORMATION

TSCA-listed, EINECS-listed (231-104-6), RCRA code D001.

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

Consult your copy of the *Flinn Science Catalog/Reference Manual* for additional information about laboratory chemicals.

Revision Date: March 21, 2014

Safety Data Sheet

Magnesium Chloride, 0.1 M

CAROLINA[®]
www.carolina.com

Section 1 Product Description

Product Name: Magnesium Chloride, 0.1 M
Recommended Use: Science education applications
Synonyms: Magnesium Chloride, Aqueous Solution
Distributor: Carolina Biological Supply Company
2700 York Road, Burlington, NC 27215
1-800-227-1150
Chemical Information: 800-227-1150 (8am-5pm (ET) M-F)
Chemtrec: 800-424-9300 (Transportation Spill Response 24 hours)

Section 2 Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Classification:

Section 3 Composition / Information on Ingredients

| <u>Chemical Name</u> | <u>CAS #</u> | <u>%</u> |
|-------------------------------|--------------|----------|
| Water | 7732-18-5 | 99.05 |
| Magnesium Chloride, 6-Hydrate | 7791-18-6 | 0.95 |

Section 4 First Aid Measures

Emergency and First Aid Procedures

Inhalation: In case of accident by inhalation: remove casualty to fresh air and keep at rest.
Eyes: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact: After contact with skin, wash immediately with plenty of water.
Ingestion: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Section 5 Firefighting Procedures

Extinguishing Media: Use media suitable to extinguish surrounding fire.
Fire Fighting Methods and Protection: Firefighters should wear full protective equipment and NIOSH approved self-contained breathing apparatus.
Fire and/or Explosion Hazards: Fire or excessive heat may produce hazardous decomposition products.
Hazardous Combustion Products: Hydrogen chloride, Metal Oxides,

Section 6 Spill or Leak Procedures

Steps to Take in Case Material Is Released or Spilled: No adverse health affects expected from the clean-up of spilled material. Avoid creating and inhaling spray or mist.
No special spill clean-up considerations. Collect and discard in regular trash.

Section 7 Handling and Storage

Handling: Do not breathe dust/vapor. Do not get in eyes, on skin, or on clothing. Retained residue may make empty containers hazardous; use caution.
Storage: Keep container tightly closed in a cool, well-ventilated place.
Storage Code: Green - general chemical storage

Section 8 Protection Information

Safety Data Sheet

| Chemical Name | ACGIH (TWA) | (STEL) | OSHA PEL (TWA) | (STEL) |
|-------------------|----------------|--------|-------------------|--------|
| No data available | N/A | N/A | N/A | N/A |

Control Parameters

Engineering Measures:

No exposure limits exist for the constituents of this product. General room ventilation might be required to maintain operator comfort under normal conditions of use.

Personal Protective Equipment (PPE):

Lab coat, apron, eye wash, safety shower.

Respiratory Protection:

No respiratory protection required under normal conditions of use.

Eye Protection:

Wear chemical splash goggles when handling this product. Have an eye wash station available.

Skin Protection:

Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves:

Nitrile

Section 9

Physical Data

Formula: Cl₂Mg

Molecular Weight: 95.21 g/mol

Appearance: Colorless

Odor: No data available

Odor Threshold: No data available

pH: No data available

Melting Point: Estimated 0 C

Boiling Point: 100 C

Flash Point: No data available

Flammable Limits in Air: N/A N/A

Vapor Pressure: 14 (water)

Evaporation Rate (BuAc=1): Slightly < 1

Vapor Density (Air=1): 0.7 (water)

Specific Gravity: Approx. 1.0

Solubility in Water: Soluble

Log Pow (calculated): No data available

Autoignition Temperature: No data available

Decomposition Temperature: No data available

Viscosity: 10

Percent Volatile by Volume: 99.05%

Section 10

Reactivity Data

Reactivity:

No data available

Chemical Stability:

Stable under normal conditions.

Conditions to Avoid:

None known.

Incompatible Materials:

Strong oxidizing agents

Hazardous Decomposition Products:

Metal Oxides,, Hydrogen chloride

Hazardous Polymerization:

Will not occur

Section 11

Toxicity Data

Routes of Entry: Inhalation, ingestion, eye or skin contact.

Symptoms (Acute): N/A

Delayed Effects: No data available

Acute Toxicity:

Chemical Name

CAS Number

Oral LD50

Dermal LD50

Inhalation LC50

Water

7732-18-5

Oral LD50 Rat

90000 mg/kg

Magnesium Chloride, 6-Hydrate

7791-18-6

Oral LD50 Rat

8100 mg/kg

Carcinogenicity:

Chemical Name

CAS Number

IARC

NTP

OSHA

No data available

Not listed

Not listed

Not listed

Chronic Effects:

Mutagenicity:

No evidence of a mutagenic effect.

Teratogenicity:

No evidence of a teratogenic effect (birth defect).

Safety Data Sheet

Sensitization: No evidence of a sensitization effect.
Reproductive: No evidence of negative reproductive effects.
Target Organ Effects:
Acute: See Section 2
Chronic: Not listed as a carcinogen by IARC, NTP or OSHA.

Section 12

Ecological Data

Overview: This material is not expected to be harmful to the ecology.
Mobility: No data
Persistence: No data
Bioaccumulation: No data
Degradability: No data
Other Adverse Effects: No data

| Chemical Name | CAS Number | Eco Toxicity |
|---------------|------------|-------------------|
| Water | 7732-18-5 | No data available |

Section 13

Disposal Information

Disposal Methods: Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance.
Waste Disposal Code(s): Not Determined

Section 14

Transport Information

| Ground - DOT Proper Shipping Name: | Air - IATA Proper Shipping Name: |
|------------------------------------|--|
| N/A | Not regulated for air transport by IATA. |

Section 15

Regulatory Information

TSCA Status: All components in this product are on the TSCA Inventory.

| Chemical Name | CAS Number | § 313 Name | § 304 RQ | CERCLA RQ | § 302 TPQ | CAA 112(2) TQ |
|-------------------|------------|------------|----------|-----------|-----------|---------------|
| No data available | | No | No | No | No | No |

Section 16

Additional Information

Revised: 09/03/2014

Replaces: 09/03/2014

Printed: 09-11-2014

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Carolina Biological Supply makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

| | | | |
|--------|---|------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists | NTP | National Toxicology Program |
| CAS | Chemical Abstract Service Number | OSHA | Occupational Safety and Health Administration |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act | PEL | Permissible Exposure Limit |
| DOT | U.S. Department of Transportation | ppm | Parts per million |
| IARC | International Agency for Research on Cancer | RCRA | Resource Conservation and Recovery Act |
| N/A | Not Available | SARA | Superfund Amendments and Reauthorization Act |
| | | TLV | Threshold Limit Value |
| | | TSCA | Toxic Substances Control Act |
| | | IDLH | Immediately dangerous to life and health |

Section 1 Chemical Product and Company Identification

Page E1 of E2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

Boreal Science
399 Vansickle Road
St. Catharines, Ontario
L2S 3T4 Canada
Tel: (800) 387-9393

CHEMTREC 24 Hour Emergency
Phone Number (800) 424-9300
For laboratory use only.
Not for drug, food or household use.

Product MAGNESIUM CHLORIDE, HEXAHYDRATE

Synonyms Magnesium Chloride, 6-Hydrate

Section 2 Hazards Identification

This substance or mixture has not been classified as hazardous according to the Globally Harmonized System (GHS) of Classification and Labeling of Chemicals.

Signal word: WARNING

Pictograms: No symbol required

Target organs: Central nervous system, Kidneys, Gastrointestinal tract

GHS Classification:

Acute toxicity, oral (Category 5)

GHS Label information: Hazard statement:

H303: May be harmful if swallowed.

Precautionary statement:

P312: Call a POISON CENTER or doctor if you feel unwell.

Ca Prop 65 - This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

Section 9 Other information on ingredients

| Chemical Name | CAS # | % | EINECS |
|---------------------------------|-----------|------|---------------------|
| Magnesium chloride, hexahydrate | 7791-18-6 | 100% | 232-094-6 anhydrous |

Section 7 First Aid Measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 8 Fire Fighting Measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Section 6 Environmental Release Measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Recover for reuse if not contaminated. Sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale dusts. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Avoid high humidity and moisture.

Section 8

Exposure Controls / Personal Protection

| Exposure Limits: | Chemical Name | ACGIH (TLV) | OSHA (PEL) | NIOSH (REL) |
|------------------|--------------------|-----------------|-----------------|-----------------|
| | Magnesium chloride | Not established | Not established | Not established |

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9

Physical & Chemical Properties

| | | |
|---|--|--|
| Appearance: Solid. Colorless, flakes or crystals | Evaporation rate (= 1): Data not available | Partition coefficient: Data not available |
| Odor: No odor. | Flammability (solid/gas): Data not available | Auto-ignition temperature: Data not available |
| Odor threshold: Data not available | Explosion limits: Lower / Upper: Not applicable | Decomposition temperature: Data not available |
| pH: 7.0 (aqueous solution) | Vapor pressure (mm Hg): Data not available | Viscosity: Data not available |
| Melting / Freezing point: 118°C (244°F) | Vapor density (Air = 1): Data not available | Molecular formula: MgCl ₂ ·6H ₂ O |
| Boiling point: Data not available | Relative density (Specific gravity): 1.57 | Molecular weight: 203.31 |
| Flash point: Non flammable | Solubility(ies): 167 g/100 ml water @ 20°C | |

Section 10

Stability & Reactivity

Chemical stability: Stable

Hazardous polymerization: Will not occur.

Conditions to avoid: Excessive temperatures and heat. Avoid high humidity and moisture.

Incompatible materials: Strong oxidizers.

Hazardous decomposition products: Hydrogen chloride gas, magnesium oxide.

Section 11

Toxicological Information

Acute toxicity: Oral-rat LD50: 2800 mg/kg (anhydrous)

Skin corrosion/irritation: Data not available

Serious eye damage/irritation: Data not available

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenicity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: Data not available

STOT-single exposure: Data not available

STOT-repeated exposure: Data not available

Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause mild irritation to the mucous membranes.

Ingestion: Ingestion may cause abdominal pain, vomiting and diarrhea.

Skin: Contact may cause mechanical irritation.

Eyes: Contact may cause mechanical irritation.

Signs and symptoms of exposure: Exercise appropriate procedures to minimize potential hazards.

Additional information: RTECS #: OM2975000

Section 12

Ecological Information

Toxicity to fish: Gambusia affinis (fish, fresh water), LC50 = 16,500 mg/L/96 hours

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacea), EC50 = 3,190 mg/L/24 hours

Toxicity to algae: Scenedesmus subspicatus (Algae), EC50 = 2,200 mg/L/72 hours

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13

Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14

Transportation and Storage

UN/NA number: Not applicable

Shipping name: Not Regulated

Hazard class: Not applicable

Packing group: Not applicable

Reportable Quantity: No

Marine pollutant: No

Exceptions: Not applicable

2012 ERG Guide # Not applicable

Section 15

Inventory

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

| Component | TSCA | CERCLA (RQ) | RCRA code | DSL | NDSL |
|---------------------------------|------------|-------------|------------|------------|------------|
| Magnesium chloride, hexahydrate | Not listed | Not listed | Not listed | Not listed | Not listed |

Section 16

Disclaimer

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.



SDS #: 477

Revision Date: March 21, 2014

Save SDS to Your Library

Safety Data Sheet (SDS)

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Magnesium Nitrate Solution

Signal Word
WARNING

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

Chemtrec Emergency Phone Number: (800) 424-9964

Pictograms

SECTION 2 — HAZARDS IDENTIFICATION

Hazard class: Skin and serious eye damage, corrosion or irritation (Category 2, 2B). Causes skin and eye irritation (H315+H320).



SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

| Component Name | CAS Number | Formula | Formula Weight | Concentration |
|-------------------|------------|--|----------------|---------------|
| Magnesium nitrate | 13446-18-9 | $\text{Mg}(\text{NO}_3)_2 \cdot 6\text{H}_2\text{O}$ | 256.43 | 2.5% - 25% |
| Water | 7732-18-5 | H_2O | 18.00 | 75% - 97.5% |

SECTION 4 — FIRST AID MEASURES

Call a POISON CENTER or physician if you feel unwell.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.**If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing (P305+P351+P338). **If eye irritation persists eyes:** Get medical advice or attention (P337+P313).**If on skin:** Wash with plenty of water (P302+P352). **If skin irritation occurs:** Get medical advice or attention (P332+P313).**If swallowed:** Rinse mouth. Call a POISON CENTER or physician if you feel unwell.

SECTION 5 — FIRE FIGHTING MEASURES

Nonflammable, noncombustible solution.

In case of fire: Use a tri-class dry chemical fire extinguisher.

NFPA Code
None established

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Ventilate area. Contain the spill with sand or absorbent material and deposit in a sealed bag or container. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Inorganic #3. Store with amides, nitrates, nitrites and azides.

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective gloves, protective clothing, and eye protection (P280). Wash hands thoroughly after handling (P264).

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Clear, colorless liquid. Odorless.

SECTION 10 — STABILITY AND REACTIVITY

Shelf life: Good, if stored properly.

SECTION 11 — TOXICOLOGICAL INFORMATION

Acute effects: Irritant.

ORL-RAT LD₅₀: 5440 mg/kg as magnesium nitrate

Chronic effects: N.A.

IHL-RAT LC₅₀: N.A.

Target organs: N.A.

SKN-RBT LD₅₀: N.A.

SECTION 12 — ECOLOGICAL INFORMATION

Data not yet available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.

Flinn Suggested Disposal Method #26b is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Not regulated. Hazard class: N/A. UN number: N/A.

SECTION 15 — REGULATORY INFORMATION

Not listed.

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

N.A. = Not available, not all health aspects of this substance have been fully investigated.

N/A = Not applicable

Consult your copy of the Flinn Science Catalog/Reference Manual for additional information about laboratory chemicals.

Revision Date: March 21, 2014

Section 1 Chemical Product and Company Identification

Page E1 of E2



**Aldon
Corporation**

221 Rochester Street
Avon, NY 14414
(585) 226-6177

**CHEMTREC 24 Hour Emergency
Phone Number (800) 424-9300**
For laboratory use only.
Not for drug, food or household use.

Product MAGNESIUM NITRATE, HEXAHYDRATE
Synonyms Magnesium Nitrate, 6-Hydrate

Section 2 Hazards Identification

Signal word: WARNING
Pictograms: GHS03
Target organs: None known



GHS Classification:
Oxidizing solid (Category 3)

GHS Label information: Hazard statement:
H272: May intensify fire; oxidizer.

Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P220: Keep away from clothing/incompatible/combustible materials.
P221: Take any precaution to avoid mixing with combustibles and incompatible materials.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P370+P378: In case of fire: Use water. Do not use dry chemicals or foams to extinguish.
P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Ca Prop 65: This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

| Chemical Name | CAS # | % | EINECS |
|--------------------------------|------------|------|-----------------------|
| Magnesium nitrate, hexahydrate | 13446-18-9 | 100% | 233-826-7 [anhydrous] |

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. MAY CAUSE RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: MAY CAUSE EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. MAY CAUSE SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Suitable Extinguishing Media: Use water. Do not use dry chemicals or foams. CO₂ or Halon® may provide limited control.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Substance will accelerate burning when involved in a fire. May ignite combustibles (wood, paper, oil, clothing, etc.). Containers may explode when heated.

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Recover for reuse if not contaminated. Remove all sources of ignition. Sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale dusts. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8 Exposure Controls / Personal Protection

| Exposure Limits: | Chemical Name | ACGIH (TLV) | OSHA (PEL) | NIOSH (REL) |
|------------------|-------------------|-----------------|-----------------|-----------------|
| | Magnesium nitrate | Not established | Not established | Not established |

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

| | | |
|--|--|--|
| Appearance: Solid. White, deliquescent crystals | Evaporation rate (= 1): Data not available | Partition coefficient: Data not available |
| Odor: No odor | Flammability (solid/gas): Data not available | Auto-ignition temperature: Data not available |
| Odor threshold: Data not available | Explosion limits: Lower / Upper: Data not available | Decomposition temperature: 330°C (626°F) |
| pH: Data not available | Vapor pressure (mm Hg): Data not available | Viscosity: Data not available |
| Melting / Freezing point: 89°C (192°F) | Vapor density (Air = 1): Data not available | Molecular formula: Mg(NO ₃) ₂ •6H ₂ O |
| Boiling point: Decomposes | Relative density (Specific gravity): 1.46 | Molecular weight: 256.41 |
| Flash point: Data not available | Solubility(ies): Soluble in water | |

Section 10 Stability & Reactivity

Chemical stability: Stable **Hazardous polymerization:** Will not occur.

Conditions to avoid: Excessive temperatures and heat.

Incompatible materials: Reducing agents, oxidizers, organic and combustible materials.

Hazardous decomposition products: Nitric acid fumes and sometimes nitrogen tetroxide are reported.

Acute toxicity: Oral-rat LD50: 5440 mg/kg

Skin corrosion/irritation: Data not available

Serious eye damage/irritation: Data not available

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenicity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Ca Prop 65: This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

Reproductive toxicity: Data not available

STOT-single exposure: Data not available

STOT-repeated exposure: Data not available

Aspiration hazard: Data not available

Potential health effects:

Inhalation: May cause mild respiratory tract irritation. Symptoms may include coughing and shortness of breath.

Ingestion: Ingestion of large doses can cause abdominal pain, cyanosis (blue lips, fingernails and skin), confusion, convulsions, dizziness, headache, nausea, and unconsciousness.

Skin: Can cause mild irritation.

Eyes: Can cause mild irritation.

Signs and symptoms of exposure: Under some circumstances methemoglobinemia occurs in individuals when the nitrate is converted by bacteria in the stomach to the nitrite. Exercise appropriate procedures to minimize potential hazards.

Additional information: RTECS #: OM3756000

Toxicity to fish: No data available

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

UN/NA number: UN1474

Shipping name: Magnesium nitrate

Hazard class: 5.1

Packing group: III

Reportable Quantity: No

Marine pollutant: No

Exceptions: Limited quantity equal to or less than 5 Kg

2016 ERG Guide # 140

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

| Component | TSCA | CERCLA (RQ) | RCRA code | DSL | NDSL |
|------------------------------|--------|-------------|------------|--------|------------|
| Magnesium nitrate, anhydrous | Listed | Not listed | Not listed | Listed | Not listed |

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

Form 08/2015

Revision Date: December 27, 2016

Supersedes: December 7, 2016

FLINN SCIENTIFIC, INC.

Safety Data Sheet (SDS)

SDS #: 478.00

Revision Date: March 25, 2014

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Magnesium Oxide

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Signal Word N/A

Pictograms

SECTION 2 — HAZARDS IDENTIFICATION

This chemical is considered nonhazardous according to GHS classifications for the Hazard Communication Standard. Treat all laboratory chemicals with caution.

Although this material is considered to be nonhazardous, unpredictable reactions among chemicals are always possible. Prudent laboratory practices should be observed.

SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

| Component Name | CAS Number | Formula | Formula Weight | Concentration |
|-------------------|------------|---------|----------------|---------------|
| Magnesium oxide | 1309-48-4 | MgO | 40.32 | |
| Synonym: Magnesia | | | | |

SECTION 4 — FIRST AID MEASURES

Call a POISON CENTER or physician if you feel unwell.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing.

If on skin: Wash with plenty of water.

If swallowed: Rinse mouth. Call a POISON CENTER or physician if you feel unwell.

SECTION 5 — FIRE FIGHTING MEASURES

Noncombustible solid.

When heated to decomposition, may emit toxic fumes.

In case of fire: Use a tri-class dry chemical fire extinguisher.

NFPA CODE
None
established

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Ventilate area and sweep up the spill, place in a sealed bag or container, and dispose. Wash spill site after material pickup is complete. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Inorganic #4. Store with hydroxides, oxides, silicates and carbonates.
Air and moisture sensitive. Store in a Flinn Chem-Saf™ bag. Store in a cool, dry place.

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective gloves, protective clothing, and eye protection. Wash hands thoroughly after handling.
Exposure guidelines: PEL 15 mg/m³ (as total fume) (OSHA); 10 mg/m³ (inhalable fraction)(ACGIH)

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--------------------------------|
| White powder. Odorless. | Boiling point: 3600 °C |
| Soluble: Acids and ammonium salts solutions. Slightly in water. | Melting point: 2800 °C |
| | Specific gravity: 2.4 (varies) |

SECTION 10 — STABILITY AND REACTIVITY

Avoid contact with strong oxidizers and acids.
Shelf life: Fair to poor. Sensitive to air and moisture. See Section 7 for further information.

SECTION 11 — TOXICOLOGICAL INFORMATION

| | |
|---|---------------------------------|
| Acute effects: Irritant, laxative effect. | ORL-RAT LD ₅₀ : N.A. |
| Chronic effects: N.A. | IHL-RAT LC ₅₀ : N.A. |
| Target organs: N.A. | SKN-RBT LD ₅₀ : N.A. |

N.A. = Not available, not all health aspects of this substance have been fully investigated.

SECTION 12 — ECOLOGICAL INFORMATION

Data not yet available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.
Flinn Suggested Disposal Method #26a is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Not regulated. Hazard class: N/A. UN number: N/A.

N/A = Not applicable

SECTION 15 — REGULATORY INFORMATION

TSCA-listed, EINECS-listed (215-171-9).

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

Consult your copy of the *Flinn Science Catalog/Reference Manual* for additional information about laboratory chemicals.

Revision Date: March 25, 2014

Section 1

Chemical Product and Company Information

Page E1 of E2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

CHEMTREC 24 Hour Emergency
Phone Number (800) 424-9300
For laboratory use only.
Not for drug, food or household use.

| | |
|----------|---------------------------------|
| Product | MAGNESIUM SULFATE, HEPTAHYDRATE |
| Synonyms | Epsom Salts |

Section 2

Hazard Identification

This substance or mixture has not been classified as hazardous according to the Globally Harmonized System (GHS) of Classification and Labeling of Chemicals.

Signal word: None

Pictograms: No symbol required

Target organs: None known

GHS Classification: Not classified

GHS Label information: Hazard statement: Not classified

Precautionary statement: Not classified

Supplementary information:

Do not breathe dust. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Get medical attention if you feel unwell.

Ca Prop 65 - This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

Section 3

Composition / Information on Ingredients

| Chemical Name | CAS # | % | EINECS |
|-------------------|------------|------|-----------------------|
| Magnesium sulfate | 10034-99-8 | 100% | 231-298-2 (anhydrous) |

Section 4

First Aid Measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. MAY CAUSE RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: MAY CAUSE EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. MAY CAUSE SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5

Fire Fighting Measures

Suitable Extinguishing Media: Use any media suitable for extinguishing supporting fire.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Section 6

Accidental Release Measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Recover for reuse if not contaminated. Sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Section 7 Handling & Storage

Page E2 of E2

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale dusts. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances.

Section 8 Exposure Controls / Personal Protection

| Exposure Limits: | Chemical Name | ACGIH (TLV) | OSHA (PEL) | NIOSH (REL) |
|------------------|-------------------|------------------|------------------|------------------|
| | Magnesium sulfate | None established | None established | None established |

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

| | | |
|---|--|--|
| Appearance: Solid, White crystalline powder | Evaporation rate (= 1): Data not available | Partition coefficient: Data not available |
| Odor: No odor. | Flammability (solid/gas): Data not available. | Auto-ignition temperature: Data not available |
| Odor threshold: Data not available. | Explosion limits: Lower / Upper: Data not available | Decomposition temperature: Data not available |
| pH: Data not available. | Vapor pressure (mm Hg): Data not available | Viscosity: Data not available. |
| Melting / Freezing point: Data not available | Vapor density (Air = 1): Data not available | Molecular formula: MgSO ₄ ·7H ₂ O |
| Boiling point: Data not available | Relative density (Specific gravity): 2.7 | Molecular weight: 246.48 |
| Flash point: Data not available | Solubility(ies): Appreciable in water. | |

Section 10 Stability & Reactivity

Chemical stability: Stable **Hazardous polymerization:** Will not occur.

Conditions to avoid: Excessive temperatures and heat. Protect from moisture.

Incompatible materials: None known.

Hazardous decomposition products: Sulfur oxides.

Section 11 Toxicological Information

Acute toxicity: Data not available

Skin corrosion/irritation: Data not available

Serious eye damage/irritation: Data not available

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenicity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: Data not available

STOT-single exposure: Data not available

STOT-repeated exposure: Data not available

Aspiration hazard: Data not available

Potential health effects:

Inhalation: May cause respiratory irritation.

Ingestion: Ingestion may cause nausea, vomiting and diarrhea.

Skin: Contact with skin may cause irritation.

Eyes: Contact with eyes may cause irritation.

Signs and symptoms of exposure: To the best of our knowledge the chemical, physical and toxicological properties have not been thoroughly investigated. Specific data is not available. Exercise appropriate procedures to minimize potential hazards.

Additional information: RTECS #: Data not available

Section 12 Ecological Information

Toxicity to fish: Gambusia affinis (fish, fresh water), LC50: 15,500 mg/L/24 hours

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacea), EC50: 1,700 mg/L/24 hours

Toxicity to algae: Scenedesmus subspicatus (Algae), EC50: 2,700 mg/L/ 72 hours

Persistence and degradability: No data available **Bioaccumulative potential:** No data available

Mobility in soil: No data available **PBT and vPvB assessment:** No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport Information (US DOT / CANADA TDG)

UN/NA number: Not applicable

Shipping name: Not Regulated

Hazard class: Not applicable

Packing group: Not applicable

Reportable Quantity: No

Marine pollutant: No

Exceptions: Not applicable

2012 ERG Guide # Not applicable

Section 15 Regulatory Information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the inventory list.

| Component | TSCA | CERCLA (RQ) | RCRA code | DSL | NDSL | WHMIS Classification |
|-------------------|--------|-------------|------------|--------|------------|----------------------|
| Magnesium sulfate | Listed | Not listed | Not listed | Listed | Not listed | Uncontrolled product |

Section 16 Additional Information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

Revision Date: November 20, 2013

Supersedes: May 29, 2013

FLINN SCIENTIFIC, INC.

Safety Data Sheet (SDS)

SDS #: 485.00

Revision Date: March 21, 2014

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Maleic Acid

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Signal Word **DANGER**

Pictograms



SECTION 2 — HAZARDS IDENTIFICATION

Hazard class: Acute toxicity, oral (Category 4). Harmful if swallowed (H302). Do not eat, drink or smoke when using this product (P270).

Hazard class: Skin and serious eye damage, corrosion or irritation (Category 2, 2B). Causes skin and eye irritation (H315+H320).

Hazard class: Sensitization, skin (Category 1). May cause an allergic skin reaction (H317). Avoid breathing dust or fumes (P261).

Hazard class: Specific target organ toxicity, single exposure; respiratory tract irritation (Category 3). May cause respiratory irritation (H335).

SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

| Component Name | CAS Number | Formula | Formula Weight | Concentration |
|---|------------|---|----------------|---------------|
| Maleic acid | 110-16-7 | HO ₂ CCH:CHCO ₂ H | 116.07 | |
| Synonyms: Maleinic acid, Butenedioic acid | | | | |

SECTION 4 — FIRST AID MEASURES

Get medical advice or attention (P313). **If inhaled:** Remove victim to fresh air and keep at rest in a position comfortable for breathing (P304+P340). **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing (P305+P351+P338). **If eye irritation persists:** Get medical advice or attention (P337+P313). **If on skin:** Wash with plenty of water (P302+P352). **If skin irritation or rash occurs:** Get medical advice or attention (P333+P313). **If swallowed:** Rinse mouth (P330). Call a POISON CENTER or physician if you feel unwell (P301+P312).

SECTION 5 — FIRE FIGHTING MEASURES

Combustible solid.

Flash point 127 °C Flammable limits: Lower: 2.7 %

When heated to decomposition, may emit toxic fumes.

In case of fire: Use a tri-class dry chemical fire extinguisher.

NFPA CODE
None
established

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Remove all ignition sources and water. Sweep up the spill, place in a sealed bag or container, and dispose. Ventilate area and wash spill site after material pickup is complete. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Organic #1. Store with acids, anhydrides and peracids.
Keep container tightly closed (P233). Use only in a hood or well-ventilated area (P271).

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective gloves, protective clothing, and eye protection (P280). Wash hands thoroughly after handling (P264).
Contaminated work clothing should not be allowed out of the workplace (P272). Use only in a hood or well-ventilated area (P271).

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

White crystal. Faint tea odor.

Melting point: 139 °C

Soluble: Water, alcohol, and acetone

Specific gravity: 1.59 (solid)

SECTION 10 — STABILITY AND REACTIVITY

Avoid contact with bases, oxidizers, and reducers.
Shelf life: Indefinite, if stored properly.

SECTION 11 — TOXICOLOGICAL INFORMATION

Acute effects: Skin and eye corrosion and irritation, gastrointestinal disturbances.

ORL-RAT LD₅₀: 708 mg/kg

Chronic effects: N.A.

IHL-RAT LC₅₀: N.A.

Target organs: Eyes, skin.

SKN-RBT LD₅₀: 1560 mg/kg

N.A. = Not available, not all health aspects of this substance have been fully investigated.

SECTION 12 — ECOLOGICAL INFORMATION

Data not yet available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.
Flinn Suggested Disposal Method #24a is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Maleic acid. Hazard class: 8, Corrosive. UN number: NA2215.

N/A = Not applicable

SECTION 15 — REGULATORY INFORMATION

TSCA-listed, EINECS-listed (203-742-5).

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

Consult your copy of the *Flinn Science Catalog/Reference Manual* for additional information about laboratory chemicals.

Revision Date: March 21, 2014

FLINN SCIENTIFIC, INC.

Safety Data Sheet (SDS)

SDS #: 486.00

Revision Date: March 21, 2014

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Malonic Acid

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Signal Word **DANGER**

Pictograms



SECTION 2 — HAZARDS IDENTIFICATION

Hazard class: Acute toxicity, oral (Category 4). Harmful if swallowed (H302). Do not eat, drink or smoke when using this product (P270).

Hazard class: Skin corrosion or irritation (Category 3). Causes mild skin irritation (H316).

Hazard class: Serious eye damage or irritation (Category 1). Causes serious eye damage (H318).

Hazard class: Acute toxicity, inhalation (Category 5). May be harmful if inhaled (H333).

SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

| Component Name | CAS Number | Formula | Formula Weight | Concentration |
|----------------------------|------------|--------------------------------------|----------------|---------------|
| Malonic acid | 141-82-2 | $\text{CH}_2(\text{CO}_2\text{H})_2$ | 104.07 | |
| Synonym: Propanedioic acid | | | | |

SECTION 4 — FIRST AID MEASURES

Immediately call a POISON CENTER or physician (P310).

If inhaled: Call a POISON CENTER or physician if you feel unwell (P304+P312).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing (P305+P351+P338).

If skin irritation occurs: Get medical advice or attention (P332+P313).

If swallowed: Rinse mouth (P330). Call a POISON CENTER or physician if you feel unwell (P301+P312).

SECTION 5 — FIRE FIGHTING MEASURES

Combustible solid.

When heated to decomposition, may emit toxic fumes.

In case of fire: Use a tri-class dry chemical fire extinguisher.

NFPA CODE

None
established

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Wipe up the spill, place in a sealed bag or container, and dispose. Ventilate area and wash spill site after material pickup is complete. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Organic #1. Store with acids, anhydrides and peracids.
Store in a cool, dry place.

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective gloves, protective clothing, and eye protection (P280). Wash hands thoroughly after handling (P264).

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

White crystals. Faint beef bouillon odor.
Soluble: Water, alcohol, and ether

Boiling point: sublimes
Melting point: 135 °C (decomposes)
Specific gravity: 1.619

SECTION 10 — STABILITY AND REACTIVITY

Avoid contact with bases, oxidizers, and reducers.
Shelf life: Indefinite, if stored properly.

SECTION 11 — TOXICOLOGICAL INFORMATION

Acute effects: Severe eye irritant, mild skin irritant, respiratory irritant, gastrointestinal disturbances.
Chronic effects: N.A.
Target organs: Skin, eyes, respiratory tract.

ORL-RAT LD₅₀: 1310 mg/kg
IHL-RAT LC₅₀: N.A.
EYE-RBT LD₅₀: 100 mg

N.A. = Not available, not all health aspects of this substance have been fully investigated.

SECTION 12 — ECOLOGICAL INFORMATION

Data not yet available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.
Flinn Suggested Disposal Method #24a is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Not regulated. Hazard class: N/A. UN number: N/A.

N/A = Not applicable

SECTION 15 — REGULATORY INFORMATION

TSCA-listed, EINECS-listed (205-503-0).

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

Consult your copy of the *Flinn Science Catalog/Reference Manual* for additional information about laboratory chemicals.

Revision Date: March 21, 2014

FLINN SCIENTIFIC, INC.

Safety Data Sheet (SDS)

SDS #: 492.10

Revision Date: March 25, 2014

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manganese(II) Sulfate Solution

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Signal Word **WARNING**

Pictograms



SECTION 2 — HAZARDS IDENTIFICATION

Hazard class: Specific target organ toxicity, repeated exposure (Category 2). May cause damage to organs through prolonged or repeated exposure (H373). Do not eat, drink or smoke when using this product (P270).

SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

| Component Name | CAS Number | Formula | Formula Weight | Concentration |
|-----------------------|------------|-------------------------------------|----------------|---------------|
| Manganese(II) sulfate | 10034-96-5 | MnSO ₄ ·H ₂ O | 169.01 | ≤36% |
| Water | 7732-18-5 | H ₂ O | 18.00 | 64-99% |

SECTION 4 — FIRST AID MEASURES

Call a POISON CENTER or physician if you feel unwell.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing.

If on skin: Wash with plenty of water.

If swallowed: Rinse mouth. Call a POISON CENTER or physician if you feel unwell.

SECTION 5 — FIRE FIGHTING MEASURES

Nonflammable, noncombustible solution.

In case of fire: Use a tri-class dry chemical fire extinguisher.

NFPA CODE

None
established

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Ventilate area. Contain the spill with sand or absorbent material and deposit in a sealed bag or container. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Inorganic #2. Store with acetates, halides, sulfates, sulfites, thiosulfates and phosphates.

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective gloves, protective clothing, and eye protection. Wash hands thoroughly after handling.

Exposure guidelines: (as manganese sulfate) Ceiling 5 mg/m³ (OSHA); 0.1 mg/m³ (inhalable fraction) (ACGIH)

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Clear liquid. Odorless.

SECTION 10 — STABILITY AND REACTIVITY

Avoid contact with strong acids.

Shelf life: Indefinite, if stored properly.

SECTION 11 — TOXICOLOGICAL INFORMATION

Acute effects: Irritant

ORL-RAT LD₅₀: N.A.

Chronic effects: Manganese is a possible mutagen

IHL-RAT LC₅₀: N.A.

Target organs: Central nervous system, lungs

SKN-RBT LD₅₀: N.A.

N.A. = Not available, not all health aspects of this substance have been fully investigated.

SECTION 12 — ECOLOGICAL INFORMATION

Data not yet available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.

Flinn Suggested Disposal Method #27f is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Not regulated. Hazard class: N/A. UN number: N/A.

N/A = Not applicable

SECTION 15 — REGULATORY INFORMATION

TSCA-listed, EINECS-listed (232-089-9).

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

Consult your copy of the *Flinn Science Catalog/Reference Manual* for additional information about laboratory chemicals.

Revision Date: March 25, 2014

Section 1 Chemical Product and Company Information

Page E1 of E2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

CHEMTREC 24 Hour Emergency
Phone Number (800) 424-9300
For laboratory use only.
Not for drug, food or household use.

Product MANGANESE(IV) DIOXIDE, 99%

Synonyms Manganese Dioxide / Manganese Peroxide / Manganese(IV) Oxide

Section 2 Hazards Identification

Signal word: WARNING

Pictograms: GHS07

Target organs: Respiratory system, Central nervous system



GHS Classification:

Acute toxicity, oral (Category 4)

Acute toxicity, inhalation (Category 4)

GHS Label information: Hazard statement:

H302: Harmful if swallowed.

H332: Harmful if inhaled.

Precautionary statement:

P261: Avoid breathing dust.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301+P330+P312: IF SWALLOWED: Rinse mouth. Call a POISON CENTER or doctor if you feel unwell.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Ca Prop 65 - This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

Section 3 Composition / Information on Ingredients

| Chemical Name | CAS # | % | EINECS |
|-------------------|-----------|------|-----------|
| Manganese dioxide | 1313-13-9 | >98% | 215-202-6 |

Section 4 First Aid Measures

INGESTION: HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire Fighting Measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Although not flammable, substance is a strong oxidizer which releases oxygen on heating, increasing the burning rate of any material with a flare-burning effect. It may cause re-ignition after a fire is extinguished.

Section 6 Accidental Release Measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Remove all sources of ignition. Recover for reuse if not contaminated. Sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Section 7 Handling & Storage Page 2 of 2

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale dusts. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8 Exposure Controls / Personal Protection

| Exposure Limits: | Chemical Name | ACGIH (TLV) | OSHA (PEL) | NIOSH (REL) |
|------------------|------------------------|----------------------------|-----------------------------|--|
| | Manganese, fume, as Mn | TWA: 0.2 mg/m ³ | STEL: 0.5 mg/m ³ | TWA: 1 mg/m ³ STEL: 3 mg/m ³ |

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

| | | |
|---|--|---|
| Appearance: Solid. Black crystalline powder. | Evaporation rate (= 1): Data not available | Partition coefficient: Data not available |
| Odor: No odor. | Flammability (solid/gas): Data not available. | Auto-ignition temperature: Data not available |
| Odor threshold: Data not available. | Explosion limits: Lower / Upper: Data not available | Decomposition temperature: Data not available. |
| pH: Data not available. | Vapor pressure (mm Hg): Data not available | Viscosity: Data not available. |
| Melting / Freezing point: 535°C (995°F) | Vapor density (Air = 1): Data not available | Molecular formula: MnO ₂ |
| Boiling point: Data not available | Relative density (Specific gravity): 5.0 | Molecular weight: 86.94 |
| Flash point: Data not available | Solubility(ies): Insoluble in water. | |

Section 10 Stability & Reactivity

Chemical stability: Stable **Hazardous polymerization:** Will not occur.

Conditions to avoid: Do not heat or rub with organic matter or other oxidizable substance. e.g. sulfur, sulfides, phosphides, hypophosphites, etc.

Incompatible materials: Chlorates, strong oxidizers, organic materials, combustible materials, aluminum powder and sulfur.

Hazardous decomposition products: Heating above 535°C (995°F) will produce oxygen and manganese oxides and/or fumes.

Section 11 Toxicological Information

Acute toxicity: Oral-rat LD50: 9000 mg/kg

Skin corrosion/irritation: Data not available

Serious eye damage/irritation: Data not available

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenicity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: Data not available

STOT-single exposure: Data not available

STOT-repeated exposure: Data not available

Aspiration hazard: Data not available

Potential health effects:

Inhalation: Chronic excess inhalational exposures may lead to pulmonary inflammation and subsequent reactive airway disease. Metal fume fever has been reported with manganese inhalation.

Ingestion: May be harmful if ingested.

Skin: Prolonged or repeated contact with dust may irritate skin.

Eyes: Contact with eyes may cause irritation.

Signs and symptoms of exposure: Toxicity from acute ingestion or acute inhalation of manganese is rare. Chronic inhalation over many years, usually from occupational exposure, may lead to manganese toxicity. Exercise appropriate procedures to minimize potential hazards.

Additional information: RTECS #: OP0350000

Section 12 Ecological Information

Toxicity to fish: No data available

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available

Persistence and degradability: No data available **Bioaccumulative potential:** No data available

Mobility in soil: No data available **PBT and vPvB assessment:** No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport Information (US DOT / CANADA TDG)

UN/NA number: UN1479 **Shipping name:** Oxidizing solid, n.o.s., (Manganese dioxide)

Hazard class: 5.1 **Packing group:** III **Reportable Quantity:** No **Marine pollutant:** No

Exceptions: Limited quantity equal to or less than 5 Kg **2012 ERG Guide #** 140

Section 15 Regulatory Information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the inventory list.

| Component | TSCA | CERCLA (RQ) | RCRA code | DSL | NDSL | WHMIS Classification |
|-------------------|--------|-------------|------------|--------|------------|----------------------|
| Manganese dioxide | Listed | Not listed | Not listed | Listed | Not listed | (A) (T) C; D2B |

Section 16 Additional Information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: #82489 MAXIMUM STRENGTH SPRAY ADHESIVE

Other means of identification

SDS number: RE1000037526

Recommended restrictions

Recommended use: Adhesive

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Company Name: CREATIVE ART MATERIALS LTD
Address: 1214 RIVER HWY UNIT G
MOORESVILLE, NC 28117-6518
US
Telephone: 866-833-7797

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Toxicity - Category 3
Single Exposure (Narcotic effect.)
Aspiration Hazard Category 1

Environmental Hazards

Acute hazards to the aquatic environment Category 3
Chronic hazards to the aquatic environment Category 3

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Harmful to aquatic life with long lasting effects.

Precautionary Statements

- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment.
- Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell.
- Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNO):

None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|---|-------------|-------------------------|
| Acetic acid, methyl ester | 79-20-9 | 20 - <50% |
| Propane | 74-98-6 | 10 - <20% |
| 2-Propanone | 67-64-1 | 10 - <20% |
| Ethane, 1,1-difluoro- | 75-37-6 | 3 - 7% |
| Heptane, branched, cyclic and linear | 426260-76-6 | 2.5 - <5% |
| Methane, 1,1'-oxybis- | 115-10-6 | 1 - 5% |
| Solvent naphtha (petroleum), light aliph. | 64742-89-8 | 1 - <5% |
| Heptane | 142-82-5 | 1 - <5% |
| Naphtha (petroleum), hydrotreated light | 64742-49-0 | 1 - <5% |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
- Ingestion:** Rinse mouth. Call a physician or poison control center immediately. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Personal Protection for First-aid Responders: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Accidental release measures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation): No data available.

Safe handling advice: Wash hands thoroughly after handling. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Contact avoidance measures: No data available.

Storage

Safe storage conditions: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2

Safe packaging materials: No data available.

Storage Temperature: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | Type | Exposure Limit Values | | Source |
|---|------|-----------------------|-------------------------|---|
| Acetic acid, methyl ester | REL | 200 ppm | 610 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | STEL | 250 ppm | 760 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | PEL | 200 ppm | 610 mg/m ³ | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| | STEL | 250 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | TWA | 200 ppm | 610 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | STEL | 250 ppm | 760 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| Propane | TWA | 200 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | REL | 1,000 ppm | 1,800 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | PEL | 1,000 ppm | 1,800 mg/m ³ | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| | TWA | 1,000 ppm | 1,800 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| 2-Propanone | STEL | 1,000 ppm | 2,400 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | PEL | 1,000 ppm | 2,400 mg/m ³ | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| | TWA | 250 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | TWA | 750 ppm | 1,800 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | STEL | 500 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | REL | 250 ppm | 590 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| Solvent naphtha (petroleum), light aliph. | TWA | 100 ppm | 400 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | PEL | 100 ppm | 400 mg/m ³ | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| | REL | 100 ppm | 400 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| Naphtha (petroleum), hydrotreated light | REL | 100 ppm | 400 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | TWA | 100 ppm | 400 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | PEL | 100 ppm | 400 mg/m ³ | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| Heptane | TWA | 400 ppm | 1,600 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | REL | 85 ppm | 350 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | PEL | 500 ppm | 2,000 mg/m ³ | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |

| | | | | |
|---------------------------|------------|---------|-------------|--|
| | STEL | 500 ppm | 2,000 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | TWA | 400 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | STEL | 500 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | Ceil_ Time | 440 ppm | 1,800 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| Methanol | STEL | 250 ppm | 325 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | TWA | 200 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | STEL | 250 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | STEL | 250 ppm | 325 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | REL | 200 ppm | 260 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | PEL | 200 ppm | 260 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| | TWA | 200 ppm | 260 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| Benzene, methyl- | STEL | 150 ppm | 560 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | REL | 100 ppm | 375 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | TWA | 100 ppm | 375 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | Ceiling | 300 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000), as amended |
| | TWA | 20 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | TWA | 200 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000), as amended |
| | MAX. CONC | 500 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000), as amended |
| | STEL | 150 ppm | 560 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| Benzene | REL | 0.1 ppm | | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | TWA | 1 ppm | | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | Ceiling | 25 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000), as amended |
| | TWA | 0.5 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | STEL | 2.5 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | STEL | 5 ppm | | US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended |
| | OSHA ACT | 0.5 ppm | | US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended |
| | TWA | 10 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000), as amended |
| | MAX. CONC | 50 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000), as amended |
| | STEL | 5 ppm | | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | TWA | 1 ppm | | US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended |
| | STEL | 1 ppm | | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| Benzene, (1-methylethyl)- | REL | 50 ppm | 245 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | TWA | 50 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | PEL | 50 ppm | 245 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| | TWA | 50 ppm | 245 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | TWA | 1 ppm | | US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values, as amended |
| Benzene, ethyl- | STEL | 125 ppm | 545 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | REL | 100 ppm | 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | PEL | 100 ppm | 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| | STEL | 125 ppm | 545 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | TWA | 100 ppm | 435 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | TWA | 20 ppm | | US. ACGIH Threshold Limit Values, as amended |
| Naphthalene | STEL | 15 ppm | 75 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | REL | 10 ppm | 50 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended |
| | PEL | 10 ppm | 50 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended |
| | TWA | 10 ppm | 50 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |
| | TWA | 10 ppm | | US. ACGIH Threshold Limit Values, as amended |
| | STEL | 15 ppm | 75 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended |

Biological Limit Values

| Chemical Identity | Exposure Limit Values | Source |
|---|--------------------------------|-----------|
| 2-Propanone (acetone: Sampling time: End of shift.) | 25 mg/l (Urine) | ACGIH BEL |
| Methanol (methanol: Sampling time: End of shift.) | 15 mg/l (Urine) | ACGIH BEL |
| Benzene, methyl- (toluene: Sampling time: End of shift.) | 0.03 mg/l (Urine) | ACGIH BEL |
| Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.) | 0.3 mg/g (Creatinine in urine) | ACGIH BEL |
| Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.) | 0.02 mg/l (Blood) | ACGIH BEL |
| Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.) | 25 µg/g (Creatinine in urine) | ACGIH BEL |
| Benzene (t,t-Muconic acid: Sampling time: End of shift.) | 500 µg/g (Creatinine in urine) | ACGIH BEL |
| Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.) | 0.15 g/g (Creatinine in urine) | ACGIH BEL |

Exposure guidelines

| | | |
|-------------|--|-----------------------------------|
| Methanol | US. ACGIH Threshold Limit Values, as amended | Can be absorbed through the skin. |
| Benzene | US. ACGIH Threshold Limit Values, as amended | Can be absorbed through the skin. |
| Naphthalene | US. ACGIH Threshold Limit Values, as amended | Can be absorbed through the skin. |

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes. When using do not smoke.

9. Physical and chemical properties

Appearance

| | |
|---|---------------------------|
| Physical state: | liquid |
| Form: | Spray Aerosol |
| Color: | No data available. |
| Odor: | No data available. |
| Odor Threshold: | No data available. |
| pH: | No data available. |
| Freezing point: | No data available. |
| Boiling Point: | No data available. |
| Flash Point: | Estimated -104.44 °C |
| Evaporation Rate: | No data available. |
| Flammability (solid, gas): | No data available. |
| Explosive limit - upper (%): | No data available. |
| Explosive limit - lower (%): | No data available. |
| Vapor pressure: | 3,240 - 4,619 hPa (20 °C) |
| Vapor density (air=1): | No data available. |
| Density: | No data available. |
| Relative density: | No data available. |
| Solubility in Water: | No data available. |
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | No data available. |

| | |
|----------------------------|--------------------|
| Self Ignition Temperature: | No data available. |
| Decomposition Temperature: | No data available. |
| Kinematic viscosity: | No data available. |
| Dynamic viscosity: | No data available. |
| Explosive properties: | No data available. |
| Oxidizing properties: | No data available. |

10. Stability and reactivity

| | |
|-------------------------------------|---|
| Reactivity: | No data available. |
| Chemical Stability: | Material is stable under normal conditions. |
| Possibility of hazardous reactions: | No data available. |
| Conditions to avoid: | Avoid heat or contamination. |
| Incompatible Materials: | No data available. |
| Hazardous Decomposition Products: | No data available. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------|--------------------|
| Inhalation: | No data available. |
| Skin Contact: | No data available. |
| Eye contact: | No data available. |
| Ingestion: | No data available. |

Symptoms related to the physical, chemical and toxicological characteristics

| | |
|---------------|--------------------|
| Inhalation: | No data available. |
| Skin Contact: | No data available. |
| Eye contact: | No data available. |
| Ingestion: | No data available. |

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

| | |
|------------------------|--|
| Oral Product: | ATEmix: 10,287.02 mg/kg |
| Dermal Product: | ATEmix: 51,427.61 mg/kg |
| Inhalation Product: | ATEmix: 113.09 mg/l Dusts, mists and fumes |

| | |
|------------------------------------|--------------------|
| Repeated dose toxicity Product: | No data available. |
|------------------------------------|--------------------|

Components:

| | |
|--|--|
| Acetic acid, methyl ester | NOAEL (Rat(Female, Male), Inhalation, 28 d): 350 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, 28 d): 2,000 ppm(m) Inhalation Experimental result, Key study |
| Propane | NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study |
| 2-Propanone | NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental result, Key study |
| Ethane, 1,1-difluoro- | NOAEL (Rat(Female, Male), Inhalation, 104 Weeks): 2.5 %(m) Inhalation Experimental result, Key study |
| Methane, 1,1'-oxybis- | NOAEL (Rat(Female, Male), Inhalation, 2 yr): 2.5 %(m) Inhalation Experimental result, Key study |
| Solvent naphtha (petroleum), light aliph. | NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402 mg/m3 Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study |
| Heptane | NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental result, Key study |
| Naphtha (petroleum), hydrotreated light | NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Read- across based on grouping of substances (category approach), Key study NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study |

Skin Corrosion/Irritation

Product: No data available.

Components:

| | |
|--|---------------------------------|
| Acetic acid, methyl ester | in vivo (Rabbit): Not irritant |
| 2-Propanone | in vivo (Rabbit): Not irritant |
| Ethane, 1,1-difluoro- | estimated Not irritating |
| Heptane, branched, cyclic and linear | estimated Irritating. |
| Heptane | in vivo (Rabbit): Irritating |
| Naphtha (petroleum), hydrotreated light | In vitro (Human): not corrosive |

Serious Eye Damage/Eye Irritation

Product: No data available.

Components:

| | |
|--|---|
| Acetic acid, methyl ester | Rabbit: Irritating |
| 2-Propanone | Irritating. Rabbit, 24 hrs: Minimum grade of severe eye irritant |
| Solvent naphtha (petroleum), light aliph. | Rabbit: Not irritating |
| Heptane | Rabbit, 24 - 72 hrs: Not irritating |
| Naphtha (petroleum), hydrotreated light | Rabbit, 24 - 72 hrs: Not irritating |

Respiratory or Skin Sensitization

Product: No data available.

Components:

| | |
|-------------|--|
| 2-Propanone | Skin sensitization:, in vivo (Guinea pig): Non sensitising |
|-------------|--|

Solvent naphtha
(petroleum), light aliph.
Heptane
Naphtha (petroleum),
hydrotreated light

Skin sensitization:, in vivo (Guinea pig): Non sensitising
Skin sensitization:, in vivo (Guinea pig): Non sensitising
Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Components:

2-Propanone Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.
Heptane Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Components:

Heptane, branched, cyclic and linear May be fatal if swallowed and enters airways.
Solvent naphtha May be fatal if swallowed and enters airways.
(petroleum), light aliph.
Heptane May be fatal if swallowed and enters airways.
Naphtha (petroleum), May be fatal if swallowed and enters airways.
hydrotreated light

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Components:

| | |
|---|---|
| Acetic acid, methyl ester | LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 295 - 348 mg/l Mortality LC 50 (Danio rerio, 48 h): 250 - 350 mg/l Experimental result, Key study |
| Propane | LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study |
| 2-Propanone | LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key study |
| Methane, 1,1'-oxybis- | LC 50 (Various, 96 h): 1,783.04 mg/l QSAR QSAR, Supporting study |
| Naphtha (petroleum), hydrotreated light | LC 50 (96 h): 8.41 mg/l Experimental result, Key study |

Aquatic Invertebrates

Product: No data available.

Components:

| | |
|---|--|
| Acetic acid, methyl ester | EC 50 (Daphnia magna, 48 h): 1,026.7 mg/l Experimental result, Key study |
| 2-Propanone | LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study |
| Solvent naphtha (petroleum), light aliph. | EC 50 (Daphnia magna, 48 h): 32 mg/l Experimental result, Supporting study |
| Naphtha (petroleum), hydrotreated light | EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study |

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Components:

| | |
|---|--|
| Naphtha (petroleum), hydrotreated light | NOAEL (Daphnia magna): 2.6 mg/l Other, Key study |
|---|--|

Aquatic Invertebrates

Product: No data available.

Components:

| | |
|---|--|
| 2-Propanone | LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study |
| Heptane, branched, cyclic and linear | NOEC : < 1 mg/l estimation |
| Naphtha (petroleum), hydrotreated light | EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study |

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Components:

| | |
|---|--|
| Acetic acid, methyl ester | 70 % Detected in water. Experimental result, Key study |
| Propane | 100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study |
| 2-Propanone | 90.9 % (28 d) Detected in water. Experimental result, Key study |
| Methane, 1,1'-oxybis- | 5 % (28 d) Detected in water. Experimental result, Key study |
| Solvent naphtha (petroleum), light aliph. | 90.35 % (28 d) Detected in water. Experimental result, Supporting study |
| Naphtha (petroleum), hydrotreated light | 95 % (10 d) The 10-day window requirement is fulfilled. 90.35 % (28 d) Detected in water. Experimental result, Supporting study |

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Components:

| | |
|---|--|
| 2-Propanone | Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment Experimental result, Not specified |
| Solvent naphtha (petroleum), light aliph. | Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study |
| Naphtha (petroleum), hydrotreated light | Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study |

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Components:

| | |
|---|---|
| Naphtha (petroleum), hydrotreated light | Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study |
|---|---|

Mobility in soil: No data available.

Components:

| | |
|---|--------------------|
| Acetic acid, methyl ester | No data available. |
| Propane | No data available. |
| 2-Propanone | No data available. |
| Ethane, 1,1-difluoro- | No data available. |
| Heptane, branched, cyclic and linear | No data available. |
| Methane, 1,1'-oxybis- | No data available. |
| Solvent naphtha (petroleum), light aliph. | No data available. |
| Heptane | No data available. |
| Naphtha (petroleum), hydrotreated light | No data available. |

Other adverse effects: Harmful to aquatic life with long lasting effects.

13. Disposal considerations

| | |
|--------------------------------|---|
| Disposal instructions: | Discharge, treatment, or disposal may be subject to national, state, or local laws. |
| Contaminated Packaging: | No data available. |

14. Transport information

DOT

| | |
|-------------------------------|---------------------|
| UN Number: | UN 1950 |
| UN Proper Shipping Name: | Aerosols, flammable |
| Transport Hazard Class(es) | |
| Class: | 2.1 |
| Label(s): | — |
| EmS No.: | |
| Packing Group: | — |
| Special precautions for user: | None known. |

IATA

| | |
|-------------------------------|---------------------|
| UN Number: | UN 1950 |
| UN Proper Shipping Name: | Aerosols, flammable |
| Transport Hazard Class(es): | |
| Class: | 2.1 |
| Label(s): | — |
| Packing Group: | — |
| Special precautions for user: | None known. |
| Other information | |
| Passenger and cargo aircraft: | Allowed. 203 |
| Cargo aircraft only: | Allowed. 203 |

IMDG

| | |
|-------------------------------|---------------------|
| UN Number: | UN 1950 |
| UN Proper Shipping Name: | Aerosols, flammable |
| Transport Hazard Class(es) | |
| Class: | 2.1 |
| Label(s): | — |
| EmS No.: | F-D, S-U |
| Packing Group: | — |
| Special precautions for user: | None known. |

The classification shown in this section may be eligible for use of an exception, such as "Limited Quantity", per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

| <u>Chemical Identity</u> | <u>OSHA hazard(s)</u> |
|--------------------------|--|
| Benzene | Flammability Cancer Aspiration Eye Blood Skin respiratory tract irritation Central nervous system |

CERCLA Hazardous Substance List (40 CFR 302.4):

| <u>Chemical Identity</u> |
|--|
| RCRA HAZARDOUS WASTE NO. D001 |
| Acetic acid, methyl ester |
| UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY |
| ACETONE |
| Ethane, 1,1-difluoro- |
| METHANOL |
| METHYL ALCOHOL |
| BENZENE, METHYL- |
| BENZENE |
| BENZENE, 1-METHYLETHYL- |
| CUMENE |
| ETHYLBENZENE |
| NAPHTHALENE |

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable (gases, aerosols, liquids, or solids), Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Aspiration Hazard

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

None present or none present in regulated quantities.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Acetic acid, methyl ester
Propane
2-Propanone
Ethane, 1,1-difluoro-
Methane, 1,1'-oxybis-
Solvent naphtha (petroleum), light aliph.
Naphtha (petroleum), hydrotreated light
Heptane

US. Massachusetts RTK - Substance List

Chemical Identity

Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Acetic acid, methyl ester
Propane
2-Propanone
Methane, 1,1'-oxybis-
Solvent naphtha (petroleum), light aliph.
Naphtha (petroleum), hydrotreated light
Heptane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Acetic acid, methyl ester
2-Propanone
Ethane, 1,1-difluoro- Group I Annex F

Stockholm convention

Acetic acid, methyl ester
2-Propanone
Ethane, 1,1-difluoro-

Rotterdam convention

Acetic acid, methyl ester
2-Propanone
Ethane, 1,1-difluoro-

Kyoto protocol

Inventory Status:

| | |
|---|--|
| Australia AICS | On or in compliance with the inventory |
| Canada DSL Inventory List | On or in compliance with the inventory |
| Canada NDSL Inventory | Not in compliance with the inventory. |
| Ontario Inventory | Not in compliance with the inventory. |
| China Inv. Existing Chemical Substances | On or in compliance with the inventory |
| Japan (ENCS) List | Not in compliance with the inventory. |
| Japan ISHL Listing | Not in compliance with the inventory. |
| Japan Pharmacopoeia Listing | Not in compliance with the inventory. |
| Korea Existing Chemicals Inv. (KECI) | On or in compliance with the inventory |
| Mexico INSQ | Not in compliance with the inventory. |
| New Zealand Inventory of Chemicals | On or in compliance with the inventory |
| Philippines PICCS | Not in compliance with the inventory. |
| Taiwan Chemical Substance Inventory | Not in compliance with the inventory. |
| US TSCA Inventory | On or in compliance with the inventory |
| EINECS, ELINCS or NLP | Not in compliance with the inventory. |

16. Other information, including date of preparation or last revision

Issue Date: 09/29/2021

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

Safety Data Sheet

Melt-N-Pour Agarose, 0.8%

CAROLINA[®]
www.carolina.com

Section 1 Product Description

Product Name: Melt-N-Pour Agarose, 0.8%
Recommended Use: Science education applications
Distributor: Carolina Biological Supply Company
2700 York Road, Burlington, NC 27215
1-800-227-1150
Chemical Information: 800-227-1150 (8am-5pm (ET) M-F)
Chemtrec: 800-424-9300 (Transportation Spill Response 24 hours)

Section 2 Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Classification:

Section 3 Composition / Information on Ingredients

| <u>Chemical Name</u> | <u>CAS #</u> | <u>%</u> |
|-----------------------------|--------------|----------|
| Tris Borate EDTA Buffer, 1X | | 99.2 |
| Agarose | | 0.8 |

Section 4 First Aid Measures

Emergency and First Aid Procedures

Inhalation: In case of accident by inhalation: remove casualty to fresh air and keep at rest.
Eyes: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact: After contact with skin, wash immediately with plenty of water.
Ingestion: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Section 5 Firefighting Procedures

Extinguishing Media: Use dry chemical, CO2 or appropriate foam.
Fire Fighting Methods and Protection: Firefighters should wear full protective equipment and NIOSH approved self-contained breathing apparatus.
Fire and/or Explosion Hazards: N/A
Hazardous Combustion Products: Carbon dioxide, Carbon monoxide, Nitrogen oxides

Section 6 Spill or Leak Procedures

Steps to Take in Case Material Is Released or Spilled: No adverse health affects expected from the clean-up of spilled material. Follow personal protective equipment recommendations found in Section 8 of this (M)SDS. Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed. Isolate area. Keep unnecessary personnel away. Remove soiled clothing and launder before reuse.
Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Contain the discharged material. Do not flush spill to drain.

Section 7 Handling and Storage

Handling: Avoid contact with skin and eyes.
Storage: Keep container tightly closed in a cool, well-ventilated place.
Suitable for any general chemical storage.

Safety Data Sheet

Storage Code: Green - general chemical storage

Section 8

Protection Information

| Chemical Name | ACGIH | | OSHA PEL | |
|---------------|-------|--------|----------|--------|
| | (TWA) | (STEL) | (TWA) | (STEL) |
| Boric Acid | N/A | N/A | N/A | N/A |

Control Parameters

Engineering Measures:

No exposure limits exist for the constituents of this product. General room ventilation might be required to maintain operator comfort under normal conditions of use. Good general room ventilation should be sufficient to control airborne contaminants to safe levels.

Personal Protective Equipment (PPE):

Lab coat, apron, eye wash, safety shower.

Respiratory Protection:

No respiratory protection required under normal conditions of use. Wear a NIOSH approved respirator if any exposure is possible.

Eye Protection:

Wear chemical splash goggles when handling this product. Have an eye wash station available.

Skin Protection:

Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves:

Natural latex, Natural rubber, Neoprene, Nitrile, Polyvinyl chloride

Section 9

Physical Data

Formula: Product is a mixture

Molecular Weight:

Appearance: Cloudy (milky) Semi-solid

Odor: No data available

Odor Threshold: No data available

pH: No data available

Melting Point: No data available

Boiling Point: 100 C

Flash Point: No data available

Flammable Limits in Air: N/A

Vapor Pressure: No data available

Evaporation Rate (BuAc=1): N/A

Vapor Density (Air=1): No data available

Specific Gravity: No data available

Solubility in Water: Soluble

Log Pow (calculated): No data available

Autoignition Temperature: No data available

Decomposition Temperature: No data available

Viscosity: 10

Percent Volatile by Volume: No data available

Section 10

Reactivity Data

Reactivity:

No data available

Chemical Stability:

Stable under normal conditions.

Conditions to Avoid:

None known.

Incompatible Materials:

Water-reactive materials

Hazardous Decomposition Products:

Carbon dioxide, Carbon monoxide, Nitrogen oxides

Hazardous Polymerization:

Will not occur

Section 11

Toxicity Data

Routes of Entry

Ingestion, skin and eye contact.

Symptoms (Acute):

No data available

Delayed Effects:

No data available

Acute Toxicity:

Chemical Name

CAS Number

Oral LD50

Dermal LD50

Inhalation LC50

Water

Oral LD50 Rat
90000 mg/kg

Boric Acid

Oral LD50 Rat
2660 mg/kg

Safety Data Sheet

EDTA, Disodium Salt, Dihydrate

Oral LD50 Rat
2000 mg/kg

Carcinogenicity:

| Chemical Name | CAS Number | IARC | NTP | OSHA |
|--------------------------------|------------|------------|------------|------------|
| Boric Acid | | Listed | Not listed | Not listed |
| EDTA, Disodium Salt, Dihydrate | | Not listed | Not listed | Not listed |
| Sodium Hydroxide | | Not listed | Not listed | Not listed |

Chronic Effects:

| | |
|------------------------------|--|
| Mutagenicity: | No evidence of a mutagenic effect. |
| Teratogenicity: | No evidence of a teratogenic effect (birth defect). |
| Sensitization: | No evidence of a sensitization effect. |
| Reproductive: | No evidence of negative reproductive effects. |
| Target Organ Effects: | |
| Acute: | See Section 2 |
| Chronic: | Not listed as a carcinogen by IARC, NTP or OSHA., Reproductive systems |

Section 12

Ecological Data

| | |
|-------------------------------|---|
| Overview: | This material is not expected to be harmful to the ecology. |
| Mobility: | No data |
| Persistence: | Dissolved into water, Photodegradation |
| Bioaccumulation: | No data |
| Degradability: | No data |
| Other Adverse Effects: | No data |

| Chemical Name | CAS Number | Eco Toxicity |
|--------------------------------|------------|--|
| Water | | No data available |
| Boric Acid | | 48 HR EC50 DAPHNIA MAGNA 115 - 153 MG/L |
| EDTA, Disodium Salt, Dihydrate | | |
| Sodium Hydroxide | | Aquatic LC50 (96h) Rainbow Trout 45.4 MG/L |

Section 13

Disposal Information

| | |
|--------------------------------|---|
| Disposal Methods: | Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance. |
| Waste Disposal Code(s): | Not Determined |

Section 14

Transport Information

| | |
|---|---|
| Ground - DOT Proper Shipping Name: Not regulated for transport by US DOT. | Air - IATA Proper Shipping Name: Not regulated for air transport by IATA. |
|---|---|

Safety Data Sheet

Section 15

Regulatory Information

TSCA Status:

All components in this product are on the TSCA Inventory.

| Chemical Name | CAS Number | § 313 Name | § 304 RQ | CERCLA RQ | § 302 TPQ | CAA 112(2) TQ |
|--------------------------------|------------|------------|----------|-----------|-----------|---------------|
| Boric Acid | | No | No | No | No | No |
| EDTA, Disodium Salt, Dihydrate | | No | No | No | No | No |
| Sodium Hydroxide | | No | No | No | No | No |

Section 16

Additional Information

Revised: 09/25/2014

Replaces: 09/25/2014

Printed: 04-22-2015

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Carolina Biological Supply makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

| | | | |
|--------|---|------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists | NTP | National Toxicology Program |
| CAS | Chemical Abstract Service Number | OSHA | Occupational Safety and Health Administration |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act | PEL | Permissible Exposure Limit |
| DOT | U.S. Department of Transportation | ppm | Parts per million |
| IARC | International Agency for Research on Cancer | RCRA | Resource Conservation and Recovery Act |
| N/A | Not Available | SARA | Superfund Amendments and Reauthorization Act |
| | | TLV | Threshold Limit Value |
| | | TSCA | Toxic Substances Control Act |
| | | IDLH | Immediately dangerous to life and health |



Fisher Scientific

Part of Thermo Fisher Scientific

SAFETY DATA SHEET

Creation Date 27-Apr-2009

Revision Date 21-Dec-2015

Revision Number 2

1. Identification

Product Name Methanol

Cat No. : A412-1; A412-4; A412-4LC; A412-20; A412-200; A412200-001;
A412-200LC; A412-500; A412CU-1300; A412P-4; A412SK-4;
A412FB-19; A412FB-50; A412FB-115; A412FB-200; A412POP-19;
A412POPB-200; A412RB50; A412RB-115; A412RB-200; A412RS-19;
A412RS-28; A412RS-50; A412RS-115; A412RS-200; A412SS-115

Synonyms Methyl alcohol

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company
Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number
CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|------------|
| Flammable liquids | Category 2 |
| Acute oral toxicity | Category 3 |
| Acute dermal toxicity | Category 3 |
| Acute Inhalation Toxicity - Vapors | Category 3 |
| Specific target organ toxicity (single exposure) | Category 1 |
| Target Organs - Optic nerve. | |
| Specific target organ toxicity - (repeated exposure) | Category 1 |
| Target Organs - Kidney, Liver, spleen, Blood. | |

Label Elements

Signal Word
Danger

Hazard Statements
Highly flammable liquid and vapor
Toxic if swallowed
Toxic in contact with skin

Toxic if inhaled
Causes damage to organs
Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Response

IF exposed: Call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell
Wash contaminated clothing before reuse
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Rinse mouth

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other hazards**

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous.
WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

3. Composition / information on ingredients

| Component | CAS-No | Weight % |
|----------------|---------|----------|
| Methyl alcohol | 67-56-1 | >95 |

4. First-aid measures

| | |
|--|---|
| General Advice | Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. |
| Eye Contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required. |
| Inhalation | Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. |
| Ingestion | Do not induce vomiting. Call a physician or Poison Control Center immediately. |
| Most important symptoms/effects | Breathing difficulties. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting |
| Notes to Physician | Treat symptomatically |

5. Fire-fighting measures

| | |
|---|---|
| Suitable Extinguishing Media | Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray. |
| Unsuitable Extinguishing Media | Water may be ineffective |
| Flash Point | 12 °C / 53.6 °F |
| Method - | No information available |
| Autoignition Temperature | 455 °C / 851 °F |
| Explosion Limits | |
| Upper | 31.00 vol % |
| Lower | 6.0 vol % |
| Sensitivity to Mechanical Impact | No information available |
| Sensitivity to Static Discharge | No information available |

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO) Formaldehyde

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
3

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

| | |
|--|--|
| Personal Precautions | Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. |
| Environmental Precautions | Should not be released into the environment. See Section 12 for additional ecological information. |
| Methods for Containment and Clean | Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. |

Up Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling Wear personal protective equipment. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

| Component | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------|--|--|--|
| Methyl alcohol | TWA: 200 ppm STEL: 250 ppm Skin | (Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³ | IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³ |
| Component | Quebec | Mexico OEL (TWA) | Ontario TWAEV |
| Methyl alcohol | TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ Skin | TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 310 mg/m ³ | TWA: 200 ppm STEL: 250 ppm Skin |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection Tightly fitting safety goggles.

Skin and body protection Long sleeved clothing.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. Physical and chemical properties

| | |
|----------------|--------------------------|
| Physical State | Liquid |
| Appearance | Colorless |
| Odor | Alcohol-like |
| Odor Threshold | No information available |

| | |
|--|-------------------------------|
| pH | Not applicable |
| Melting Point/Range | -98 °C / -144.4 °F |
| Boiling Point/Range | 64.7 °C / 148.5 °F @ 760 mmHg |
| Flash Point | 12 °C / 53.6 °F |
| Evaporation Rate | 5.2 (ether = 1) |
| Flammability (solid,gas) | Not applicable |
| Flammability or explosive limits | |
| Upper | 31.00 vol % |
| Lower | 6.0 vol % |
| Vapor Pressure | 128 hPa @ 20 °C |
| Vapor Density | 1.11 |
| Specific Gravity | 0.791 |
| Solubility | Miscible with water |
| Partition coefficient; n-octanol/water | No data available |
| Autoignition Temperature | 455 °C / 851 °F |
| Decomposition Temperature | No information available |
| Viscosity | 0.55 cP at 20 °C |
| Molecular Formula | C H4 O |
| Molecular Weight | 32.04 |
| VOC Content(%) | 100 |
| Surface tension | 0.02255 N/m @ 20°C |

10. Stability and reactivity

| | |
|----------------------------------|---|
| Reactive Hazard | None known, based on information available |
| Stability | Stable under normal conditions. |
| Conditions to Avoid | Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. |
| Incompatible Materials | Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases, Metals, Peroxides |
| Hazardous Decomposition Products | Carbon monoxide (CO), Formaldehyde |
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions | None under normal processing. |

11. Toxicological information

Acute Toxicity

Product Information

Component Information

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|----------------|--|---|--|
| Methyl alcohol | Calc. ATE 60 mg/kg LD50 > 1187 – 2769 mg/kg (Rat) | Calc. ATE 60 mg/kg LD50 = 17100 mg/kg (Rabbit) | Calc. ATE 0.6 mg/L (vapours) or 0.5 mg/L (mists) LC50 = 128.2 mg/L (Rat) 4 h |

Toxicologically Synergistic Products Carbon tetrachloride

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|-----------------|--|
| Irritation | Irritating to eyes and skin |
| Sensitization | No information available |
| Carcinogenicity | The table below indicates whether each agency has listed any ingredient as a carcinogen. |

| Component | CAS-No | IARC | NTP | ACGIH | OSHA | Mexico |
|-----------|--------|------|-----|-------|------|--------|
|-----------|--------|------|-----|-------|------|--------|

| | | | | | | |
|----------------|---------|------------|------------|------------|------------|------------|
| Methyl alcohol | 67-56-1 | Not listed | Not listed | Not listed | Not listed | Not listed |
|----------------|---------|------------|------------|------------|------------|------------|

| | |
|---|--|
| Mutagenic Effects | No information available |
| Reproductive Effects | Experiments have shown reproductive toxicity effects on laboratory animals. |
| Developmental Effects | Developmental effects have occurred in experimental animals. Component substance is listed on California Proposition 65 as a developmental hazard. |
| Teratogenicity | Teratogenic effects have occurred in experimental animals. |
| STOT - single exposure | Optic nerve |
| STOT - repeated exposure | Kidney Liver spleen Blood |
| Aspiration hazard | No information available |
| Symptoms / effects, both acute and delayed | May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting |
| Endocrine Disruptor Information | No information available |
| Other Adverse Effects | The toxicological properties have not been fully investigated. |

12. Ecological information

Ecotoxicity

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|----------------|------------------|--|---|-----------------------|
| Methyl alcohol | Not listed | Pimephales promelas: LC50 > 10000 mg/L 96h | EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min | EC50 > 10000 mg/L 24h |

| | |
|--------------------------------------|---|
| Persistence and Degradability | Persistence is unlikely based on information available. |
| Bioaccumulation/ Accumulation | No information available. |

| | |
|-----------------|---|
| Mobility | Will likely be mobile in the environment due to its volatility. |
|-----------------|---|

| Component | log Pow |
|----------------|---------|
| Methyl alcohol | -0.74 |

13. Disposal considerations

| | |
|-------------------------------|--|
| Waste Disposal Methods | Should not be released into the environment. |
|-------------------------------|--|

| Component | RCRA - U Series Wastes | RCRA - P Series Wastes |
|--------------------------|------------------------|------------------------|
| Methyl alcohol - 67-56-1 | U154 | - |

14. Transport information

DOT

| | |
|----------------------|----------|
| UN-No | UN1230 |
| Proper Shipping Name | METHANOL |
| Hazard Class | 3 |
| Packing Group | II |

TDG

| | |
|-------------------------|----------|
| UN-No | UN1230 |
| Proper Shipping Name | METHANOL |
| Hazard Class | 3 |
| Subsidiary Hazard Class | 6.1 |
| Packing Group | II |

IATA

| | |
|----------------------|----------|
| UN-No | UN1230 |
| Proper Shipping Name | METHANOL |
| Hazard Class | 3 |

| | |
|-------------------------|----------|
| Subsidiary Hazard Class | 6.1 |
| Packing Group | II |
| IMDG/IMO | |
| UN-No | UN1230 |
| Proper Shipping Name | METHANOL |
| Hazard Class | 3 |
| Subsidiary Hazard Class | 6.1 |
| Packing Group | II |

15. Regulatory information

All of the components in the product are on the following Inventory lists: Complete Regulatory Information contained in following SDS's. Australia China Canada Europe TSCA Korea Philippines Japan

International Inventories

| Component | TSCA | DSL | NDSL | EINECS | ELINCS | NLP | PICCS | ENCS | AICS | IECSC | KECL |
|----------------|------|-----|------|-----------|--------|-----|-------|------|------|-------|------|
| Methyl alcohol | X | X | - | 200-659-6 | - | | X | X | X | X | X |

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

| Component | CAS-No | Weight % | SARA 313 - Threshold Values % |
|----------------|---------|----------|-------------------------------|
| Methyl alcohol | 67-56-1 | >95 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act) Not applicable

Clean Air Act

| Component | HAPS Data | Class 1 Ozone Depletors | Class 2 Ozone Depletors |
|----------------|-----------|-------------------------|-------------------------|
| Methyl alcohol | X | | - |

OSHA Occupational Safety and Health Administration
Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Component | Hazardous Substances RQs | CERCLA EHS RQs |
|----------------|--------------------------|----------------|
| Methyl alcohol | 5000 lb | - |

California Proposition 65 This product contains the following proposition 65 chemicals

| Component | CAS-No | California Prop. 65 | Prop 65 NSRL | Category |
|----------------|---------|---------------------|--------------|---------------|
| Methyl alcohol | 67-56-1 | Developmental | - | Developmental |

U.S. State Right-to-Know Regulations

| Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|----------------|---------------|------------|--------------|----------|--------------|
| Methyl alcohol | X | X | X | X | X |

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B2 Flammable liquid
 D2A Very toxic materials
 D1A Very toxic materials



16. Other information

Prepared By Regulatory Affairs
 Thermo Fisher Scientific
 Email: EMSDS.RA@thermofisher.com

Creation Date 27-Apr-2009
Revision Date 21-Dec-2015
Print Date 21-Dec-2015
Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

1 Identification

- **Product identifier**
- **Trade name:** Methanol (Methyl Alcohol)
- **Product code:** ME1000-P
- **CAS Number:**
67-56-1
- **Recommended use and restriction on use**
- **Recommended use:**
Laboratory chemicals
Industrial uses.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
AquaPhoenix Scientific, Inc.
860 Gitts Run Road
Hanover, PA 17331
Phone: (717)632-1291
Toll-Free: (866)632-1291
info@aquaphoenixsci.com
- **Distributor:**
AquaPhoenix Scientific, Inc.
860 Gitts Run Road
Hanover, PA 17331
(717) 632-1291
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Acute Tox. 3 H301 Toxic if swallowed.
Acute Tox. 3 H311 Toxic in contact with skin.
Acute Tox. 3 H331 Toxic if inhaled.
Eye Irrit. 2B H320 Causes eye irritation.
STOT SE 1 H370 Causes damage to the nervous system and optic nerve.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS02 GHS06 GHS08

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 1)

· **Signal word:** Danger

· **Hazard statements:**

- H225 Highly flammable liquid and vapor.
- H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
- H320 Causes eye irritation.
- H370 Causes damage to the nervous system and optic nerve.

· **Precautionary statements:**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P330 Rinse mouth.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a poison center/doctor if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P361+P364 Take off immediately all contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

67-56-1 methanol

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air.
Seek immediate medical advice.
If experiencing respiratory symptoms: Call a poison center/doctor.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 2)

- **After skin contact:**
Immediately remove any clothing soiled by the product.
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; immediately call for medical help.
- **Most important symptoms and effects, both acute and delayed:**
Breathing difficulty
Dizziness
Coughing
Causes eye irritation.
Causes mild skin irritation.
Gastric or intestinal disorders when ingested.
Nausea
Acidosis
Blindness
Disorientation
Unconsciousness
- **Danger:**
Danger of impaired breathing.
Toxic if swallowed, in contact with skin or if inhaled.
Causes damage to the nervous system and optic nerve.
- **Indication of any immediate medical attention and special treatment needed:**
Contains ethanediol. Consult literature for specific antidotes.
Medical supervision for at least 48 hours.
If necessary oxygen respiration treatment.
If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Alcohol resistant foam
Gaseous extinguishing agents
Carbon dioxide
Water fog / haze
Water spray
Fire-extinguishing powder
- **For safety reasons unsuitable extinguishing agents:** No relevant information available.
- **Special hazards arising from the substance or mixture**
Highly flammable liquid and vapor.
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 3)

· **Additional information:**

- Eliminate all ignition sources if safe to do so.
- Cool endangered receptacles with water in flooding quantities.
- Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation.
- Keep away from ignition sources.
- Use respiratory protective device against the effects of fumes/dust/aerosol.
- Isolate area and prevent access.

· **Environmental precautions** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up**

- Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
- Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

- Avoid splashes or spray in enclosed areas.
- Use only in well ventilated areas.
- Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

- Highly flammable liquid and vapor.
- Keep ignition sources away - Do not smoke.
- Protect from heat.
- Protect against electrostatic charges.
- Flammable gas-air mixtures may be formed in empty containers/receptacles.

· **Conditions for safe storage, including any incompatibilities**

· **Requirements to be met by storerooms and receptacles:**

- Store in cool, dry conditions in well sealed receptacles.

· **Information about storage in one common storage facility:**

- Store away from foodstuffs.
- Store away from oxidizing agents.

· **Further information about storage conditions:** This product is hygroscopic.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 4)

· Control parameters

· Components with limit values that require monitoring at the workplace:

67-56-1 methanol

| | |
|---------------|--|
| PEL (USA) | Long-term value: 260 mg/m ³ , 200 ppm |
| REL (USA) | Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin |
| TLV (USA) | Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI |
| EL (Canada) | Short-term value: 250 ppm Long-term value: 200 ppm Skin |
| EV (Canada) | Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin |
| LMPE (Mexico) | Short-term value: 250 ppm Long-term value: 200 ppm PIEL, IBE |

· Ingredients with biological limit values:

67-56-1 methanol

| | |
|-----------|---|
| BEI (USA) | 15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific) |
|-----------|---|

· Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Engineering controls: Provide adequate ventilation.

· Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Neoprene gloves

Butyl rubber, BR

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 5)

Laminated film gloves.

- **Not suitable are gloves made of the following materials:**

PVA gloves

Natural rubber, NR

- **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- **Body protection:** Solvent resistant protective clothing
- **Limitation and supervision of exposure into the environment**
No relevant information available.
- **Risk management measures** No relevant information available.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

Form:

Liquid

Color:

Colorless

- **Odor:**

Like alcohol

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Melting point/Melting range:**

-98 °C (-144.4 °F)

- **Boiling point/Boiling range:**

65 °C (149 °F)

- **Flash point:**

12 °C (53.6 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Auto-ignition temperature:**

>260 °C (>500 °F)

- **Decomposition temperature:**

Not determined.

- **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits**

Lower:

6 Vol %

Upper:

31 Vol %

- **Oxidizing properties:**

Not determined.

- **Vapor pressure at 20 °C (68 °F):**

130 hPa (97.5 mm Hg) (97.5 mm Hg)

- **Density:**

Relative density:

0.79

Vapor density at 20 °C (68 °F):

1.11

Evaporation rate:

Not determined.

- **Solubility in / Miscibility with**

Water:

Fully miscible.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 6)

- **Partition coefficient (n-octanol/water) at 20 °C (68 °F):** -0.77 log POW
- **Viscosity**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Other information** No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Highly flammable liquid and vapor.
Reacts violently with oxidizing agents.
Toxic fumes may be released if heated above the decomposition point.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Reacts with strong acids and alkali.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
Under fire conditions only:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Toxic if swallowed, in contact with skin or if inhaled.

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

| | | |
|------------|---------|-----------|
| Oral | LD50 | 100 mg/kg |
| Dermal | LD50 | 300 mg/kg |
| Inhalative | LC50/4h | 3 mg/l |

- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Irritating effect.
- **Sensitization:** Based on available data, the classification criteria are not met.

· IARC (International Agency for Research on Cancer):

Substance is not listed.

· NTP (National Toxicology Program):

Substance is not listed.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 7)

· **OSHA-Ca (Occupational Safety & Health Administration):**

Substance is not listed.

· **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Causes damage to the nervous system and optic nerve.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

· **Toxicity**

- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.

· **Additional ecological information**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Incinerate in accordance with local, state and federal regulations.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· **Uncleaned packagings**

- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 8)

· UN-Number
 · DOT, ADR/RID/ADN, IMDG, IATA UN1230

· UN proper shipping name
 · DOT, IATA Methanol
 · ADR/RID/ADN, IMDG METHANOL

· Transport hazard class(es)

· DOT



· Class 3
 · Label 3

· ADR/RID/ADN



· Class 3 (FT1)
 · Label 3+6.1

· IMDG



· Class 3
 · Label 3/6.1

· IATA



· Class 3
 · Label 3 (6.1)

· Packing group
 · DOT, ADR/RID/ADN, IMDG, IATA II

· Environmental hazards

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 336

· EMS Number: F-E,S-D

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 9)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

Substance is not listed.

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is listed.

· **TSCA (Toxic Substances Control Act)**

Substance is listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity for females:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is listed.

· **EPA (Environmental Protection Agency):**

Substance is not listed.

· **IARC (International Agency for Research on Cancer):**

Substance is not listed.

· **Canadian Domestic Substances List (DSL) (Substances not listed.):**

Substance is listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 05, 2018

Revision: July 05, 2018

Trade name: Methanol (Methyl Alcohol)

(Cont'd. of page 10)

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

• **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com

Section 1 Chemical Product and Company Information

5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: 800/962-2660

CHEMTREC 24 Hour Emergency
Phone Number (800) 424-9300
For laboratory use only.
Not for drug, food or household use.

Product METHYL ALCOHOL

Synonyms Methanol ; Wood Alcohol

Section 2 Hazards Identification

Signal word: DANGER

Pictograms: GHS02 / GHS06 / GHS08

Target organs: Central nervous system, Liver, Kidneys, Heart

**GHS Classification:**

Flammable liquid (Category 2)

Acute toxicity, oral (Category 3)

Acute toxicity, dermal (Category 3)

Acute toxicity, inhalation (Category 3)

STOT-SE (Category 1)

GHS Label Information: Hazard statement:

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H331: Toxic if inhaled.

H370: Causes damage to organs.

Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330 +P310: IF SWALLOWED: Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P312: IF exposed or concerned: Call a POISON CENTER or doctor/physician if you feel unwell.

P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P233+P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405: Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with all local, state and federal regulations.

Ca Prop 65: This product contains a chemical known to the State of California to cause reproductive toxicity (Methanol, developmental).

Section 3 Composition / Information on Ingredients

| Chemical Name | CAS # | % | EINECS |
|---------------|---------|------|-----------|
| Methanol | 67-56-1 | 100% | 200-659-6 |

Section 4 First Aid Measures

INGESTION: MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: VAPOR HARMFUL. HARMFUL IF INHALED. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: HARMFUL IN CONTACT WITH SKIN. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire Fighting Measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Fires involving a small amount of combustibles may be smothered by dry chemical. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Closed containers exposed to heat may explode. Burns with a clear, almost invisible flame. Contact with strong oxidizers may cause fire.

Section 6 Accidental Release Measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Section 7 Handling & Storage

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8 Exposure Controls / Personal Protection

| Exposure Limits: | Chemical Name | ACGIH (TLV) | OSHA (PEL) | NIOSH (REL) |
|------------------|---------------|--|----------------------------|--|
| | Methanol | TWA: 262 mg/m ³ / STEL: 328 mg/m ³ | TWA: 260 mg/m ³ | TWA: 260 mg/m ³ / STEL: 325 mg/m ³ |

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

| | | |
|---|--|--|
| Appearance: Clear, colorless liquid. Odor: Pungent+ odor. Odor threshold: Data not available. pH: Data not available. Melting / Freezing point: -98°C (-144°F) Boiling point: 65°C (149°F) Flash point: 11°C (52°F) CC | Evaporation rate (Butyl acetate = 1): 4.6 Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: 7.3% / 36% Vapor pressure (mm Hg): 96 mm @ 20°C Vapor density (Air = 1): 1.11 Relative density (Specific gravity): 0.79 Solubility(ies): Complete in water. | Partition coefficient: (n-octanol / water): Low Pow: -82 Auto-ignition temperature: 463°C (867°F) Decomposition temperature: Data not available. Viscosity: Data not available. Molecular formula: CH ₃ OH Molecular weight: 32.04 |
|---|--|--|

Section 10 Stability & Reactivity

Chemical stability: Stable

Hazardous polymerization: Will not occur.

Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizing agents, strong acids, zinc, aluminum and magnesium, reducers, alkalies.

Hazardous decomposition products: Oxides of carbon and formaldehyde.

Section 11 Toxicological Information

Acute toxicity: Oral-rat LD50: 5,628 mg/kg ; Inhalation-rat LC50: 64,000 mg/kg/4hours ; Skin-rabbit LD50: 15,800 mg/kg

Skin corrosion/irritation: Data not available

Serious eye damage/irritation: Data not available

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenicity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1 with narcotic effects.

STOT-repeated exposure: Data not available

Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation of this material may cause irritation of the respiratory tract, nausea, shortness of breath and headache.

Ingestion: Ingestion may cause headache, dizziness, weakness, euphoria, drowsiness, shortness of breath, vomiting and incoordination. Can also cause blindness and death. Cannot be made nonpoisonous.

Skin: Contact with skin can cause moderate irritation, defatting, cracking and dermatitis. Skin absorption may contribute to overall exposure.

Eyes: Contact with eyes can cause severe irritation, even corneal burns. High concentrations of vapors may cause irritation.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: PC1400000

Section 12 Ecological Information

Toxicity to fish: Lepomis macrochirus (fish, fresh water); LC50 = 15,400 mg/l/96 hours

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna, EC50 = >10,000 mg/l/48 hours

Toxicity to algae: No data available

Persistence and degradability: Readily biodegradable

Bioaccumulative potential: Not expected to bioaccumulate

Mobility in soil: No data available

PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport Information

UN/NA number: UN1230

Shipping name: Methanol

Hazard class: 3 **Packing group:** II **Reportable Quantity:** Yes **Marine pollutant:** No **Exceptions:** Limited quantity equal to or less than 1 Lt.

Section 15 Regulatory Information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

| Component | TSCA | CERCLA (RQ) | RCRA code | DSL | NDSL | WHMIS Classification |
|-----------|--------|----------------------|-----------|--------|------------|----------------------|
| Methanol | Listed | 5,000 lbs. (2270 kg) | U154 | Listed | Not listed | B2; D1B; D2A; D2B |

Section 16 Additional Information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure.

FLINN SCIENTIFIC, INC.

Safety Data Sheet (SDS)

SDS #: 516.00

Revision Date: March 21, 2014

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Methyl Orange

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Signal Word **DANGER**

Pictograms



SECTION 2 — HAZARDS IDENTIFICATION

Hazard class: Acute toxicity, oral (Category 3). Toxic if swallowed (H301). Do not eat, drink or smoke when using this product (P270).

SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

| Component Name | CAS Number | Formula | Formula Weight | Concentration |
|--|------------|-------------------------|----------------|---------------|
| Methyl orange | 547-58-0 | $C_{14}H_{15}N_3O_3SNa$ | 327.334 | |
| Synonyms: Sodium p-dimethylaminoazobenzenesulfonate; C.I. 13025 | | | | |

SECTION 4 — FIRST AID MEASURES

Call a POISON CENTER or physician if you feel unwell.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing.

If on skin: Wash with plenty of water.

If swallowed: Rinse mouth. Immediately call a POISON CENTER or physician (P301+P310+P330).

SECTION 5 — FIRE FIGHTING MEASURES

Noncombustible solid.

When heated to decomposition, may emit toxic fumes.

In case of fire: Use a tri-class dry chemical fire extinguisher.

NFPA CODE
None
established

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Sweep up the spill, place in a sealed bag or container, and dispose. Ventilate area and wash spill site after material pickup is complete. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Organic #9. Store with dyes, indicators and stains.
Keep container tightly closed. Store in a cool, dry place.

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective gloves, protective clothing, and eye protection. Wash hands thoroughly after handling (P264). Will stain skin, clothing, and surfaces.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Orange powder. Odor like burnt rubber. pH indicator: 3.0 red to 4.4 yellow.
Soluble: Hot water. Partially in alcohol.

SECTION 10 — STABILITY AND REACTIVITY

Avoid contact with strong oxidizers.
Shelf life: Indefinite, if stored properly.

SECTION 11 — TOXICOLOGICAL INFORMATION

| | |
|--------------------------------------|-------------------------------------|
| Acute effects: Harmful if swallowed. | ORL-RAT LD ₅₀ : 60 mg/kg |
| Chronic effects: N.A. | IHL-RAT LC ₅₀ : N.A. |
| Target organs: N.A. | SKN-RBT LD ₅₀ : N.A. |

N.A. = Not available, not all health aspects of this substance have been fully investigated.

SECTION 12 — ECOLOGICAL INFORMATION

Data not yet available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.
Flinn Suggested Disposal Method #26a is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Toxic solids, organic, N.O.S.; Hazard class: 6.1, Keep away from food; UN number: UN2811

N/A = Not applicable

SECTION 15 — REGULATORY INFORMATION

TSCA-listed, EINECS-listed (208-925-3).

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

Consult your copy of the *Flinn Science Catalog/Reference Manual* for additional information about laboratory chemicals.

Revision Date: March 21, 2014

FLINN SCIENTIFIC, INC.

Safety Data Sheet (SDS)

SDS #: 519.00

Revision Date: February 6, 2014

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Methyl Red Indicator Solution

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Signal Word N/A

Pictograms

SECTION 2 — HAZARDS IDENTIFICATION

This chemical is considered nonhazardous according to GHS classifications for the Hazard Communication Standard. Treat all laboratory chemicals with caution.

Although this material is considered to be nonhazardous, unpredictable reactions among chemicals are always possible. Prudent laboratory practices should be observed.

SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

| Component Name | CAS Number | Formula | Formula Weight | Concentration |
|-------------------------|------------|------------------------|----------------|---------------|
| Methyl red, sodium salt | 845-10-3 | $C_{15}H_{14}N_3O_2Na$ | 291.28 | 0.1% |
| Water | 7732-18-5 | H_2O | 18.00 | >99% |

SECTION 4 — FIRST AID MEASURES

Call a POISON CENTER or physician if you feel unwell.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing.

If on skin: Wash with plenty of water.

If swallowed: Rinse mouth. Call a POISON CENTER or physician if you feel unwell.

SECTION 5 — FIRE FIGHTING MEASURES

Nonflammable, noncombustible solution.

In case of fire: Use a tri-class dry chemical fire extinguisher.

NFPA CODE
Nonc
established

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Ventilate area. Contain the spill with sand or absorbent material and deposit in a sealed bag or container. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Organic #9. Store with dyes, indicators and stains.
Avoid storing for prolonged periods. Color fades because of reduction.

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective gloves, protective clothing, and eye protection. Wash hands thoroughly after handling.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Red, orange or yellow liquid. Odorless.

pH indicator: 4.4 red to 6.2 yellow.

SECTION 10 — STABILITY AND REACTIVITY

Shelf life: Fair to poor. Color fades because of reduction.

SECTION 11 — TOXICOLOGICAL INFORMATION

Acute effects: N.A.

ORL-RAT LD₅₀: N.A.

Chronic effects: N.A.

IHL-RAT LC₅₀: N.A.

Target organs: N.A.

SKN-RBT LD₅₀: N.A.

N.A. = Not available, not all health aspects of this substance have been fully investigated.

SECTION 12 — ECOLOGICAL INFORMATION

Data not yet available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.

Flinn Suggested Disposal Method #26b is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Not regulated. Hazard class: N/A. UN number: N/A.

N/A = Not applicable

SECTION 15 — REGULATORY INFORMATION

Not listed.

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

Consult your copy of the *Flinn Science Catalog/Reference Manual* for additional information about laboratory chemicals.

Revision Date: February 6, 2014

Section 1 Chemical Product and Company Information

Page E1 of E2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

CHEMTREC 24 Hour Emergency
Phone Number (800) 424-9300
For laboratory use only.
Not for drug, food or household use.

| | |
|-----------------|---|
| Product | METHYL RED, INDICATOR SOLUTION |
| Synonyms | Methyl Red, 0.02% Aqueous pH Indicator Solution |

Section 2 Hazards Identification

This substance or mixture has not been classified as hazardous according to the Globally Harmonized System (GHS) of Classification and Labeling of Chemicals.

Signal word: Not classified
Pictograms: Not classified
Target organs: None known

GHS Classification: Not classified
GHS Label information: Hazard statement: Not classified
Precautionary statement: Not classified

Supplementary information:

Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Get medical attention if you feel unwell.

Ca Prop 65 - This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

Section 3 Composition / Information on Ingredients

| Chemical Name | CAS # | % | EINECS |
|-------------------------|-----------|--------|-----------|
| Water | 7732-18-5 | 99.98% | 231-791-2 |
| Methyl red, sodium salt | 845-10-3 | 0.02% | 212-682-9 |

Section 4 First Aid Measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. MAY CAUSE RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: MAY CAUSE EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY CAUSE SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire Fighting Measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: In fire conditions, water may evaporate from this solution which may cause hazardous decomposition products to be formed as dust or fume.

Section 6 Accidental Release Measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Section 7 Handling & Storage

Page E2 of E2

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale mist/vapors/spray. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, well-ventilated area away from incompatible substances. Protect from light.

Section 8 Exposure Controls / Personal Protection

| Exposure Limits: | Chemical Name | ACGIH (TLV) | OSHA (PEL) | NIOSH (REL) |
|------------------|---------------|------------------|------------------|------------------|
| | Methyl red | None established | None established | None established |

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

| | | |
|--|--|---|
| Appearance: Clear, colorless red liquid. Odor: No odor. Odor threshold: Data not available. pH: Data not available. Melting / Freezing point: Approximately 0°C (32°F) (water) Boiling point: Approximately 100°C (212°F) (water) Flash point: Data not available | Evaporation rate (Water = 1): <1 Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: Data not available Vapor pressure (mm Hg): 14 (water) Vapor density (Air = 1): 0.7 (water) Relative density (Specific gravity): Approximately 1.0 (water) Solubility(ies): Complete in water. | Partition coefficient: Data not available Auto-ignition temperature: Data not available Decomposition temperature: Data not available. Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture |
|--|--|---|

Section 10 Stability & Reactivity

Chemical stability: Stable **Hazardous polymerization:** Will not occur.

Conditions to avoid: Excessive temperatures which cause evaporation. Protect from light.

Incompatible materials: Strong oxidizers, reducing agents.

Hazardous decomposition products: Carbon oxides, nitrogen oxides and sodium oxides.

Section 11 Toxicological Information

Acute toxicity: Oral-rat TD_{50} : 12000 mg/kg [Methyl red]

Skin corrosion/irritation: Data not available

Serious eye damage/irritation: Data not available

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenicity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: Data not available

STOT-single exposure: Data not available

STOT-repeated exposure: Data not available

Aspiration hazard: Data not available

Potential health effects:

Inhalation: May be harmful if inhaled.

Ingestion: May be harmful if swallowed.

Skin: May cause irritation.

Eyes: May cause irritation.

Signs and symptoms of exposure: To the best of our knowledge, the chemical, physical and toxicological properties have not been thoroughly investigated. Specific data is not available. Exercise appropriate procedures to minimize potential hazards.

Additional information: RTECS #: DG8960000 [Methyl red]

Section 12 Ecological Information

Toxicity to fish: No data available

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport Information

UN/NA number: Not applicable

Shipping name: Not Regulated

Hazard class: Not applicable

Packing group: Not applicable

Reportable Quantity: No

Marine pollutant: No

Exceptions: Not applicable

2012 ERG Guide # Not applicable

Section 15 Regulatory Information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

| Component | TSCA | CERLCA (RQ) | RCRA code | DSL | NDSL | WHMIS Classification |
|-------------------------|--------|-------------|------------|--------|------------|----------------------|
| Methyl red, sodium salt | Listed | Not listed | Not listed | Listed | Not listed | Not listed |

Section 16 Additional Information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

Revision Date: May 21, 2013

Supersedes: June 21, 2011

Safety Data Sheet

Methylene Blue, 0.1%



Section 1 Product Description

Product Name: Methylene Blue, 0.1%
Recommended Use: Science education applications
Synonyms: Basic Blue 9, Methylene Blue Chloride, C.I. #52015
Distributor: Carolina Biological Supply Company
2700 York Road, Burlington, NC 27215
1-800-227-1150
Chemical Information: 800-227-1150 (8am-5pm (ET) M-F)
Chemtrec: 800-424-9300 (Transportation Spill Response 24 hours)

Section 2 Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Classification:

Other Safety Precautions: Not a dangerous substance according to GHS classification criteria.
No known OSHA hazards.

Section 3 Composition / Information on Ingredients

| <u>Chemical Name</u> | <u>CAS #</u> | <u>%</u> |
|-------------------------|--------------|----------|
| Water | 7732-18-5 | 99.9 |
| Methylene Blue Chloride | 61-73-4 | 0.1 |

Section 4 First Aid Measures

Emergency and First Aid Procedures

Inhalation: In case of accident by inhalation: remove casualty to fresh air and keep at rest.
Eyes: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact: After contact with skin, wash immediately with plenty of water.
Ingestion: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Section 5 Firefighting Procedures

Extinguishing Media: Use media suitable to extinguish surrounding fire.
Fire Fighting Methods and Protection: Firefighters should wear full protective equipment and NIOSH approved self-contained breathing apparatus.
Fire and/or Explosion Hazards: Fire or excessive heat may produce hazardous decomposition products.
Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

Section 6 Spill or Leak Procedures

Steps to Take in Case Material Is Released or Spilled: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

Section 7 Handling and Storage

Safety Data Sheet

Storage: Keep container tightly closed in a cool, well-ventilated place.
Storage Code: Green - general chemical storage

Section 8

Protection Information

| Chemical Name | ACGIH | | OSHA PEL | |
|-------------------------|-------|--------|----------|--------|
| | (TWA) | (STEL) | (TWA) | (STEL) |
| Methylene Blue Chloride | N/A | N/A | N/A | N/A |

Control Parameters

Engineering Measures:

No exposure limits exist for the constituents of this product. General room ventilation might be required to maintain operator comfort under normal conditions of use.

Personal Protective Equipment (PPE):

Lab coat, apron, eye wash, safety shower.

Respiratory Protection:

No respiratory protection required under normal conditions of use. Provide general room exhaust ventilation if symptoms of overexposure occur as explained Section 11. A respirator is not normally required.

Eye Protection:

Wear chemical splash goggles when handling this product. Have an eye wash station available.

Skin Protection:

Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves:

No information available

Section 9

Physical Data

Formula: C₁₆H₁₈ClN₃S (aq)
Molecular Weight: No data available
Appearance: Blue Green Liquid
Odor: None
Odor Threshold: No data available
pH: No data available
Melting Point: 0 C
Boiling Point: 100 C
Flash Point: No data available
Flammable Limits in Air: No data available

Vapor Pressure: No data available
Evaporation Rate (BuAc=1): No data available
Vapor Density (Air=1): No data available
Specific Gravity: 1
Solubility in Water: Soluble
Log Pow (calculated): No data available
Autoignition Temperature: No data available
Decomposition Temperature: No data available
Viscosity: No data available
Percent Volatile by Volume: No data available

Section 10

Reactivity Data

Reactivity: Not generally reactive under normal conditions.
Chemical Stability: Stable under normal conditions.
Conditions to Avoid: Exposure to light.
Incompatible Materials: Water-reactive materials
Hazardous Polymerization: Will not occur

Section 11

Toxicity Data

Routes of Entry: Ingestion, Skin contact.
Symptoms (Acute): Methemoglobinemia, Anemia
Delayed Effects: No data available

Acute Toxicity:

| Chemical Name | CAS Number | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|-------------------------|------------|-----------|-------------|-----------------|
| Water | 7732-18-5 | | | |
| Methylene Blue Chloride | 61-73-4 | | | |

Carcinogenicity:

| Chemical Name | CAS Number | IARC | NTP | OSHA |
|---------------|------------|------|-----|------|
|---------------|------------|------|-----|------|

Safety Data Sheet

Methylene Blue Chloride

61-73-4

Not listed

Not listed

Not listed

Chronic Effects:

Mutagenicity: No evidence of a mutagenic effect.
Teratogenicity: No evidence of a teratogenic effect (birth defect).
Sensitization: No evidence of a sensitization effect.
Reproductive: No evidence of negative reproductive effects.
Target Organ Effects:
Acute: No data available
Chronic: No data available

Section 12**Ecological Data**

Overview: This material is not expected to be harmful to the ecology.
Mobility: This material is expected to have moderate mobility in soil. It absorbs to most soil types.
Persistence: Adsorbs to soil., Photodegradation
Bioaccumulation: No data
Degradability: Biodegrades at a moderate rate.
Other Adverse Effects: No data

Chemical Name
Water

CAS Number
7732-18-5

Eco Toxicity
No data available

Section 13**Disposal Information**

Disposal Methods: Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance.
Waste Disposal Code(s): Not Determined

Section 14**Transport Information**

Ground - DOT Proper Shipping Name:
Not regulated for transport by US DOT.

Air - IATA Proper Shipping Name:
Not regulated for air transport by IATA.

Section 15**Regulatory Information**

TSCA Status: All components in this product are on the TSCA Inventory.

| Chemical Name | CAS Number | § 313 Name | § 304 RQ | CERCLA RQ | § 302 TPQ | CAA 112(2) TQ |
|-------------------------|------------|------------|----------|-----------|-----------|---------------|
| Methylene Blue Chloride | 61-73-4 | No | No | No | No | No |

Section 16**Additional Information****Revised: 11/19/2015****Replaces: 11/19/2015****Printed: 07-06-2016**

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Carolina Biological Supply makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

| | | | |
|--------|---|------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists | NTP | National Toxicology Program |
| CAS | Chemical Abstract Service Number | OSHA | Occupational Safety and Health Administration |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act | PEL | Permissible Exposure Limit |
| DOT | U.S. Department of Transportation | ppm | Parts per million |
| IARC | International Agency for Research on Cancer | RCRA | Resource Conservation and Recovery Act |
| N/A | Not Available | SARA | Superfund Amendments and Reauthorization Act |
| | | TLV | Threshold Limit Value |
| | | TSCA | Toxic Substances Control Act |
| | | IDLH | Immediately dangerous to life and health |

Safety Data Sheet

Methylene Blue Staining Solution

CAROLINA®
www.carolina.com

Section 1 Product Description

Product Name: Methylene Blue Staining Solution
Recommended Use: Science education applications
Synonyms: Methylene Blue Stain
Distributor: Carolina Biological Supply Company, 2700 York Road, Burlington, NC 27215-3398
Chemical Information: 800-227-1150 (8am-5pm (ET) M-F)
Chemtrec: 800-424-9300 (Transportation Spill Response 24 hours)

Section 2 Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

DANGER



May damage fertility or the unborn child. Causes damage to organs.

GHS Classification:

Reproductive Toxicity Category 1A, Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1

Other Safety Precautions: IF exposed or concerned: Get medical advice/attention.
IF exposed: Call a POISON CENTER or doctor/physician.

Acute Toxicity Dermal Contains 21.72375 % of the mixture consists of ingredient(s) of unknown toxicity

Section 3 Composition / Information on Ingredients

| <u>Chemical Name</u> | <u>CAS #</u> | <u>%</u> |
|-------------------------|--------------|----------|
| Water | 7732-18-5 | 76.02 |
| Ethanol | 64-17-5 | 21.49 |
| 2-Propanol | 67-63-0 | 1.19 |
| Methanol | 67-56-1 | 1.07 |
| Methylene Blue Chloride | 61-73-4 | 0.23 |

Section 4 First Aid Measures

Emergency and First Aid Procedures

Inhalation: In case of accident by inhalation: remove casualty to fresh air and keep at rest.
Eyes: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact: After contact with skin, wash immediately with plenty of water.
Ingestion: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Section 5 Firefighting Procedures

Extinguishing Media: Use media suitable to extinguish surrounding fire.
Fire Fighting Methods and Protection: Firefighters should wear full protective equipment and NIOSH approved self-contained breathing apparatus.
Fire and/or Explosion Hazards: Fire or excessive heat may produce hazardous decomposition products.
Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

Section 6 Spill or Leak Procedures

Steps to Take in Case Material Is Released or Spilled: No health effects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Ventilate the contaminated area.

Safety Data Sheet

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

Section 7

Handling and Storage

Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use personal protective equipment as required.

Storage: Store locked up. Keep container tightly closed in a cool, well-ventilated place.

Storage Code: Green - general chemical storage

Section 8

Protection Information

| Chemical Name | ACGIH | | OSHA PEL | |
|-------------------------|-------------|---------------|---------------------------------|--------|
| | (TWA) | (STEL) | (TWA) | (STEL) |
| Ethanol | N/A | 1000 ppm STEL | 1000 ppm TWA; 1900 mg/m3 TWA | N/A |
| 2-Propanol | 200 ppm TWA | 400 ppm STEL | 400 ppm TWA; 980 mg/m3 TWA | N/A |
| Methanol | 200 ppm TWA | 250 ppm STEL | 200 ppm TWA; 260 mg/m3 TWA | N/A |
| Methylene Blue Chloride | N/A | N/A | N/A | N/A |

Control Parameters

Engineering Measures:

No exposure limits exist for the constituents of this product. General room ventilation might be required to maintain operator comfort under normal conditions of use.

Personal Protective Equipment (PPE):

Lab coat, apron, eye wash, safety shower.

Respiratory Protection:

No respiratory protection required under normal conditions of use.

Respirator Type(s):

None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

Eye Protection:

Wear chemical splash goggles when handling this product. Have an eye wash station available.

Skin Protection:

Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves:

Nitrile

Section 9

Physical Data

Formula: See Section 3

Molecular Weight: No data available

Appearance: Blue Liquid

Odor: Mild Alcohol Odor

Odor Threshold: No data available

pH: No data available

Melting Point: No data available

Boiling Point: No data available

Flash Point: No data available

Flammable Limits in Air: No data available

Vapor Pressure: No data available

Evaporation Rate (BuAc=1): No data available

Vapor Density (Air=1): No data available

Specific Gravity: < 1

Solubility in Water: Soluble

Log Pow (calculated): No data available

Autoignition Temperature: No data available

Decomposition Temperature: No data available

Viscosity: No data available

Percent Volatile by Volume: No data available

Section 10

Reactivity Data

Reactivity:

Not generally reactive under normal conditions.

Chemical Stability:

Stable under normal conditions.

Conditions to Avoid:

Temperatures above flash point in combination with sparks, open flames, or other sources of ignition.

Incompatible Materials:

Water-reactive materials, Organic Peroxides, Strong acids, Oxidizing materials

Hazardous Polymerization:

Will not occur

Section 11

Toxicity Data

Routes of Entry Inhalation and ingestion.

Safety Data Sheet

Symptoms (Acute): Respiratory Irritation, Dermatitis, Central Nervous System Depression, Dizziness, Respiratory disorders, Eye disorders
Delayed Effects: No data available

Acute Toxicity:

| Chemical Name | CAS Number | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|-------------------------|------------|--------------------------|---|--|
| Water | 7732-18-5 | Oral LD50 Rat 90 g/kg | | |
| Ethanol | 64-17-5 | Oral LD50 Rat 7060 mg/kg | | INHALATION LC50-4H Rat 124.7 MG/L |
| 2-Propanol | 67-63-0 | Oral LD50 Rat 4396 mg/kg | Dermal LD50 Rat 12800 mg/kg Dermal LD50 Rabbit 12870 mg/kg | INHALATION LC50-4H Rat 72.6 MG/L |
| Methanol | 67-56-1 | Oral LD50 Rat 5628 mg/kg | Dermal LD50 Rabbit 15800 mg/kg | INHALATION LC50-4H Rat 83.2 MG/L INHALATION LC50-4H Rat 64000 ppm |
| Methylene Blue Chloride | 61-73-4 | Oral LD50 Rat 1180 mg/kg | | |

Carcinogenicity:

| Chemical Name | CAS Number | IARC | NTP | OSHA |
|-------------------------|------------|------------|------------|------------|
| Ethanol | 64-17-5 | Listed | Listed | Listed |
| 2-Propanol | 67-63-0 | Listed | Not listed | Not listed |
| Methanol | 67-56-1 | Not listed | Not listed | Not listed |
| Methylene Blue Chloride | 61-73-4 | Not listed | Not listed | Not listed |

Chronic Effects:

Mutagenicity: No evidence of a mutagenic effect.
Teratogenicity: Evidence of a teratogenic effect (birth defect).
Sensitization: No evidence of a sensitization effect.
Reproductive: Evidence of negative reproductive effects.
Target Organ Effects:
Acute: Central Nervous System, Eyes, Blood
Chronic: Eyes, Blood

Section 12

Ecological Data

Overview: This material is not expected to be harmful to the ecology.
Mobility: No data
Persistence: Biodegradation, Adsorbs to soil.
Bioaccumulation: No data
Degradability: No data
Other Adverse Effects: No data

| Chemical Name | CAS Number | Eco Toxicity |
|---------------|------------|--|
| Water | 7732-18-5 | No data available |
| Ethanol | 64-17-5 | 96 HR LC50 PIMEPHALES PROMELAS > 100 MG/L [STATIC] 48 HR EC50 DAPHNIA MAGNA 2 MG/L [STATIC] 24 HR EC50 DAPHNIA MAGNA 10800 MG/L 48 HR LC50 DAPHNIA MAGNA 9268 - 14221 MG/L |
| 2-Propanol | 67-63-0 | 96 HR LC50 LEPOMIS MACROCHIRUS > 1400000 µG/L 96 HR LC50 PIMEPHALES PROMELAS 11130 MG/L [STATIC] 48 HR EC50 DAPHNIA MAGNA 13299 MG/L 72 HR EC50 DESMODESMUS SUBSPICATUS > 1000 MG/L 96 HR EC50 DESMODESMUS SUBSPICATUS > 1000 MG/L |
| Methanol | 67-56-1 | 96 HR LC50 PIMEPHALES PROMELAS > 100 MG/L [STATIC] |

Section 13

Disposal Information

Safety Data Sheet

Disposal Methods:

Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance.

Waste Disposal Code(s):

Not Determined

Section 14

Transport Information

Ground - DOT Proper Shipping Name:

Not regulated for transport by US DOT.

Air - IATA Proper Shipping Name:

Not regulated for air transport by IATA.

Section 15

Regulatory Information

TSCA Status:

All components in this product are on the TSCA Inventory.

| Chemical Name | CAS Number | § 313 Name | § 304 RQ | CERCLA RQ | § 302 TPQ | CAA 112(2) TQ |
|-------------------------|------------|------------|----------|-----------|-----------|---------------|
| Ethanol | 64-17-5 | No | No | No | No | No |
| 2-Propanol | 67-63-0 | No | No | No | No | No |
| Methanol | 67-56-1 | No | No | No | No | No |
| Methylene Blue Chloride | 61-73-4 | No | No | No | No | No |

California Prop 65:

WARNING: This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

Section 16

Additional Information

Revised: 06/20/2013

Replaces: 05/09/2013

Printed: 06-21-2013

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Carolina Biological Supply makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

| | | | |
|--------|---|------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists | NTP | National Toxicology Program |
| CAS | Chemical Abstract Service Number | OSHA | Occupational Safety and Health Administration |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act | PEL | Permissible Exposure Limit |
| DOT | U.S. Department of Transportation | ppm | Parts per million |
| IARC | International Agency for Research on Cancer | RCRA | Resource Conservation and Recovery Act |
| N/A | Not Available | SARA | Superfund Amendments and Reauthorization Act |
| | | TLV | Threshold Limit Value |
| | | TSCA | Toxic Substances Control Act |
| | | IDLH | Immediately dangerous to life and health |

SAFETY DATA SHEET

7000

Section 1. Identification

Product name : MINWAX® Antique Oil Finish
Natural

Product code : 7000

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION (Fertility) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 65.4%

GHS label elements

Hazard pictograms :



Signal word :

Hazard statements :

: Danger

: Flammable liquid and vapor.
May cause an allergic skin reaction.
Suspected of damaging fertility.
Suspected of causing cancer.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness and dizziness.
May cause damage to organs through prolonged or repeated exposure.

Date of issue/Date of revision

: 5/23/2015.

Date of previous issue

: 4/6/2015.

Version : 1.01

1/12

Section 2. Hazards Identification

Precautionary statements

- General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Contaminated work clothing should not be allowed out of the workplace.
- Response** : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention.
- Storage** : Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
- Please refer to the SDS for additional information. Do not transfer contents to other containers for storage.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------------------------|-------------|------------|
| Med. Aliphatic Hydrocarbon Solvent | 65.4 | 64742-88-7 |
| Methyl Ethyl Ketoxime | 0.2 | 96-29-7 |
| Cobalt 2-Ethylhexanoate | 0.2 | 136-52-7 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 4. First aid measures

- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.

- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions :

Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 400 mg/m ³ 8 hours. AIHA WEEL (United States, 10/2011). Skin sensitizer. TWA: 10 ppm 8 hours. |
| Methyl Ethyl Ketoxime | |

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

| | |
|--|--|
| Physical state | : Liquid. |
| Color | : Not available. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| pH | : Not available. |
| Melting point | : Not available. |
| Boiling point | : 148°C (298.4°F) |
| Flash point | : Closed cup: 39°C (102.2°F) [Pensky-Martens Closed Cup] |
| Evaporation rate | : 0.13 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Lower: 1% Upper: 6% |
| Vapor pressure | : 0.023 kPa (0.169 mm Hg) [at 20°C] |
| Vapor density | : 5 [Air = 1] |
| Relative density | : 0.85 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (room temperature): <0.205 cm ² /s (<20.5 cSt) Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt) |

Aerosol product

| | |
|--------------------|-------------------|
| Heat of combustion | : 0.00002721 kJ/g |
|--------------------|-------------------|

Section 10. Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|-------------|---------|-----------|----------|
| Methyl Ethyl Ketoxime Cobalt 2-Ethylhexanoate | LD50 Oral | Rat | 930 mg/kg | - |
| | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | 1.22 g/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|------------------------|---------|-------|-----------------|-------------|
| Methyl Ethyl Ketoxime | Eyes - Severe irritant | Rabbit | - | 100 microliters | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|----------------|
| Med. Aliphatic Hydrocarbon Solvent | Category 2 | Not determined | Not determined |

Aspiration hazard

| Name | Result |
|------------------------------------|--------------------------------|
| Med. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

| | |
|---------------------|---|
| Eye contact | : No specific data. |
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations |
| Skin contact | : Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations |
| Ingestion | : Adverse symptoms may include the following: nausea or vomiting reduced fetal weight increase in fetal deaths skeletal malformations |

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

| | |
|------------------------------|--|
| General | : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : Suspected of damaging fertility. |

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|------------------------------------|----------------------------|----------|
| Methyl Ethyl Ketoxime | Acute LC50 843000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|------------|-----------|
| Methyl Ethyl Ketoxime | - | 2.5 to 5.8 | low |
| Cobalt 2-Ethylhexanoate | - | 15600 | high |

Mobility in soil




Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|----------------------------|-----------------------|-----------------------|--|--|--|
| UN number | Not regulated. | Not regulated. | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | - | - | PAINT | PAINT | PAINT |
| Transport hazard class(es) | - | - | 3  | 3  | 3  |
| Packing group | - | - | III | III | III |
| Environmental hazards | No. | No. | No. | No. | No. |

Section 14. Transport information

| Additional information | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> (ERG#128) | <u>Special provisions</u> Not Applicable | <u>Emergency schedules (EmS)</u> F-E, S-E |
|------------------------|---|---|--|---|--|
|------------------------|---|---|--|---|--|

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available.
to Annex II of MARPOL
73/78 and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | | |
|------------------|---|---|
| Health | * | 2 |
| Flammability | | 2 |
| Physical hazards | | 0 |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

| | | | | | | |
|--------------------------------|--------------|------------------------|-------------|---------|--------|-------|
| Date of issue/Date of revision | : 5/23/2015. | Date of previous issue | : 4/6/2015. | Version | : 1.01 | 11/12 |
|--------------------------------|--------------|------------------------|-------------|---------|--------|-------|

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

33250

Section 1. Identification

Product name : MINWAX® Indoor/Outdoor HELMSMAN® Spar Urethane (Aerosol)
Clear Gloss

Product code : 33250

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 33.6%

GHS label elements

Hazard pictograms :



Signal word :

Hazard statements :

Danger
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
May cause an allergic skin reaction.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness and dizziness.
May cause damage to organs through prolonged or repeated exposure.

Date of issue/Date of revision

: 4/6/2015.

Date of previous issue

: No previous validation.

Version : 1

1/13

Section 2. Hazards Identification

Precautionary statements

| | |
|---|--|
| General | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. |
| Response | : Get medical attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
| Storage | : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. |
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | <p>DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.</p> <p>Please refer to the SDS for additional information. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.</p> |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| | |
|--------------------------------------|------------------|
| Substance/mixture | : Mixture |
| Other means of identification | : Not available. |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------------------------|-------------|-------------|
| Acetone | 39.0 | 67-64-1 |
| Propane | 13.8 | 74-98-6 |
| Butane | 13.2 | 106-97-8 |
| Med. Aliphatic Hydrocarbon Solvent | 12.7 | 64742-88-7 |
| Heptane | 7.1 | 64742-49-0 |
| UV Light Absorber | 0.1 | 104810-48-2 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Section 4. First aid measures

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.
- Specific hazards arising from the chemical** : Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Section 6. Accidental release measures

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|-----------------|---|
| Acetone | ACGIH TLV (United States, 4/2014). TWA: 500 ppm 8 hours. TWA: 1188 mg/m ³ 8 hours. STEL: 750 ppm 15 minutes. STEL: 1782 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 250 ppm 10 hours. TWA: 590 mg/m ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 2400 mg/m ³ 8 hours. |
| Propane | NIOSH REL (United States, 10/2013). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. |

Section 8. Exposure controls/personal protection

| | |
|------------------------------------|--|
| Butane | OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 4/2014). STEL: 1000 ppm 15 minutes. |
| Med. Aliphatic Hydrocarbon Solvent | OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 400 mg/m ³ 8 hours. |

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

| | |
|--|--|
| Physical state | : Liquid. |
| Color | : Not available. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| pH | : 7 |
| Melting point | : Not available. |
| Boiling point | : Not available. |
| Flash point | : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup] |
| Evaporation rate | : 5.6 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Lower: 1% Upper: 12.8% |
| Vapor pressure | : 13.5 kPa (101.325 mm Hg) [at 20°C] |
| Vapor density | : 1.55 [Air = 1] |
| Relative density | : 0.71 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (room temperature): <0.07 cm ² /s (<7 cSt) Kinematic (40°C (104°F)): <0.07 cm ² /s (<7 cSt) |

Aerosol product

| | |
|--------------------|------------------|
| Type of aerosol | : Spray |
| Heat of combustion | : 0.0000314 kJ/g |

Section 10. Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|--------------------------|----------|
| Acetone | LD50 Oral | Rat | 5800 mg/kg | - |
| Butane | LC50 Inhalation Vapor | Rat | 658000 mg/m ³ | 4 hours |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|--------------------------|-------------|
| Acetone | Eyes - Mild irritant | Human | - | 186300 parts per million | - |
| | Eyes - Mild irritant | Rabbit | - | 10 microliters | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 20 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 395 milligrams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|---|
| Acetone | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Propane | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Butane | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Med. Aliphatic Hydrocarbon Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Heptane | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|----------------|
| Acetone | Category 2 | Not determined | Not determined |
| Propane | Category 2 | Not determined | Not determined |
| Butane | Category 2 | Not determined | Not determined |
| Med. Aliphatic Hydrocarbon Solvent | Category 2 | Not determined | Not determined |
| Heptane | Category 2 | Not determined | Not determined |

Aspiration hazard

| Name | Result |
|------------------------------------|--------------------------------|
| Propane | ASPIRATION HAZARD - Category 1 |
| Butane | ASPIRATION HAZARD - Category 1 |
| Med. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |
| Heptane | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.

Potential chronic health effects

Not available.

| | |
|------------------------------|--|
| General | : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|-------------------------------------|--|----------|
| Acetone | Acute EC50 20.565 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute LC50 6000000 µg/l Fresh water | Crustaceans - Gammarus pulex | 48 hours |
| | Acute LC50 10000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 5600 ppm Fresh water | Fish - Poecilia reticulata | 96 hours |
| | Chronic NOEC 4.95 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Chronic NOEC 0.016 ml/L Fresh water | Crustaceans - Daphniidae | 21 days |
| | Chronic NOEC 0.1 ml/L Fresh water | Daphnia - Daphnia magna - Neonate | 21 days |
| | Chronic NOEC 5 µg/l Marine water | Fish - Gasterosteus aculeatus - Larvae | 42 days |
| | | | |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Acetone | - | - | Readily |

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|------------|-----------|
| Heptane | - | 10 to 2500 | high |

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.






Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|-------------------------------|--|--|--|--|--|
| UN number | UN1950 | UN1950 | UN1950 | UN1950 | UN1950 |
| UN proper shipping name | AEROSOLS | AEROSOLS | AEROSOLS | AEROSOLS, flammable | AEROSOLS |
| Transport hazard class(es) | 2.1  | 2.1  | 2.1  | 2.1  | 2.1  |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | <u>Special provisions</u> LIMITED QUANTITY | <u>Special provisions</u> LIMITED QUANTITY | <u>Special provisions</u> (ERG#126) | <u>Special provisions</u> LIMITED QUANTITY | <u>Emergency schedules (EmS)</u> LIMITED QUANTITY, F-D, S-U |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | |
|------------------|---|
| Health | 2 |
| Flammability | 4 |
| Physical hazards | 0 |
| | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

3333

Section 1. Identification

Product name : MINWAX® POLYCRYLIC® Water-Based Protective Finish
Clear Satin

Product code : 3333

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : TOXIC TO REPRODUCTION (Unborn child) - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 11.1%

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : May damage the unborn child.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe vapor.

Response : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention.

Storage : Store locked up.

Section 2. Hazards identification

| | |
|----------------------------------|---|
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Please refer to the SDS for additional information. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| | |
|-------------------------------|------------------|
| Substance/mixture | : Mixture |
| Other means of identification | : Not available. |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|-----------------------------------|-------------|------------|
| Butoxypropanol | 3.0 | 5131-66-8 |
| Ethylene Glycol | 2.3 | 107-21-1 |
| 1-Methyl-2-Pyrrolidone | 1.6 | 872-50-4 |
| 1-(2-Butoxymethylethoxy)-propanol | 1.5 | 29911-28-2 |
| Decylpoly(ethyleneoxy)ethanol | 1.2 | 9014-85-1 |
| Tetramethyl Decynediol | 0.2 | 126-86-3 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| | |
|--------------|---|
| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

Section 4. First aid measures

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------|---|
| Ethylene Glycol | ACGIH TLV (United States, 4/2014). C: 100 mg/m ³ Form: Aerosol |
| 1-Methyl-2-Pyrrolidone | AIHA WEEL (United States, 10/2011). Absorbed through skin. TWA: 10 ppm 8 hours. |

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyeface protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

| | |
|--|--|
| Physical state | : Liquid. |
| Color | : Not available. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| pH | : 8.5 |
| Melting point | : Not available. |
| Boiling point | : 100°C (212°F) |
| Flash point | : Closed cup: 100°C (212°F) [Pensky-Martens Closed Cup] |
| Evaporation rate | : 0.09 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Lower: 0.6% Upper: 20.4% |
| Vapor pressure | : 0.31 kPa (2.333 mm Hg) [at 20°C] |
| Vapor density | : 1 [Air = 1] |
| Relative density | : 1.03 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (room temperature): >0.07 cm ² /s (>7 cSt) Kinematic (40°C (104°F)): >0.07 cm ² /s (>7 cSt) |

Aerosol product

| | |
|--------------------|--------------------|
| Heat of combustion | : 0.000004002 kJ/g |
|--------------------|--------------------|

Section 10. Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Section 11. Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-------------|---------|------------|----------|
| Butoxypropanol | LD50 Dermal | Rabbit | 3100 mg/kg | - |
| Ethylene Glycol | LD50 Oral | Rat | 4700 mg/kg | - |
| 1-Methyl-2-Pyrrolidone | LD50 Dermal | Rabbit | 8 g/kg | - |
| | LD50 Oral | Rat | 3914 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|-------------------------|-------------|
| Ethylene Glycol | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 1 hours 100 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 6 hours 1440 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 555 milligrams | - |
| 1-Methyl-2-Pyrrolidone | Eyes - Moderate irritant | Rabbit | - | 100 milligrams | - |
| Tetramethyl Decynediol | Eyes - Severe irritant | Rabbit | - | 0.1 Milliliters | - |
| | Skin - Mild irritant | Rabbit | - | 0.5 Grams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|-----------------------------------|------------|-------------------|---|
| Butoxypropanol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Ethylene Glycol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| 1-(2-Butoxymethylethoxy)-propanol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Tetramethyl Decynediol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

| Name | Category | Route of exposure | Target organs |
|-----------------------------------|------------|-------------------|----------------|
| Butoxypropanol | Category 2 | Not determined | Not determined |
| Ethylene Glycol | Category 2 | Not determined | Not determined |
| 1-(2-Butoxymethylethoxy)-propanol | Category 2 | Not determined | Not determined |
| Tetramethyl Decynediol | Category 2 | Not determined | Not determined |

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
Skin contact : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : May damage the unborn child.
Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|--------|---------------|
| Oral | 70075.7 mg/kg |
| Dermal | 92720.5 mg/kg |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|--|----------|
| Ethylene Glycol | Acute LC50 6900000 µg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 41000000 µg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| 1-Methyl-2-Pyrrolidone | Acute LC50 8050000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute LC50 1.23 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 832 ppm Fresh water | Fish - Lepomis macrochirus | 96 hours |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Ethylene Glycol | - | - | Readily |

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|-------------------------------|---|---|---|---|--|
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - | - |
| Transport hazard class(es) | - | - | - | - | - |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Emergency schedules (EmS)</u> Not Applicable |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available.
to Annex II of MARPOL
73/78 and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | |
|------------------|---|
| Health | 2 |
| Flammability | 0 |
| Physical hazards | 0 |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Section 16. Other information

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

4444

Section 1. Identification

Product name : MINWAX® POLYCRYLIC® Water-Based Protective Finish
Clear Semi-Gloss

Product code : 4444

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : TOXIC TO REPRODUCTION (Unborn child) - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 12.3%

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : May damage the unborn child.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe vapor.

Response : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention.

Storage : Store locked up.

Date of issue/Date of revision

: 4/6/2015.

Date of previous issue

: No previous validation.

Version : 1

1/12

Section 2. Hazards identification

| | |
|---|---|
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Please refer to the SDS for additional information. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| | |
|--------------------------------------|------------------|
| Substance/mixture | : Mixture |
| Other means of identification | : Not available. |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|-----------------------------------|-------------|------------|
| Butoxypropanol | 3.0 | 5131-66-8 |
| Ethylene Glycol | 2.3 | 107-21-1 |
| 1-Methyl-2-Pyrrolidone | 1.7 | 872-50-4 |
| 1-(2-Butoxymethylethoxy)-propanol | 1.5 | 29911-28-2 |
| Decylpoly(ethyleneoxy)ethanol | 1.2 | 9014-85-1 |
| 2-Methoxymethylethoxypropanol | 1.0 | 34590-94-8 |
| Tetramethyl Decynediol | 0.2 | 126-86-3 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| | |
|---------------------|--|
| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |

Section 4. First aid measures

- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date of revision

: 4/6/2015.

Date of previous issue

: No previous validation.

Version : 1

3/12

Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|-------------------------------|--|
| Ethylene Glycol | ACGIH TLV (United States, 4/2014). C: 100 mg/m ³ Form: Aerosol AIHA WEEL (United States, 10/2011). Absorbed through skin. TWA: 10 ppm 8 hours. ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 606 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 909 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). Absorbed through skin. TWA: 100 ppm 10 hours. TWA: 600 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 900 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 600 mg/m ³ 8 hours. |
| 1-Methyl-2-Pyrrolidone | |
| 2-Methoxymethylethoxypropanol | |

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Section 8. Exposure controls/personal protection

| | |
|-------------------------------|--|
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |

Section 9. Physical and chemical properties

Appearance

| | |
|---|--|
| Physical state | : Liquid. |
| Color | : Not available. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| pH | : 8.5 |
| Melting point | : Not available. |
| Boiling point | : 100°C (212°F) |
| Flash point | : Closed cup: 100°C (212°F) [Pensky-Martens Closed Cup] |
| Evaporation rate | : 0.8 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Lower: 0.6% Upper: 20.4% |
| Vapor pressure | : 0.31 kPa (2.333 mm Hg) [at 20°C] |
| Vapor density | : 1 [Air = 1] |
| Relative density | : 1.02 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (room temperature): >0.07 cm ² /s (>7 cSt) Kinematic (40°C (104°F)): >0.07 cm ² /s (>7 cSt) |

Aerosol product

| | |
|---------------------------|--------------------|
| Heat of combustion | : 0.000004057 kJ/g |
|---------------------------|--------------------|

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-------------|---------|------------|----------|
| Butoxypropanol | LD50 Dermal | Rabbit | 3100 mg/kg | - |
| Ethylene Glycol | LD50 Oral | Rat | 4700 mg/kg | - |
| 1-Methyl-2-Pyrrolidone | LD50 Dermal | Rabbit | 8 g/kg | - |
| | LD50 Oral | Rat | 3914 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------------|--------------------------|---------|-------|-------------------------|-------------|
| Ethylene Glycol | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 1 hours 100 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 6 hours 1440 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 555 milligrams | - |
| 1-Methyl-2-Pyrrolidone | Eyes - Moderate irritant | Rabbit | - | 100 milligrams | - |
| 2-Methoxymethylethoxypropanol | Eyes - Mild irritant | Human | - | 8 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 500 milligrams | - |
| Tetramethyl Decynediol | Eyes - Severe irritant | Rabbit | - | 0.1 Milliliters | - |
| | Skin - Mild irritant | Rabbit | - | 0.5 Grams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Section 11. Toxicological information

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|-----------------------------------|------------|-------------------|---|
| Butoxypropanol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Ethylene Glycol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| 1-(2-Butoxymethylethoxy)-propanol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| 2-Methoxymethylethoxypropanol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Tetramethyl Decynediol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|-----------------------------------|------------|-------------------|----------------|
| Butoxypropanol | Category 2 | Not determined | Not determined |
| Ethylene Glycol | Category 2 | Not determined | Not determined |
| 1-(2-Butoxymethylethoxy)-propanol | Category 2 | Not determined | Not determined |
| 2-Methoxymethylethoxypropanol | Category 2 | Not determined | Not determined |
| Tetramethyl Decynediol | Category 2 | Not determined | Not determined |

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : May damage the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|--------|---------------|
| Oral | 94473.8 mg/kg |
| Dermal | 90279.4 mg/kg |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|--|----------|
| Ethylene Glycol | Acute LC50 6900000 µg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 41000000 µg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| 1-Methyl-2-Pyrrolidone | Acute LC50 8050000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute LC50 1.23 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 832 ppm Fresh water | Fish - Lepomis macrochirus | 96 hours |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Ethylene Glycol | - | - | Readily |

Bioaccumulative potential

Not available.

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|----------------------------|---|---|---|---|--|
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - | - |
| Transport hazard class(es) | - | - | - | - | - |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Emergency schedules (EmS)</u> Not Applicable |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | |
|------------------|---|
| Health | 2 |
| Flammability | 0 |
| Physical hazards | 0 |
| | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

5555

Section 1. Identification

Product name : MINWAX® POLYCRYLIC® Water-Based Protective Finish
Clear Gloss

Product code : 5555

Other means of identification : Not available.

CAS # : Not applicable.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 5.2%
Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 4.6%
Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 9.3%

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Do not breathe vapor.

Response : Get medical attention if you feel unwell.

Storage : Not applicable.

Section 2. Hazards identification

- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
- Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|-------------------------------|-------------|------------|
| Butoxypropanol | 2.99 | 5131-66-8 |
| Ethylene Glycol | 2.32 | 107-21-1 |
| 1-Methyl-2-Pyrrolidone | 1.71 | 872-50-4 |
| Decylpoly(ethyleneoxy)ethanol | 1.22 | 9014-85-1 |
| 2-Methoxymethylethoxypropanol | 1.02 | 34590-94-8 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments : No specific treatment.
Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Ingredient name | Exposure limits |
|--|---|
| Butoxypropanol Ethylene Glycol | None. ACGIH TLV (United States, 3/2016). C: 100 mg/m ³ Form: Aerosol |
| 1-Methyl-2-Pyrrolidone | AIHA WEEL (United States, 10/2011). Absorbed through skin. TWA: 10 ppm 8 hours. |
| Decylpoly(ethyleneoxy)ethanol 2-Methoxymethylethoxypropanol | None. ACGIH TLV (United States, 3/2016). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 606 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 909 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2016). Absorbed through skin. TWA: 100 ppm 10 hours. TWA: 600 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 900 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2016). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 600 mg/m ³ 8 hours. |

Occupational exposure limits (Canada)

| Ingredient name | Exposure limits |
|-------------------------------|---|
| ethanediol | CA British Columbia Provincial (Canada, 7/2016). C: 100 mg/m ³ Form: Aerosol TWA: 10 mg/m ³ 8 hours. Form: Particulate STEL: 20 mg/m ³ 15 minutes. Form: Particulate C: 50 ppm Form: Vapour CA Ontario Provincial (Canada, 7/2015). C: 100 mg/m ³ Form: Aerosol only. CA Saskatchewan Provincial (Canada, 7/2013). CEIL: 100 mg/m ³ Form: aerosol CA Alberta Provincial (Canada, 4/2009). C: 100 mg/m ³ CA Québec Provincial (Canada, 1/2014). STEV: 50 ppm 15 minutes. Form: vapour and mist STEV: 127 mg/m ³ 15 minutes. Form: vapour and mist |
| 1-Methyl-2-Pyrrolidone | CA Ontario Provincial (Canada, 7/2015). TWA: 400 mg/m ³ 8 hours. |
| 2-Methoxymethylethoxypropanol | CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 8 hrs OEL: 100 ppm 8 hours. 15 min OEL: 909 mg/m ³ 15 minutes. 8 hrs OEL: 606 mg/m ³ 8 hours. 15 min OEL: 150 ppm 15 minutes. |

Section 8. Exposure controls/personal protection

CA British Columbia Provincial (Canada, 7/2016). Absorbed through skin.

TWA: 100 ppm 8 hours.

STEL: 150 ppm 15 minutes.

CA Québec Provincial (Canada, 1/2014). Absorbed through skin.

TWAEV: 100 ppm 8 hours.

TWAEV: 606 mg/m³ 8 hours.

STEV: 150 ppm 15 minutes.

STEV: 909 mg/m³ 15 minutes.

CA Ontario Provincial (Canada, 7/2015). Absorbed through skin.

STEL: 150 ppm 15 minutes.

TWA: 100 ppm 8 hours.

CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin.

STEL: 150 ppm 15 minutes.

TWA: 100 ppm 8 hours.

Occupational exposure limits (Mexico)

| Ingredient name | Exposure limits |
|-------------------------------|---|
| ethanediol | NOM-010-STPS-2014 (Mexico, 4/2016). CEIL: 100 mg/m ³ Form: Only AEROSOL |
| 2-Methoxymethylethoxypropanol | NOM-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes. |

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 8
- Melting point** : Not available.
- Boiling point** : 100°C (212°F)
- Flash point** : Closed cup: 100°C (212°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 0.8 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 0.6%
Upper: 20.4%
- Vapor pressure** : 2.3 kPa (17.5 mm Hg) [at 20°C]
- Vapor density** : 1 [Air = 1]
- Relative density** : 1.02
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): >0.205 cm²/s (>20.5 cSt)
- Molecular weight** : Not applicable.

Aerosol product

- Heat of combustion** : 4.056 kJ/g

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : No specific data.
- Incompatible materials** : No specific data.

Section 10. Stability and reactivity

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-------------|---------|------------|----------|
| Butoxypropanol | LD50 Dermal | Rabbit | 3100 mg/kg | - |
| Ethylene Glycol | LD50 Oral | Rat | 4700 mg/kg | - |
| 1-Methyl-2-Pyrrolidone | LD50 Dermal | Rabbit | 8 g/kg | - |
| | LD50 Oral | Rat | 3914 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------------|--------------------------|---------|-------|-------------------------|-------------|
| Ethylene Glycol | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 1 hours 100 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 6 hours 1440 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 555 milligrams | - |
| 1-Methyl-2-Pyrrolidone | Eyes - Moderate irritant | Rabbit | - | 100 milligrams | - |
| 2-Methoxymethylethoxypropanol | Eyes - Mild irritant | Human | - | 8 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 500 milligrams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------|------------|-------------------|---|
| Butoxypropanol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Ethylene Glycol | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| 1-Methyl-2-Pyrrolidone | Category 3 | Not applicable. | Respiratory tract irritation |

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|-----------------|------------|-------------------|----------------|
| Butoxypropanol | Category 2 | Not determined | Not determined |
| Ethylene Glycol | Category 2 | Not determined | Not determined |

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|--------|--------------|
| Oral | 19707 mg/kg |
| Dermal | 103595 mg/kg |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|--------------------------------------|--|----------|
| Ethylene Glycol 1-Methyl-2-Pyrrolidone | Acute LC50 6900000 µg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 41000000 µg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 8050000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute LC50 1.23 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 832 ppm Fresh water | Fish - Lepomis macrochirus | 96 hours |
| | | | |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Ethylene Glycol | - | - | Readily |

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|----------------------------|--------------------|--------------------|-----------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - | - |
| Transport hazard class(es) | - | - | - | - | - |
| | | | | | |

Section 14. Transport information

| | | | | | |
|------------------------|-----|-----|-----|-----|-----|
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | - | - | - | - | - |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Proper shipping name : Not available.

Ship type : Not available.

Pollution category : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | |
|------------------|---|
| Health | 2 |
| Flammability | 0 |
| Physical hazards | 0 |

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

| Classification | Justification |
|---|--------------------|
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 | Calculation method |

History

Date of printing : 8/1/2017

Date of issue/Date of revision : 8/1/2017

Date of previous issue : 6/9/2017

Section 16. Other information

Version : 5

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

235

Section 1. Identification

Product name : MINWAX® WOOD FINISH®
Cherry

Product code : 235

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 78%

GHS label elements

Hazard pictograms :



Signal word : Danger

Section 2. Hazards Identification

Hazard statements : Flammable liquid and vapor.
Causes serious eye irritation.
Causes skin irritation.
Suspected of causing cancer.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness and dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Response : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Please refer to the SDS for additional information. Do not transfer contents to other containers for storage.

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------------------------|-------------|------------|
| Med. Aliphatic Hydrocarbon Solvent | 55.7 | 64742-88-7 |
| Heavy Naphthenic Petroleum Oil | 19.1 | 64742-52-5 |
| Titanium Dioxide | 0.3 | 13463-67-7 |

Section 3. Composition/Information on Ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.
- Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions :

Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Section 8. Exposure controls/personal protection

| Ingredient name | Exposure limits |
|------------------------------------|--|
| Med. Aliphatic Hydrocarbon Solvent | OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 400 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2015). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2015). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 2/2013). TWA: 15 mg/m ³ 8 hours. Form: Total dust |
| Heavy Naphthenic Petroleum Oil | |
| Titanium Dioxide | |

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.
Color : Not available.
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : 148°C (298.4°F)
Flash point : Closed cup: 43°C (109.4°F) [Pensky-Martens Closed Cup]
Evaporation rate : 0.13 (butyl acetate = 1)
Flammability (solid, gas) : Not available.
Lower and upper explosive (flammable) limits : Lower: 1%
Upper: 6%
Vapor pressure : 0.023 kPa (0.169 mm Hg) [at 20°C]
Vapor density : 5 [Air = 1]
Relative density : 0.86
Solubility : Not available.
Partition coefficient: n-octanol/water : Not available.
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
Viscosity : Kinematic (room temperature): <0.205 cm²/s (<20.5 cSt)
Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
Molecular weight : Not applicable.

Aerosol product

Heat of combustion : 29.44 kJ/g

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials

Section 10. Stability and reactivity

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--------------------------------|-----------|---------|-------------|----------|
| Heavy Naphthenic Petroleum Oil | LD50 Oral | Rat | >5000 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--------------------------------|------------------------|---------|-------|--------------------------------------|-------------|
| Heavy Naphthenic Petroleum Oil | Skin - Severe irritant | Rabbit | - | 500 milligrams | - |
| Titanium Dioxide | Skin - Mild irritant | Human | - | 72 hours 300 Micrograms Intermittent | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Titanium Dioxide | - | 2B | - |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Heavy Naphthenic Petroleum Oil | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|----------------|
| Med. Aliphatic Hydrocarbon Solvent | Category 2 | Not determined | Not determined |
| Heavy Naphthenic Petroleum Oil | Category 2 | Not determined | Not determined |

Aspiration hazard

Section 11. Toxicological information

| Name | Result |
|------------------------------------|--------------------------------|
| Med. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- General** : May cause damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

| | | | | | | |
|--------------------------------|-------------|------------------------|-------------|---------|--------|------|
| Date of issue/Date of revision | : 9/24/2015 | Date of previous issue | : 7/30/2015 | Version | : 1.05 | 9/12 |
|--------------------------------|-------------|------------------------|-------------|---------|--------|------|

Numerical measures of toxicity**Acute toxicity estimates**

Not available.

Section 12. Ecological information**Toxicity**

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---------------------------------------|------------------------------|----------|
| Titanium Dioxide | Acute LC50 >1000000 µg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| Titanium Dioxide | - | 352 | low |

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations






Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|----------------------------|-----------------------|-----------------------|--------------------------|--------|--------|
| UN number | UN1263 | UN1263 | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | PAINT | PAINT | PAINT | PAINT | PAINT |
| | | | | | |

Date of issue/Date of revision : 9/24/2015 Date of previous issue : 7/30/2015 Version : 1.05 10/12

Section 14. Transport information

| | | | | | |
|----------------------------|--|--|--|--|--|
| Transport hazard class(es) | 3  | 3  | 3  | 3  | 3  |
| Packing group | III | III | III | III | III |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials. <u>Special provisions</u> Not Applicable | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3). <u>Special provisions</u> Not Applicable | <u>Special provisions</u> (ERG#128) | <u>Special provisions</u> Not Applicable | <u>Emergency schedules (EmS)</u> F-E, S-E |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Proper shipping name : Not available.
Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | | |
|------------------|---|---|
| Health | * | 2 |
| Flammability | | 2 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

241

Section 1. Identification

Product name : MINWAX® WOOD FINISH®
Fruitwood

Product code : 241

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 78.7%

GHS label elements

Hazard pictograms :



Signal word :

Hazard statements :

Danger

Flammable liquid and vapor.
Causes serious eye irritation.
Causes skin irritation.
Suspected of causing cancer.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness and dizziness.
May cause damage to organs through prolonged or repeated exposure.

Date of issue/Date of revision

: 7/30/2015.

Date of previous issue

: 6/3/2015.

Version : 1.04

1/12

Section 2. Hazards identification

Precautionary statements

| | |
|---|--|
| General | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling. |
| Response | : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
| Storage | : Store locked up. Store in a well-ventilated place. Keep cool. |
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Please refer to the SDS for additional information. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| | |
|--------------------------------------|------------------|
| Substance/mixture | : Mixture |
| Other means of identification | : Not available. |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------------------------|-------------|------------|
| Med. Aliphatic Hydrocarbon Solvent | 58.5 | 64742-88-7 |
| Heavy Naphthenic Petroleum Oil | 17.3 | 64742-52-5 |
| Titanium Dioxide | 1.0 | 13463-67-7 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Section 4. First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------------------|--|
| Med. Aliphatic Hydrocarbon Solvent | OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. |
| Heavy Naphthenic Petroleum Oil | TWA: 400 mg/m ³ 8 hours. ACGIH TLV (United States, 4/2014). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). |

Section 8. Exposure controls/personal protection

Titanium Dioxide

TWA: 5 mg/m³ 8 hours.

ACGIH TLV (United States, 4/2014).

TWA: 10 mg/m³ 8 hours.

OSHA PEL (United States, 2/2013).

TWA: 15 mg/m³ 8 hours. Form: Total dust

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.

Section 9. Physical and chemical properties

| | |
|--|--|
| Melting point | : Not available. |
| Boiling point | : 148°C (298.4°F) |
| Flash point | : Closed cup: 41°C (105.8°F) [Pensky-Martens Closed Cup] |
| Evaporation rate | : 0.13 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Lower: 1% Upper: 6% |
| Vapor pressure | : 0.023 kPa (0.169 mm Hg) [at 20°C] |
| Vapor density | : 5 [Air = 1] |
| Relative density | : 0.85 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (room temperature): <0.205 cm ² /s (<20.5 cSt) Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt) |
| Molecular weight | : Not applicable. |
| <u>Aerosol product</u> | |
| Heat of combustion | : 0.00003006 kJ/g |

Section 10. Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--------------------------------|-----------|---------|-------------|----------|
| Heavy Naphthenic Petroleum Oil | LD50 Oral | Rat | >5000 mg/kg | - |

Irritation/Corrosion

Section 11. Toxicological information

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--------------------------------|------------------------|---------|-------|--------------------------------------|-------------|
| Heavy Naphthenic Petroleum Oil | Skin - Severe irritant | Rabbit | - | 500 milligrams | - |
| Titanium Dioxide | Skin - Mild irritant | Human | - | 72 hours 300 Micrograms Intermittent | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Titanium Dioxide | - | 2B | - |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Heavy Naphthenic Petroleum Oil | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|----------------|
| Med. Aliphatic Hydrocarbon Solvent | Category 2 | Not determined | Not determined |
| Heavy Naphthenic Petroleum Oil | Category 2 | Not determined | Not determined |

Aspiration hazard

| Name | Result |
|------------------------------------|--------------------------------|
| Med. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation.

enters airways. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---------------------------------------|------------------------------|----------|
| Titanium Dioxide | Acute LC50 >1000000 µg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| Titanium Dioxide | - | 352 | low |

Mobility in soil




Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|----------------------------|-----------------------|-----------------------|--|--|--|
| UN number | Not regulated. | Not regulated. | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | - | - | PAINT | PAINT | PAINT |
| Transport hazard class(es) | - | - | 3  | 3  | 3  |
| Packing group | - | - | III | III | III |
| Environmental hazards | No. | No. | No. | No. | No. |
| | | | | | |

Date of issue/Date of revision : 7/30/2015. Date of previous issue : 6/3/2015. Version : 1.04 10/12

Section 14. Transport information

| Additional information | Special provisions | Special provisions | Special provisions | Special provisions | Emergency schedules (EmS) |
|------------------------|--------------------|--------------------|--------------------|--------------------|---------------------------|
| | Not Applicable | Not Applicable | (ERG#128) | Not Applicable | F-E, S-E |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Proper shipping name : Not available.
Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | | |
|------------------|---|---|
| Health | * | 2 |
| Flammability | | 2 |
| Physical hazards | | 0 |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Section 16. Other information

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

210B

Section 1. Identification

Product name : MINWAX® WOOD FINISH®
Golden Oak

Product code : 210B

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
TOXIC TO REPRODUCTION (Unborn child) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 79.9%

GHS label elements

Hazard pictograms :



Signal word : Danger

Section 2. Hazards identification

Hazard statements : Flammable liquid and vapor.
Causes serious eye irritation.
Causes skin irritation.
Suspected of damaging the unborn child.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness and dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Response : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Please refer to the SDS for additional information. Do not transfer contents to other containers for storage.

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------------------------|-------------|------------|
| Med. Aliphatic Hydrocarbon Solvent | 57.9 | 64742-88-7 |
| Heavy Naphthenic Petroleum Oil | 17.6 | 64742-52-5 |
| Aliphatic Solvent | 1.4 | 64742-47-8 |
| Toluene | 0.1 | 108-88-3 |

Section 3. Composition/Information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Section 6. Accidental release measures

- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. |
| Heavy Naphthenic Petroleum Oil | TWA: 400 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2015). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction |
| Aliphatic Solvent | NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2015). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours. |
| Toluene | OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 3/2015). TWA: 20 ppm 8 hours. |

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Section 8. Exposure controls/personal protection

| | |
|-------------------------------|--|
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |

Section 9. Physical and chemical properties

Appearance

| | |
|---|--|
| Physical state | : Liquid. |
| Color | : Not available. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| pH | : Not available. |
| Melting point | : Not available. |
| Boiling point | : 148°C (298.4°F) |
| Flash point | : Closed cup: 41°C (105.8°F) [Pensky-Martens Closed Cup] |
| Evaporation rate | : 0.13 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Lower: 1% Upper: 8.8% |
| Vapor pressure | : 0.023 kPa (0.169 mm Hg) [at 20°C] |
| Vapor density | : 5 [Air = 1] |
| Relative density | : 0.84 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (room temperature): <0.205 cm ² /s (<20.5 cSt) Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt) |
| Molecular weight | : Not applicable. |

Aerosol product

| | |
|---------------------------|--------------|
| Heat of combustion | : 31.03 kJ/g |
|---------------------------|--------------|

Section 10. Stability and reactivity

| | |
|---|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--------------------------------|-----------------------|---------|---------------------|----------|
| Heavy Naphthenic Petroleum Oil | LD50 Oral | Rat | >5000 mg/kg | - |
| Toluene | LC50 Inhalation Vapor | Rat | 49 g/m ³ | 4 hours |
| | LD50 Oral | Rat | 636 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--------------------------------|--------------------------|---------|-------|--------------------------|-------------|
| Heavy Naphthenic Petroleum Oil | Skin - Severe irritant | Rabbit | - | 500 milligrams | - |
| Toluene | Eyes - Mild irritant | Rabbit | - | 0.5 minutes | - |
| | Eyes - Mild irritant | Rabbit | - | 100 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 870 Micrograms | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 2 milligrams | - |
| | Skin - Mild irritant | Pig | - | 24 hours 250 microliters | - |
| | Skin - Mild irritant | Rabbit | - | 435 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 500 milligrams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Section 11. Toxicological information

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Toluene | - | 3 | - |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Heavy Naphthenic Petroleum Oil | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Aliphatic Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Toluene | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|----------------|
| Med. Aliphatic Hydrocarbon Solvent | Category 2 | Not determined | Not determined |
| Heavy Naphthenic Petroleum Oil | Category 2 | Not determined | Not determined |
| Aliphatic Solvent | Category 2 | Not determined | Not determined |
| Toluene | Category 2 | Not determined | Not determined |

Aspiration hazard

| Name | Result |
|------------------------------------|--------------------------------|
| Med. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |
| Toluene | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

| | |
|---------------------|---|
| | Adverse symptoms may include the following: |
| | respiratory tract irritation |
| | coughing |
| | nausea or vomiting |
| | headache |
| | drowsiness/fatigue |
| | dizziness/vertigo |
| | unconsciousness |
| | reduced fetal weight |
| | increase in fetal deaths |
| | skeletal malformations |
| Skin contact | : Adverse symptoms may include the following: |
| | irritation |
| | redness |
| | reduced fetal weight |
| | increase in fetal deaths |
| | skeletal malformations |
| Ingestion | : Adverse symptoms may include the following: |
| | nausea or vomiting |
| | reduced fetal weight |
| | increase in fetal deaths |
| | skeletal malformations |

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|------------------------------|--|---|---------------------|
| Aliphatic Solvent Toluene | Acute LC50 2200 µg/l Fresh water | Fish - Lepomis macrochirus | 4 days |
| | Acute EC50 12500 µg/l Fresh water | Algae - Pseudokirchneriella subcapitata | 72 hours |
| | Acute EC50 11600 µg/l Fresh water | Crustaceans - Gammarus pseudolimnaeus - Adult | 48 hours |
| | Acute EC50 6000 µg/l Fresh water | Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) | 48 hours |
| | Acute LC50 5500 µg/l Fresh water Chronic NOEC 1000 µg/l Fresh water | Fish - Oncorhynchus kisutch - Fry Daphnia - Daphnia magna | 96 hours 21 days |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Toluene | - | - | Readily |

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| Toluene | - | 90 | low |

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.






Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|-------------------------------|--|--|--|--|--|
| UN number | UN1263 | UN1263 | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | PAINT | PAINT | PAINT | PAINT | PAINT |
| Transport hazard class(es) | 3  | 3  | 3  | 3  | 3  |
| Packing group | III | III | III | III | III |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials. <u>Special provisions</u> Not Applicable | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3). <u>Special provisions</u> Not Applicable | <u>Special provisions</u> (ERG#128) | <u>Special provisions</u> Not Applicable | <u>Emergency schedules (EmS)</u> F-E, S-E |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Proper shipping name : Not available.
Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | |
|------------------|---|
| Health | 2 |
| Flammability | 2 |
| Physical hazards | 0 |
| | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

209

Section 1. Identification

Product name : MINWAX® WOOD FINISH®
Natural

Product code : 209

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 81.2%

GHS label elements

Hazard pictograms :



Signal word :

Hazard statements :

Danger

Flammable liquid and vapor.
Causes serious eye irritation.
Causes skin irritation.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness and dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Date of issue/Date of revision

: 5/19/2015.

Date of previous issue

: 4/6/2015.

Version : 1.01

1/12

Section 2. Hazards Identification

| | |
|---|---|
| General | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling. |
| Response | : Get medical attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
| Storage | : Store locked up. Store in a well-ventilated place. Keep cool. |
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | <p>DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.</p> <p>Please refer to the SDS for additional information. Do not transfer contents to other containers for storage.</p> |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| | |
|--------------------------------------|------------------|
| Substance/mixture | : Mixture |
| Other means of identification | : Not available. |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------------------------|-------------|------------|
| Med. Aliphatic Hydrocarbon Solvent | 59.9 | 64742-88-7 |
| Heavy Naphthenic Petroleum Oil | 18.3 | 64742-52-5 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Section 4. First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. |
| Heavy Naphthenic Petroleum Oil | TWA: 400 mg/m ³ 8 hours. ACGIH TLV (United States, 4/2014). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours. |

Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : 148°C (298.4°F)
- Flash point** : Closed cup: 38°C (100.4°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 0.13 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.

Section 9. Physical and chemical properties

| | |
|--|--|
| Lower and upper explosive (flammable) limits | : Lower: 1% Upper: 6% |
| Vapor pressure | : 0.023 kPa (0.169 mm Hg) [at 20°C] |
| Vapor density | : 5 [Air = 1] |
| Relative density | : 0.84 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (room temperature): <0.205 cm ² /s (<20.5 cSt) Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt) |

Aerosol product

| | |
|--------------------|-------------------|
| Heat of combustion | : 0.00003071 kJ/g |
|--------------------|-------------------|

Section 10. Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--------------------------------|-----------|---------|-------------|----------|
| Heavy Naphthenic Petroleum Oil | LD50 Oral | Rat | >5000 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--------------------------------|------------------------|---------|-------|----------------|-------------|
| Heavy Naphthenic Petroleum Oil | Skin - Severe irritant | Rabbit | - | 500 milligrams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

| | | | | | | |
|--------------------------------|--------------|------------------------|-------------|---------|--------|------|
| Date of issue/Date of revision | : 5/19/2015. | Date of previous issue | : 4/6/2015. | Version | : 1.01 | 7/12 |
|--------------------------------|--------------|------------------------|-------------|---------|--------|------|

Section 11. Toxicological information

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Heavy Naphthenic Petroleum Oil | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|----------------|
| Med. Aliphatic Hydrocarbon Solvent | Category 2 | Not determined | Not determined |
| Heavy Naphthenic Petroleum Oil | Category 2 | Not determined | Not determined |

Aspiration hazard

| Name | Result |
|------------------------------------|--------------------------------|
| Med. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness

reverses symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.




Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|-------------------------------|---|---|--|--|--|
| UN number | Not regulated. | Not regulated. | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | - | - | PAINT | PAINT | PAINT |
| Transport hazard class(es) | - | - | 3  | 3  | 3  |
| Packing group | - | - | III | III | III |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> (ERG#128) | <u>Special provisions</u> Not Applicable | <u>Emergency schedules (EmS)</u> F-E, S-E |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | |
|------------------|---|
| Health | 2 |
| Flammability | 2 |
| Physical hazards | 0 |
| | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

225

Section 1. Identification

Product name : MINWAX® WOOD FINISH®
Red Mahogany

Product code : 225

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 83.9%

GHS label elements

Hazard pictograms :



Signal word :

Hazard statements :

: Danger

: Flammable liquid and vapor.
Causes serious eye irritation.
Causes skin irritation.
Suspected of causing cancer.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness and dizziness.
May cause damage to organs through prolonged or repeated exposure.

Date of issue/Date of revision

: 7/30/2015.

Date of previous issue

: 6/3/2015.

Version : 1.04

1/12

Section 2. Hazards Identification

Precautionary statements

| | |
|---|--|
| General | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling. |
| Response | : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
| Storage | : Store locked up. Store in a well-ventilated place. Keep cool. |
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Please refer to the SDS for additional information. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| | |
|--------------------------------------|------------------|
| Substance/mixture | : Mixture |
| Other means of identification | : Not available. |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------------------------|-------------|------------|
| Med. Aliphatic Hydrocarbon Solvent | 44.4 | 64742-88-7 |
| Heavy Naphthenic Petroleum Oil | 12.0 | 64742-52-5 |
| Aliphatic Solvent | 10.7 | 64742-47-8 |
| Mineral Spirits (Odorless) | 1.3 | 64742-47-8 |
| Carbon Black | 0.2 | 1333-86-4 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Section 4. First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 400 mg/m ³ 8 hours. |
| Heavy Naphthenic Petroleum Oil | ACGIH TLV (United States, 4/2014). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). |

Section 8. Exposure controls/personal protection

| | |
|----------------------------|---|
| Aliphatic Solvent | TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 4/2014). Absorbed through skin. |
| Mineral Spirits (Odorless) | TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours. ACGIH TLV (United States, 4/2014). Absorbed through skin. |
| Carbon Black | TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours. NIOSH REL (United States, 10/2013). TWA: 3.5 mg/m ³ 10 hours. TWA: 0.1 mg of PAHs/cm ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 3.5 mg/m ³ 8 hours. ACGIH TLV (United States, 4/2014). TWA: 3 mg/m ³ 8 hours. Form: Inhalable fraction |

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.
Color : Not available.
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : 148°C (298.4°F)
Flash point : Closed cup: 41°C (105.8°F) [Pensky-Martens Closed Cup]
Evaporation rate : 0.13 (butyl acetate = 1)
Flammability (solid, gas) : Not available.
Lower and upper explosive (flammable) limits : Lower: 1%
Upper: 8.8%
Vapor pressure : 0.023 kPa (0.169 mm Hg) [at 20°C]
Vapor density : 5 [Air = 1]
Relative density : 0.86
Solubility : Not available.
Partition coefficient: n-octanol/water : Not available.
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
Viscosity : Kinematic (room temperature): <0.205 cm²/s (<20.5 cSt)
Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
Molecular weight : Not applicable.

Aerosol product

Heat of combustion : 0.00003255 kJ/g

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials

Section 10. Stability and reactivity

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--------------------------------|-----------|---------|--------------|----------|
| Heavy Naphthenic Petroleum Oil | LD50 Oral | Rat | >5000 mg/kg | - |
| Carbon Black | LD50 Oral | Rat | >15400 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--------------------------------|------------------------|---------|-------|----------------|-------------|
| Heavy Naphthenic Petroleum Oil | Skin - Severe irritant | Rabbit | - | 500 milligrams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Carbon Black | - | 2B | - |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Heavy Naphthenic Petroleum Oil | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Aliphatic Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Mineral Spirits (Odorless) | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|----------------|
| Med. Aliphatic Hydrocarbon Solvent | Category 2 | Not determined | Not determined |
| Heavy Naphthenic Petroleum Oil | Category 2 | Not determined | Not determined |
| Aliphatic Solvent | Category 2 | Not determined | Not determined |
| Mineral Spirits (Odorless) | Category 2 | Not determined | Not determined |

Aspiration hazard

| Name | Result |
|------------------------------------|--------------------------------|
| Med. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

| | |
|------------------------------|--|
| Carcinogenicity | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|--------------------------------|----------------------------------|----------------------------|-----------------|
| Aliphatic Solvent | Acute LC50 2200 µg/l Fresh water | Fish - Lepomis macrochirus | 4 days |
| Mineral Spirits (Odorless) | Acute LC50 2200 µg/l Fresh water | Fish - Lepomis macrochirus | 4 days |

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil




Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|----------------------------|---|---|--|--|--|
| UN number | Not regulated. | Not regulated. | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | - | - | PAINT | PAINT | PAINT |
| Transport hazard class(es) | - | - | 3  | 3  | 3  |
| Packing group | - | - | III | III | III |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> (ERG#128) | <u>Special provisions</u> Not Applicable | <u>Emergency schedules (EmS)</u> F-E, S-E |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Proper shipping name : Not available.
Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | |
|------------------|---|
| Health | 2 |
| Flammability | 2 |
| Physical hazards | 0 |

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

224

Section 1. Identification

Product name : MINWAX® WOOD FINISH®
Special Walnut

Product code : 224

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Manufacturer : MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 523-9299

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 76.8%

GHS label elements

Hazard pictograms :



Signal word : Danger

Section 2. Hazards Identification

| | |
|---|--|
| Hazard statements | : Flammable liquid and vapor. Causes serious eye irritation. Causes skin irritation. May damage the unborn child. Suspected of causing cancer. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness and dizziness. May cause damage to organs through prolonged or repeated exposure. |
| <u>Precautionary statements</u> | |
| General | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling. |
| Response | : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
| Storage | : Store locked up. Store in a well-ventilated place. Keep cool. |
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Please refer to the SDS for additional information. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| | |
|--|------------------|
| Substance/mixture | : Mixture |
| Other means of identification | : Not available. |
| <u>CAS number/other identifiers</u> | |

Section 3. Composition/Information on ingredients

| Ingredient name | % by weight | CAS number |
|------------------------------------|-------------|------------|
| Med. Aliphatic Hydrocarbon Solvent | 53.8 | 64742-88-7 |
| Heavy Naphthenic Petroleum Oil | 17.1 | 64742-52-5 |
| Aliphatic Solvent | 1.4 | 64742-47-8 |
| 1-Methyl-2-Pyrrolidone | 0.1 | 872-50-4 |
| Carbon Black | 0.1 | 1333-86-4 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Section 4. First aid measures

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.
- Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 400 mg/m ³ 8 hours. |
| Heavy Naphthenic Petroleum Oil | ACGIH TLV (United States, 4/2014). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist |
| Aliphatic Solvent | OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours. |
| 1-Methyl-2-Pyrrolidone | AIHA WEEL (United States, 10/2011). Absorbed through skin. TWA: 10 ppm 8 hours. |
| Carbon Black | NIOSH REL (United States, 10/2013). TWA: 3.5 mg/m ³ 10 hours. TWA: 0.1 mg of PAHs/cm ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 3.5 mg/m ³ 8 hours. ACGIH TLV (United States, 4/2014). TWA: 3 mg/m ³ 8 hours. Form: Inhalable fraction |

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

| | |
|-------------------------------|--|
| Eye/face protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| <u>Skin protection</u> | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |

Section 9. Physical and chemical properties

Appearance

| | |
|---|--|
| Physical state | : Liquid. |
| Color | : Not available. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| pH | : Not available. |
| Melting point | : Not available. |
| Boiling point | : 148°C (298.4°F) |
| Flash point | : Closed cup: 48°C (118.4°F) [Pensky-Martens Closed Cup] |
| Evaporation rate | : 0.13 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Lower: 1% Upper: 8.8% |
| Vapor pressure | : 0.023 kPa (0.169 mm Hg) [at 20°C] |
| Vapor density | : 5 [Air = 1] |
| Relative density | : 0.86 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (room temperature): <0.205 cm ² /s (<20.5 cSt) Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt) |
| Molecular weight | : Not applicable. |

Aerosol product

| | |
|---------------------------|-------------------|
| Heat of combustion | : 0.00002948 kJ/g |
|---------------------------|-------------------|

Section 10. Stability and reactivity

| | |
|---|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--------------------------------|-------------|---------|--------------|----------|
| Heavy Naphthenic Petroleum Oil | LD50 Oral | Rat | >5000 mg/kg | - |
| 1-Methyl-2-Pyrrolidone | LD50 Dermal | Rabbit | 8 g/kg | - |
| | LD50 Oral | Rat | 3914 mg/kg | - |
| Carbon Black | LD50 Oral | Rat | >15400 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--------------------------------|--------------------------|---------|-------|----------------|-------------|
| Heavy Naphthenic Petroleum Oil | Skin - Severe irritant | Rabbit | - | 500 milligrams | - |
| 1-Methyl-2-Pyrrolidone | Eyes - Moderate irritant | Rabbit | - | 100 milligrams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Carbon Black | - | 2B | - |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|---|
| Med. Aliphatic Hydrocarbon Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Heavy Naphthenic Petroleum Oil | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |
| Aliphatic Solvent | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|------------------------------------|------------|-------------------|----------------|
| Med. Aliphatic Hydrocarbon Solvent | Category 2 | Not determined | Not determined |
| Heavy Naphthenic Petroleum Oil | Category 2 | Not determined | Not determined |
| Aliphatic Solvent | Category 2 | Not determined | Not determined |

Aspiration hazard

| Name | Result |
|------------------------------------|--------------------------------|
| Med. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion

Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

: Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : May damage the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity**Acute toxicity estimates**

Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|----------------------------------|----------------------------|----------|
| Aliphatic Solvent 1-Methyl-2-Pyrrolidone | Acute LC50 2200 µg/l Fresh water | Fish - Lepomis macrochirus | 4 days |
| | Acute LC50 1.23 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 832 ppm Fresh water | Fish - Lepomis macrochirus | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Section 12. Ecological information




Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IATA | IMDG |
|----------------------------|---|---|--|--|--|
| UN number | Not regulated. | Not regulated. | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | - | - | PAINT | PAINT | PAINT |
| Transport hazard class(es) | - | - | 3  | 3  | 3  |
| Packing group | - | - | III | III | III |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> Not Applicable | <u>Special provisions</u> (ERG#128) | <u>Special provisions</u> Not Applicable | <u>Emergency schedules (EmS)</u> F-E, S-E |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Proper shipping name : Not available.

Section 14. Transport information

Ship type : Not available.

Pollution category : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | | |
|------------------|---|---|
| Health | * | 2 |
| Flammability | | 2 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.



SAFETY DATA SHEET

8/15/2019

SECTION I - IDENTIFICATION

Material Name

MOD PODGE ACRYLIC SEALER, GLUE AND FINISH

Company Information

Plaid Enterprises, Inc.
3225 Westech Drive
Norcross, GA 30092
Phone: 1-678-291-8259
Fax: 1-678-291-8363
Email: htrundle@PlaidOnline.Com

For transportation emergencies only call: 770-630-0380

For health emergencies call the Poison Control Center: 1-800-222-1222

SECTION II - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

There are no GHS label elements.

PRIMARY ROUTES OF ENTRY: INHALATION, INGESTION, EYE, SKIN

EFFECTS AND SYMPTOMS OF ACUTE EXPOSURE: NONE EXPECTED

EFFECTS AND SYMPTOMS OF CHRONIC EXPOSURE: NONE EXPECTED

CARCINOGEN LISTING: NTP: **NO** IARC: **NO** OSHA: **NO**

SEE SECTION III FOR COMPONENTS AFFECTED

MEDICAL CONDITIONS USUALLY AGGRAVATED BY OVER EXPOSURE TO THIS PRODUCT: NONE

SECTION III - COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| <u>Hazardous Ingredients</u> | <u>CAS/EC #</u> | <u>PEL/TLV (MG/M#)</u> | <u>Max % Weight</u> | <u>NTP</u> | <u>IARC</u> |
|------------------------------|-----------------|----------------------------|-------------------------|------------|-------------|
| None | | | | | |

SECTION IV - FIRST AID MEASURES

EYES: Flush eyes with a large amount of water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected skin areas thoroughly with soap and water. Consult a physician if irritation persists.

INGESTION: Small amounts are not anticipated to be harmful. Give 2 glasses of water to drink.

INHALATION: Remove to fresh air. Get medical attention if breathing is difficult.

NOTE TO PHYSICIANS: Please contact your local poison control center for information regarding this product.

SECTION V - FIRE FIGHTING MEASURES

FLASH POINT (METHOD): N/A
EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE
EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED
FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED
UNUSUAL FIRE & EXPLOSION HAZARDS: NOT COMBUSTIBLE

AUTOIGNITION TEMPERATURE: N/A

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section XIII

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: NONE REQUIRED
OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): NONE REQUIRED
WORK/HYGIENE PRACTICES: NONE REQUIRED
ENGINEERING CONTROLS: NONE REQUIRED

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A
VAPOR PRESSURE: N/A
SPECIFIC VAPOR DENSITY (AIR=1): N/A
SOLUBILITY IN WATER: N/A

MELTING POINT: N/A
SPECIFIC GRAVITY: N/A
REACTIVITY IN WATER: NON-REACTIVE

SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: N/A
STABILITY: STABLE CONDITIONS TO AVOID: N/A
INCOMPATIBILITY (MATERIALS TO AVOID): N/A
HAZARDOUS DECOMPOSITION PRODUCTS: N/A

SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: NONE EXPECTED
The summated LD50 is 26293 mg/kg.
The summated LC50 is 99999 mg/cubic meter.
This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

SECTION XII - ECOLOGICAL INFORMATION

NO HARMFUL EFFECTS KNOWN OTHER THAN THOSE ASSOCIATED WITH SUSPENDED INERT SOLIDS IN WATER.

SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE.
WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION XIV - TRANSPORTATION INFORMATION

U.S. DOT (49 CFR 172.101): THIS IS NOT A HAZARDOUS MATERIAL AS CLASSIFIED BY CFR 172.101.

SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS SDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200

EPA SARA TITLE III CHEMICAL LISTINGS:
SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372):
NONE

INTERNATIONAL REGULATIONS

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS:
NONE

SUPPLEMENTAL STATE COMPLIANCE INFORMATION:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED UNDER NEW JERSEY'S RIGHT TO KNOW PROGRAM:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) REQUIRING NOTIFICATION TO THE STATE OF WASHINGTON UNDER THEIR CHILDREN'S SAFE PRODUCTS ACT:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN FLORIDA'S TOXIC SUBSTANCE LIST:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MAINE'S PRIORITY CHEMICAL LIST:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS CONSIDERED BY VERMONT AS BEING OF VERY HIGH CONCERN TO CHILDREN:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MASSACHUSETTS HAZARDOUS SUBSTANCE LIST:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MICHIGAN'S CRITICAL MATERIALS REGISTER:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MINNESOTA'S HAZARDOUS SUBSTANCES LIST:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN PENNSYLVANIA'S HAZARDOUS SUBSTANCES LIST:
NONE

Under CPSC's consumer product regulations (16CFR1500.3 and 1500.14), this product has the following required acute and chronic hazard labeling:

NONE

SECTION XVI - OTHER INFORMATION

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

LAST REVISION DATE: 08/15/2019

Prepared by Duke OEM Toxicology

COLOR INFORMATION

THIS SDS APPLIES TO THE FOLLOWING COLORS WHICH ARE ASSOCIATED WITH HAZARDOUS AND/OR NON-HAZARDOUS INGREDIENTS

| Product Color | SKU | Hazardous Ingredient |
|---------------------|--------|----------------------|
| CS11201 8OZ GLOSS | 047537 | (NONE) |
| CS11202 16OZ GLOSS | 228881 | (NONE) |
| CS11203 32 OZ GLOSS | 047538 | (NONE) |
| CS11204 128OZ GLOSS | | (NONE) |
| CS11205 4OZ GLOSS | 047537 | (NONE) |
| CS15091 64OZ GLOSS | 326504 | (NONE) |
| CS15138 2OZ GLOSS | 406883 | (NONE) |
| FBCS11205 4OZ GLOSS | | (NONE) |

BRAND NAMES

THIS SDS APPLIES TO THE FOLLOWING BRAND NAMES

| Brand Name |
|------------|
| MOD PODGE |



SAFETY DATA SHEET

8/15/2019

SECTION I - IDENTIFICATION

Material Name

MOD PODGE ACRYLIC MATTE SEALER, GLUE AND FINISH

Company Information

Plaid Enterprises, Inc.
3225 Westech Drive
Norcross, GA 30092
Phone: 1-678-291-8259
Fax: 1-678-291-8363
Email: htrundle@PlaidOnline.Com

For transportation emergencies only call: 770-630-0380

For health emergencies call the Poison Control Center: 1-800-222-1222

SECTION II - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

There are no GHS label elements.

PRIMARY ROUTES OF ENTRY: INHALATION, INGESTION, EYE, SKIN

EFFECTS AND SYMPTOMS OF ACUTE EXPOSURE: NONE EXPECTED

EFFECTS AND SYMPTOMS OF CHRONIC EXPOSURE: NONE EXPECTED

CARCINOGEN LISTING: NTP: **NO** IARC: **NO** OSHA: **NO**

SEE SECTION III FOR COMPONENTS AFFECTED

MEDICAL CONDITIONS USUALLY AGGRAVATED BY OVER EXPOSURE TO THIS PRODUCT: NONE

SECTION III - COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| <u>Hazardous Ingredients</u> | <u>CAS/EC #</u> | <u>PEL/TLV (MG/M#)</u> | <u>Max % Weight</u> | <u>NTP</u> | <u>IARC</u> |
|------------------------------|-----------------|----------------------------|-------------------------|------------|-------------|
| None | | | | | |

SECTION IV - FIRST AID MEASURES

EYES: Flush eyes with a large amount of water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected skin areas thoroughly with soap and water. Consult a physician if irritation persists.

INGESTION: Small amounts are not anticipated to be harmful. Give 2 glasses of water to drink.

INHALATION: Remove to fresh air. Get medical attention if breathing is difficult.

NOTE TO PHYSICIANS: Please contact your local poison control center for information regarding this product.

SECTION V - FIRE FIGHTING MEASURES

FLASH POINT (METHOD): N/A
EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE
EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED
FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED
UNUSUAL FIRE & EXPLOSION HAZARDS: NOT COMBUSTIBLE

AUTOIGNITION TEMPERATURE: N/A

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section XIII

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: NONE REQUIRED
OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): NONE REQUIRED
WORK/HYGIENE PRACTICES: NONE REQUIRED
ENGINEERING CONTROLS: NONE REQUIRED

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A
VAPOR PRESSURE: N/A
SPECIFIC VAPOR DENSITY (AIR=1): N/A
SOLUBILITY IN WATER: N/A

MELTING POINT: N/A

SPECIFIC GRAVITY: N/A

REACTIVITY IN WATER: NON-REACTIVE

SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: N/A
STABILITY: STABLE CONDITIONS TO AVOID: N/A
INCOMPATIBILITY (MATERIALS TO AVOID): N/A
HAZARDOUS DECOMPOSITION PRODUCTS: N/A

SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: NONE EXPECTED
The summated LD50 is 26765 mg/kg.
The summated LC50 is 99999 mg/cubic meter.
This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

SECTION XII - ECOLOGICAL INFORMATION

NO HARMFUL EFFECTS KNOWN OTHER THAN THOSE ASSOCIATED WITH SUSPENDED INERT SOLIDS IN WATER.

SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE.
WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION XIV - TRANSPORTATION INFORMATION

U.S. DOT (49 CFR 172.101): THIS IS NOT A HAZARDOUS MATERIAL AS CLASSIFIED BY CFR 172.101.

SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS SDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200

EPA SARA TITLE III CHEMICAL LISTINGS:
SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372):
NONE

INTERNATIONAL REGULATIONS

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS:
NONE

SUPPLEMENTAL STATE COMPLIANCE INFORMATION:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED UNDER NEW JERSEY'S RIGHT TO KNOW PROGRAM:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) REQUIRING NOTIFICATION TO THE STATE OF WASHINGTON UNDER THEIR CHILDREN'S SAFE PRODUCTS ACT:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN FLORIDA'S TOXIC SUBSTANCE LIST:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MAINE'S PRIORITY CHEMICAL LIST:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS CONSIDERED BY VERMONT AS BEING OF VERY HIGH CONCERN TO CHILDREN:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MASSACHUSETTS HAZARDOUS SUBSTANCE LIST:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MICHIGAN'S CRITICAL MATERIALS REGISTER:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MINNESOTA'S HAZARDOUS SUBSTANCES LIST:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN PENNSYLVANIA'S HAZARDOUS SUBSTANCES LIST:
NONE

Under CPSC's consumer product regulations (16CFR1500.3 and 1500.14), this product has the following required acute and chronic hazard labeling:

NONE

SECTION XVI - OTHER INFORMATION

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

LAST REVISION DATE: 08/15/2019

Prepared by Duke OEM Toxicology

COLOR INFORMATION

THIS SDS APPLIES TO THE FOLLOWING COLORS WHICH ARE ASSOCIATED WITH HAZARDOUS AND/OR NON-HAZARDOUS INGREDIENTS

| Product Color | SKU | Hazardous Ingredient |
|---------------------|--------|----------------------|
| CS11301 8OZ MATTE | 047540 | (NONE) |
| CS11302 16OZ MATTE | 047541 | (NONE) |
| CS11303 32OZ MATTE | 228880 | (NONE) |
| CS11304 128OZ MATTE | | (NONE) |
| CS11305 4OZ MATTE | 047539 | (NONE) |
| CS15092 64OZ MATTE | 326512 | (NONE) |
| CS15139 2OZ MATTE | 406884 | (NONE) |
| FBCS11305 4OZ MATTE | | (NONE) |

BRAND NAMES

THIS SDS APPLIES TO THE FOLLOWING BRAND NAMES

| Brand Name |
|-----------------|
| MOD PODGE MATTE |



MATERIAL SAFETY DATA SHEET

SECTION 1 – GENERAL INFORMATION

Manufacturer:

Modern Masters®, Inc.
9380 San Fernando Road
North Hollywood, California 91352
818-683-0201

HMIS Rating

| | |
|--------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 0 |
| REACTIVITY | 0 |

Emergency Telephone: 800-942-3166

Preparation Date: August 13, 2002

Revision Date: April 20, 2006

Product Name:

Modern Masters “Metallic Paint Collection”
Water-based Metallic Decorative Paints

Product Codes: ME150, ME164, ME194, ME190, ME195, ME196, ME200, ME204, ME205, ME206, ME209, ME221, ME230, ME238, ME243, ME244, ME246, ME247, ME249, ME289, ME427, ME429, ME432, ME434, ME435, ME510, ME511, ME513, ME514, ME525, ME579, ME591, ME654, ME655, ME656, ME657, ME658, ME659, ME660, ME661

SECTION 2 – HAZARDOUS INGREDIENTS

| <u>Hazardous Component</u> | <u>CAS #</u> | <u>OSHA PEL</u> | <u>ACGIH TLV</u> |
|-----------------------------|--------------|--------------------------------|-------------------------------------|
| Crystalline Silica (Quartz) | 14808-60-7 | 0.1 mg/m3 (Respirable Dust) | 0.05 mg/m3 (Respirable Fraction) |

NA: Not Applicable

N/D: Not Determined

N/E: Not Established

N/R: Not Required

Est.: Estimated

Modern Masters®, Incorporated, 9380 San Fernando Road, North Hollywood, California 91352

818-683-0201

MSDS Code: MPC MSDS (04/20/2006)

Page 1 of 7 pages



MATERIAL SAFETY DATA SHEET

SECTION 3 – HAZARD IDENTIFICATION

Emergency Overview: These materials are pigmented topcoats. They are stable, non-flammable, opaque flowable liquids with flash points above 200°F.

Primary Routes of Exposure:

Inhalation Skin contact Eye contact Ingestion

Potential Acute Health Effects:

Inhalation: May cause respiratory tract irritation **Eye:** May cause eye irritation
Skin: Prolonged or repeated skin contact may cause irritation
Ingestion: Not hazardous under intended use conditions

Potential Chronic Health Effects: None known

SECTION 4 – FIRST AID MEASURES

Eye contact: Flush eyes with clean water for 15 minutes. Seek medical attention.

Skin contact: Thoroughly wash with soap and warm water before the coating dries.

Inhalation: If irritation occurs, remove to fresh air and seek medical attention if cough or other symptoms develop.

Ingestion: Do not induce vomiting. Seek medical attention.

Note to Physician: Treat symptomatically. This material is basically non-toxic. A small quantity (approximately one tablespoon) is unlikely to cause harm.



MATERIAL SAFETY DATA SHEET

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point (method): N/D (est. >200°F)

Extinguishing Media: Use water spray, foam, or carbon dioxide when fighting fires involving this material.

Protection of Firefighters: As in any fire, wear NIOSH approved self-contained breathing apparatus pressure-demand and full protective gear.

Fire and Explosion Hazards: Material will not burn.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: Slippery: can cause slips and falls if walked on.

Clean Up Methods: Contain spill with sand or other diking material. Soak up small spills with absorbent material. Dispose of in accordance with federal, state, and local regulations.

(See also Section 8 for information on Exposure Controls and Personal Protective Equipment.)

SECTION 7 – HANDLING AND STORAGE

Handling: Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash hands with soap and warm water after use.

Storage: Keep from freezing. Keep container closed when not in use. Do not reuse container and properly dispose of empty containers.



MATERIAL SAFETY DATA SHEET

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: If necessary, use general room dilution ventilation, process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Eye contact should be avoided. Where eye contact is likely, wear chemical splash goggles and/or full-face shield.

Skin Protection: Wear gloves to prevent prolonged skin contact.

Respiratory Protection: None needed under normally anticipated use conditions. If vapor levels exceed allowable limits, wear a NIOSH approved air-purifying respirator with an organic vapor cartridge.

General Hygiene Practices: Avoid eye and skin contact. Avoid breathing vapors. Wash hands with soap and warm water before eating, drinking, or using the toilet.

SECTION 9 – PHYSICAL DATA

| | | | |
|-----------------------------|---|--------------------------------------|------------------|
| Appearance: | Opaque flowable liquid | Odor: | Mild odor |
| Physical State: | Liquid | pH: | 5.0-10.0 |
| Boiling Point: | Above 200°F | Melting Point: | <32°F |
| Vapor Pressure: | N/D | Vapor Density: | N/D |
| Odor Threshold: | N/D | Viscosity: | 1,000-25,000 cps |
| Solubility in Water: | Dilutable in water | Specific Gravity (water = 1): | 1.1-1.5 |
| Coating VOC: | Coating, less water, contains less than 150 grams per liter Volatile Organic Compounds. | | |



MATERIAL SAFETY DATA SHEET

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable, non-reactive **Incompatibility:** Strong acids and strong bases
Hazardous Polymerization: Will not occur
Hazardous Decomposition Products: None known

SECTION 11 – TOXICOLOGICAL INFORMATION

Carcinogenicity: This material is not considered a carcinogen by IARC or NTP and is not regulated as a carcinogen by OSHA.

(See also Section 15 for related information.)

SECTION 12 – ECOLOGICAL INFORMATION

Chemical Fate and Effects: No data available.

SECTION 13 – DISPOSAL CONSIDERATIONS

Recommended Waste Disposal Method: This material is not considered hazardous waste under Federal Hazardous Waste Regulations (40CFR 261). However, state and local requirements for waste disposal may be more restrictive or otherwise differ from federal regulations. Chemical additions, processing, or otherwise altering this material may render the waste management information presented in this MSDS incomplete, inaccurate, or otherwise inappropriate. Consult all applicable federal, state, and local regulations regarding the proper disposal of this material.

SECTION 14 – TRANSPORTATION INFORMATION

Regulated by the DOT: Not regulated

DOT Proper Shipping Name: Paint



MATERIAL SAFETY DATA SHEET

SECTION 15 – REGULATORY INFORMATION

CERCLA:

The Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification to the National Response Center for releases of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4 (for CERCLA 102).

Components present in this product at a level which could require reporting under the statute are:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>Maximum Concentration (Wt. %)</u> |
|----------------------|--------------|--------------------------------------|
| none | N/A | N/A |

SARA Title III, section 311/312:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQs) in 40 CFR 355 (used for SARA 302, 304, 311, and 312).

Components present in this product at a level which could require reporting under the statute are:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>Maximum Concentration (Wt. %)</u> |
|----------------------|--------------|--------------------------------------|
| none | N/A | N/A |

SARA Title III, section 313:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313).

Components present in this product at a level which could require reporting under the statute are:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>Maximum Concentration (Wt. %)</u> |
|-----------------------------|--------------|--------------------------------------|
| Crystalline Silica (Quartz) | 14808-60-7 | 2% |

TSCA:

The components of this mixture are listed in the Toxic Substance Control Act Inventory of Chemical Substances.

This product does not contain any chemicals that would require export notification under Section 12(b) of the TSCA regulation.



MATERIAL SAFETY DATA SHEET

SECTION 16 – OTHER INFORMATION

Legend: N/A: Not Applicable N/D: Not Determined
N/E: Not Established N/R: Not Required
STEL: Short Term Exposure Limit C: Ceiling Value
cps: Centipoise mg/m³: milligrams per cubic centimeter
PPM: Parts Per Million PPB: Parts Per Billion
PEL: Permissible Exposure Limit TLV: Time Weighted Average
mppcf: million particles per cubic foot of air
ACGIH: American Conference of Governmental Industrial Hygienists
CPSC: Consumer Product Safety Commission
DOT: US Department of Transportation
FHSA: Federal Hazardous Substance Act
OSHA: Occupational Safety and Health Administration (US Dept. of Labor)
RCRA: Resource Conservation and Recovery Act
SARA: Superfund Amendment and Reauthorization Act
TSCA: Toxic Substance Control Act

HMIS Key

4 = Severe Hazard
3 = Serious Hazard
2 = Moderate Hazard
1 = Slight Hazard
0 = Minimal Hazard

Prepared by: Modern Masters Regulatory Compliance Manager, Technical Management Dept.
9380 San Fernando Road, North Hollywood, California 91352 (818) 683-0201

Disclaimer: Modern Masters, Inc. believes, to the best of its knowledge, information, and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data to comply with all applicable international, federal, state, and local laws and regulations.

| | |
|---|---------------------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 Page 1 of 12 |
|---|---------------------------|

This safety data sheet complies with the requirements of 29CFR1910.1200.

1.0 IDENTIFICATION

Date Created: 8/10/2015

PRODUCT IDENTIFIER

Product Name Alcohol Prep Pad
Item Numbers 96959, 98721

OTHER MEANS OF IDENTIFICATION

Synonyms None

Other information None

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

Recommended use Topical Skin Cleanser
Uses advised against For Professional and Hospital Use

DETAIL OF THE SUPPLIER OF THE SAFETY DATA SHEET (SDS)

Supplier Address

Cypress Medical Products, LLC
1600 South Wolfe Road
Suite 200
Wheeling, IL 60090

EMERGENCY TELEPHONE NUMBER

Company Phone Number 1-800-777-4908
Emergency Telephone Call CHEMTREC day or night
Within USA and Canada: 1-800-424-9300

2.0 HAZARDS IDENTIFICATION

CLASSIFICATION

OSHA Regulatory Status


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

| | | |
|------------------------------|-----------------------------------|-------------|
| Physical Hazards | Flammable Solids | Category 1 |
| Health Hazards | Serious eye damage/eye irritation | Category 2A |
| Environmental Hazards | Not determined | |
| OSHA defined hazards | None additional | |

| | |
|---|--------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 |
| | Page 2 of 12 |

Label Elements

Pictograms

**Signal Word**

Danger

Hazard Statements

Flammable solid.

Causes serious eye irritation.

Precautionary Statements – Prevention

Keep away from heat/spark/open flames/hot surfaces.

No smoking.

Use only in a well ventilated area.

Precautionary Statements – Response

If case of fire: use appropriate media to extinguish.

If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Immediately call a poison control center.

If inhaled: remove victim to fresh air and keep comfortable for breathing.

Precautionary Statement – Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazards not otherwise classified (HNOC)

Not applicable

Other information

Not know.

| | |
|---|--------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 |
| | Page 3 of 12 |

3.0 COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms None

Substance: Mixture

| CHEMICAL NAME | CAS NO. | WEIGHT (%) |
|-------------------|-----------|------------|
| Isopropyl Alcohol | 67-63-0 | 70 |
| Purified Water | 7732-18-5 | 30 |

4.0 FIRST AID MEASURES**DESCRIPTION OF FIRST AID MEASURES**

General Advice Keep victim warm and quiet. Monitor for systemic secondary effects on liver and kidney. Ensure that medical personnel are aware of the material (s) involved and take precautions to protect themselves.

Eye Contact Immediately flush with plenty of water. After initial flushing remove any contact lenses and continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

Skin Contact In case of skin irritation, discontinue use of product. Wash off with soap and water. Get medical attention if irritation develops and persists.

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Ingestion If swallowed, contact a Poison Control Center immediately. Immediately rinse mouth out with water. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Symptoms May include stinging, tearing, redness, swelling and blurred vision.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

| | |
|---|---------------------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 Page 4 of 12 |
|---|---------------------------|

Provide general supportive measures and treat asymptotically.

5.0 FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA

Use foam, dry chemical or carbon dioxide. Be aware of possibility of re-ignition. Keep containers and surroundings cool with water spray.

Unsuitable extinguishing media: None

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

During fire, gases hazardous to health may be formed.

Explosion data

Sensitivity to Mechanical Impact None

Sensitivity to Static Discharge None

PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

In case of fire or explosion, do not breathe fumes. In the event of fire, use water spray to cool fire exposed surfaces and to protect personnel. Shut off fuel to the fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

6.0 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

| | |
|---------------------------------|--|
| Personal Precautions | Wear appropriate protective equipment and clothing during clean up. |
| Other Information | Eliminate all sources of ignition. |
| For Emergency Responders | Use personal protective equipment as required. Vapors can accumulate in low areas. Consider need for evacuation. |

| | |
|---|--------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 |
| | Page 5 of 12 |

ENVIRONMENTAL PRECAUTIONS

Collect spillage. Prevent material from entering water courses.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP**Methods for Containment**

Contain and absorb using earth, sand or inert materials. Transfer into suitable containers for recovery or disposal.

Methods for Cleaning up

N/A

7.0 HANDLING AND STORAGE**PRECAUTIONS FOR SAFE HANDLING****Advice on Safe Handling**

Do not handle near open flame or heat sources. Do not use with electrocautery procedures. Use according to package label instructions. Discard after single use. Avoid inhaling vapor and contact with eyes.

CONDITIONS FOR SAFE STORAGE**Storage Conditions**

Keep container closed. Store in a cool, dry, well ventilated place. Keep away from sources of ignition.

Incompatible Materials

N/A

8.0 EXPOSURE CONTROLS/PERSONAL PROTECTION**CONTROL PARAMETERS****Exposure Guidelines**

OSHA PEL Limits for Air contaminants
US ACGIH Threshold Limit Values

Isopropanol 980 mg/m³, 400 ppm

Isopropanol STEL 400 ppm

Isopropanol TWA 200 ppm

US NIOSH

Isopropanol STEL 1225 mg/m³, 500 ppm

Isopropanol TWA 980 mg/m³, 400 ppm

Biological Limit Values

ACGIH Biological Exposure Indices

| | |
|---|---------------------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 Page 6 of 12 |
|---|---------------------------|

Isopropanol

40mg/l, Acetone, Urine

APPROPRIATE ENGINEERING CONTROLS

Ventilation systems. Eyewash stations. Showers.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PPE**Eye/Face Protection**

Wear gear deemed necessary.

Skin and Body Protection

Wear gear as deemed necessary.

Respiratory Protection

Wear positive pressure self contained breathing apparatus (SCBA)

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not smoke. When using do not eat or drink.

9.0 PHYSICAL AND CHEMICAL PROPERTIES**INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES****Physical State**

Liquid

Appearance

Clear, Colorless

Form

Pre-moistened towelette

Color

N/A

Odor

Alcohol odor

Odor Threshold

No information available

| Property | Values | Remarks |
|--|------------------------|---------------|
| pH (1-3% aqueous solution) | Not applicable | |
| Melting point/freezing point | -88.5° C | |
| Boiling point/boiling range | Between 82 and 83 C | |
| Flash point | 12 C | |
| Evaporation rate | 2.5 | |
| Flammability (solid, gas) | Not applicable | |
| Flammability Limit in Air <ul style="list-style-type: none"> Upper flammability limit | LEL/UEL 2.0/12.7 vol % | Not Flammable |

| | |
|---|---------------------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 Page 7 of 12 |
|---|---------------------------|

| | | |
|----------------------------|----------------|--|
| • Lower flammability limit | | |
| Vapor pressure | 33 mmHg | |
| Vapor density | Not applicable | |
| Specific Gravity | 0.785 | |
| Water solubility | Not applicable | |
| Solubility in water | 100% | |
| Partition coefficient | Not applicable | |
| Autoignition temperature | 399 C | |
| Decomposition temperature | Not applicable | |
| Kinematic viscosity | Not applicable | |
| Dynamic viscosity | Not applicable | |
| Explosive properties | Not applicable | |
| Oxidizing properties | Not applicable | |
| Softening point | Not applicable | |
| Molecular weight | Not applicable | |
| VOC Content (%) | Not applicable | |
| Density | Not applicable | |
| Bulk Density | 0.9g/cc | |

10.0 STABILITY AND REACTIVITY

CHEMICAL STABILITY

Stable under normal condition of handling, use and transport.

POSSIBILITY OF HAZARDOUS REACTIONS

None under normal processing.

Hazardous polymerization

Does not occur.

CONDITIONS TO AVOID

Heat, flames and sparks. Avoid temperatures exceeding flash point.

INCOMPATIBLE MATERIALS

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

May include but are not limited to oxides of carbon.

11.0 TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE

Product Information

Available toxicological data for individual ingredients are summarized below.

| | |
|---|---------------------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 Page 8 of 12 |
|---|---------------------------|

Inhalation

Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Health injuries are not known or expected under normal use.

Eye Contact

Causes serious eye irritation.

Skin Contact

Not expected to be a primary skin irritant.

Ingestion

Not applicable under normal conditions of use.

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LD50 |
|------------------------|---------------------|-----------------------------|------------------|
| Isopropanol 67-63-0 | 5045 mg/kg (rat) | Eye 12800 mg/kg (rabbit) | 16970 mg/l/4h |

INFORMATION ON TOXICOLOGICAL EFFECTS

No information available.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE**Skin corrosion/irritation**

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Causes serious irritation to the eye

Respiratory or skin sensitization

Not expected to cause skin sensitization.

Sensitization

No sensitization responses were observed.

Germ cell mutagenicity

Not expected to have chronic health effects.

Carcinogenicity

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC, ACGHI or NTP.

US OSHA Specifically Regulated Substances Not listed

Reproductivity Toxicity

Finished product not expected to have chronic health effects.

STOT- single exposure

Narcotic effects.

STOT – repeated exposure

Not classified.

Chronic Toxicity

No known effect.

Sub-chronic Toxicity

No known effect.

Neurological Effects

Not applicable.

NUMERICAL MEASURES OF TOXICITY

Not available.

12.0 ECOLOGICAL INFORMATION**ECOTOXICITY**

| Chemical Name | Algae/Aquatic Plants | Fish | Crustacea |
|------------------------|-------------------------|--------------------------------------|--------------------------------------|
| Isopropanol 67-63-0 | IC 50 100mg/L, 72 hours | LC 50 Bluegill > 1400 ml/l, 96 hours | EC 50 13299 mg/L: 72 h Daphnia magna |

| | |
|---|---------------------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 Page 9 of 12 |
|---|---------------------------|

| | |
|---|--------------------|
| Persistence and degradability | No data available. |
| Bioaccumulation | No data available. |
| Partition coefficient n-octanol/water (log Kow) | Isopropanol 0.05 |
| Mobility | No data available. |
| Other adverse effects | None expected. |

13.0 DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

| | |
|---|---|
| DISPOSAL OF WASTE | Disposal should be in accordance with applicable regional, national and local laws and regulations. Dispose of contents/containers in accordance with local regulations. This material, as supplied, is not a hazardous waste according to state and federal regulations (40 CFR 61). |
| Contaminated packaging | Following warning label. |
| State of California Hazardous Waste Status | Isopropanol (67-63-0) Listed |

14.0 TRANSPORT INFORMATION

NOTE: THIS MATERIAL IS NOT SUBJECT TO REGULATION AS A DANGEROUS GOOD.

| | |
|-------------|---|
| DOT | Not regulated |
| TDG | Not regulated |
| MEX | Not regulated |
| ICAO | Not regulated |
| IATA | Not regulated |
| IMDG | Not regulated |
| RID | Not regulated |
| ADR | Not regulated. European requirement only. |
| AND | Not regulated. European requirement only. |

15.0 REGULATORY INFORMATION

INTERNATIONAL INVENTORIES

| | |
|---|------------|
| OSHA Specifically regulated substances | Not listed |
|---|------------|

LEGEND

| | |
|---|----------------------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 Page 10 of 12 |
|---|----------------------------|

TSCA – United States Toxic Substances Control Act Section 8b Inventory

DSL/NDSL – Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS – European Inventory of Existing chemical Substances/European List of Notified Chemical

ENCS – Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS – Phillipines Inventory of Chemicals and Chemical Substances

AICS – Australian Inventory of Chemical Substances

US FEDERAL REGULATION

SARA

| | |
|--------------------------|--|
| Hazard categories | Immediate Hazard – Yes Delayed Hazard – No Fire Hazard – Yes Pressure Hazard – No Reactivity Hazard - No |
|--------------------------|--|

SARA 302 Extremely Hazardous Substances No

SARA 311/312 Hazard Categories

| | |
|--|----|
| Acute Health Hazard | No |
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

SARA 313 (TRI Reporting)

| | |
|-----------------------|------------------|
| Isopropanol (67-63-0) | 40-70% by weight |
|-----------------------|------------------|

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

FDA Regulated as a drug.

CERCLA Isopropanol (67-63-0) Listed

US STATE REGULATIONS

| | |
|---|----------------------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 Page 11 of 12 |
|---|----------------------------|

CALIFORNIA PROPOSITION 65

This product does not contain any Proposition 65 chemicals.

US RIGHT TO KNOW REGULATIONS

| | |
|---|---|
| Isopropanol (67-63-0) | Listed California (Hazardous Substances (Director's), Illinois, Louisiana, Minnesota, New Jersey, Massachusetts, Pennsylvania, Rhode Island |
| Country(s) of Origin | United States & Puerto Rico |
| Toxic Substances Control Act (TSCA) Inventory | On inventory? Yes |

US EPA LABEL INFORMATION

Not applicable.

16.0 OTHER INFORMATION**NFPA**

| | |
|------------------------|---|
| Health Hazards | 1 |
| Flammability | 3 |
| Reactivity/Instability | 0 |

HMIS

| | |
|---------------------|---|
| Health Hazards | 1 |
| Flammability | 3 |
| Physical Hazards | 0 |
| Personal Protection | X |

Prepared by

Cypress Medical Products, LLC Quality Assurance

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

---End of Document---

| | |
|---|---------------|
| Title: Safety Data Sheet – Alcohol Prep Pad | SDS - 002 |
| | Page 12 of 12 |

SAFETYDATASHEET

1. PRODUCT IDENTIFICATION

PRODUCT NAME: Mosaic Tile Adhesive

PRODUCT TYPE: Adhesive

MANUFACTURER'S NAME: **Mosaic Mercantile, Inc.**
ADDRESS: 1234 Indiana Street,
San Francisco, CA 94107

BUSINESS PHONE: 415-282-5410
FAX NUMBER: 415-282-5413

DATE OF PREPARATION: June 8, 2015

2. HAZARD IDENTIFICATION

EMERGENCYOVERVIEW:

NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

| GHS HAZARD CLASS | HAZARD CATEGORY |
|------------------|-----------------|
| None | None |

PICTOGRAM

NONE

PRECAUTIONARY STATEMENT:

NONE PRESCRIBED.

Classification complies with OSHA Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

3. COMPOSITION and INFORMATION ON INGREDIENTS

| HazardousIngredients: | CAS# | WT%* |
|-----------------------|------|------|
| None | N/A | N/A |

* Exact percentage is proprietary information. Concentration range is provided to assist users in providing appropriate protection.

SAFETY DATASHEET

4. FIRST-AID MEASURES

Contaminated individuals of chemical exposure must be taken for medical attention if any adverse effect occurs. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to health professional with contaminated individual.

SKIN CONTACT: Wash affected area immediately soap and water. Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention.

EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get immediate medical attention.

INHALATION: Move to fresh air. If symptoms develop and persist, get medical attention.

INGESTION: Routine use of this product is not expected to cause any situation which could lead to ingestion. If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and eliminate overexposure.

5. FIRE-FIGHTING MEASURES

FLASHPOINT: Aqueous. Does not flash

AUTOIGNITION TEMPERATURE: Not Established

FLAMMABLE LIMITS (in air by volume, %): Lower: NA Upper: NA

FIRE EXTINGUISHING MATERIALS: Use fire extinguishing materials appropriate for surrounding fire including water spray (for cooling), dry extinguishing media, carbon dioxide, foam.


UNUSUAL FIRE AND EXPLOSION HAZARDS: This product has no unusual fire or explosion hazards..

Explosion Sensitivity to Mechanical Impact: Not Sensitive

Explosion Sensitivity to Static Discharge: Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent run off water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING



Hazard Scale: 0=Minimal 1=Slight
2=Moderate
3=Serious 4=Severe

SAFETYDATASHEET

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Personnel should be trained for spill response operations. Wear appropriate protective equipment such as rubber gloves, safety glasses, and appropriate body protection. Stop discharge if safe to do so.

CLEAN-UP METHOD: Wear suitable protective clothing, gloves and eye/face protection. Avoid skin contact and inhalation of vapors during disposal of spills. Confine in small space area; use absorbent to clean up.

DISPOSAL: Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations). Dispose of recovered material and report spill per regulatory requirements. It is recommended you contact local authorities to determine if there may be other local reporting requirements.

7. HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: All employees who handle this material should be trained to handle it safely. Avoid contact with eyes, skin and clothing. Keep the container tightly closed and dry.

EMPTY CONTAINER PRECAUTION: Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for humans or animal consumption, or where skin contact can occur.

8. EXPOSURE CONTROLS- PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided below. Use local exhaust ventilation, and process enclosure if necessary, to control airborne dust. Ensure eyewash/safety shower stations are available near areas where this product is used.

EXPOSURE LIMITS/GUIDELINES:

| <u>ComponentName</u> | <u>CAS#</u> | <u>ACGIH-TLV's</u> | <u>OSHA PEL's</u> | <u>Other</u> |
|-----------------------------|--------------------|---------------------------|--------------------------|---------------------|
| None | N/A | N/A | N/A | N/A |

Currently, International exposure limits are established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

SAFETYDATASHEET

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29CFR1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-face piece pressure/demand SCBA or a full face piece, supplied air respirator with auxiliary self-contained air supply is required under U.S. Federal OSHA's Respiratory Protection Standard (1910.134-1998) or the regulations of various U.S. States, Canada, EU Member States, or those of Japan. Air-purifying respirators with dust/mist/fume filters are recommended if operations may produce mists or sprays from this product.

EYE PROTECTION: Full face protection should be used if the potential for splashing or spraying of products exist. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

BODY PROTECTION: Work clothing sufficient to prevent skin contact. If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards

9. PHYSICAL and CHEMICAL PROPERTIES

APPEARANCE, ODOR and COLOR: White liquid, cherry odor.

BOILING POINT/RANGE: >212°F (>100°C)

MELTING POINT/RANGE: 32°F (0°C) (Freezing point)

SPECIFIC GRAVITY@20°C: 1.01–1.02 (water=1)

VAPOR PRESSURE, mm Hg@20°C(68°F): N/A

ODOR THRESHOLD: N/A

pH: 8.0 to 9.0

EVAPORATION RATE(n-BuAc=1): same as water

SOLUBILITY IN WATER: Dilutable

VAPOR DENSITY: N/A

VOC: <0.009% (Calculated)

10. STABILITY and REACTIVITY

STABILITY: Stable.

DECOMPOSITION PRODUCTS: Thermal degradation produces carbon monoxide, carbon dioxide and other low molecular weight hydrocarbons

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: The product may react to strong acids, bases and oxidizing agents.

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

CONDITIONS TO AVOID: None known.

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: No LD50 Data Available for this product

SUSPECTED CANCER AGENT: The components of this product are not listed by agencies tracking the carcinogenic potential of chemical compounds as follows:

Carcinogenicity

NTP Regulated No

IARC Regulated No

OSHA Regulated No

SAFETY DATASHEET

IRITANCY OF PRODUCT: Not established.

SENSITIZATION TO THE PRODUCT: These products are not known to cause human skin or respiratory sensitization.

REPRODUCTIVE TOXICITY INFORMATION: Listed below is information concerning the effects of this product and its components on the human reproductive system.

Mutagenicity: The components of this product are not reported to produce mutagenic effects in humans.

Embryotoxicity: The components of this product are not reported to produce embryotoxic effects in humans.

Teratogenicity: The components of this product are not reported to produce teratogenicity effects in humans.

Reproductive Toxicity: The components of this product are not reported to produce reproductive effects in humans.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

MOBILITY IN SOIL: This product has not been tested for mobility in soil.

PERSISTENCE/DEGRADABILITY: This product have not been tested for persistence or biodegradability. The components may slowly degrade in the environment and form a variety of organic and inorganic materials; however, no specific information is known.

ENVIRONMENTAL STABILITY: Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways

BIOACCUMULATION/ACCUMULATION: These products have not been tested for bio-accumulation potential.

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

14. TRANSPORTATION INFORMATION

US DOT. IATA. IMO. ADR:

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS: This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101. Non-Regulated

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: These products are not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA): These products are not classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION: These products are not classified as Dangerous Goods by the International Maritime Organization

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): These products are not classified by the United Nations Economic Commission for Europe to be dangerous goods

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of these products are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for any component of these products. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) therefore applies, per 40 CFR 370.20.

SAFETYDATASHEET

U.S. CERCLA REPORTABLE QUANTITY (RQ): None.

U.S. TSCA INVENTORY STATUS: The components of these products are listed in the TSCA Inventory.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product contains a chemical known in the State of California to cause cancer.

CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: The components of this product are on the DSL Inventory, or are exempted from listing.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Not Controlled as per the Controlled Product Regulations.

EUROPEAN ECONOMIC COMMUNITY INFORMATION:

SEE SECTION 2 FOR DETAILS

AUSTRALIAN INFORMATION FOR PRODUCT:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: The components of this product are listed on the AICS or are exempt.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: The components of this product are not listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac: Listed or exempt

Australian Inventory of Chemical Substances (AICS): Listed or exempt

Korean Existing Chemicals List (ECL): Listed or exempt

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed or exempt

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed or exempt

Swiss Giftlist List of Toxic Substances: Listed or exempt

U.S. TSCA: Listed or exempt

16. OTHER INFORMATION

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in Section 1) and is not necessarily correct for use with other chemicals/products.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

INTERNATIONAL EMERGENCY NUMBER: 352-323-3500 - INFOTRAC

1. Identification

Product identifier Motor Medic Thrust Starting Fluid

Other means of identification

SDS number M3815
Part No. M3815
Tariff code 2909.11.0000

Recommended use Starting Fluid

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name RSC Chemical Solutions
Address 600 Radiator Road
Indian Trail, NC 28079
United States
Telephone Customer Service: (704) 821-7643
Technical: (704) 684-1811
Website www.rscbrands.com
E-mail sds@rscbrands.com
Emergency phone number Emergency Telephone: (303) 623-5716
Emergency Contact: RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Acute toxicity, oral Category 4
Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2B
Carcinogenicity Category 1B
Specific target organ toxicity, single exposure Category 3 narcotic effects
Specific target organ toxicity, repeated exposure Category 2
Environmental hazards Hazardous to the aquatic environment, acute hazard Category 1
Hazardous to the aquatic environment, long-term hazard Category 1
OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Harmful if swallowed. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. May cause cancer. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

| | |
|---|---|
| Precautionary statement | |
| Prevention | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. |
| Response | If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage. |
| Storage | Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNO C) | None known. |
| Supplemental information | 81.58% of the mixture consists of component(s) of unknown acute oral toxicity. 26.34% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 26.34% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| Heptane | | 142-82-5 | 70 - < 80 |
| ETHANE, 1,1'-OXYBIS- | | 60-29-7 | 10 - < 20 |
| Carbon Dioxide | | 124-38-9 | 5 - < 10 |
| Distillates (petroleum), Hydrotreated Light Naphthenic | | 64742-53-6 | < 1 |
| Hydrotreated Heavy Naphthenic Distillate (petroleum) | | 64742-52-5 | < 1 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Skin contact | Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell. |
| Most important symptoms/effects, acute and delayed | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. |

5. Fire-fighting measures

| | |
|---------------------------------------|--|
| Suitable extinguishing media | Powder. Alcohol resistant foam. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |

| | |
|--|--|
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire fighting equipment/instructions | Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|---------------------|-------|
| Carbon Dioxide (CAS 124-38-9) | PEL | 9000 mg/m3 | |
| Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) | PEL | 5000 ppm 5 mg/m3 | Mist. |
| | | 2000 mg/m3 | |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--|------|------------|-------|
| ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) | PEL | 500 ppm | |
| | | 1200 mg/m3 | |
| Heptane (CAS 142-82-5) | PEL | 400 ppm | |
| | | 2000 mg/m3 | |
| Hydrotreated Heavy Naphthenic Distillate (petroleum) (CAS 64742-52-5) | PEL | 500 ppm | Mist. |
| | | 5 mg/m3 | |
| | | 2000 mg/m3 | |
| | | 500 ppm | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|--|------|-----------|---------------------|
| Carbon Dioxide (CAS 124-38-9) | STEL | 30000 ppm | |
| Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) | TWA | 5000 ppm | Inhalable fraction. |
| | TWA | 5 mg/m3 | |
| ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) | STEL | 500 ppm | |
| | TWA | 400 ppm | |
| Heptane (CAS 142-82-5) | STEL | 500 ppm | |
| | TWA | 400 ppm | |
| | TWA | 5 mg/m3 | |
| Hydrotreated Heavy Naphthenic Distillate (petroleum) (CAS 64742-52-5) | TWA | 5 mg/m3 | Inhalable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|--|---------|-------------------------------------|-------|
| Carbon Dioxide (CAS 124-38-9) | STEL | 54000 mg/m3 | |
| | TWA | 30000 ppm 9000 mg/m3 5000 ppm | |
| Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) | Ceiling | 1800 mg/m3 | |
| | STEL | 10 mg/m3 | |
| Heptane (CAS 142-82-5) | Ceiling | 1800 mg/m3 | Mist. |
| | | 440 ppm | |
| | TWA | 350 mg/m3 85 ppm | |
| Hydrotreated Heavy Naphthenic Distillate (petroleum) (CAS 64742-52-5) | Ceiling | 1800 mg/m3 | |
| | STEL | 10 mg/m3 | |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

| | |
|---------------------------------------|---|
| Eye/face protection | Chemical respirator with organic vapor cartridge and full facepiece. |
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. |
| Other | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. |
| Respiratory protection | Chemical respirator with organic vapor cartridge and full facepiece. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| | |
|---|-----------------------------------|
| Appearance | Liquid. Clear. |
| Physical state | Liquid. |
| Form | Aerosol. |
| Color | Colorless |
| Odor | Ester-like. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -189.94 °F (-123.3 °C) estimated |
| Initial boiling point and boiling range | -109.3 °F (-78.5 °C) estimated |
| Flash point | -1.0 °F (-18.3 °C) Tag Closed Cup |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 1.9 % estimated |
| Flammability limit - upper (%) | 36.5 % estimated |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 4083.55 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Partial Solubility |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 320 °F (160 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 5.75 lbs/gal |
| Explosive properties | Not explosive. |
| Flammability class | Flammable IA estimated |
| Heat of combustion (NFPA 30B) | 30.83 kJ/g estimated |
| Oxidizing properties | Not oxidizing. |
| Percent volatile | 18.42 % estimated |
| Specific gravity | 0.69 |

VOC (Weight %) 93 %

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. Aluminum. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---|---|
| Inhalation | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful. |
| Skin contact | Causes skin irritation. |
| Eye contact | Causes eye irritation. |
| Ingestion | Harmful if swallowed. |
| Symptoms related to the physical, chemical and toxicological characteristics | Headache. May cause drowsiness and dizziness. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. |

Information on toxicological effects

| | |
|-----------------------|---|
| Acute toxicity | Harmful if swallowed. Narcotic effects. |
|-----------------------|---|

| Components | Species | Test Results |
|------------------------------------|---------|--------------------|
| ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Rat | 32000 ppm, 4 Hours |
| Oral | | |
| LD50 | Rat | 3230 - 3920 mg/kg |
| Heptane (CAS 142-82-5) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Rat | 103 mg/l, 4 Hours |
| LD50 | Mouse | 75 mg/l, 2 Hours |

* Estimates for product may be based on additional component data not shown.

| | |
|--|--|
| Skin corrosion/irritation | Causes skin irritation. |
| Serious eye damage/eye irritation | Causes eye irritation. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | May cause cancer. |

IARC Monographs. Overall Evaluation of Carcinogenicity

ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) Known To Be Human Carcinogen.

| | |
|---|--|
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | May cause drowsiness and dizziness. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Prolonged inhalation may be harmful. |

12. Ecological information

| | |
|--------------------|---|
| Ecotoxicity | Very toxic to aquatic life with long lasting effects. |
|--------------------|---|

| Components | Species | Test Results |
|------------------------------------|---------|--|
| ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) | | |
| Aquatic | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 2560 mg/l, 96 hours |
| Heptane (CAS 142-82-5) | | |
| Aquatic | | |
| Fish | LC50 | Mozambique tilapia (Tilapia mossambica) 375 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

| | |
|--------------------------------------|--|
| Persistence and degradability | No data is available on the degradability of this product. |
|--------------------------------------|--|

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|----------------------|------|
| ETHANE, 1,1'-OXYBIS- | 0.89 |
| Heptane | 4.66 |

| | |
|-------------------------|--------------------|
| Mobility in soil | No data available. |
|-------------------------|--------------------|

| | |
|------------------------------|---|
| Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |
|------------------------------|---|

13. Disposal considerations

| | |
|--|---|
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. |

14. Transport information

DOT

| | |
|-------------------------------------|---|
| UN number | Not available. |
| UN proper shipping name | Consumer Commodity |
| Transport hazard class(es) | |
| Class | ORM-D |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Environmental hazards | |
| Marine pollutant | Yes |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

| | |
|----------------------|----------|
| Special provisions | T75, TP5 |
| Packaging exceptions | 306 |
| Packaging non bulk | 304 |
| Packaging bulk | 314, 315 |

IATA

| | |
|------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, Flammable (Starting Fluid) |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Environmental hazards | Yes |
| ERG Code | 9L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed. |
| Cargo aircraft only | Allowed. |

IMDG

| | |
|--|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols (ILimited QtY) |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Environmental hazards | |
| Marine pollutant | Yes |
| EmS | F-D, S-U |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not established. |

IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) Listed.
Heptane (CAS 142-82-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

ETHANE, 1,1'-OXYBIS- (CAS 60-29-7)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) 6584

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) 35 %WV

DEA Exempt Chemical Mixtures Code Number

ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) 6584

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)
Hydrotreated Heavy Naphthenic Distillate (petroleum) (CAS 64742-52-5)

US. Massachusetts RTK - Substance List

Carbon Dioxide (CAS 124-38-9)
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)
ETHANE, 1,1'-OXYBIS- (CAS 60-29-7)
Heptane (CAS 142-82-5)
Hydrotreated Heavy Naphthenic Distillate (petroleum) (CAS 64742-52-5)

US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (CAS 124-38-9)
ETHANE, 1,1'-OXYBIS- (CAS 60-29-7)
Heptane (CAS 142-82-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Dioxide (CAS 124-38-9)
ETHANE, 1,1'-OXYBIS- (CAS 60-29-7)
Heptane (CAS 142-82-5)

US. Rhode Island RTK

ETHANE, 1,1'-OXYBIS- (CAS 60-29-7)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|---------------|---|
| Issue date | 05-07-2015 |
| Revision date | 11-03-2015 |
| Version # | 05 |
| HMIS® ratings | Health: 2* Flammability: 4 Physical hazard: 0 |
| NFPA ratings | Health: 2 Flammability: 4 Instability: 0 |
| NFPA ratings | |



| | |
|----------------------|--|
| Disclaimer | The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. |
| Revision Information | Physical & Chemical Properties: Multiple Properties Transport Information: Material Transportation Information |

MATERIAL SAFETY DATA SHEET

B51W8020
31 00

DATE OF PREPARATION
Oct 27, 2012

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

B51W8020

PRODUCT NAME

Multi-Purpose Latex Primer, Interior/Exterior Latex, White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

Telephone Numbers and Websites

| | |
|---|-------------------------------------|
| Product Information | www.sherwin-williams.com |
| Regulatory Information | (216) 566-2902 www.paintdocs.com |
| Medical Emergency | (216) 566-2917 |
| Transportation Emergency* | (800) 424-9300 |
| *for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident) | |

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

| % by Weight | CAS Number | Ingredient | Units | Vapor Pressure |
|-------------|------------|------------------|-----------------------------|----------------|
| 1 | 107-21-1 | Ethylene Glycol | | |
| | | ACGIH TLV | 100 MG/M3 CEILING (aerosol) | 0.12 mm |
| | | OSHA PEL | 50 PPM CEILING | |
| 0.4 | 14464-46-1 | Cristobalite | | |
| | | ACGIH TLV | 0.025 mg/m3 as Resp. Dust | |
| | | OSHA PEL | 0.05 mg/m3 as Resp. Dust | |
| 3 | 14807-96-6 | Talc | | |
| | | ACGIH TLV | 2 mg/m3 as Resp. Dust | |
| | | OSHA PEL | 2 mg/m3 as Resp. Dust | |
| 17 | 13463-67-7 | Titanium Dioxide | | |
| | | ACGIH TLV | 10 mg/m3 as Dust | |
| | | OSHA PEL | 10 mg/m3 Total Dust | |
| | | OSHA PEL | 5 mg/m3 Respirable Fraction | |

SECTION 3 — HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.
EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the liver
- the urinary system

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

HMIS Codes

| | |
|--------------|----|
| Health | 2* |
| Flammability | 0 |
| Reactivity | 0 |

SECTION 4 — FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
SKIN: Wash affected area thoroughly with soap and water.
 Remove contaminated clothing and launder before re-use.
INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
INGESTION: Do not induce vomiting. Get medical attention immediately.

SECTION 5 — FIRE FIGHTING MEASURES

| | | | |
|--------------------|----------------|----------------|------------------------------------|
| FLASH POINT | LEL | UEL | FLAMMABILITY CLASSIFICATION |
| Not Applicable | Not Applicable | Not Applicable | Not Applicable |
| | Applicable | Applicable | EXTINGUISHING MEDIA |

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.
 Remove with inert absorbent.

SECTION 7 — HANDLING AND STORAGE

STORAGE CATEGORY

Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.
 Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.
 Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction). Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|-------------------|--|
| PRODUCT WEIGHT | 11.13 lb/gal | 1333 g/l |
| SPECIFIC GRAVITY | 1.34 | |
| BOILING POINT | 212 - 500 °F | 100 - 260 °C |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 64% | |
| EVAPORATION RATE | Slower than ether | |
| VAPOR DENSITY | Heavier than air | |
| SOLUBILITY IN WATER | Not Available | |
| pH | 8.8 | |
| VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged) | | |
| | 0.80 lb/gal | 96 g/l |
| | 0.31 lb/gal | 38 g/l |
| | | Less Water and Federally Exempt Solvents |
| | | Emitted VOC |

SECTION 10 — STABILITY AND REACTIVITY

STABILITY — Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

SECTION 11 — TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

TOXICOLOGY DATA

| CAS No. | Ingredient Name | | | |
|------------|------------------|----------|-----|---------------|
| 107-21-1 | Ethylene Glycol | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | 4700 mg/kg |
| 14464-46-1 | Cristobalite | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |
| 14807-96-6 | Talc | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |
| 13463-67-7 | Titanium Dioxide | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

SECTION 13 — DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

US Ground (DOT)

Not Regulated for Transportation.

Canada (TDG)

Not Regulated for Transportation.

IMO

Not Regulated for Transportation.

IATA/ICAO

Not Regulated for Transportation.

SECTION 15 — REGULATORY INFORMATION**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|----------|-------------------|---------|-----------|
| 107-21-1 | Ethylene Glycol | 1 | |

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.