

EXHIBIT A – SCOPE OF WORK/DRAWING/SPECIFICATIONS

The Tamalpais Union High School District (TUHSD) has prepared the following specifications for this project as described further below. The TUHSD will consider any product/service that meets or exceeds the minimum requirements.

Contractor to provide all necessary services and materials for the six (6) tennis courts listed and located at the Redwood High School per the following specifications.

1. EXAMINATION OF SITE AND SPECIFICATIONS

Before submitting a bid, each Bidder/Contractor is required to:

- Examine the specifications and scope of work thoroughly.
- Visit the site to familiarize themselves with conditions at the site that may affect the performance of the work.
- Familiarize themselves with all local laws, ordinances, rules, and regulations affecting the performance of the work.
- Carefully correlate observations with the requirements of the specifications.

2. RESURFACING MATERIALS

The Contractor shall identify the manufacturer of the product chosen and submit, along with the bid, the manufacturer's product data, including surface and crack preparations, application instructions, and color samples.

- Approved materials must meet the United States Tennis Association (USTA) Standards.
- All acrylic materials must be the products of a single manufacturer. Only collegiate/professional-grade acrylic color coatings with an International Tennis Federation (ITF) speed rating will be accepted. Acrylic color mixed with locally purchased sand is not acceptable.

3. MATERIALS DELIVERY, STORAGE, AND HANDLING

The Contractor shall:

- Deliver materials to site in manufacturer's original, unopened containers and packaging with labels clearly identifying product name and manufacturer.
- Store and handle materials in accordance with manufacturer's instructions.
- Keep materials in manufacturer's original, unopened containers and packaging until application.
- Store materials in clean, dry areas, out of direct sunlight and prevent from freezing.
- Protect materials during storage, handling, and application to prevent contamination or damage. Close containers when not in use.

4. ACRYLIC RESURFACING APPLICATION

All courts will be resurfaced to match existing colors (green playing area surrounded by red) with white lines painted for courts. Work shall include:

- **Cleaning:** All surfaces shall be thoroughly cleaned with pressure; loose material scraped and removed. The surface shall be free of oil, grease, dirt, debris, tool marks, ridges, and valleys.
- **Repairs:** Prior to applying material, level any depressions 1/8" or deeper with Court Patch Binder in accordance with manufacturer's instructions. Cracks shall be cleaned, dried, filled, and sealed, such that there are no ridges. All repairs shall be made prior to the squeegee application of Acrylic Resurfacer.
- **Filler Course (Acrylic Resurfacer):** Filler course shall be applied to the clean underlying surface in one application, according to manufacturer's instructions. Acrylic Resurfacer may be used to pre-coat depression and crack/hole repairs to achieve better planarity prior to filler course application. Allow to dry thoroughly.

EXHIBIT A – SCOPE OF WORK/DRAWING/SPECIFICATIONS

- **Color Surface System:** Acrylic color playing surface shall be applied on the clean, dry underlying surface in accordance with manufacturer's instructions. Do not apply tennis court surface color coating when air or surface temperatures are below 50 degrees F during application or within 24 hours after application. Do not apply tennis court surface color coating when rain is expected during application or within 24 hours after application.

Allow material drying times in accordance with manufacturer's instructions before applying materials or opening completed surface to foot traffic.

5. PLAYING LINES

After the surface has thoroughly cured, layout six (6) tennis court line markings in accordance with USTA Rules of tennis. Apply line markings in two (2) inch wide playing lines, masked and painted with two (2) coats of approved line paint.

6. NEW NET POSTS

- Demo and off haul existing footings.
- Set new aluminum square 3"x3" sleeves.
- Install new FE Deluxe Net Posts

END OF PAGE



gh School

spur CA