

**SECTION 26 0500**

**COMMON WORK RESULTS FOR ELECTRICAL**

**PART 1 - GENERAL**

**1.1 RELATED DOCUMENTS**

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Specified Elsewhere:
  - 1. Division 26 – Other Electrical Specifications and Drawings

**1.2 SUMMARY**

- A. Section Includes:
  - 1. Labor and materials for complete electrical systems. These materials include, but are not limited to; circuit breakers, devices, boxes, conduit, conductors, connectors, fittings, and anchors, as required and/or indicated in these specifications and/or shown on the Electrical drawings.
  - 2. Power connections and control equipment and wiring, as required for equipment furnished and installed under other sections or by Owner.
  - 3. All minor system components reasonably required for the proper functioning and/or safe operation of the electrical systems, and to meet all related codes and ordinances.
  - 4. Required system and component testing, as required in associated specification sections and/or related codes and ordinances.
  - 5. Coordination with other trades, Owner(s), suppliers, utilities, and Authorities Having Jurisdiction.
  - 6. General requirements included in this section apply to all other Division 26 specifications and drawings.

**1.3 DEFINITIONS**

- A. ADA: Americans with Disabilities Act
- B. AHJ: Authority Having Jurisdiction
- C. FBO: Furnished by Others
- D. IAC: Illinois Accessibility Code

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- E. IBC: International Building Code
- F. IECC: International/Illinois Energy Conservation Code
- G. IFC: International Fire Code
- H. NEC: National Electrical Code (NFPA 72)
- I. NFPA: National Fire Protection Association
- J. Provide: Furnish and install.

#### **1.4 VERIFICATION OF CONNECTION POINTS**

- A. Before submitting his proposal, Contractor shall visit the site to carefully verify all exposed points of existing utilities and new connections. Contractor shall verify concealed or buried points for connection, as near as possible. Verify these points as to locations, size, type, depth, operating characteristics, and complications; including, but not limited to:
  - 1. Present site conditions.
  - 2. Present and new electrical utility distribution system and requirements.
  - 3. Present and new communication utilities' distribution system and requirements.
  - 4. Work associated with equipment provided under other sections, or by Owner.

#### **1.5 COORDINATION**

- A. Coordinate all work per requirements of Division 1.
- B. See mechanical, plumbing, and architectural specifications, drawings, and submittals for work concerning the connection of electrical systems and any required controls.
- C. Contractor shall verify electrical characteristics and requirements (name plate data) of equipment furnished by others for proper coordination and equipment operation. Contractor shall confirm requirements of final equipment furnished by others and shall select associated electrical devices and materials accordingly. Before any work is installed, and before any equipment is purchased, the Contractor shall carefully inspect specifications and plans for every trade and job condition, and any lack of coordination between his work, the plans, specifications, or job conditions, shall be immediately reported to the Architect/Engineer in writing.
- D. Contractor shall coordinate equipment connection requirements with approved equipment submittals, prior to rough-in.
- E. Coordinate arrangement, mounting, and support of electrical equipment;
  - 1. To allow maximum possible headroom unless specific mounting heights that reduce headroom are indicated.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

2. To provide for ease of disconnecting the equipment with minimum interference to other installations.
  3. To allow right of way for piping and conduit installed at required slope.
  4. So connecting raceways, cables and wireways will be clear of obstructions and of the working and access space of other equipment.
- F. Coordinate installation of required supporting devices and set sleeves in cast-in-place concrete, masonry walls, and other structural components as they are constructed.
- G. Coordinate location of access panels and doors for electrical items that are behind finished surfaces or otherwise concealed.
- H. Coordinate sleeve selection and application with selection and application of firestopping.

## **PART 2 - PRODUCTS**

### **2.1 GENERAL REQUIREMENTS**

- A. When two or more items of the same material or equipment are required, they shall be of the same manufacturer. Product manufacturer uniformity does not apply to raw materials, bulk materials, wire, conduit, fittings, sheet metal, steel bar stock, welding rods, solder, fasteners, motors for dissimilar equipment units, and similar items in Work, except as otherwise indicated.
- B. Provide products compatible within systems, with interconnected systems, and with other connected items.
- C. Products shall be provided with permanent operational data nameplate for each item of power operated equipment, indicating manufacturer, product name, model number, serial number, capacity, operating and power characteristics, labels of tested compliances, and similar essential data. Locate nameplate in an accessible location.

### **2.2 PRODUCT OPTIONS AND SUBSTITUTIONS**

- A. Options and Substitutions shall be done per Division 1 instructions.
- B. All product substitutions shall include any incurred costs by the Contractor, any sub-contractor, other trades, Owner, or Owner's consultants. No increase in cost or contract shall be allowed for modifications or corrections, due to approval of Contractor requested changes or substitutions.

### **2.3 SUBMITTALS FOR ELECTRICAL ITEMS**

- A. Submit per Division 1 specification requirements.
- B. Electrical equipment and material submittals shall include a clear item description. Catalog numbers only, are not acceptable.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- C. Catalog pages must be clearly marked to indicate the exact product being proposed, with all necessary accessories and options identified and selected. Pages including multiple products or options, where selections are not clearly indicated, may be rejected for re-submittal.

## **2.4 DELIVERY, STORAGE AND HANDLING**

- A. Deliver products and materials to project site with proper identification, including; names, model numbers, types, grades, compliance labels, and similar information needed for distinct identifications; adequately packaged and protected to prevent damage during shipment, storage, and handling.
- B. Store equipment and materials at the site unless off-site storage is authorized in writing. Protect stored equipment and materials from damage.
- C. Coordinate deliveries of electrical materials and equipment to minimize construction site congestion. Limit each shipment of materials and equipment to the items and quantities needed for smooth and efficient flow of installations.

## **PART 3 - EXECUTION**

### **3.1 COMMON REQUIREMENTS FOR ELECTRICAL INSTALLATION**

- A. Comply with NECA 1.
- B. Measure indicated mounting heights to bottom of unit for suspended items and to center of unit for wall-mounting items.
- C. Headroom Maintenance: If mounting heights or other location criteria are not indicated, arrange and install components and equipment to provide maximum possible headroom consistent with these requirements.
- D. Coordinate electrical equipment and materials installation with other building components.
- E. Equipment: Install to facilitate service, maintenance, and repair or replacement of components of both electrical equipment and other nearby installations. Connect in such a way as to facilitate future disconnecting with minimum interference with other items in the vicinity.
- F. Right of Way: Give to piping systems installed at a required slope.
- G. Verify all dimensions with field measurements.
- H. Arrange for chases, slots, and openings in other building components to all for electrical installations.
- I. Sequence, coordinate, and integrate installations of electrical materials and equipment for efficient flow of work.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- J. Coordinate the cutting and patching of building components to accommodate the installation of electrical equipment and materials.
- K. Install electrical equipment for compliance with code-required clearances. Contractor shall be responsible for identification of necessary clearance issues at the time products are submitted for approval.
- L. Coordinate the installation of electrical materials and equipment above ceilings with suspension system, mechanical equipment, piping, ductwork, and other systems and structural components.
- M. Drawings for work under Divisions 26, 27, and 28 are diagrammatic and are intended to convey the scope of work and indicate the general arrangement of conduit, boxes, equipment, lighting fixtures, and other work included in the contract.
  - 1. See details and schedules on drawings and specifications for meanings of abbreviations, additional requirements and information. Check civil, structural, mechanical, plumbing, and other electrical drawings for scale, space limitations, beams, door swings, windows, ductwork, coordination, and additional information, and report any discrepancies or conflicts to Architect/Engineer prior to submitting bid.
  - 2. The Contractor shall install and completely wire all equipment furnished by others (FBO) in accordance with the manufacturer's wiring diagrams and recommendations, necessary for a complete and operational installation. Contractor shall verify and coordinate electrical characteristics and requirements of FBO equipment prior to ordering associated equipment and materials, or rough-in of boxes, conduit, and wiring, to avoid conflicts.

### **3.2 RECORD DOCUMENTS**

- A. Provide Record Documents as required by the Section and Division 1 specifications.
- B. Mark drawings to indicate revisions to conduit size and location, both exterior and interior, actual equipment locations, and concealed equipment dimensioned to column lines or wall face. Record distribution and branch electrical circuitry, fuse and circuit breaker size and arrangements, and support and hanger details.
- C. Accurately mark locations of underground and under floor electrical conduits and conductors. Provide dimensions from fixed points of reference.
- D. Record Change Orders, Supplemental Instructions, or Field Directives, that modify work shown in contract documents, on drawings and in specifications.

### **3.3 OPERATION AND MAINTENANCE DATA**

- A. Procedures and requirements for preparation and submittal of maintenance manuals shall be done as required by Division 1.
- B. In addition to the information required by Division 1 specifications, include the following information when requested:

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

1. Description of function, normal operating characteristics and limitations, performance curves, engineering data and tests, and complete nomenclature and commercial numbers of all replaceable parts.
2. Manufacturers' printed operating procedures to include start-up, break-in, and routine and normal operating instructions.
3. Maintenance procedures for routine preventative maintenance and trouble-shooting, disassembly, repair, and reassembly, aligning and adjusting instructions.

### **3.4 WARRANTIES**

- A. Procedures and submittal requirements for warranties shall be done as directed by the Division 1 specifications, and as pertains to specific warranties. See individual specification sections for warranty requirements that exceed 1 year or are otherwise distinct.
- B. Compile and assemble warranties specified for Division 26 into a file folder labeled for this project.
- C. Provide complete warranty information for each product or equipment item, to include date of beginning of warranty or bond, duration of warranty or bond, and names, addresses, and telephone numbers and procedures for filing a claim and obtaining warranty services.
- D. Except as modified in individual specification sections:
  1. All materials and workmanship shall be warranted for 1 year.
  2. All warranties begin upon official date of substantial completion, allowing Owner's beneficial use of the work.
  3. Warranted materials shall be provided for replacement within 30 days of notice of failure to Contractor (or as specifically allowed by Owner's Representative).
  4. The first year of warranted items shall include materials and labor for replacement/repair and shall be responded to within 10 working days of notice of problem to Contractor. If the issue is of a severe nature, with the use of the facility at risk, response shall be within 2 calendar days.
  5. Warranty material replacements shall not diminish the Owner's stock of extra items.

### **3.5 CLEANING**

- A. General requirements for final cleaning shall be done as required by Division 1.
- B. Maintain clean work spaces with daily cleanup of all occupied areas.

### **3.6 TESTING**

- A. Provide testing and documented results as required by each specification section or applicable codes, laws, and ordinances.
- B. Provide testing and documented results as required by manufacturer(s) for certification or warranty.

**END OF SECTION 26 0500**

## SECTION 26 0519

### LOW-VOLTAGE ELECTRICAL POWER CONDUCTORS AND CABLES

#### PART 1 - GENERAL

##### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

##### 1.2 SUMMARY

- A. This Section includes the following:
  - 1. Building wires and cables rated 600 V and less.
  - 2. Connectors, splices, and terminations rated 600 V and less.

##### 1.3 DEFINITIONS

- A. EPDM: Ethylene-propylene-diene terpolymer rubber.
- B. NBR: Acrylonitrile-butadiene rubber.

##### 1.4 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Qualification Data: For testing agency.
- C. Field quality-control test reports.

##### 1.5 QUALITY ASSURANCE

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- B. Comply with NFPA 70.

#### PART 2 - PRODUCTS

##### 2.1 CONDUCTORS AND CABLES

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

1. Alcan Products Corporation; Alcan Cable Division.
2. American Insulated Wire Corp.; a Leviton Company.
3. General Cable Corporation.
4. Senator Wire & Cable Company.
5. Southwire Company.

- B. Copper Conductors: Comply with NEMA WC 70.
- C. Conductor Insulation: Comply with NEMA WC 70 for Types THHN-THWN.
- D. Multiconductor Cable: Not permitted.

## **2.2 CONNECTORS AND SPLICES**

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
1. AFC Cable Systems, Inc.
  2. Hubbell Power Systems, Inc.
  3. O-Z/Gedney; EGS Electrical Group LLC.
  4. 3M; Electrical Products Division.
  5. Tyco Electronics Corp.
- B. Description: Factory-fabricated connectors and splices of size, ampacity rating, material, type, and class for application and service indicated.

## **PART 3 - EXECUTION**

### **3.1 CONDUCTOR MATERIAL APPLICATIONS**

- A. Feeders: Copper. Stranded for all conductors.
- B. Branch Circuits: Copper. Stranded for all conductors.

### **3.2 CONDUCTOR INSULATION AND MULTICONDUCTOR CABLE APPLICATIONS AND WIRING METHODS**

- A. Service Entrance: Type THHN-THWN, single conductors in raceway.
- B. Exposed Feeders: Type THHN-THWN, single conductors in raceway.
- C. Exposed Branch Circuits: Type THHN-THWN, single conductors in raceway. Homerun conductors shall be minimum #10 AWG.



OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- D. Branch Circuits Concealed in Ceilings, Walls, and Partitions: Type THHN-THWN, single conductors in raceway. Metal-clad multi-conductor cable is not permitted. Homerun conductors shall be minimum #10 AWG. Metal-clad, multi-conductor cable (MC) is not permitted without specific documented allowance.
- E. Cord Drops and Portable Appliance Connections: Type SO, hard service cord with stainless-steel, wire-mesh, strain relief device at terminations to suit application.
- F. Class 1 Control Circuits: Type THHN-THWN, in raceway.
- G. Class 2 Control Circuits: Type THHN-THWN, in raceway.

### **3.3 INSTALLATION OF CONDUCTORS AND CABLES**

- A. Conceal cables in finished walls, ceilings, and floors, unless otherwise indicated.
- B. Use manufacturer-approved pulling compound or lubricant where necessary; compound used must not deteriorate conductor or insulation. Do not exceed manufacturer's recommended maximum pulling tensions and sidewall pressure values.
- C. Use pulling means, including fish tape, cable, rope, and basket-weave wire/cable grips that will not damage cables or raceway.

### **3.4 CONNECTIONS**

- A. Tighten electrical connectors and terminals according to manufacturer's published torque-tightening values. If manufacturer's torque values are not indicated, use those specified in UL 486A and UL 486B.
- B. Make splices and taps that are compatible with conductor material and that possess equivalent or better mechanical strength and insulation ratings than un-spliced conductors.
  - 1. Use oxide inhibitor in each splice and tap conductor for aluminum conductors.
- C. Wiring at Outlets: Install conductor at each outlet, with at least 6 inches of slack.

### **3.5 FIELD QUALITY CONTROL**

- A. Perform tests and inspections.
- B. Tests and Inspections:
  - 1. Perform each visual and mechanical inspection and electrical test stated in NETA Acceptance Testing Specification. Certify compliance with test parameters.
- C. Remove and replace damaged or malfunctioning materials/units and retest.

**END OF SECTION 26 0519**

**SECTION 26 0526**

**GROUNDING AND BONDING FOR ELECTRICAL SYSTEMS**

**PART 1 - GENERAL**

**1.1 RELATED DOCUMENTS**

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

**1.2 SUMMARY**

- A. Section includes grounding and bonding systems and equipment.

**1.3 PRODUCT SUBMITTALS**

- A. Submit product information for review, including the following:
  - 1. Ground rods.
  - 2. Bonding Fittings, Connectors, and Accessories.
  - 3. Grounding conductors.

**1.4 CLOSEOUT SUBMITTALS**

- A. Operation and Maintenance Data: For grounding to include in emergency, operation, and maintenance manuals.
  - 1. In addition to items specified in Section 01 78 23 "Operation and Maintenance Data," include the following:
    - a. Plans showing as-built, dimensioned locations of grounding features, including the following:
      - 1) Ground rods.
      - 2) Bonding Fittings, Connectors, and Accessories.
      - 3) Grounding conductors.

**PART 2 - PRODUCTS**

**2.1 SYSTEM DESCRIPTION**

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- B. Comply with UL 467 for grounding and bonding materials and equipment.

## 2.2 MANUFACTURERS

- A. Provide products that meet project requirements from the following, or other approved manufacturers:
1. Appleton
  2. Arlington
  3. Bridgeport
  4. Burndy
  5. Erico
  6. Greaves
  7. Harger
  8. ILSCO
  9. Panduit
  10. RACO
  11. Thomas & Betts

## 2.3 CONDUCTORS

- A. Insulated Conductors: Copper wire or cable insulated for 600 V unless otherwise required by applicable Code or authorities having jurisdiction.
- B. Bare Copper Conductors:
1. Stranded Conductors: ASTM B 8.
  2. Sizes and types of conductors in four subparagraphs below are typical examples. 28-kcmil bonding cable in "Bonding Cable" Subparagraph below is slightly larger than No. 6 AWG.
  3. Bonding Cable: 28 kcmil, 14 strands of No. 17 AWG conductor, 1/4 inch in diameter.
  4. Bonding Conductor: No. 4 or No. 6 AWG, stranded conductor.
  5. Bonding Jumper: Copper tape, braided conductors terminated with copper ferrules; 1-5/8 inches wide and 1/16 inch thick.

## 2.4 CONNECTORS

- A. Listed and labeled by an NRTL acceptable to authorities having jurisdiction for applications in which used and for specific types, sizes, and combinations of conductors and other items connected.
- B. Welded Connectors: Exothermic-welding kits of types recommended by kit manufacturer for materials being joined and installation conditions.
- C. Beam Clamps: Mechanical type, terminal, ground wire access from four directions, with dual, tin-plated or silicon bronze bolts.
- D. Cable-to-Cable Connectors: Compression type, copper or copper alloy.
- E. Conduit Hubs: Mechanical type, terminal with threaded hub.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- F. Ground Rod Clamps: Exothermic or one-shot compression type, copper or copper alloy, terminal with hex head bolt.
- G. Straps: Solid copper, copper lugs. Rated for 600 A.
- H. U-Bolt Clamps: Mechanical type, copper or copper alloy, terminal listed for direct burial.
- I. Water Pipe Clamps:
  - 1. Mechanical type, two pieces with zinc-plated bolts.
    - a. Material: Tin-plated aluminum.
    - b. Listed for direct burial.
  - 2. U-bolt type with malleable-iron clamp and copper ground connector.

## **2.5 GROUNDING ELECTRODES**

- A. Ground Rods: Copper-clad steel; 3/4 inch by 10 feet.

## **PART 3 - EXECUTION**

### **3.1 APPLICATIONS**

- A. Underground Grounding Conductors: Install bare tinned-copper conductor, No. 4/0 AWG minimum.
  - 1. Bury at least 24 inches below grade.
  - 2. Duct-Bank Grounding Conductor: Bury 12 inches above duct bank when indicated as part of duct-bank installation.
- B. Conductor Terminations and Connections:
  - 1. Pipe and Equipment Grounding Conductor Terminations: Bolted connectors.
  - 2. Underground Connections: Welded connectors.
  - 3. Connections to Structural Steel: Welded connectors.

### **3.2 GROUNDING AT THE SERVICE**

- A. Verify existing service entrance ground is compliant with NEC 250.
- B. Test ground resistance and record readings.
- C. Document grounding method with photos and identify ground location and components on As-Built markup plans.

### **3.3 GROUNDING UNDERGROUND DISTRIBUTION SYSTEM COMPONENTS**

- A. Comply with IEEE C2 grounding requirements (if existing grounding is insufficient).
- B. Grounding Handholes: Install a driven ground rod through handhole floor, close to wall, and set rod depth so 4 inches will extend above finished floor. If necessary, install ground rod before is placed and provide No. 1/0 AWG bare, tinned-copper conductor from ground rod. Protect ground rods passing through concrete floor with a double wrapping of pressure-sensitive insulating tape or heat-shrunk insulating sleeve from 2 inches above to 6 inches below concrete. Seal floor opening with waterproof, non-shrink grout.
- C. Pad-Mounted Transformers and Switches: Install two ground rods and ground ring around the pad. Ground pad-mounted equipment and noncurrent-carrying metal items associated with substations by connecting them to underground cable and grounding electrodes. Install tinned-copper conductor not less than No. 2 AWG for ground ring and for taps to equipment grounding terminals. Bury ground ring not less than 6 inches from the foundation.

### **3.4 EQUIPMENT GROUNDING**

- A. Install insulated equipment grounding conductors with all feeders and branch circuits.
- B. Install insulated equipment grounding conductors with the following items, in addition to those required by NFPA 70:
  - 1. Retain applicable subparagraphs below.
    - 2. Feeders and branch circuits.
    - 3. Lighting circuits.
    - 4. Receptacle circuits.
    - 5. Single-phase motor and appliance branch circuits.
    - 6. Three-phase motor and appliance branch circuits.
    - 7. Flexible raceway runs.
- C. Water Heater and Heat-Tracing Cables: Install a separate insulated equipment grounding conductor to each electric water heater and heat-tracing cable. Bond conductor to heater units, piping, connected equipment, and components.

### **3.5 FENCE GROUNDING**

- A. Fence Grounding: Install at maximum intervals of 40 feet except as follows:
  - 1. Gates and Other Fence Openings: Ground fence on each side of opening.
    - a. Bond metal gates to gate posts.

- b. Coordinate subparagraph below with Drawings for projects where intentional discontinuities are provided in metal-fencing conductivity to localize lightning effects to the vicinity of strokes.
  - c. Bond across openings, with and without gates, except at openings indicated as intentional fence discontinuities. Use No. 2 AWG wire and bury it at least 18 inches below finished grade.
- B. Fences Enclosing Electrical Power Distribution Equipment or Mechanical Equipment: Ground as required by IEEE C2 unless otherwise indicated.
- C. Grounding Method: At each grounding location, drive a grounding rod vertically until the top is 6 inches below finished grade. Connect rod to fence with No. 6 AWG conductor. Connect conductor to each fence component at grounding location.
- D. Bonding Method for Gates: Connect bonding jumper between gate post and gate frame.

### 3.6 INSTALLATION

- A. Grounding Conductors: Route along shortest and straightest paths possible unless otherwise indicated or required by Code. Avoid obstructing access or placing conductors where they may be subjected to strain, impact, or damage.
- B. Ground Rods: Drive rods until tops are 2 inches below finished floor or final grade unless otherwise indicated.
- 1. Interconnect ground rods with grounding electrode conductor below grade and as otherwise indicated. Make connections without exposing steel or damaging coating if any.
  - 2. Use exothermic welds for all below-grade connections.
  - 3. Retain subparagraph below if grounding installation requirements are not indicated on Drawings. Subparagraph exceeds NFPA 70 requirements.
  - 4. For grounding electrode system, install at least three rods spaced at least one-rod length from each other and located at least the same distance from other grounding electrodes, and connect to the service grounding electrode conductor.
- C. Bonding Straps and Jumpers: Install in locations accessible for inspection and maintenance except where routed through short lengths of conduit.
- 1. Bonding to Structure: Bond straps directly to basic structure, taking care not to penetrate any adjacent parts.
  - 2. Bonding to Equipment Mounted on Vibration Isolation Hangers and Supports: Install bonding so vibration is not transmitted to rigidly mounted equipment.
  - 3. Use exothermic-welded connectors for outdoor locations; if a disconnect-type connection is required, use a bolted clamp.

D. Grounding and Bonding for Piping:

1. Metal Water Service Pipe: Install insulated copper grounding conductors, in conduit, from building's main service equipment, or grounding bus, to main metal water service entrances to building. Connect grounding conductors to main metal water service pipes; use a bolted clamp connector or bolt a lug-type connector to a pipe flange by using one of the lug bolts of the flange. Where a dielectric main water fitting is installed, connect grounding conductor on street side of fitting. Bond metal grounding conductor conduit or sleeve to conductor at each end.
2. Water Meter Piping: Use braided-type bonding jumpers to electrically bypass water meters. Connect to pipe with a bolted connector.
3. Bond each aboveground portion of gas piping system downstream from equipment shutoff valve.

E. Bonding Interior Metal Ducts: Bond metal air ducts to equipment grounding conductors of associated fans, blowers, electric heaters, and air cleaners. Install tinned bonding jumper to bond across flexible duct connections to achieve continuity.

F. Connections: Make connections so possibility of galvanic action or electrolysis is minimized. Select connectors, connection hardware, conductors, and connection methods so metals in direct contact are galvanically compatible.

1. Use electroplated or hot-tin-coated materials to ensure high conductivity and to make contact points closer in order of galvanic series.
2. Make connections with clean, bare metal at points of contact.
3. Make aluminum-to-steel connections with stainless-steel separators and mechanical clamps.
4. Make aluminum-to-galvanized-steel connections with tin-plated copper jumpers and mechanical clamps.
5. Coat and seal connections having dissimilar metals with inert material to prevent future penetration of moisture to contact surfaces.

### 3.7 FIELD QUALITY CONTROL

A. Tests and Inspections:

1. After installing grounding system but before permanent electrical circuits have been energized, test for compliance with requirements.
2. Inspect physical and mechanical condition. Verify tightness of accessible, bolted, electrical connections with a calibrated torque wrench according to manufacturer's written instructions.
3. Test completed grounding system at each location where a maximum ground-resistance level is specified, at service disconnect enclosure grounding terminal, and at individual ground rods. Make tests at ground rods before any conductors are connected.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- a. Measure ground resistance no fewer than two full days after last trace of precipitation and without soil being moistened by any means other than natural drainage or seepage and without chemical treatment or other artificial means of reducing natural ground resistance.
  - b. Perform tests by fall-of-potential method or the attached rod technique according to IEEE 81.
  - c. Coordinate subparagraph below with "Informational Submittals" Article; revise to suit Project.
4. Prepare dimensioned Drawings locating each ground rod and ground-rod assembly, and other grounding electrodes. Identify each by letter in alphabetical order, and key to the record of tests and observations. Include the number of rods driven and their depth at each location, and include observations of weather and other phenomena that may affect test results. Describe measures taken to improve test results.
- B. Grounding system will be considered defective if it does not pass tests and inspections.
- C. Report measured ground resistances that exceed the following values:
1. See the Evaluations for discussion on appropriate ground-resistance values. Typical maximum permitted values are listed below for different grounding applications; retain applicable subparagraphs and revise to suit Project. Coordinate with requirements in Sections specifying equipment to be grounded.
  2. Power and Lighting Equipment or System with Capacity of 500 kVA and Less: 3 ohms.
  3. Power and Lighting Equipment or System with Capacity of 500 to 1000 kVA: 3 ohms.
  4. Power and Lighting Equipment or System with Capacity More Than 1000 kVA: 3 ohms.
  5. Substations and Pad-Mounted Equipment: 3 ohms.
- D. Excessive Ground Resistance: If resistance to ground exceeds specified values, notify Architect/Engineer promptly and include recommendations to reduce ground resistance.

**END OF SECTION 26 0526**



## SECTION 26 0529

### HANGERS AND SUPPORTS FOR ELECTRICAL SYSTEMS

#### PART 1 - GENERAL

##### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

##### 1.2 SUMMARY

- A. This Section includes the following:
  - 1. Hangers and supports for electrical equipment and systems.
  - 2. Construction requirements for concrete bases.

##### 1.3 DEFINITIONS

- A. EMT: Electrical metallic tubing.
- B. IMC: Intermediate metal conduit.
- C. RMC: Rigid metal conduit.

##### 1.4 PERFORMANCE REQUIREMENTS

- A. Design supports for multiple raceways capable of supporting combined weight of supported systems and its contents.
- B. Design equipment supports capable of supporting combined operating weight of supported equipment and connected systems and components.
- C. Rated Strength: Adequate in tension, shear, and pullout force to resist maximum loads calculated or imposed for this Project, with a minimum structural safety factor of five times the applied force.

##### 1.5 SUBMITTALS

- A. Product Data: For the following:
  - 1. Steel slotted support systems.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

## **1.6 QUALITY ASSURANCE**

- A. Welding: Qualify procedures and personnel according to AWS D1.1/D1.1M, "Structural Welding Code - Steel."
- B. Comply with NFPA 70.

## **1.7 COORDINATION**

- A. Coordinate size and location of all hangers and supports with other building systems.
- B. Coordinate installation of penetrations through any building component.

## **PART 2 - PRODUCTS**

### **2.1 SUPPORT, ANCHORAGE, AND ATTACHMENT COMPONENTS**

- A. Steel Slotted Support Systems: Comply with MFMA-4, factory-fabricated components for field assembly.
  - 1. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
    - a. Allied Tube & Conduit.
    - b. Cooper B-Line, Inc.; a division of Cooper Industries.
    - c. ERICO International Corporation.
    - d. GS Metals Corp.
    - e. Thomas & Betts Corporation.
    - f. Unistrut; Tyco International, Ltd.
    - g. Wesanco, Inc.
  - 2. Metallic Coatings: Hot-dip galvanized after fabrication and applied according to MFMA-4.
  - 3. Painted Coatings: Manufacturer's standard painted coating applied according to MFMA-5.
  - 4. Channel Dimensions: Selected for applicable load criteria.
- B. Raceway and Cable Supports: As described in NECA 1 and NECA 101.
- C. Conduit and Cable Support Devices: Steel and malleable-iron hangers, clamps, and associated fittings, designed for types and sizes of raceway or cable to be supported.
- D. Structural Steel for Fabricated Supports and Restraints: ASTM A 36/A 36M, steel plates, shapes, and bars; black and galvanized.
- E. Mounting, Anchoring, and Attachment Components: Items for fastening electrical items or their supports to building surfaces include the following:
  - 1. Verify suitability of fasteners in subparagraph below for use in lightweight concrete or concrete slabs less than 4 inches (100 mm) thick.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

2. Mechanical-Expansion Anchors: Insert-wedge-type, zinc-coated steel, for use in hardened portland cement concrete with tension, shear, and pullout capacities appropriate for supported loads and building materials in which used.
  - a. See Editing Instruction No. 1 in the Evaluations for cautions about naming manufacturers and products. Retain one of first two subparagraphs and list of manufacturers below. See Division 01 Section "Product Requirements."
  - b. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
    - 1) Cooper B-Line, Inc.; a division of Cooper Industries.
    - 2) Empire Tool and Manufacturing Co., Inc.
    - 3) Hilti Inc.
    - 4) ITW Ramset/Red Head; a division of Illinois Tool Works, Inc.
    - 5) MKT Fastening, LLC.
3. Concrete Inserts: Steel or malleable-iron, slotted support system units similar to MSS Type 18; complying with MFMA-4 or MSS SP-58.
4. Clamps for Attachment to Steel Structural Elements: MSS SP-58, type suitable for attached structural element.
5. Through Bolts: Structural type, hex head, and high strength. Comply with ASTM A 325.
6. Toggle Bolts: All-steel springhead type.
7. Hanger Rods: Threaded steel.

## **2.2 FABRICATED METAL EQUIPMENT SUPPORT ASSEMBLIES**

- A. Description: Welded or bolted, structural-steel shapes, shop or field fabricated to fit dimensions of supported equipment.

## **PART 3 - EXECUTION**

### **3.1 APPLICATION**

- A. Comply with NECA 1 and NECA 101 for application of hangers and supports for electrical equipment and systems except if requirements in this Section are stricter.
- B. Maximum Support Spacing and Minimum Hanger Rod Size for Raceway: Space supports for EMT, IMC, and RMC as scheduled in NECA 1, where its Table 1 lists maximum spacings less than stated in NFPA 70. Minimum rod size shall be 1/4 inch in diameter.
- C. Multiple Raceways or Cables: Install trapeze-type supports fabricated with steel slotted or other support system, sized so capacity can be increased by at least 25 percent in future without exceeding specified design load limits.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

1. Secure raceways and cables to these supports with two-bolt conduit clamps, single-bolt conduit clamps, or single-bolt conduit clamps using spring friction action for retention in support channel.
- D. Spring-steel clamps designed for supporting single conduits without bolts may be used for 1-1/2-inch and smaller raceways serving branch circuits and communication systems above suspended ceilings and for fastening raceways to trapeze supports.

### 3.2 SUPPORT INSTALLATION

- A. Comply with NECA 1 and NECA 101 for installation requirements except as specified in this Article.
- B. Raceway Support Methods: In addition to methods described in NECA 1, EMT, IMC, and RMC may be supported by openings through structure members, as permitted in NFPA 70.
- C. Strength of Support Assemblies: Where not indicated, select sizes of components so strength will be adequate to carry present and future static loads within specified loading limits. Minimum static design load used for strength determination shall be weight of supported components plus 200 lb.
- D. Mounting and Anchorage of Surface-Mounted Equipment and Components: Anchor and fasten electrical items and their supports to building structural elements by the following methods unless otherwise indicated by code:
  1. To Wood: Fasten with lag screws or through bolts.
  2. To New Concrete: Bolt to concrete inserts.
  3. To Masonry: Approved toggle-type bolts on hollow masonry units and expansion anchor fasteners on solid masonry units.
  4. To Existing Concrete: Expansion anchor fasteners.
  5. Retain first subparagraph below if powder-actuated devices are allowed. Consider deleting if Project contains both lightweight and standard-weight concrete or more than one thickness of concrete slab.
  6. To Steel: Welded threaded studs complying with AWS D1.1/D1.1M, with lock washers and nuts, Beam clamps (MSS Type 19, 21, 23, 25, or 27) complying with MSS SP-69, or Spring-tension clamps.
  7. To Light Steel: Sheet metal screws.
  8. Items Mounted on Hollow Walls and Nonstructural Building Surfaces: Mount cabinets, panelboards, disconnect switches, control enclosures, pull and junction boxes, transformers, and other devices on slotted-channel racks attached to substrate.
- E. Drill holes for expansion anchors in concrete at locations and to depths that avoid reinforcing bars.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

### **3.3 INSTALLATION OF FABRICATED METAL SUPPORTS**

- A. Cut, fit, and place miscellaneous metal supports accurately in location, alignment, and elevation to support and anchor electrical materials and equipment.
- B. Field Welding: Comply with AWS D1.1/D1.1M.

### **3.4 PAINTING**

- A. Touchup: Clean field welds and abraded areas of shop paint. Paint exposed areas immediately after erecting hangers and supports. Use same materials as used for shop painting. Comply with SSPC-PA 1 requirements for touching up field-painted surfaces.
  - 1. Apply paint by brush or spray to provide minimum dry film thickness of 2.0 mils.
- B. Touchup: Comply with requirements in painting Sections for cleaning and touchup painting of field welds, bolted connections, and abraded areas of shop paint on miscellaneous metal.
- C. Galvanized Surfaces: Clean welds, bolted connections, and abraded areas and apply galvanizing-repair paint to comply with ASTM A 780.

**END OF SECTION 26 0529**

## SECTION 26 0533

### RACEWAY AND BOXES FOR ELECTRICAL SYSTEMS

#### PART 1 - GENERAL

##### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

##### 1.2 SUMMARY

- A. This Section includes raceways, fittings, boxes, enclosures, and cabinets for electrical wiring.

##### 1.3 DEFINITIONS

- A. EMT: Electrical metallic tubing.
- B. FMC: Flexible metal conduit.
- C. IMC: Intermediate metal conduit.
- D. LFMC: Liquidtight flexible metal conduit.
- E. RSC/RGC/RMC: Rigid steel conduit / Rigid galvanized conduit/Rigid metal conduit.
- F. PVC/RNC: Polyvinylchloride / Rigid nonmetallic conduit.

##### 1.4 QUALITY ASSURANCE

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- B. Comply with NFPA 70.

#### PART 2 - PRODUCTS

##### 2.1 METAL CONDUIT AND TUBING

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
  - 1. AFC Cable Systems, Inc.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

2. Alflex Inc.
  3. Allied Tube & Conduit; a Tyco International Ltd. Co.
  4. Anamet Electrical, Inc.; Anaconda Metal Hose.
  5. Electri-Flex Co.
  6. Manhattan/CDT/Cole-Flex.
  7. Maverick Tube Corporation.
  8. O-Z Gedney; a unit of General Signal.
  9. Wheatland Tube Company.
- B. Rigid Steel Conduit: ANSI C80.1.
- C. IMC: ANSI C80.6.
- D. EMT: ANSI C80.3.
- E. FMC: Zinc-coated steel or aluminum.
- F. LFMC: Flexible steel conduit with PVC jacket.
- G. Fittings for Conduit (Including all Types and Flexible and Liquidtight), EMT, and Cable: NEMA FB 1; listed for type and size raceway with which used, and for application and environment in which installed.
1. Conduit Fittings for Hazardous (Classified) Locations: Comply with UL 886.
  2. Fittings for EMT: Steel, set-screw or compression type.

## **2.2 NONMETALLIC CONDUIT AND TUBING**

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
1. AFC Cable Systems, Inc.
  2. Anamet Electrical, Inc.; Anaconda Metal Hose.
  3. CANTEX Inc.
  4. CertainTeed Corp.; Pipe & Plastics Group.
  5. Condux International, Inc.
  6. Electri-Flex Co.
  7. Lamson & Sessions; Carlon Electrical Products.
  8. Manhattan/CDT/Cole-Flex.
  9. RACO; Hubbell Co.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

10. Thomas & Betts Corp.

B. RNC: NEMA TC2, Type EPC-40-PVC, unless otherwise indicated.

C. Fittings for RNC: NEMA TC 3; match to conduit or tubing type and material.

### **2.3 METAL WIREWAYS**

A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:

1. Cooper B-Line, Inc.
2. Hoffman.
3. Square D; Schneider Electric.

B. Description: Sheet metal sized and shaped as indicated, NEMA 250, Type 1, unless otherwise indicated.

C. Fittings and Accessories: Include couplings, offsets, elbows, expansion joints, adapters, hold-down straps, end caps, and other fittings to match and mate with wireways as required for complete system.

D. Wireway Covers: Screw-cover type unless specifically noted otherwise on the drawings.

E. Finish: Manufacturer's standard enamel finish.

### **2.4 SURFACE RACEWAYS**

A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:

1. Hubbell
2. Panduit
3. Thomas & Betts Corp.
4. Wiremold Company; Legrand.

B. Surface metal raceways: Galvanized steel with snap-on covers. Manufacturer's standard enamel finish color with final field applied paint color selected by Owner to match mounting surface.

### **2.5 BOXES, ENCLOSURES, AND CABINETS**

A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:

1. Cooper Crouse-Hinds; Div. of Cooper Industries, Inc.



OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

2. EGS/Appleton Electric.
  3. Erickson Electrical Equipment Company.
  4. Hoffman.
  5. Hubbell Incorporated; Killark Electric Manufacturing Co. Division.
  6. O-Z/Gedney; a unit of General Signal.
  7. RACO; a Hubbell Company.
  8. Robroy Industries, Inc.; Enclosure Division.
  9. Scott Fetzer Co.; Adalet Division.
  10. Spring City Electrical Manufacturing Company.
  11. Thomas & Betts Corporation.
  12. Woodhead, Daniel Company; Woodhead Industries, Inc. Subsidiary.
- B. Sheet Metal Outlet and Device Boxes: NEMA OS 1.
- C. Small Sheet Metal Pull and Junction Boxes: NEMA OS 1.
- D. Hinged-Cover Enclosures: NEMA 250, Type 1, with continuous-hinge cover with flush latch, unless otherwise indicated.
1. Metal Enclosures: Steel, finished inside and out with manufacturer's standard enamel.

### **PART 3 - EXECUTION**

#### **3.1 RACEWAY APPLICATION**

- A. Outdoors: Apply raceway products as specified below, unless otherwise indicated:
1. Exposed Conduit: Rigid steel or IMC conduit.
  2. Concealed Conduit, Aboveground: RNC, Type EPC-40-PVC.
  3. Connection to Vibrating Equipment (Including Transformers and Hydraulic, Pneumatic, Electric Solenoid, or Motor-Driven Equipment): LFMC.
  4. Boxes and Enclosures, Aboveground: NEMA 250, Type 3R.
- B. Comply with the following indoor applications, unless otherwise indicated:
1. Exposed, Not Subject to Physical Damage: EMT.
  2. Exposed, Not Subject to Severe Physical Damage: EMT.
  3. Concealed in Ceilings and Interior Walls and Partitions: EMT.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

4. Connection to Vibrating Equipment (Including Transformers and Hydraulic, Pneumatic, Electric Solenoid, or Motor-Driven Equipment): FMC, except use LFMC in damp, oily, or wet locations.
  5. Damp or Wet Locations: Rigid steel conduit or IMC.
  6. Raceways for Communications Cable in Spaces Used for Environmental Air: EMT.
  7. Raceways for Concealed General Purpose Distribution of Low-Voltage and Communications Cable: EMT.
  8. Boxes and Enclosures: NEMA 250, Type 1, except use NEMA 250, Type 4, nonmetallic in damp or wet locations.
- C. Minimum Raceway Size: 3/4-inch trade size.
- D. Raceway Fittings: Compatible with raceways and suitable for use and location.
1. Rigid and Intermediate Steel Conduit: Use threaded rigid steel conduit fittings, unless otherwise indicated.

### 3.2 INSTALLATION

- A. Comply with NECA 1 for installation requirements applicable to products specified in Part 2 except where requirements on Drawings or in this Article are stricter.
- B. Keep raceways at least 6 inches away from parallel runs of flues and steam or hot-water pipes. Install horizontal raceway runs above water and steam piping.
- C. Complete raceway installation before starting conductor installation.
- D. Arrange stub-ups so curved portions of bends are not visible above the finished slab.
- E. Install no more than the equivalent of three 90-degree bends in any conduit run except for communications conduits, for which fewer bends are allowed.
- F. Conceal conduit and EMT within finished walls, ceilings, and floors, unless otherwise indicated.
- G. Raceway Terminations at locations subject to moisture or vibration: Use insulating bushings to protect conductors, including conductors smaller than No. 4 AWG.
- H. Install pull wires in empty raceways. Use polypropylene or monofilament plastic line with not less than 200-lb tensile strength. Leave at least 12 inches of slack at each end of pull wire.
- I. Flexible Conduit Connections: Use maximum of 72 inches of flexible conduit for recessed and semi-recessed lighting fixtures, equipment subject to vibration, noise transmission, or movement; and for transformers and motors.
  1. Use LFMC in all damp or wet location applications in this scope of work where the conduit is exposed.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

### **3.3 PROTECTION**

- A. Provide final protection and maintain conditions that ensure coatings, finishes, and cabinets are without damage or deterioration at time of Substantial Completion.
  - 1. Repair damage to galvanized finishes with zinc-rich paint recommended by manufacturer.
  - 2. Repair damage to paint finishes with matching touchup coating recommended by manufacturer.

**END OF SECTION 26 0533**

## SECTION 26 0553

### IDENTIFICATION FOR ELECTRICAL SYSTEMS

#### PART 1 - GENERAL

##### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

##### 1.2 SUMMARY

- A. This Section includes the following:
  - 1. Identification for raceway.
  - 2. Identification for conductors and communication and control cable.
  - 3. Equipment identification labels.
  - 4. Wiring device circuit identification labels.
  - 5. Miscellaneous identification products.

##### 1.3 QUALITY ASSURANCE

- A. Comply with NFPA 70.
- B. Comply with 29 CFR 1910.145.

##### 1.4 COORDINATION

- A. Coordinate identification names, abbreviations, colors, and other features with requirements in the Contract Documents, Shop Drawings, manufacturer's wiring diagrams, and the Operation and Maintenance Manual, and with those required by codes, standards, and 29 CFR 1910.145. Use consistent designations throughout Project.
- B. Coordinate installation of identifying devices with completion of covering and painting of surfaces where devices are to be applied.
- C. Coordinate installation of identifying devices with location of access panels and doors.
- D. Install identifying devices before installing acoustical ceilings and similar concealment.

#### PART 2 - PRODUCTS

##### 2.1 EQUIPMENT IDENTIFICATION LABELS

- A. Self-Adhesive, Engraved, Laminated Acrylic or Melamine Label: Adhesive backed, with white letters on a dark-gray background. Minimum letter height shall be 1/2 inch for equipment name and 5/32 inch for additional informational text.
- B. See drawings for specific identification requirements for panelboards and related equipment.

## **2.2 WIRING DEVICE LABELS**

- A. Embossed, clear adhesive tape, with 1/4" high black (depending on cover plate color selection) lettering with circuit number and panel identification for electrical devices (receptacles and switches). Labels shall be located on the face of the device cover plate, unless noted otherwise.
- B. All labels shall be machine printed.

## **2.3 MISCELLANEOUS IDENTIFICATION PRODUCTS**

- A. Cable Ties: Fungus-inert, self-extinguishing, 1-piece, self-locking, Type 6/6 nylon cable ties.
  - 1. Minimum Width: 3/16 inch.
  - 2. Tensile Strength: 50 lb, minimum.
  - 3. Temperature Range: Minus 40 to plus 185 deg F.
  - 4. Color: Black, except where used for color-coding.
- B. Fasteners for Labels and Signs: Self-tapping, stainless-steel screws or stainless-steel machine screws with nuts and flat and lock washers.

## **PART 3 - EXECUTION**

### **3.1 APPLICATION**

- A. Power-Circuit Conductor Identification: For primary and secondary conductors No. 1/0 AWG and larger in vaults, pull and junction boxes, manholes, and handholes use color-coding conductor tape marker tape. Identify source and circuit number of each set of conductors. For single conductor cables, identify phase in addition to the above.
- B. Branch-Circuit Conductor Identification: Where there are conductors for more than three branch circuits in same junction or pull box, use color-coding conductor tape. Identify each ungrounded conductor according to source and circuit number.
- C. Equipment Identification Labels: On each unit of equipment, install unique designation label that is consistent with wiring diagrams, schedules, and Operation and Maintenance Manual. Apply labels to disconnect switches and protection equipment, central or master units, control panels, control stations, terminal cabinets, and racks of each system. Systems include power, lighting, control, communication, signal, monitoring, and alarm systems unless equipment is provided with its own identification.
  - 1. Labeling Instructions:
    - a. Indoor Equipment: Self-adhesive, engraved, laminated acrylic or melamine label. Unless otherwise indicated, provide a single line of text with 1/2-inch-high letters on 1-1/2-inch-high label; where 2 lines of text are required, use labels 2 inches high.
    - b. Elevated Components: Increase sizes of labels and letters to those appropriate for viewing from the floor.
  - 2. Equipment to Be Labeled:

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- a. Switchboards, Transformers, Panelboards, electrical cabinets, and enclosures.
- b. Equipment safety disconnect switches
- c. Equipment furnished by the Electrical Contractor

### 3.2 INSTALLATION

- A. Verify identity of each item before installing identification products.
- B. Location: Install identification materials and devices at locations for most convenient viewing without interference with operation and maintenance of equipment.
- C. Apply identification materials to surfaces that require finish after completing finish work.
- D. Conduit/raceway color system identification.
  1. System Identification Color for surface wireway: Each color band shall completely wrap outer portion of raceway cover. Place adjacent bands of multiple-color markings in contact, side by side, where wireway is used for more than one system. Locate bands at changes in direction, at penetrations of walls and floors, at 50-foot maximum intervals in straight runs, and at 25-foot maximum intervals in congested areas.
  2. System Identification Color for conduit:
    - a. Provide red colored anodized conduit, where conduit is used for new fire alarm system cabling.
    - b. Provide blue colored anodized conduit, where conduit is used for new or rerouted data system cabling.
    - c. Provide orange colored anodized conduit for all new fiber optic cabling.
    - d. Provide white colored anodized conduit, where conduit is used for new or rerouted control systems cabling.
- E. Color-Coding for Phase and Voltage Level Identification, 600 V and Less: Use the colors listed below for ungrounded service, feeder, and branch-circuit conductors.
  1. Color shall be factory applied or, for sizes larger than No. 10 AWG if authorities having jurisdiction permit, field applied.
  2. Colors for 208/120-V Circuits:
    - a. Phase A: Black.
    - b. Phase B: Red.
    - c. Phase C: Blue.
  3. Colors for 480/277-V Circuits:
    - a. Phase A: Brown
    - b. Phase B: Orange
    - c. Phase C: Yellow
  4. Field-Applied, Color-Coding Conductor Tape: Apply in half-lapped turns for a minimum distance of 6 inches from terminal points and in boxes where splices or taps are made. Apply last two turns of tape with no tension to prevent possible unwinding. Locate bands to avoid obscuring factory cable markings.

**END OF SECTION 26 0553**

## SECTION 26 0572

### OVERCURRENT PROTECTIVE DEVICE SHORT-CIRCUIT STUDY

#### PART 1 - GENERAL

##### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

##### 1.2 SUMMARY

- A. Section includes a computer-based, fault-current study to determine the minimum interrupting capacity of circuit protective devices.

##### 1.3 DEFINITIONS

- A. Existing to Remain: Existing items of construction that are not to be removed and that are not otherwise indicated to be removed, removed and salvaged, or removed and reinstalled.
- B. One-Line Diagram: A diagram which shows, by means of single lines and graphic symbols, the course of an electric circuit or system of circuits and the component devices or parts used therein.
- C. Protective Device: A device that senses when an abnormal current flow exists and then removes the affected portion from the system.
- D. SCCR: Short-circuit current rating.
- E. Service: The conductors and equipment for delivering electric energy from the serving utility to the wiring system of the premises served.

##### 1.4 ACTION SUBMITTALS

- A. Submit the following after the approval of system protective devices submittals. Submittals shall be in digital form.
  - 1. Short-circuit study input data, including completed computer program input data sheets.
  - 2. Short-circuit study and equipment evaluation report; signed, dated, and sealed by a qualified professional engineer.
    - a. Submit study report for action prior to receiving final approval of the distribution equipment submittals. If formal completion of studies will cause delay in equipment manufacturing, obtain approval from Architect for preliminary submittal of sufficient

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

study data to ensure that the selection of devices and associated characteristics is satisfactory.

- b. Revised single-line diagram, reflecting field investigation results and results of short-circuit study.

## 1.5 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For Short-Circuit Study Software Developer.
- B. Product Certificates: For short-circuit study software, certifying compliance with IEEE 399.

## 1.6 QUALITY ASSURANCE

- A. Studies shall use computer programs that are distributed nationally and are in wide use. Software algorithms shall comply with requirements of standards and guides specified in this Section. Manual calculations are unacceptable.
- B. Short-Circuit Study Software Developer Qualifications: An entity that owns and markets computer software used for studies, having performed successful studies of similar magnitude on electrical distribution systems using similar devices.
  1. The computer program shall be developed under the charge of a licensed professional engineer who holds IEEE Computer Society's Certified Software Development Professional certification.
- C. Short-Circuit Study Specialist Qualifications: Professional engineer in charge of performing the study and documenting recommendations, licensed in the state where Project is located. All elements of the study shall be performed under the direct supervision and control of this professional engineer.
- D. Field Adjusting Agency Qualifications: An independent agency, with the experience and capability to adjust overcurrent devices and to conduct the testing indicated, that is a member company of the International Electrical Testing Association or is a nationally recognized testing laboratory (NRTL) as defined by OSHA in 29 CFR 1910.7, and that is acceptable to authorities having jurisdiction.

## PART 2 - PRODUCTS

### 2.1 COMPUTER SOFTWARE

- A. Comply with IEEE 399 and IEEE 551.
- B. Analytical features of fault-current-study computer software program shall have the capability to calculate "mandatory," "very desirable," and "desirable" features as listed in IEEE 399.

### 2.2 SHORT-CIRCUIT STUDY REPORT CONTENTS

- A. Executive summary.



OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- B. Study descriptions, purpose, basis, and scope. Include case descriptions, definition of terms, and guide for interpretation of the computer printout.
- C. One-line diagram, showing the following:
  - 1. Protective device designations and ampere ratings.
  - 2. Cable size and lengths.
  - 3. Transformer kilovolt ampere (kVA) and voltage ratings.
  - 4. Motor designations and kVA ratings.
  - 5. Switchgear, switchboard, motor-control center, and panelboard designations.
- D. Comments and recommendations for system improvements, where needed.
- E. Protective Device Evaluation:
  - 1. Evaluate equipment and protective devices and compare to short-circuit ratings.
  - 2. Tabulations of circuit breaker, fuse, and other protective device ratings versus calculated short-circuit duties.
  - 3. For 600-V overcurrent protective devices, ensure that interrupting ratings are equal to or higher than calculated 1/2-cycle symmetrical fault current.
  - 4. For devices and equipment rated for asymmetrical fault current, apply multiplication factors listed in the standards to 1/2-cycle symmetrical fault current.
  - 5. Verify adequacy of phase conductors at maximum three-phase bolted fault currents; verify adequacy of equipment grounding conductors and grounding electrode conductors at maximum ground-fault currents. Ensure that short-circuit withstand ratings are equal to or higher than calculated 1/2-cycle symmetrical fault current.
- F. Short-Circuit Study Input Data: As described in "Power System Data" Article in the Evaluations.
- G. Short-Circuit Study Output:
  - 1. Low-Voltage Fault Report: Three-phase and unbalanced fault calculations, showing the following for each overcurrent device location:
    - a. Voltage.
    - b. Calculated fault-current magnitude and angle.
    - c. Fault-point X/R ratio.
    - d. Equivalent impedance.
  - 2. Momentary Duty Report: Three-phase and unbalanced fault calculations, showing the following for each overcurrent device location:
    - a. Voltage.
    - b. Calculated symmetrical fault-current magnitude and angle.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- c. Fault-point X/R ratio.
- d. Calculated asymmetrical fault currents:
  - 1) Based on fault-point X/R ratio.
  - 2) Based on calculated symmetrical value multiplied by 1.6.
  - 3) Based on calculated symmetrical value multiplied by 2.7.
- 3. Interrupting Duty Report: Three-phase and unbalanced fault calculations, showing the following for each overcurrent device location:
  - a. Voltage.
  - b. Calculated symmetrical fault-current magnitude and angle.
  - c. Fault-point X/R ratio.
  - d. No AC Decrement (NACD) ratio.
  - e. Equivalent impedance.
  - f. Multiplying factors for 2-, 3-, 5-, and 8-cycle circuit breakers rated on a symmetrical basis.
  - g. Multiplying factors for 2-, 3-, 5-, and 8-cycle circuit breakers rated on a total basis.

### **PART 3 - EXECUTION**

#### **3.1 EXAMINATION**

- A. Obtain all data necessary for the conduct of the study.
  - 1. Verify completeness of data supplied on the one-line diagram. Call any discrepancies to the attention of Architect.
  - 2. For equipment provided that is Work of this Project, use characteristics submitted under the provisions of action submittals and information submittals for this Project.
  - 3. For relocated equipment and that which is existing to remain, obtain required electrical distribution system data by field investigation and surveys, conducted by qualified technicians and engineers. The qualifications of technicians and engineers shall be qualified as defined by NFPA 70E.
- B. Gather and tabulate the following input data to support the short-circuit study. Comply with recommendations in IEEE 551 as to the amount of detail that is required to be acquired in the field. Field data gathering shall be under the direct supervision and control of the engineer in charge of performing the study, and shall be by the engineer or its representative who holds NETA ETT Level III certification or NICET Electrical Power Testing Level III certification.
  - 1. Product Data for Project's overcurrent protective devices involved in overcurrent protective device coordination studies. Use equipment designation tags that are consistent with electrical distribution system diagrams, overcurrent protective device submittals, input and output data, and recommended device settings.
  - 2. Obtain electrical power utility impedance at the service.
  - 3. Power sources and ties.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

4. For transformers, include kVA, primary and secondary voltages, connection type, impedance, X/R ratio, taps measured in percent, and phase shift.
5. For reactors, provide manufacturer and model designation, voltage rating, and impedance.
6. For circuit breakers and fuses, provide manufacturer and model designation. List type of breaker, type of trip, SCCR, current rating, and breaker settings.
7. Busway manufacturer and model designation, current rating, impedance, lengths, and conductor material.
8. Motor horsepower and NEMA MG 1 code letter designation.
9. Cable sizes, lengths, number, conductor material and conduit material (magnetic or nonmagnetic).

### 3.2 **SHORT-CIRCUIT STUDY**

- A. Perform study following the general study procedures contained in IEEE 399.
- B. Calculate short-circuit currents according to IEEE 551.
- C. Base study on the device characteristics supplied by device manufacturer.
- D. The extent of the electrical power system to be studied is indicated on Drawings.
- E. Begin short-circuit current analysis at the service, extending down to the system overcurrent protective devices as follows:
  1. To normal system low-voltage load buses where fault current is 10 kA or less.
- F. Study electrical distribution system from normal and alternate power sources throughout electrical distribution system for Project. Study all cases of system-switching configurations and alternate operations that could result in maximum fault conditions.
- G. The calculations shall include the ac fault-current decay from induction motors, synchronous motors and shall apply to low- and medium-voltage, three-phase ac systems. The calculations shall also account for the fault-current dc decrement, to address the asymmetrical requirements of the interrupting equipment.
  1. For grounded systems, provide a bolted line-to-ground fault-current study for areas as defined for the three-phase bolted fault short-circuit study.
- H. Calculate short-circuit momentary and interrupting duties for a three-phase bolted fault at each of the following:
  1. Electric utility's supply termination point.
  2. Incoming switchgear.
  3. Unit substation primary and secondary terminals.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

4. Low-voltage switchgear.
5. Control panels.
6. Branch circuit panelboards.
7. Disconnect switches.

### **3.3 ADJUSTING**

- A. Make minor modifications to equipment to be purchased, as required to accomplish compliance with short-circuit study.

### **3.4 DEMONSTRATION**

- A. Train Owner's operating and maintenance personnel in the use of study results.

**END OF SECTION 26 0572**

## SECTION 26 0573

### OVERCURRENT PROTECTIVE DEVICE COORDINATION STUDY

#### PART 1 - GENERAL

##### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

##### 1.2 SUMMARY

- A. Section includes computer-based, overcurrent protective device coordination studies to determine overcurrent protective devices and to determine overcurrent protective device settings for selective tripping.
  - 1. Study results shall be used to determine coordination of series-rated devices.

##### 1.3 DEFINITIONS

- A. Existing to Remain: Existing items of construction that are not to be removed and that are not otherwise indicated to be removed, removed and salvaged, or removed and reinstalled.
- B. One-Line Diagram: A diagram which shows, by means of single lines and graphic symbols, the course of an electric circuit or system of circuits and the component devices or parts used therein.
- C. Protective Device: A device that senses when an abnormal current flow exists and then removes the affected portion from the system.
- D. SCCR: Short-circuit current rating.
- E. Service: The conductors and equipment for delivering electric energy from the serving utility to the wiring system of the premises served.

##### 1.4 ACTION SUBMITTALS

- A. Product Data: For computer software program to be used for studies.
- B. Other Action Submittals: Submit the following after the approval of system protective devices submittals. Submittals shall be in digital form.
  - 1. Coordination-study input data, including completed computer program input data sheets.
  - 2. Study and equipment evaluation reports.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

3. Overcurrent protective device coordination study report; signed, dated, and sealed by a qualified professional engineer.
  - a. Submit study report for action prior to receiving final approval of the distribution equipment submittals. If formal completion of studies will cause delay in equipment manufacturing, obtain approval from Architect for preliminary submittal of sufficient study data to ensure that the selection of devices and associated characteristics is satisfactory.

#### **1.5 INFORMATIONAL SUBMITTALS**

- A. Qualification Data: For Coordination Study Software Developer.
- B. Product Certificates: For overcurrent protective device coordination study software, certifying compliance with IEEE 399.

#### **1.6 CLOSEOUT SUBMITTALS**

- A. Operation and Maintenance Data: For the overcurrent protective devices to include in emergency, operation, and maintenance manuals.
  1. In addition to items specified in Section 01 78 23 "Operation and Maintenance Data," include the following:
    - a. The following parts from the Protective Device Coordination Study Report:
      - 1) One-line diagram.
      - 2) Protective device coordination study.
      - 3) Time-current coordination curves.
    - b. Power system data.

#### **1.7 QUALITY ASSURANCE**

- A. Studies shall use computer programs that are distributed nationally and are in wide use. Software algorithms shall comply with requirements of standards and guides specified in this Section. Manual calculations are unacceptable.
- B. Coordination Study Software Developer Qualifications: An entity that owns and markets computer software used for studies, having performed successful studies of similar magnitude on electrical distribution systems using similar devices.
  1. The computer program shall be developed under the charge of a licensed professional engineer who holds IEEE Computer Society's Certified Software Development Professional certification.

## **PART 2 - PRODUCTS**

### **2.1 COMPUTER SOFTWARE DEVELOPERS**

#### **A. Software Developers:**

1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
  - a. CGI CYME.
  - b. EDSA Micro Corporation.
  - c. ESA Inc.
  - d. Operation Technology, Inc.
  - e. Power Analytics, Corporation.
  - f. SKM Systems Analysis, Inc.

#### **B. Comply with IEEE 242 and IEEE 399.**

#### **C. Analytical features of device coordination study computer software program shall have the capability to calculate "mandatory," "very desirable," and "desirable" features as listed in IEEE 399.**

#### **D. Computer software program shall be capable of plotting and diagramming time-current-characteristic curves as part of its output. Computer software program shall report device settings and ratings of all overcurrent protective devices and shall demonstrate selective coordination by computer-generated, time-current coordination plots.**

#### **1. Optional Features:**

- a. Arcing faults.
- b. Simultaneous faults.
- c. Explicit negative sequence.
- d. Mutual coupling in zero sequence.

### **2.2 PROTECTIVE DEVICE COORDINATION STUDY REPORT CONTENTS**

#### **A. Executive summary.**

#### **B. Study descriptions, purpose, basis and scope. Include case descriptions, definition of terms and guide for interpretation of the computer printout.**

#### **C. One-line diagram, showing the following:**

1. Protective device designations and ampere ratings.
2. Cable size and lengths.
3. Transformer kilovolt ampere (kVA) and voltage ratings.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

4. Motor designations and kVA ratings.
  5. Switchgear, switchboard, motor-control center, and panelboard designations.
- D. Study Input Data: As described in "Power System Data" Article.
- E. Short-Circuit Study Output: As specified in "Short-Circuit Study Output" Paragraph in "Short-Circuit Study Report Contents" Article in Section 26 05 72 "Overcurrent Protective Device Short-Circuit Study."
- F. Protective Device Coordination Study:
1. Report recommended settings of protective devices, ready to be applied in the field. Use manufacturer's data sheets for recording the recommended setting of overcurrent protective devices when available.
    - a. Circuit Breakers:
      - 1) Adjustable pickups and time delays (long time, short time, ground).
      - 2) Adjustable time-current characteristic.
      - 3) Adjustable instantaneous pickup.
      - 4) Recommendations on improved trip systems, if applicable.
    - b. Fuses: Show current rating, voltage, and class.
- G. Time-Current Coordination Curves: Determine settings of overcurrent protective devices to achieve selective coordination. Graphically illustrate that adequate time separation exists between devices installed in series, including power utility company's upstream devices. Prepare separate sets of curves for the switching schemes and for emergency periods where the power source is local generation. Show the following information:
1. Device tag and title, one-line diagram with legend identifying the portion of the system covered.
  2. Terminate device characteristic curves at a point reflecting maximum symmetrical or asymmetrical fault current to which the device is exposed.
  3. Identify the device associated with each curve by manufacturer type, function, and, if applicable, tap, time delay, and instantaneous settings recommended.
  4. Plot the following listed characteristic curves, as applicable:
    - a. Power utility's overcurrent protective device.
    - b. Medium-voltage equipment overcurrent relays.
    - c. Medium- and low-voltage fuses including manufacturer's minimum melt, total clearing, tolerance, and damage bands.
    - d. Low-voltage equipment circuit-breaker trip devices, including manufacturer's tolerance bands.
    - e. Transformer full-load current, magnetizing inrush current, and ANSI through-fault protection curves.
    - f. Cables and conductors damage curves.



OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- g. Ground-fault protective devices.
  - h. Motor-starting characteristics and motor damage points.
  - i. The largest feeder circuit breaker in each motor-control center and panelboard.
5. Series rating on equipment allows the application of two series interrupting devices for a condition where the available fault current is greater than the interrupting rating of the downstream equipment. Both devices share in the interruption of the fault and selectivity is sacrificed at high fault levels. Maintain selectivity for tripping currents caused by overloads.
6. Provide adequate time margins between device characteristics such that selective operation is achieved.
7. Comments and recommendations for system improvements.

### **PART 3 - EXECUTION**

#### **3.1 EXAMINATION**

- A. Examine Project overcurrent protective device submittals for compliance with electrical distribution system coordination requirements and other conditions affecting performance. Devices to be coordinated are indicated on Drawings.
1. Proceed with coordination study only after relevant equipment submittals have been assembled. Overcurrent protective devices that have not been submitted and approved prior to coordination study may not be used in study.

#### **3.2 PROTECTIVE DEVICE COORDINATION STUDY**

- A. Comply with IEEE 242 for calculating short-circuit currents and determining coordination time intervals.
- B. Comply with IEEE 399 for general study procedures.
- C. The study shall be based on the device characteristics supplied by device manufacturer.
- D. Begin analysis at the service, extending down to the system overcurrent protective devices as follows:
1. To normal system low-voltage load buses where fault current is 10 kA or less.
- E. Study electrical distribution system from normal and alternate power sources throughout electrical distribution system for Project. Study all cases of system-switching configurations and alternate operations that could result in maximum fault conditions.
- F. Transformer Primary Overcurrent Protective Devices:
1. Device shall not operate in response to the following:
- a. Inrush current when first energized.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- b. Self-cooled, full-load current or forced-air-cooled, full-load current, whichever is specified for that transformer.
    - c. Permissible transformer overloads according to IEEE C57.96 if required by unusual loading or emergency conditions.
  2. Device settings shall protect transformers according to IEEE C57.12.00, for fault currents.
- G. Motor Protection:
  1. Select protection for low-voltage motors according to IEEE 242 and NFPA 70.
  2. Select protection for motors served at voltages more than 600 V according to IEEE 620.
- H. Conductor Protection: Protect cables against damage from fault currents according to ICEA P-32-382, ICEA P-45-482, and protection recommendations in IEEE 242. Demonstrate that equipment withstands the maximum short-circuit current for a time equivalent to the tripping time of the primary relay protection or total clearing time of the fuse. To determine temperatures that damage insulation, use curves from cable manufacturers or from listed standards indicating conductor size and short-circuit current.
- I. The calculations shall include the ac fault-current decay from induction motors, synchronous motors and shall apply to low- and medium-voltage, three-phase ac systems. The calculations shall also account for the fault-current dc decrement, to address the asymmetrical requirements of the interrupting equipment.
  1. For grounded systems, provide a bolted line-to-ground fault-current study for areas as defined for the three-phase bolted fault short-circuit study.
- J. Calculate short-circuit momentary and interrupting duties for a three-phase bolted fault and single line-to-ground fault at each of the following:
  1. Electric utility's supply termination point.
  2. Switchgear.
  3. Unit substation primary and secondary terminals.
  4. Low-voltage switchgear.
  5. Branch circuit panelboards.
- K. Protective Device Evaluation:
  1. Evaluate equipment and protective devices and compare to short-circuit ratings.
  2. Adequacy of switchgear, motor-control centers, and panelboard bus bars to withstand short-circuit stresses.
  3. Any application of series-rated devices shall be recertified, complying with requirements in NFPA 70.

### **3.3 LOAD-FLOW AND VOLTAGE-DROP STUDY**

- A. Perform a load-flow and voltage-drop study to determine the steady-state loading profile of the system. Analyze power system performance two times as follows:
  - 1. Determine load-flow and voltage drop based on full-load currents obtained in "Power System Data" Article.
  - 2. Determine load-flow and voltage drop based on 80 percent of the design capacity of the load buses.
  - 3. Prepare the load-flow and voltage-drop analysis and report to show power system components that are overloaded, or might become overloaded; show bus voltages that are less than as prescribed by NFPA 70.

### **3.4 MOTOR-STARTING STUDY**

- A. Perform a motor-starting study to analyze the transient effect of the system's voltage profile during motor starting. Calculate significant motor-starting voltage profiles and analyze the effects of the motor starting on the power system stability.

### **3.5 POWER SYSTEM DATA**

- A. Obtain all data necessary for the conduct of the overcurrent protective device study.
  - 1. Verify completeness of data supplied in the one-line diagram on Drawings. Call discrepancies to the attention of Architect.
  - 2. For new equipment, use characteristics submitted under the provisions of action submittals and information submittals for this Project.
  - 3. For existing equipment, whether or not relocated obtain required electrical distribution system data by field investigation and surveys, conducted by qualified technicians and engineers. The qualifications of technicians and engineers shall be qualified as defined by NFPA 70E.
- B. Gather and tabulate the following input data to support coordination study. The list below is a guide. Comply with recommendations in IEEE 551 for the amount of detail required to be acquired in the field. Field data gathering shall be under the direct supervision and control of the engineer in charge of performing the study, and shall be by the engineer or its representative who holds NETA ETT Level III certification or NICET Electrical Power Testing Level III certification.
  - 1. Product Data for overcurrent protective devices specified in other Sections and involved in overcurrent protective device coordination studies. Use equipment designation tags that are consistent with electrical distribution system diagrams, overcurrent protective device submittals, input and output data, and recommended device settings.
  - 2. Electrical power utility impedance at the service.
  - 3. Power sources and ties.
  - 4. Short-circuit current at each system bus, three phase and line-to-ground.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

5. Full-load current of all loads.
6. Voltage level at each bus.
7. For transformers, include kVA, primary and secondary voltages, connection type, impedance, X/R ratio, taps measured in percent, and phase shift.
8. For reactors, provide manufacturer and model designation, voltage rating, and impedance.
9. For circuit breakers and fuses, provide manufacturer and model designation. List type of breaker, type of trip and available range of settings, SCCR, current rating, and breaker settings.
10. For relays, provide manufacturer and model designation, current transformer ratios, potential transformer ratios, and relay settings.
11. Maximum demands from service meters.
12. Busway manufacturer and model designation, current rating, impedance, lengths, and conductor material.
13. Motor horsepower and NEMA MG 1 code letter designation.
14. Low-voltage cable sizes, lengths, number, conductor material, and conduit material (magnetic or nonmagnetic).
15. Medium-voltage cable sizes, lengths, conductor material, and cable construction and metallic shield performance parameters.
16. Data sheets to supplement electrical distribution system diagram, cross-referenced with tag numbers on diagram, showing the following:
  - a. Special load considerations, including starting inrush currents and frequent starting and stopping.
  - b. Transformer characteristics, including primary protective device, magnetic inrush current, and overload capability.
  - c. Motor full-load current, locked rotor current, service factor, starting time, type of start, and thermal-damage curve.
  - d. Ratings, types, and settings of utility company's overcurrent protective devices.
  - e. Special overcurrent protective device settings or types stipulated by utility company.
  - f. Time-current-characteristic curves of devices indicated to be coordinated.
  - g. Manufacturer, frame size, interrupting rating in amperes rms symmetrical, ampere or current sensor rating, long-time adjustment range, short-time adjustment range, and instantaneous adjustment range for circuit breakers.
  - h. Manufacturer and type, ampere-tap adjustment range, time-delay adjustment range, instantaneous attachment adjustment range, and current transformer ratio for overcurrent relays.
  - i. Panelboards, switchboards ampacity and SCCR in amperes rms symmetrical.
  - j. Identify series-rated interrupting devices for a condition where the available fault current is greater than the interrupting rating of the downstream equipment. Obtain device data details to allow verification that series application of these devices complies with NFPA 70 and UL 489 requirements.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

### **3.6 FIELD ADJUSTING**

- A. Adjust relay and protective device settings according to the recommended settings provided by the coordination study. Field adjustments shall be completed by the engineering service division of the equipment manufacturer under the Startup and Acceptance Testing contract portion.
- B. Make minor modifications to equipment as required to accomplish compliance with short-circuit and protective device coordination studies.
- C. Testing and adjusting shall be by a full-time employee of the Field Adjusting Agency, who holds NETA ETT Level III certification or NICET Electrical Power Testing Level III certification.
  - 1. Perform each visual and mechanical inspection and electrical test stated in NETA Acceptance Testing Specification. Certify compliance with test parameters. Perform NETA tests and inspections for all adjustable overcurrent protective devices.

### **3.7 DEMONSTRATION**

- A. Engage the Coordination Study Specialist to train Owner's maintenance personnel in the following:
  - 1. Hand-out and explain the objectives of the coordination study, study descriptions, purpose, basis, and scope. Include case descriptions, definition of terms, and guide for interpreting the time-current coordination curves.
  - 2. Adjust, operate, and maintain overcurrent protective device settings.

**END OF SECTION 26 0573**

## SECTION 26 0574

### OVERCURRENT PROTECTIVE DEVICE ARC-FLASH STUDY

#### PART 1 - GENERAL

##### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

##### 1.2 SUMMARY

- A. Section includes a computer-based, arc-flash study to determine the arc-flash hazard distance and the incident energy to which personnel could be exposed during work on or near electrical equipment.

##### 1.3 DEFINITIONS

- A. Existing to Remain: Existing items of construction that are not to be removed and that are not otherwise indicated to be removed, removed and salvaged, or removed and reinstalled.
- B. One-Line Diagram: A diagram which shows, by means of single lines and graphic symbols, the course of an electric circuit or system of circuits and the component devices or parts used therein.
- C. Protective Device: A device that senses when an abnormal current flow exists and then removes the affected portion from the system.
- D. SCCR: Short-circuit current rating.
- E. Service: The conductors and equipment for delivering electric energy from the serving utility to the wiring system of the premises served.

##### 1.4 ACTION SUBMITTALS

- A. Product Data: For computer software program to be used for studies.
- B. Study Submittals: Submit the following submittals after the approval of system protective devices submittals. Submittals shall be in digital form.
  - 1. Arc-flash study input data, including completed computer program input data sheets.

##### 1.5 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For Arc-Flash Study Software Developer.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- B. Product Certificates: For arc-flash hazard analysis software, certifying compliance with IEEE 1584 and NFPA 70E.

## **1.6 CLOSEOUT SUBMITTALS**

- A. Operation and Maintenance Data:
  - 1. Maintenance procedures according to requirements in NFPA 70E shall be provided in the equipment manuals.
  - 2. Operation and Maintenance Procedures: In addition to items specified in Section 01 78 23 "Operation and Maintenance Data," provide maintenance procedures for use by Owner's personnel that comply with requirements in NFPA 70E.

## **1.7 QUALITY ASSURANCE**

- A. Studies shall use computer programs that are distributed nationally and are in wide use. Software algorithms shall comply with requirements of standards and guides specified in this Section. Manual calculations are unacceptable.
- B. Arc-Flash Study Software Developer Qualifications: An entity that owns and markets computer software used for studies, having performed successful studies of similar magnitude on electrical distribution systems using similar devices.
  - 1. The computer program shall be developed under the charge of a licensed professional engineer who holds IEEE Computer Society's Certified Software Development Professional certification.

## **PART 2 - PRODUCTS**

### **2.1 COMPUTER SOFTWARE DEVELOPERS**

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
  - 1. CGI CYME.
  - 2. EDSA Micro Corporation.
  - 3. ESA Inc.
  - 4. Operation Technology, Inc.
  - 5. Power Analytics, Corporation.
  - 6. SKM Systems Analysis, Inc.
- B. Comply with IEEE 1584 and NFPA 70E.

- C. Analytical features of device coordination study computer software program shall have the capability to calculate "mandatory," "very desirable," and "desirable" features as listed in IEEE 399.

## **2.2 ARC-FLASH STUDY REPORT CONTENT**

- A. Executive summary.
- B. Study descriptions, purpose, basis and scope.
- C. One-line diagram, showing the following:
  - 1. Protective device designations and ampere ratings.
  - 2. Cable size and lengths.
  - 3. Transformer kilovolt ampere (kVA) and voltage ratings.
  - 4. Motor designations and kVA ratings.
  - 5. Switchgear, switchboard, motor-control center and panelboard designations.
- D. Study Input Data: As described in "Power System Data" Article.
- E. Short-Circuit Study Output: As specified in "Short Circuit Study Output" Paragraph in "Short-Circuit Study Report Contents" Article in Section 26 05 72 "Overcurrent Protective Device Short-Circuit Study."
- F. Protective Device Coordination Study Report Contents: As specified in "Protective Device Coordination Study Report Contents" Article in Section 26 05 73 "Overcurrent Protective Device Coordination Study."
- G. Arc-Flash Study Output:
  - 1. Interrupting Duty Report: Three-phase and unbalanced fault calculations, showing the following for each overcurrent device location:
    - a. Voltage.
    - b. Calculated symmetrical fault-current magnitude and angle.
    - c. Fault-point X/R ratio.
    - d. No AC Decrement (NACD) ratio.
    - e. Equivalent impedance.
    - f. Multiplying factors for 2-, 3-, 5-, and 8-cycle circuit breakers rated on a symmetrical basis.
    - g. Multiplying factors for 2-, 3-, 5-, and 8-cycle circuit breakers rated on a total basis.
- H. Incident Energy and Flash Protection Boundary Calculations:
  - 1. Arcing fault magnitude.



OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

2. Protective device clearing time.
  3. Duration of arc.
  4. Arc-flash boundary.
  5. Working distance.
  6. Incident energy.
  7. Hazard risk category.
  8. Recommendations for arc-flash energy reduction.
- I. Fault study input data, case descriptions, and fault-current calculations including a definition of terms and guide for interpretation of the computer printout.

### **2.3 ARC-FLASH WARNING LABELS**

- A. Comply with requirements in Section 26 05 53 "Identification for Electrical Systems" for self-adhesive equipment labels. Produce a 3.5-by-5-inch self-adhesive equipment label for each work location included in the analysis.
- B. The label shall have an orange header with the wording, "WARNING, ARC-FLASH HAZARD," and shall include the following information taken directly from the arc-flash hazard analysis:
1. Location designation.
  2. Nominal voltage.
  3. Flash protection boundary.
  4. Hazard risk category.
  5. Incident energy.
  6. Working distance.
  7. Engineering report number, revision number, and issue date.
- C. Labels shall be machine printed, with no field-applied markings.

## **PART 3 - EXECUTION**

### **3.1 EXAMINATION**

- A. Examine Project overcurrent protective device submittals. Proceed with arc-flash study only after relevant equipment submittals have been assembled. Overcurrent protective devices that have not been submitted and approved prior to arc-flash study may not be used in study.

### **3.2 ARC-FLASH HAZARD ANALYSIS**

- A. Comply with NFPA 70E and its Annex D for hazard analysis study.

- B. Calculate maximum and minimum contributions of fault-current size.
  - 1. The minimum calculation shall assume that the utility contribution is at a minimum and shall assume no motor load.
  - 2. The maximum calculation shall assume a maximum contribution from the utility and shall assume motors to be operating under full-load conditions.
- C. Calculate the arc-flash protection boundary and incident energy at locations in the electrical distribution system where personnel could perform work on energized parts.
- D. Include medium- and low-voltage equipment locations, except equipment rated 240-V ac or less fed from transformers less than 125 kVA.
- E. Safe working distances shall be specified for calculated fault locations based on the calculated arc-flash boundary, considering incident energy of 1.2 cal/sq.cm.
- F. Incident energy calculations shall consider the accumulation of energy over time when performing arc-flash calculations on buses with multiple sources. Iterative calculations shall take into account the changing current contributions, as the sources are interrupted or decremented with time. Fault contribution from motors shall be decremented as follows:
  - 1. Fault contribution from induction motors should not be considered beyond three to five cycles.
  - 2. Fault contribution from synchronous motors should be decayed to match the actual decrement of each as closely as possible.
- G. Arc-flash computation shall include both line and load side of a circuit breaker as follows:
  - 1. When the circuit breaker is in a separate enclosure.
  - 2. When the line terminals of the circuit breaker are separate from the work location.
- H. Base arc-flash calculations on actual overcurrent protective device clearing time. Cap maximum clearing time at two seconds based on IEEE 1584, Section B.1.2.

### 3.3 POWER SYSTEM DATA

- A. Obtain all data necessary for the conduct of the arc-flash hazard analysis.
  - 1. Verify completeness of data supplied on the one-line diagram on Drawings and under "Preparatory Studies" Paragraph in "Arc-Flash Hazard Analysis" Article. Call discrepancies to the attention of Architect.
  - 2. For new equipment, use characteristics submitted under the provisions of action submittals and information submittals for this Project.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

3. For existing equipment, whether or not relocated, obtain required electrical distribution system data by field investigation and surveys, conducted by qualified technicians and engineers.
- B. Electrical Survey Data: Gather and tabulate the following input data to support study. Comply with recommendations in IEEE 1584 and NFPA 70E as to the amount of detail that is required to be acquired in the field. Field data gathering shall be under the direct supervision and control of the engineer in charge of performing the study, and shall be by the engineer or its representative who holds NETA ETT Level III certification or NICET Electrical Power Testing Level III certification.
1. Product Data for overcurrent protective devices specified in other Sections and involved in overcurrent protective device coordination studies. Use equipment designation tags that are consistent with electrical distribution system diagrams, overcurrent protective device submittals, input and output data, and recommended device settings.
  2. Obtain electrical power utility impedance at the service.
  3. Power sources and ties.
  4. Short-circuit current at each system bus, three phase and line-to-ground.
  5. Full-load current of all loads.
  6. Voltage level at each bus.
  7. For transformers, include kVA, primary and secondary voltages, connection type, impedance, X/R ratio, taps measured in per cent, and phase shift.
  8. For reactors, provide manufacturer and model designation, voltage rating and impedance.
  9. For circuit breakers and fuses, provide manufacturer and model designation. List type of breaker, type of trip and available range of settings, SCCR, current rating, and breaker settings.
  10. For relays, provide manufacturer and model designation, current transformer ratios, potential transformer ratios, and relay settings.
  11. Busway manufacturer and model designation, current rating, impedance, lengths, and conductor material.
  12. Motor horsepower and NEMA MG 1 code letter designation.
  13. Low-voltage cable sizes, lengths, number, conductor material and conduit material (magnetic or nonmagnetic).
  14. Medium-voltage cable sizes, lengths, conductor material, and cable construction and metallic shield performance parameters.

### 3.4 LABELING

- A. Apply one arc-flash labels for new 208-V ac service panelboards and disconnects and for each of the following locations:
1. Low-voltage switchboard.
  2. Switchgear.

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

3. Panelboards

**3.5 APPLICATION OF WARNING LABELS**

- A. Install the arc-fault warning labels under the direct supervision and control of the Arc-Flash Study Specialist.

**3.6 DEMONSTRATION**

- A. Engage the Arc-Flash Study Specialist to train Owner's maintenance personnel in the potential arc-flash hazards associated with working on energized equipment and the significance of the arc-flash warning labels.

**END OF SECTION 26 0574**

## **SECTION 26 2416**

### **PANELBOARDS**

#### **PART 1 - GENERAL**

##### **1.1 RELATED DOCUMENTS**

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

##### **1.2 SUMMARY**

- A. Section Includes:
  - 1. Distribution panelboards.
  - 2. Lighting and appliance branch-circuit panelboards.

##### **1.3 SUBMITTALS**

- A. Product Data: For each type of panelboard, switching and overcurrent protective device, transient voltage suppression device, accessory, and component indicated. Include dimensions and manufacturers' technical data on features, performance, electrical characteristics, ratings, and finishes.
- B. Shop Drawings: For each panelboard and related equipment.
  - 1. Include dimensioned plans, elevations, sections, and details. Show tabulations of installed devices, equipment features, and ratings.
  - 2. Detail enclosure types and details for types other than NEMA 250, Type 1.
  - 3. Detail bus configuration, current, and voltage ratings.
  - 4. Short-circuit current rating of panelboards and overcurrent protective devices.
  - 5. Detail features, characteristics, ratings, and factory settings of individual overcurrent protective devices and auxiliary components.
  - 6. Include wiring diagrams for power, signal, and control wiring.
- C. Panelboard Schedules: For installation in panelboards. Submit final versions after load balancing.
- D. Operation and Maintenance Data: For panelboards and components to include in emergency, operation, and maintenance manuals.
  - 1. Manufacturer's written instructions for testing and adjusting overcurrent protective devices.
  - 2. Time-current curves, including selectable ranges for each type of overcurrent protective device that allows adjustments.

#### **1.4 QUALITY ASSURANCE**

- A. Source Limitations: Obtain panelboards, overcurrent protective devices, components, and accessories from single source from single manufacturer.
- B. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- C. Comply with NEMA PB 1.
- D. Comply with NFPA 70.

#### **1.5 DELIVERY, STORAGE, AND HANDLING**

- A. Remove loose packing and flammable materials from inside panelboards.
- B. Handle and prepare panelboards for installation according to NECA 407 and NEMA PB 1.

#### **1.6 COORDINATION**

- A. Coordinate layout and installation of panelboards and components with other construction that penetrates walls or is supported by them, including electrical and other types of equipment, raceways, piping, encumbrances to workspace clearance requirements, and adjacent surfaces. Maintain required workspace clearances and required clearances for equipment access doors and panels.

#### **1.7 EXTRA MATERIALS**

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
  - 1. Keys: Two spares for each type of panelboard cabinet lock.

### **PART 2 - PRODUCTS**

#### **2.1 GENERAL REQUIREMENTS FOR PANELBOARDS**

- A. Enclosures: Flush- and surface-mounted cabinets.
  - 1. Rated for environmental conditions at installed location.
    - a. Indoor Dry and Clean Locations: NEMA 250, Type 1.
    - b. Indoor Locations Subject to Dust, Falling Dirt, and Dripping Noncorrosive Liquids: NEMA 250, Type 12.
  - 2. Hinged Front Cover: Entire front trim hinged to box and with standard door within hinged trim cover.
  - 3. Finishes:

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

- a. Panels and Trim: Steel factory finished immediately after cleaning and pretreating with manufacturer's standard two-coat, baked-on finish consisting of prime coat and thermosetting topcoat.
  - b. Back Boxes: Galvanized steel.
4. Directory Card: Inside panelboard door, mounted in transparent card holder.
- B. Incoming Mains Location: As required for each specific instance. Field verify prior to order.
- C. Phase, Neutral, and Ground Buses:
1. Material: Hard-drawn copper, 98 percent conductivity.
  2. Equipment Ground Bus: Adequate for feeder and branch-circuit equipment grounding conductors; bonded to box.
- D. Conductor Connectors: Suitable for use with conductor material and sizes.
1. Material: Hard-drawn copper, 98 percent conductivity.
  2. Main and Neutral Lugs: Mechanical type.
  3. Ground Lugs and Bus-Configured Terminators: Mechanical type.
- E. Future Devices: Mounting brackets, bus connections, filler plates, and necessary appurtenances required for future installation of devices.
- F. Panelboard Short-Circuit Current Rating: Fully rated to interrupt symmetrical short-circuit current available at terminals.

## **2.2 DISTRIBUTION PANELBOARDS**

- A. Branch Overcurrent Protective Devices for Circuit-Breaker Frame Sizes 125 A and Smaller: Bolt-on circuit breakers.
- B. Branch Overcurrent Protective Devices for Circuit-Breaker Frame Sizes Larger Than 125 A: Bolt-on circuit breakers; plug-in circuit breakers where individual positive-locking device requires mechanical release for removal.

## **2.3 LIGHTING AND APPLIANCE BRANCH-CIRCUIT PANELBOARDS**

- A. Basis-of-Design Product: Subject to compliance with requirements, provide products indicated on Drawings.
- B. Panelboards: NEMA PB 1, lighting and appliance branch-circuit type.
- C. Mains: As indicated on the drawings.
- D. Branch Overcurrent Protective Devices: Bolt-on circuit breakers, replaceable without disturbing adjacent units.
- E. Doors: Concealed hinges; secured with flush latch with tumbler lock; keyed alike.

## **2.4 DISCONNECTING AND OVERCURRENT PROTECTIVE DEVICES**

- A. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings.
- B. Molded-Case Circuit Breaker (MCCB): Comply with UL 489, with interrupting capacity to meet available fault currents.
  - 1. Thermal-Magnetic Circuit Breakers: Inverse time-current element for low-level overloads, and instantaneous magnetic trip element for short circuits. Adjustable magnetic trip setting for circuit-breaker frame sizes 250 A and larger.

## **PART 3 - EXECUTION**

### **3.1 EXAMINATION**

- A. Receive, inspect, handle, and store panelboards according to NECA 407 and NEMA PB 1.1.
- B. Examine panelboards before installation. Reject panelboards that are damaged or rusted or have been subjected to water saturation.
- C. Examine elements and surfaces to receive panelboards for compliance with installation tolerances and other conditions affecting performance of the Work.
- D. Proceed with installation only after unsatisfactory conditions have been corrected.

### **3.2 INSTALLATION**

- A. Install panelboards and accessories according to NECA 407 and NEMA PB 1.1.
- B. Temporary Lifting Provisions: Remove temporary lifting eyes, channels, and brackets and temporary blocking of moving parts from panelboards.
- C. Mount top of trim 72 inches above finished floor unless otherwise indicated.
- D. Mount panelboard cabinet plumb and rigid without distortion of box. Mount recessed panelboards with fronts uniformly flush with wall finish and mating with back box.
- E. Install overcurrent protective devices not already factory installed.
- F. Install filler plates in unused spaces.
- G. Arrange conductors in gutters into groups and bundle and wrap with wire ties after completing load balancing.
- H. Comply with NECA 1.

### **3.3 IDENTIFICATION**

- A. Identify field-installed conductors, interconnecting wiring, and components; provide warning signs complying with Division 26 Section "Identification for Electrical Systems."
- B. Create a directory to indicate installed circuit loads after balancing panelboard loads;



OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

1. Incorporate Owner's room designations. Obtain approval before installing.
  2. Use a computer to create directory; handwritten directories are not acceptable.
  3. Leave locations of spare breakers or panel spaces blank. Indicate spare breaker locations in pencil.
  4. For existing panelboards: Revise identification of breakers or switches to indicate modifications to loads, circuit uses, or to correct inaccuracies found.
  5. Directory circuit identifications shall comply with NEC 408.4. Panel schedules furnished on drawings shall not be considered sufficient.
- C. Spaces in new panelboards shall be identified as follows:
1. Each single pole space shall have a separate identification.
  2. Example: The left side of a 42-space panelboard shall use odd numbers 1-41, in descending order, from top to bottom. The right side of the panelboard shall use even numbers 2-42, in descending order, from top to bottom.
  3. Multi-pole breakers or spaces shall use numbers from all spaces occupied (i.e. a 2-pole space or breaker shall be identified using both single pole spaces taken up). Multi-pole breakers and spaces shall not be identified using a single number.
  4. Circuits with emergency loads shall be marked with highlighter type marker.
  5. Circuits with fire alarm equipment loads shall have red handle lock device.
- D. Panelboard Nameplates:
1. Label each panelboard with a nameplate complying with requirements for identification specified in Division 26 Section "Identification for Electrical Systems" and in drawing details.
  2. Include power source on panelboard nameplate to satisfy requirement of NEC 408.4.
- E. Distribution Panelboard Device Nameplates:
1. Label each branch circuit device in distribution panelboards with a nameplate complying with requirements for identification specified in Division 26 Section "Identification for Electrical Systems" and in drawing details.
  2. Include power source on panelboard nameplate to satisfy requirement of NEC 408.4.

### **3.4 FIELD QUALITY CONTROL**

- A. Perform tests and inspections.
- B. Acceptance Testing Preparation:
1. Test insulation resistance for each panelboard bus, component, connecting supply, feeder, and control circuit.
  2. Test continuity of each circuit.
- C. Tests and Inspections:

OSC ComEd NEW ELECTRICAL SERVICE  
OPERATIONS SUPPORT CENTER  
ROCKFORD PUBLIC SCHOOLS 205  
ROCKFORD, ILLINOIS

1. Perform each visual and mechanical inspection and electrical test stated in NETA Acceptance Testing Specification. Certify compliance with test parameters.
  2. Correct malfunctioning units on-site, where possible, and retest to demonstrate compliance; otherwise, replace with new units and retest.
- D. Panelboards will be considered defective if they do not pass tests and inspections.

### **3.5 ADJUSTING**

- A. Adjust moving parts and operable components to function smoothly, and lubricate as recommended by manufacturer.
- B. Set field-adjustable circuit-breaker trip ranges in coordination with OCPD coordination study.
- C. Load Balancing: After Substantial Completion, but not more than 60 days after Final Acceptance, measure load balancing and make circuit changes.
  1. Measure as directed during period of normal system loading.
  2. Perform load-balancing circuit changes outside normal occupancy/working schedule of the facility and at time directed. Avoid disrupting critical 24-hour services such as fax machines and on-line data processing, computing, transmitting, and receiving equipment.
  3. After circuit changes, recheck loads during normal load period. Record all load readings before and after changes and submit test records.
  4. Tolerance: Difference exceeding 20 percent between phase loads, within a panelboard, is not acceptable. Rebalance and recheck as necessary to meet this minimum requirement.

**END OF SECTION 26 2416**