



*50 Years of Quality Construction*

Lic# 235465 A, B & C10

November 3, 2023

Ray Sifuentes  
Director of Maintenance and Operations  
San Pasqual Union School District  
15305 Rockwood Road  
Escondido, CA 92027

Re: San Pasqual ES – Bottle Filling Stations

Dear Mr. Sifuentes,

We propose to furnish labor, material, and equipment to replace two stone ADA free standing drinking fountains with two new free standing Elkay bottle filling stations at San Pasqual Elementary School, per site walk. This proposal shall include, but is not limited to the following:

1. Remove and dispose of existing fountains
2. Relocate plumbing for one filling station
3. Furnish and install two Elkay free bottle filling stations, model LK4430BF1U
4. Prevailing wages

This work shall be completed in a neat and workmanlike manner during normal working hours, for the sum of the sum of Twenty-five Thousand, Eight Hundred Twenty-three Dollars (\$25,823.00).

Respectfully submitted:

*Douglas MacLachlan*

Doug MacLachlan  
President

**PRODUCT SPECIFICATIONS**

Elkay Outdoor ezH2O® Upper Bottle Filling Station Tri-Level Pedestal Non-Filtered Non-Refrigerated. Features shall include 316 Stainless. Heavy Duty Vandal Resistant. Laminar Flow. Furnished with Vandal Resistant bubbler. Mechanical Front Bubbler Button activation. Product shall be Floor Mount/Freestanding. for Outdoor applications. serving 3 station(s).

<b>Special Features:</b>	316 Stainless. Heavy Duty Vandal Resistant. Laminar Flow
<b>Finish:</b>	Beige (BGE). Black (BK). Blue (BLU). Brown (BRN). Evergreen (EVG). Gray (GRY). Orange (ORN). Powder Coat (12 Color Options). Purple (PUR). Red (RED). Terracotta (TER). White (WHT). Yellow (YLW)
<b>Power:</b>	No Electrical Required
<b>Bubbler Style:</b>	Vandal Resistant
<b>Activation by:</b>	Mechanical Front Bubbler Button
<b>Mounting Type:</b>	Floor Mount/Freestanding
<b>Chilling Capacity:</b>	Non-refrigerated
<b>Dimensions (L x W x H):</b>	14" x 48" x 64"
<b>Approx. Shipping Weight:</b>	215 lbs.
<b>Installation Location:</b>	Outdoor
<b>No. of Stations Served:</b>	3
**When used in non-temperature controlled environments. unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.	

**Special Note: Bottle Filler Stations 1 (Upper), Bubbler Stations 2 (Mid-Low), Choose from 12 color options**

- Mechanically-Activated bubbler continues to supply water in event of service disruptions.
- Laminar flow provides clean fill with minimal splash.
- Base material constructed from marine-grade 316 stainless steel provides the ultimate corrosion protection from even the most corrosive elements.



**Included with Product: Outdoor Bottle Filler Ships in one box.**

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier. inspire change and leave the world a better place.



**PRODUCT COMPLIANCE**

- ADA & ICC A117.1
- ASME A112.19.3/CSA B45.4
- Buy American Act
- GreenSpec®
- NSF/ANSI 61 & 372 (lead free)



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.



[Installation Instructions \(PDF\) - 1000004246](#)

**Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

[Warranty \(PDF\)](#)

PART: \_\_\_\_\_ QTY: \_\_\_\_\_  
 PROJECT: \_\_\_\_\_  
 CONTACT: \_\_\_\_\_  
 DATE: \_\_\_\_\_  
 NOTES: \_\_\_\_\_  
 APPROVAL: \_\_\_\_\_

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*

Optional Accessories		
<a href="#">LK4471LHB</a>	Locking Hose Bib <a href="#">Spec Sheet (PDF)</a>	
<a href="#">97890C</a>	Accessory - Direct Bury Adaptor <a href="#">Spec Sheet (PDF)</a>	

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](http://elkay.com) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*

### MOUNTING INSTRUCTIONS and PLUMBING CONNECTIONS

Provide solid, well-drained surface to mount pedestal fountain (concrete pad recommended) with adequate support (300 lb. load minimum) (6) 3/8" minimum fasteners (not included) should be attached firmly to mounting surface in order to secure unit (Refer to rough in diagram)

Locate and install plumbing through ground as required


**NOTE:** Unit is not furnished with service valve

Position pedestal over plumbing and secure base to fasteners. Remove access panels and connect supply and water lines. Turn on water supply and check for leaks. Reassemble access panels to pedestal.

Trap and service stop not included.

### OPERATING PRESSURES:

Supply water 20 – 105 psi maximum



In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](http://elkay.com) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.