

Clsrc # 350120

ITEM NUMBER: 818 - PREMIUM FURNITURE POLISH 17 0 Z
VERSION 4 EFFECTIVE DATE: 8/17/05 SUPERCEDES: 01/01/05 PREPARED BY: Regulatory Compliance
Section(s) Revised: IX
IDENTITY (As Used On Label and List): Reflection Furniture Polish

EMERGENCY MEDICAL Telephone# 1-866-836-8855 (24 Hrs) Outside of the U.S.A. Call 952-852-4646

PRODUCT HAZARD RATINGS (HMIS): Health = 1, Fire = 2, Reactivity = 0 Protective Equipment = A
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal, * = Chronic Hazard)

SECTION I

CLEAN SOURCE/COMMERCE TELEPHONE NUMBER FOR INFORMATION :
650 BRENNAN STREET

SAN JOSE
CA 95131

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Chemical Names (CAS #)	SARA SEC 313	ACGIH TLV-TWA/STEL	OSHA PEL-TWA/STEL	% By Wt.
------------------------	-----------------	-----------------------	----------------------	----------

Synthetic Isoparaffinic Hydrocarbon (64742-47-8)	No	NE / NE	152 ppm*/ NE	10-30
Liquefied Petroleum Gas Mixture (68476-86-8)	No	See below ingredient data		10-30
Propane (74-98-6)	No	1000 ppm/ NE	1000 ppm/ NE	(48-55)
n-Butane (106-97-8)	No	1000 ppm/ NE	NE / NE	(45-49)

Balance of ingredients are non-hazardous or below reportable levels.
* ExxonMobil recommendation

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig)(± 5 psig): 89 @ 130°F / 38 @ 70°F
Specific Gravity - calculated (H2O=1): 0.8509 ± 0.005 pH: 7.00 Solubility/Water: Slight
Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): ND
Appearance and Odor: White aerosol spray with lemon odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: Product is not required to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45.
Flashpoint: <0°F (Propellant): 177°F (Concentrate)
Flammable Limits - % Volume In Air (Propellant): LEL: 1.9 UEL: 9.5
Extinguishing Media: Carbon dioxide, water spray, foam, or dry chemical.
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up. Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: Fire fighters and others who may be exposed to the products of Combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protection clothing. At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA

Conditions to Avoid: Keep away from heat, sparks, and flames. Dropping of containers may cause bursting.

-_*-*_*-*_*-*_*-*_*-*_*-*_*-*_*-*_*-*_*-*_*-*_*-

No data available.

* * * * *

Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health. FLOORS COVERED WITH RESIDUAL SPRAY MAY BECOME EXTREMELY SLIPPERY.

_**

Other Protective Clothing or Equipment: Wearing of impervious clothing to prevent skin contact is

Protective clothing and equipment should be in accordance with 29 CFR 1910.132 and CFR 1910.133.

***_**_**_**_**_**_**_**_**_

Ingredients of this product are listed.

***_***_*_*_*_*_*_*_*_*

While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.