

WAXIE Select™ Edge-Off Baseboard Wax Stripper



DESCRIPTION

Special high foaming floor stripper formulation developed to let chemistry do the hard work of removing years of unsightly wax and buildup. Ideal for use on vertical surfaces such as baseboards and kick plates not normally reached with water-thin conventional liquid stripper applications. It is excellent also for spot stripping hard-to-reach vertical and horizontal areas where foot traffic is minimal: under desks, tables, counters, along walls, behind fixtures, etc. This heavy-duty product leaves your floor ready for new wax to be applied. Multiple layers of build up are quickly emulsified by chemical action for easy, speedy removal. Uses can be found in most any commercial setting including offices, institutions, hotels, hospitals, schools, public places and more.

SPECIFICATIONS

AS SOLD

Appearance	Aerosol containing a liquefied gas
Color	Light yellow
Odor	Characteristic
pH.....	11.5-12.5
VOC	N/A
Melting Point/Freezing Point	No data available
Initial Boiling Point/Boiling Range	No data available
Flash Point	No data available
Flammability	Non-flammable aerosol
Relative Vapor Density	No data available
Density.....	1.006 g/cm ³
Solubility(ies) / Water Solubility.....	No data available
Solubility in other Solvents	No data available
Heat of Combustion.....	2.47 kJ/g

ACTIVE INGREDIENTS:

Butane	≥ 1 - < 5%
2-Aminoethanol	≥ 1 - < 5%

SHELF LIFE: All WAXIE brand chemical products have a guaranteed shelf life of up to one year after the date product was manufactured, when stored in ambient conditions. The actual manufacturing date is included in a date code on every product container.

DIRECTIONS FOR USE

Not for use in food contact applications. Before using, always determine suitability and safety of using this product on the surface to be stripped. Avoid allowing overspray to come in contact with any surface not desired to be affected by this product. Do not allow contact on painted surfaces. **IMPORTANT:** Always shake well before using and periodically during consistent or heavy use. Remove cap. Hold can in the inverted position and target the baseboard or flooring area to be stripped. Apply the fan spray in a side-to-side motion 6 to 10 inches from the desired surface in thin coats so as not to build up to the point of sliding down a vertical surface. Be sure all areas desired for stripping are covered with the foaming product. Allow 3-5 minutes of contact time.

Item: 320971 16 oz 12/cs

APPLICATION



FEATURES & BENEFITS

- Professional-strength
- 96% VOC free
- Unique designed cap provides source reduction of 75% compared to other caps
- Boxes contain 45% post-consumer recycled material
- Can is tin-free; 100% recyclable
- Can contains 50% recycled steel from post-consumer recycled waste
- Ultimate Biodegradable using ASTM E1720-01 test method
- Water base; Nonflammable
- One application strips numerous coats

PRODUCT REGISTRATIONS & CERTIFICATIONS

- RespirTek Certified for Biodegradability
- NSF A4+C1 Certified

WAXIE Select™ Edge-Off Baseboard Wax Stripper

DIRECTIONS FOR USE (CONTINUED)

Wet scrub the surface with a commercial grade cleaning pad, sponge, or similar item. Rinse surface with clean water. Repeat if necessary. **ATTENTION:** Never use in the upright position, sideways, or at an angle greater than 45 degrees to the desired surface.

DILUTION RATIO: Ready-to-use.

SAFETY INFORMATION

PERSONAL PROTECTIVE EQUIPMENT:

Ready-to-Use D – Safety Glasses, Gloves, Protective Apron & Face Shield



Read the Safety Data Sheet (SDS) and product label before use. The SDS and product label contain hazard warnings, precautionary statements and first aid procedures. SDS documents are available online at www.waxie.com or by calling (800) 995-4466.

For sale to, use and storage by service professionals only. Keep out of reach of children.

HOTLINE NUMBER: You may contact Chem-Tel at (800) 255-3924 for emergency medical treatment information.