

GENERAL NOTES

GENERAL

- THE CONTRACT STRUCTURAL DRAWINGS AND SPECIFICATIONS REPRESENT THE FINISHED STRUCTURE. UNLESS OTHERWISE INDICATED, THEY DO NOT INDICATE THE METHOD OF CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY TO PROTECT THE STRUCTURE, WORKMEN, AND OTHER PERSONS DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, SHORING FOR CONSTRUCTION EQUIPMENT, SHORING FOR THE BUILDING, SHORING FOR THE EARTH BANKS, FORMS, SCAFFOLDING, PLANNING, SAFETY NETS, SUPPORT AND BRACING FOR CRANES, GIN POLES, ETC. THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE WORK, AND HE SHALL BE SOLELY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. OBSERVATION VISITS TO THE SITE BY THE ARCHITECT OR THE ENGINEER SHALL NOT INCLUDE INSPECTION OF THE ABOVE ITEMS.
- IT IS SOLELY THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL APPLICABLE SAFETY CODES AND REGULATIONS DURING ALL PHASES OF CONSTRUCTION.
- EQUIPMENT FRAMING LOADS, OPENINGS AND STRUCTURE IN ANY WAY RELATED TO HVAC, PLUMBING, OR ELECTRICAL REQUIREMENTS ARE SHOWN FOR BIDDING PURPOSES ONLY. EXACT WEIGHTS AND LOCATIONS OF MECHANICAL EQUIPMENT SHALL BE COORDINATED BY CONTRACTOR. IF THE FINAL LOCATION VARIES FROM THAT SHOWN ON THE PLANS, CONTRACTOR TO NOTIFY ARCHITECT AND ENGINEER FOR APPROVAL BEFORE INSTALLATION.
- SHOULD ANY OF THE DETAILED INSTRUCTIONS SHOWN ON THE PLANS CONFLICT WITH THESE STRUCTURAL NOTES, THE SPECIFICATIONS, OR WITH EACH OTHER, THE STRICTEST PROVISION SHALL GOVERN.
- THE GENERAL CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS AT THE JOB SITE AND SHALL BE RESPONSIBLE FOR CONDITIONS OF ALL WORK AND MATERIALS.
- THE CONTRACTOR SHALL REVIEW AND VERIFY ALL DIMENSIONS AND ELEVATIONS. CONTRACTOR SHALL REPORT ANY DISCREPANCIES IN WRITING TO THE ARCHITECT. ANY CONFLICT BETWEEN THE DRAWING AND SPECIFICATIONS OF THE VARIOUS TRADES INVOLVED SHALL BE REPORTED TO THE ARCHITECT AND ENGINEER.
- DETAILS SHOWN ON DRAWINGS APPLY AT SIMILAR CONDITIONS.
- ALL WORK SHALL BE DONE IN ACCORDANCE WITH LOCAL STANDARDS AND TO ALL APPLICABLE PROVISIONS OF THE GOVERNING BUILDING CODE.
- THE ARCHITECT AND ENGINEER SHALL BE NOTIFIED IN WRITING WHEN WORK COMMENCES.
- CONTRACTOR SUBSTITUTIONS: ANY MATERIALS OR PRODUCTS THAT ARE SUBMITTED FOR APPROVAL THAT ARE DIFFERENT FROM THE MATERIALS OR PRODUCTS SPECIFIED IN THE CONTRACT DOCUMENTS WILL ONLY BE CONSIDERED IF THE FOLLOWING CRITERIA ARE SATISFIED:
 - A COST SAVING TO THE OWNER IS DOCUMENTED AND SUBMITTED WITH THE REQUEST
 - THE MATERIAL OR PRODUCT HAS BEEN APPROVED BY THE INTERNATIONAL CONFERENCE OF BUILDING OFFICIALS (ICBO) AND THE ICBO REPORT IS SUBMITTED WITH THE REQUEST.

STRUCTURAL OBSERVATION

- THE PROFESSIONAL ENGINEER OR HIS/HER AUTHORIZED REPRESENTATIVE SHALL CONDUCT ALL STRUCTURAL OBSERVATIONS. STRUCTURAL OBSERVATIONS SHALL BE FOR THE PURPOSE OF ASCERTAINING GENERAL COMPLIANCE WITH THE CONSTRUCTION DOCUMENTS. HOWEVER, SUCH OBSERVATION VISITS SHALL NOT RELIEVE THE CONTRACTOR FROM HIS OBLIGATIONS AND RESPONSIBILITIES TO THE CONSTRUCTION DOCUMENTS.
- ITEMS THAT REQUIRE A STRUCTURAL OBSERVATION ARE AS FOLLOWS:
 - A. STEEL REINFORCEMENT IN SLAB OR FOUNDATION
- NOTIFY ENGINEER 24 HOURS IN ADVANCE WHEN A STRUCTURAL OBSERVATION IS REQUIRED.

DESIGN CRITERIA

- DESIGN LOADS, STRUCTURAL ANALYSIS AND PREPARATION OF STRUCTURAL MEMBERS ARE BASED ON THE FOLLOWING CRITERIA:
 - CODE: IBC 2018
 - VERTICAL LOADS
 - A. DEAD LOAD: 200 PSF
 - B. MECHANICAL LOAD: THE GENERAL CONTRACTOR SHALL SUBMIT ACTUAL WEIGHTS AND LOCATIONS OF EQUIPMENT TO BE USED IN THE PROJECT TO THE STRUCTURAL ENGINEER FOR VERIFICATION OF LOADS USED IN THE DESIGN AT LEAST TWO WEEKS PRIOR TO FABRICATION AND CONSTRUCTION OF THE SUPPORTING STRUCTURE.
- LATERAL LOADS

A. WIND SPEED (V-ULT):	126 MPH
B. WIND SPEED (U-ASD):	98 MPH
C. EXPOSURE CATEGORY:	C
D. BUILDING CATEGORY:	I
E. SEISMIC DESIGN CATEGORY:	A
F. SITE CLASS:	D
- GEOTECHNICAL ENGINEERING REPORT: NONE PROVIDED

GEOTECHNICAL INVESTIGATION

THE OWNER OF THIS PROJECT HAS DECLINED TO FURNISH A GEOTECHNICAL INVESTIGATION REPORT THEREFORE THE FOUNDATION DESIGN WAS BASED UPON AVERAGE SOIL CONDITIONS IN HIDALGO COUNTY, TEXAS. IF HIGHLY EXPANSIVE SOILS OR SOFT SOILS ARE ENCOUNTERED, DIFFERENTIAL FOUNDATION MOVEMENTS CAN BE EXPECTED. ALTHOUGH WE ATTEMPT TO MAKE ASSUMPTIONS THAT WILL NOT IMPAIR STRUCTURAL INTEGRITY OF THE PROJECT, WE DO NOT HAVE THE EXPERTISE OR BENEFIT OF LABORATORY INVESTIGATIONS OF A GEOTECHNICAL ENGINEER, THEREFORE THIS FIRM CANNOT ASSUME RESPONSIBILITY FOR THE PERFORMANCE OF THE DESIGN. FOUNDATION SHOULD ACTUAL SURFACE OR SUBSURFACE SOIL CONDITIONS VARY FROM THOSE ASSUMED, FOLLOWING ASSUMPTIONS:

- SOIL BEARING PRESSURE (AT PROPOSED SITE) = 1000 PSF

FOUNDATION NOTES

- CONSTRUCTION AREAS REMOVE AT LEAST 24 INCHES OF TOP SOIL, VEGETATION, DEBRIS, ETC., FROM THE PROPOSED BUILDING AREA TO A DISTANCE OF 5'-0" OUTSIDE THE BUILDING LINE PROPOSED.
- EXPOSED SUBGRADE SHOULD BE THOROUGHLY PROOF ROLLED IN ORDER TO LOCATE AND DENSIFY ANY WEAK, COMPRESSIBLE ZONES. WEAK OR SOFT AREAS IDENTIFIED DURING PROOF ROLLING SHOULD BE REMOVED AND REPLACED WITH A SUITABLE, COMPACTION SELECT FILL IN ACCORDANCE WITH THE REQUIREMENTS BELOW. PRIOR TO FILL PLACEMENT, THE EXPOSED SUBGRADE SHOULD BE MOISTURE CONDITIONED BY SCARIFYING TO A MINIMUM DEPTH OF 8" AND RECOMPOSING TO A MINIMUM OF 95% OF THE MAXIMUM DRY DENSITY AS DETERMINED FROM THE ASTM D698 COMPACTION TEST. THE MOISTURE CONTENT SHOULD BE MAINTAINED WITHIN THE OPTIMUM TO 3% ABOVE.
- FILL BACK TO REQUIRED GRADE (A MINIMUM OF 24" OF SELECT FILL IS REQUIRED. REFER TO CIVIL PLANS FOR FINISHED FLOOR ELEVATION TO DETERMINE ADDITIONAL AMOUNT OF SELECT FILL NEEDED) WITH MATERIAL SELECTED AND COMPACTED IN ACCORDANCE WITH THE REQUIREMENTS BELOW.
- SELECT FILL, WHEN PROPERLY SLAKED AND TESTED BY STANDARD LABORATORY METHODS, SHALL MEET THE FOLLOWING REQUIREMENTS:
 - MEET THE TxDOT 2014 STANDARD SPECIFICATION FOR CONSTRUCTION AND MAINTENANCE OF HIGHWAYS, STREETS, AND BRIDGES, ITEM 247 FLEXIBLE BASE, TYPE A, TYPE B, OR TYPE C, GRADES 1 THROUGH 3.

ALTERNATIVELY

- THE FOLLOWING SOILS, AS CLASSIFIED ACCORDING TO THE USCS, MAY BE CONSIDERED SATISFACTORY FOR USE AS SELECT FILL MATERIALS AT THIS SITE: SC, GC, AND COMBINATIONS OF THESE SOILS. IN ADDITION TO THE USCS CLASSIFICATION, ALTERNATIVE SELECT FILL MATERIALS SHALL HAVE A MAXIMUM LIQUID LIMIT OF 35 PERCENT, A PLASTICITY INDEX BETWEEN 5 AND 17 PERCENT, AND A MAXIMUM PARTICLE SIZE NOT EXCEEDING 4 INCHES OR ONE-HALF THE LOOSE LIFT THICKNESS, WHICHEVER IS SMALLER.
- SAMPLES OF PROPOSED SELECT FILL SHALL BE FURNISHED TO THE TESTING LABORATORY 7 DAYS PRIOR TO INSTALLATION TO PERMIT TIME FOR SPECIFICATION COMPLIANCE INSPECTION AND APPROVAL.
- SELECT FILL UNDER ALL FLOORS AND WALKS SHALL BE COMPACTION IN THE FIELD IN LIFTS NOT TO EXCEED 8' TO 98% OF THE MAXIMUM DENSITY, 2% BELOW OR 2% ABOVE OF THE OPTIMUM MOISTURE CONTENT, AS DETERMINED BY TEST METHOD ASTM D698.
- SITE PREPARATION TESTING SHALL BE AS FOLLOWS:
 - A. ATTERBERG LIMITS OF SELECT FILL MATERIAL:
 - (1) ONE TEST PER 5,000 CY
 - B. COMPACTION TEST:
 - TO BE PERFORMED PER LIFT ON TEST PER 3,000 SF MINIMUM OF (4) FOUR TEST PER LIFT
 - FINAL SITE GRADING TO SLOPE AWAY FROM THE STRUCTURE AND SHALL PREVENT WATER FROM PONDING IN THE AREAS ADJACENT TO THE STRUCTURE FOR A MINIMUM DISTANCE OF 10'-0". ANY PONDING CLOSE TO THE STRUCTURE MAY CREATE VOLUMETRIC CHANGES IN THE SOIL AND MAY LEAD TO LESS THAN OPTIMUM PERFORMANCE OF THE BUILDING FOUNDATION.

- IT IS ALSO IMPORTANT TO MINIMIZE CHANGES IN MOISTURE CONTENT CREATED BY ROOF DRAINAGE, PLUMBING LEAKS, LANDSCAPING / IRRIGATION, AND DOWNSPOUT OUTFALLS. ANY PLUMBING LEAKS SHALL BE REPAIRED AS SOON AS POSSIBLE AND PROPER DRAINAGE PROVIDED AWAY FROM THE BUILDING. LARGE BUSHES AND TREES SHALL NOT BE PLACED IN AREAS DIRECTLY ADJACENT TO THE FOUNDATION AS THEIR ROOT SYSTEM MAY CREATE SUBSTANTIAL MOISTURE DIFFERENTIALS THAT MAY LEAD TO VOLUME CHANGES IN THE SOIL. LARGE BUSHES AND TREES SHOULD BE LOCATED AT A REASONABLE DISTANCE FROM THE FOUNDATION.

STEEL REINFORCING

- ALL REINFORCEMENT SHALL BE NEW BILLET STEEL CONFORMING TO ASTM A-615 GRADE 60.
- REINFORCING STEEL SHALL BE DESIGNED, DETAILED, FABRICATED AND PLACED IN ACCORDANCE WITH THE LATEST ACI DETAILING MANUAL (SP-66) AND CSRI MANUAL OF STANDARD PRACTICE FOR DETAILING REINFORCED CONCRETE, (ACI #315) LATEST EDITIONS.
- BARS SCHEDULED OR DETAILED "CONT" SHALL BE SPLICED ONLY WHEN UNAVOIDABLE AT POINTS OF MINIMUM STRESS AND WITH A MINIMUM LAP AS FOLLOWS:
 - A. HORIZONTAL BARS w/ MORE THAN 12" OF FRESH CONCRETE CAST BELOW LAPS:

# 6 BARS AND SMALLER	-	57 BAR DIAMETERS
# 7 BARS AND BIGGER	-	72 BAR DIAMETERS
 - B. OTHER BARS

# 6 BARS AND SMALLER	-	44 BAR DIAMETERS
# 7 BARS AND BIGGER	-	55 BAR DIAMETERS
 - C. ALL SPLICES TO BE STAGGERED A MINIMUM OF 4'-0", TOP BAR AND BOTTOM BAR SPLICES TO BE LOCATED AT MID-SPAN AND WITHIN 1/3 SPAN RESPECTIVELY.
- CORNER REINFORCING BARS SHALL BE USED AT ALL CORNERS AND INTERSECTIONS.
- EXTEND THE SLAB REINFORCING STEEL PERPENDICULAR TO EXTERIOR GRADE BEAM TO THE TOP OUT SIDE REINFORCING BAR OF BEAM.
- SPACE REINFORCING BARS WITH MINIMUM CLEAR SPACING IN ACCORDANCE WITH ACI 318 OF ONE BAR DIAMETER, BUT NOT LESS THAN 1 INCH. FOR COMPRESSION MEMBERS, SPACE AT A MINIMUM OF 1.5 INCHES OR 1.5 BAR DIAMETERS, WHICHEVER IS GREATER.
- WHERE REINFORCING BARS ARE PLACED IN MULTIPLE LAYERS, PLACE UPPER BARS DIRECTLY ABOVE LOWER BARS.
- Maintain concrete cover around reinforcement in accordance with ACI 318 and as follows:
 - A. FOOTING AND CONCRETE CAST AGAINST EARTH
 - B. EXPOSED TO EARTH OR WEATHER
 - C. BEAMS AND COLUMNS
 - D. SLABS AND WALLS

-	3 INCHES
-	2 INCHES
# 5 BARS AND SMALLER	1.5 INCHES
C. BEAMS AND COLUMNS	1.5 INCHES
D. SLABS AND WALLS	1 INCH
- REPAIR ANY DAMAGE TO VAPOR RETARDER PER MANUFACTURER SPECIFICATIONS.
- ADDITIONAL REINFORCING TO BE PROVIDED ON SITE FOR USE AS DIRECTED BY STRUCTURAL ENGINEER.

# 4 BARS	-	100 FT.
# 5 BARS	-	100 FT.
# 6 BARS	-	100 FT.

CONCRETE

- ALL CONCRETE WORK SHALL BE EXECUTED IN ACCORDANCE WITH ACI 318 AND ACI 301 LATEST EDITION.
- CEMENT SHALL CONFORM TO ASTM C150 TYPE I AGGREGATE SHALL CONFORM TO ASTM C33.
- CONCRETE SHALL HAVE A MINIMUM 28 DAYS COMPRESSIVE STRENGTH AS FOLLOWS:

MEMBER TYPE	STRENGTH	SLUMP	MAX AGG.
FOUNDATION	3000 PSI	4"-6"	1.5 IN.
SLAB			
- INSTALL 10 MIL VAPOR RETARDER UNDER SLABS ON GRADE AND ALONG SIDE OF TRENCHES IN ACCORDANCE WITH ASTM E1643. LAP JOINTS MINIMUM OF 12 INCHES.
- PLACE CONCRETE CONTINUOUSLY BETWEEN PRE-DETERMINED EXPANSION AND CONSTRUCTION JOINTS.
- ALL CONSTRUCTION JOINT LOCATIONS TO BE APPROVED BY ARCHITECT AND STRUCTURAL ENGINEER.
- HORIZONTAL CONSTRUCTION JOINTS SHALL NOT BE PERMITTED.
- CURE CONCRETE IN ACCORDANCE WITH ACI 308.1
- REFER TO ARCHITECTURAL AND MECHANICAL PLANS FOR LOCATIONS OF ALL DEPRESSIONS, OPENINGS, ACCESSORIES, ETC.
- CONDUIT AND PLUMBING LINES SHALL BE PLACED BELOW SLAB REINFORCING AND SHALL BE NO BIGGER THAN 1 INCH.
- FLYASH MAY BE USED TO REPLACE A PORTION OF THE PORTLAND CEMENT. THE RATIO OF FLYASH TO THE TOTAL OF THE FLYASH AND CEMENT IN A MIX SHALL NOT EXCEED 20%. FLYASH SHALL CONFORM TO ASTM C618, TYPE C OR F.
- ALL FLOORS SHALL BE CONSTRUCTED WITH A MINIMUM FLATNESS FF = 35 AND A MINIMUM LEVELNESS OF FL = 25
- CONTRACTION JOINTS TO BE INSTALLED WITHIN 12 HOURS OF POURING FOUNDATION.
- TESTING OF CONCRETE SHALL BE DONE AS FOLLOWS:
 - 1) SETS SHALL CONSIST OF 3 CYLINDERS
ONE TESTED AT 7 DAYS
TWO TESTED AT 28 DAYS
 - 2) ONE SET SHALL BE TAKEN FOR EACH 150 CY AND FOR EVERY 5000 SF OF SURFACE AREA AND AT LEAST ONCE PER DAY OF POURING
 - 3) A MINIMUM OF 3 SETS SHALL BE TAKEN FOR EACH CLASS OF CONCRETE
- NO WATER SHALL BE ADDED TO THE CONCRETE AT THE JOBSITE. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE WITH THE CONCRETE SUPPLIER TO ENSURE A PUMPABLE AND WORKABLE MIX WITHOUT THE ADDITION OF WATER AT THE JOBSITE. THE USE OF PLASTICIZERS, RETARDANTS AND OTHER ADDITIVES SHALL BE AT THE OPTION OF THE CONTRACTOR SUBJECT TO THE APPROVAL OF THE STRUCTURAL ENGINEER. FOLLOW THE RECOMMENDATIONS OF THE MANUFACTURER FOR THE PROPER USE OF ADDITIVES. THE USE OF CALCIUM CHLORIDE OR OTHER CHLORIDE BEARING SALTS SHALL NOT BE PERMITTED.
- PLACE CONCRETE IN A MANNER SO AS TO PREVENT SEGREGATION OF THE MIX. DELAY FLOATING AND TROWELING OPERATIONS UNTIL CONCRETE HAS LOST SURFACE WATER SHEEN OR ALL FREE WATER. DO NOT SPRINKLE FREE CEMENT ON THE SLAB SURFACE. FINISHING OF SLAB SURFACES SHALL COMPLY WITH THE RECOMMENDATIONS OF ACI 302.1 AND 304.
- UNLESS SPECIFIED, CONCRETE MUST REACH THE FOLLOWING PERCENTAGES OF ITS 28-DAY COMPRESSIVE STRENGTH (F'c), BEFORE FORMS MAY BE REMOVED.

WALL, COLUMNS, & BEAM SIDES.....	40%
JOIST PANS & BEAM BOTTOMS (IF RESHORED).....	70%
SHORING FOR FLOOR SYSTEMS (IF NOT RESHORED).....	85%
- NO CONCRETE SHALL BE PLACED OUTSIDE OF THESE SPECIFICATIONS WITHOUT THE OWNER'S PRIOR APPROVAL. ANY ITEMS NOT IN COMPLIANCE WITH THE OUTLINED SPECIFICATION SHALL BE REPORTED TO THE OWNER AND STRUCTURAL ENGINEER WITHIN 24 HOURS.
- CONSTRUCTION VEHICLE LOADS SHALL NOT BE PERMITTED ON ELEVATED SLABS AT ANY TIME.
- ALL RETAINING WALLS TO BE SHORED UNTIL UPPER SLAB IS IN PLACE AND HAS REACHED 70% OF ITS DESIGN STRENGTH OR THE RETAINING WALL HAS REACHED 100% OF ITS DESIGN STRENGTH. PROVIDE GRANULAR BACKFILL AND PERFORATED DRAIN PIPE CONNECTED TO SITE DRAINAGE, RE: CIVIL PLAN.

SHOP DRAWINGS & SUBMITTALS

- SUBMITTAL THAT WILL BE REQUIRED FOR APPROVAL INCLUDE:
 - A. CONCRETE MIX DESIGN
 - B. CURING COMPOUND FOR CONCRETE
 - C. REINFORCING STEEL
- ALLOW (2) WEEKS MINIMUM FOR REVIEW OF SHOP DRAWINGS.
- PRIOR TO ISSUING THE SUBMITTALS TO THE ENGINEER, THE CONTRACTOR SHALL REVIEW THE SHOP DRAWINGS. CONTRACTOR MUST VERIFY ALL DIMENSION WITH ARCHITECTURAL PLANS.
- REVIEW OF SHOP DRAWINGS BY THE ENGINEER IS FOR GENERAL CONFORMANCE TO THE STRUCTURAL DRAWINGS. APPROVAL OF THE SHOP DRAWINGS BY THE ENGINEER DOES NOT RELIEVE THE CONTRACTOR FOR ANY ERRORS IN DIMENSIONS OR MATERIAL INDICATED ON THE SHOP DRAWINGS.

CONTRACTOR NOTE


THE STRUCTURAL SYSTEM FOR THIS PROJECT SHALL NOT BE CONSTRUCTED BY USING THE STRUCTURAL DRAWINGS ALONE. THESE DRAWINGS WERE DEVELOPED FROM DATA DERIVED PRIMARILY FROM THE ARCHITECTURAL DRAWINGS AND SECONDARILY FROM MEP, CIVIL AND OTHER DISCIPLINES DOCUMENTS. IT IS INTENDED THAT CONSTRUCTION PROCEED BY UTILIZING ALL OF THE INFORMATION CONTAINED IN THE ENTIRE SET OF CONSTRUCTION DOCUMENTS TAKEN AS A WHOLE. FAILURE TO DO SO WILL RESULT IN ERRORS WHICH SHALL BE CORRECTED AT THE CONTRACTOR'S EXPENSE.

© COPYRIGHT 2024 - ALL RIGHTS RESERVED

These drawings, as instruments of professional service, are the property of Chanin Engineering LLC for use solely with respect to this Project and shall not be reproduced for other purposes.

The Professional Engineer whose seal appears on the structural construction documents is the project Structural Engineer-of-Record (SER) who bears legal responsibility for the performance of the structural framing relating to the public health, safety and welfare. No other party, whether or not a Professional Engineer, may complete, correct, revise, delete or add to these construction documents or perform inspections of the work without the written permission of the SER.

CHANIN
ENGINEERING, LLC
TBPE FIRM REG. NUMBER F-9369
(956) 687-9424
FAX: (956) 687-9411
400 Nolana, Suite N2
McAllen, Texas 78504
www.chaninengineering.com


HECTOR RAMIREZ
103720
PROFESSIONAL ENGINEER
Hector.Perez.6-03-24

PROJECT # : 24195
DATE: 06/03/24
CHECKED BY: HR

REVISION:
△ - - - - -

TEXAS

WISD MEMORIAL ELEMENTARY SCHOOL
HVAC REPLACEMENT


WESLACO

TRINITY
MEP ENGINEERING
8833 Morland Dr, Ste A, Weslaco, Tx 78596
p:956.973.0200 | f:956.351.5750
www.trinitymep.com | Copyright 2022
Texas Registered Engineering Firm - F10362
Project number: 23.140

S1.0

WISD MEMORIAL ELEMENTARY SCHOOL
HVAC REPLACEMENT

WESLACO



FOUNDATION NOTES:

1. CONTRACTOR TO VERIFY ALL DIMENSIONS WITH ARCHITECTURAL PLANS BEFORE COMMENCING WORK.
2. CONTRACTOR TO VERIFY LOCATION OF ANY/ALL DROPS AND DRAINS IN SLAB WITH ARCHITECTURAL DRAWINGS.
3. CONTRACTOR TO VERIFY REQUIRED F.F.E. WITH EXISTING CONDITIONS AND MEP DRAWINGS.



1

FOUNDATION PLAN FOR MEMORIAL ELEMENTARY

SCALE: 1/4"=1'-0"

NOT USED	17	NOT USED	13	EXTERIOR FOOTING	9	PIPE EXTERIOR FOOTING	5	NOT USED	1										
NOT USED	18	NOT USED	14	INTERIOR FOOTING	10	STANDARD HOOKS	6	TYPICAL SLEEVE IN GRADE BEAM	2										
						<p>DIAMETER OF BENDS</p> <table border="1"> <tr><td>STIRRUPS AND TIES</td><td>4 db FOR #3 THRU #5 BARS</td></tr> <tr><td></td><td>6 db FOR #6 THRU #8 BARS</td></tr> <tr><td></td><td>6 db FOR #3 THRU #8 BARS</td></tr> <tr><td></td><td>8 db FOR #9 THRU #11 BARS</td></tr> <tr><td></td><td>10 db FOR #14 THRU #18 BARS</td></tr> </table>	STIRRUPS AND TIES	4 db FOR #3 THRU #5 BARS		6 db FOR #6 THRU #8 BARS		6 db FOR #3 THRU #8 BARS		8 db FOR #9 THRU #11 BARS		10 db FOR #14 THRU #18 BARS			
STIRRUPS AND TIES	4 db FOR #3 THRU #5 BARS																		
	6 db FOR #6 THRU #8 BARS																		
	6 db FOR #3 THRU #8 BARS																		
	8 db FOR #9 THRU #11 BARS																		
	10 db FOR #14 THRU #18 BARS																		
NOT USED	19	NOT USED	15	EXTERIOR FOOTING	11	OPENINGS IN SLAB	7	TYPICAL CORNER BARS	3										
NOT USED	20	NOT USED	16	NOT USED	12	CONTRACTION JOINT DETAIL	8	NOT USED	4										
						<p>1. JOINT PATTERN SHALL BE NEARLY SQUARE 2. JOINT SPACING SHALL NOT EXCEED 15'-0"</p>													

GENERAL NOTES - MECHANICAL:

(1) THE MECHANICAL CONTRACTOR IS FULLY RESPONSIBLE FOR PERFORMING THE WORK IN FULL COMPLIANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL CODES UNDER THIS SECTION OF THE CONTRACT. IF THE CONTRACTOR DETERMINES THAT THE CONTRACT DOCUMENTS AND PLANS ARE NOT IN COMPLIANCE WITH THE APPLICABLE LOCAL CODES, HE/SHE SHALL INFORM THE ENGINEER PRIOR TO CONSTRUCTION START FOR DIRECTION. FAILURE TO DO SO SHALL NOT RELIEVE THE CONTRACTOR OF HIS RESPONSIBILITY TO MEET APPLICABLE LOCAL CODES, AND RE-WORK SHALL BE AT CONTRACTOR'S EXPENSE.

(2) CONTRACTOR SHALL HANG AND INSTALL ALL DUCTWORK FLUSH WITH THE BUILDING STRUCTURE TO ACCOMMODATE NEW CEILINGS. CONTRACTOR SHALL COORDINATE ALL INSTALLATION WORK WITH ARCHITECTURAL AND ELECTRICAL DESIGN. ALL DUCTWORK SHALL BE MODIFIED AS NECESSARY AND REQUIRED TO FIT AROUND BUILDING STRUCTURES, ARCHITECTURAL BUILD-OUT AND ELECTRICAL CABLE TRAY INSTALLATIONS. MECHANICAL CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE WORK SCOPE OF OTHER TRADES AND PARTICIPATE IN COORDINATING ALL CONSTRUCTION EFFORTS.

(3) CONNECT EACH DIFFUSER TO THE MAIN DISTRIBUTION DUCTS WITH A FLEX-DUCT SECTION; CONNECTIONS SHALL BE COMPLETED IN ACCORDANCE WITH THE DETAIL. EACH FLEX-DUCT CONNECTION SHALL INCLUDE A BUTTERFLY DAMPER TO BE INSTALLED AT THE TRUNK DUCT.

(4) CONTRACTOR SHALL PROVIDE ALL DUCTWORK REQUIRED TO COMPLETE THE HVAC SYSTEM. TIE IN BRANCH DUCTS TO MAIN DUCTS WITH SHEET METAL FLANGES. FLANGE CONNECTION SHALL BE FASTENED WITH CRIMPED SHEET METAL STRIPS AND SEALED WITH SILICONE CAULK.

(5) CONTRACTOR SHALL SUPPLY AND INSTALL FIRE DAMPERS AND ACCESS DOORS IN THE HORIZONTAL DUCTS WHERE THEY PENETRATE FIRE WALLS & BARRIERS.

(6) ALL OPENINGS CUT IN MASONRY AND PLASTER WALLS OR CONCRETE FLOORS SHALL BE CORE DRILLED OR SAWED WHEN POSSIBLE. CONTRACTOR SHALL CHECK BUILDING CONSTRUCTION BEFORE MAKING PENETRATIONS TO AVOID CUTTING THROUGH STRUCTURAL BEAMS AND REINFORCING. CONTRACTOR SHALL INFORM THE ENGINEER IF REINFORCING IS CUT OR DAMAGED WHILE MAKING OPENINGS. CONTRACTOR SHALL REINFORCE ALL OPENINGS AS REQUIRED BY DRAWINGS AND SPECIFICATIONS. PATCH AND SEAL OPENINGS WITH 8000 PSI CEMENT GROUT. INSTALL DECORATIVE TRIM (EQUIPMENT FLANGES, FRAMING OR ESCUTCHEONS) AROUND OPENINGS IN FINISHED AREAS. COORDINATE ALL CUTTING AND PATCHING WITH THE OTHER TRADES

(7) ON ANY WORK SHOWN ON MECHANICAL DRAWINGS REQUIRING DEMOLITION OF EXISTING OR NEW BUILDING STRUCTURES AND FINISHES, IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO COMPLETE THE NECESSARY DEMOLITION. CONTRACTOR SHALL PATCH AND REPAIR ALL DEMOLITION WORK. PATCHING SHALL BE COMPLETED WITH THE SAME MATERIALS AS THE SURROUNDING AREAS, OR WITH ARCHITECT-APPROVED PATCHING MATERIALS. REPAIRS SHALL BE COMPLETED ACCORDING TO ARCHITECTURAL SPECIFICATIONS. ALL REFINISHING SHALL BE APPROVED BY THE ARCHITECT.

(8) CONTRACTOR SHALL BE RESPONSIBLE FOR COMPLETING THE INSTALLATION OF THE AIR DISTRIBUTION SYSTEM SHOWN. DUCTWORK, DUCT ACCESSORIES AND CONTROLS SHOWN AND REQUIRED SHALL BE SUPPLIED AND INSTALLED. ALL INSTALLATION WORK SHALL BE DONE IN ACCORDANCE WITH APPLICABLE CODES, INCLUDING NFPA 90A AND 90B. (NFPA 90A: STANDARD FOR THE INSTALLATION OF AIR-CONDITIONING AND VENTILATING SYSTEMS) (NFPA 90B: STANDARD FOR THE INSTALLATION OF WARM AIR HEATING AND AIR-CONDITIONING SYSTEMS)

(9) MOUNT ALL THERMOSTATS (SENSORS) 48" ABOVE THE FINISHED FLOOR LEVEL. THERMOSTATS SHOWN SHALL BE IN CONTROL OF THE ZONE SYSTEM WHICH IS SUPPLYING AIR TO THE AREA WHERE THE THERMOSTAT IS LOCATED. CONTRACTOR SHALL SUPPLY AND INSTALL ALL CONTROL VOLTAGE WIRING AND CONDUIT FOR THERMOSTAT (DDC CONTROL) INSTALLATION.

(10) CONTRACTOR SHALL INSTALL NEW REFRIGERANT PIPING FLUSH WITH THE BUILDING STRUCTURE AND MECHANICAL ROOM BOUNDARIES AS SHOWN. CONTRACTOR SHALL COORDINATE ALL INSTALLATION WORK WITH DUCTS AND ELECTRICAL CONDUIT. MECHANICAL CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE WORK SCOPE OF OTHER TRADES AND PARTICIPATE IN COORDINATING ALL CONSTRUCTION EFFORTS.

(11) ALL PIPING SHALL BE INSULATED AND JACKETED. REFER TO THE SPECIFICATIONS. THE CONDENSING AND ROOF TOP CONDENSER COILS ARE TO BE COATED IN ACCORDANCE WITH THE SPECIFICATIONS.

(12) PROVIDE EACH HVAC SYSTEM OF 2000 CFM & GREATER W/ DUCT SMOKE DETECTOR(S) IN COMPLIANCE WITH IBC 907.2.13.1.2 & 907.3.1 IN RETURN AIR DUCTWORK TO SHUTDOWN CONTROLS ON AIR HANDLERS AND SUPPLY FANS. SMOKE DETECTORS SHALL BE PROVIDED BY MECHANICAL & INSTALLED BY ELECTRICAL (OR REGISTERED FIRE ALARM COMPANY WHERE APPLICABLE). COORDINATE W/ EQUIPMENT MANUFACTURER & AUTHORITY HAVING JURISDICTION FOR RECOMMENDED MOUNTING LOCATION AND METHOD. COORDINATE TO PROVIDE A COMPLETE SYSTEM. PROVIDE BOTH SUPPLY AND RETURN SIDE DEVICES.

(13) CONTRACTOR SHALL INCLUDE ALL COST IN BID TO COMPLETE PROJECT BY NOVEMBER 2024.

(14) INCLUDE ALL COST TO EXPEDITE ALL HVAC EQUIPMENT FOR A DELIVERY TIME OF 20 WEEKS.

(15) FILTER INSTALLATION AND REPLACEMENT

A. INSTALL CONSTRUCTION RETURN FILTER AT EACH RETURN GRILLE BEFORE OPERATING PERMANENT AIR HANDLERS DURING CONSTRUCTION.

B.REPLACE FILTERS AFTER COMPLETING CONSTRUCTION AND BEFORE CONDUCTING BUILDING FLUSH-OUT

1.REPLACE CONSTRUCTION RETURN FILTERS WITH FLUSH-OUT RETURN FILTERS.






2.REPLACE SUPPLY FILTERS.

(16) PRIOR TO START UP

A. CONTRACTOR SHALL FOLLOW THE AIR CONDITIONING EQUIPMENT MANUFACTURER'S STARTUP CHECKLIST.


1. CONTRACTOR SHALL MAKE SURE THAT ALL DUCTWORK & EVAPORATOR COILS ARE CLEAN AND THAT FILTERS ARE PROVIDED FOR EACH UNIT. IF INTERIOR CONDITIONS ARE NOT CLEAN AND AIR BORN DUST IS STILL PRESENT, TEMPORARY FILTERS SHALL BE PROVIDED AT EVERY RETURN AIR GRILLE.

(17) WISD TO PROVIDE TESTING AND BALANCING (TAB).

MECHANICAL SYMBOL LEGEND		MECHANICAL ABBREVIATIONS																																																																																																																																																																																																																																											
		<p>A/C AIR CONDITIONED AD ACCESS DOOR AFF ABOVE FINISHED FLOOR AHU AIR HANDLING UNIT APPROX APPROXIMATE ARCH ARCHITECTURAL BDD BACK DRAFT DAMPER BHP BRAKE HORSEPOWER BTU BRITISH THERMAL UNIT CFM CUBIC FEET PER MINUTE CH CHILLER CHP CHILLED WATER PUMP CLG CEILING CWP CONDENSER WATER PUMP CO CLEANOUT CT COOLING TOWER CU CONDENSING UNIT CW COLD WATER CL CENTER LINE</p>																																																																																																																																																																																																																																											
		<p>MAX MAXIMUM MBD MANUAL BALANCING DAMPER MD MOTORIZED DAMPER MECH MECHANICAL MIN MINIMUM MS MOTOR STARTER NA NOT APPLICABLE NC NORMALLY CLOSED NIC NOT IN CONTRACT NO NORMALLY OPEN NTS NOT TO SCALE</p>																																																																																																																																																																																																																																											
		<p>OA OUTSIDE AIR OAH OUTSIDE AIR INTAKE HOOD OBD OPPOSED BLADE DAMPER OC ON CENTER</p>																																																																																																																																																																																																																																											
		<p>P PUMP PBD PARALLEL BLADE DAMPER PP PRIMARY CHILLED WATER PUMP PRESS PRESSURE PRV PRESSURE REDUCING VALVE PSIG POUNDS PER SQUARE INCH (GAUGE)</p>																																																																																																																																																																																																																																											
		<p>R RETURN (AIR DEVICE) RA RETURN AIR RE: 4M7.01 REFER TO DETAIL 4, SHEET M7.01 RET RETURN RH RELATIVE HUMIDITY RHD RELIEF HOOD RPM REVOLUTIONS PER MINUTE RTU ROOF TOP UNIT</p>																																																																																																																																																																																																																																											
		<p>SUPPLY AIR GRILLE</p>																																																																																																																																																																																																																																											
		<p>SUPPLY AIR GRILLE-SLOT DIFFUSER</p>																																																																																																																																																																																																																																											
		<p>RETURN AIR GRILLE</p>																																																																																																																																																																																																																																											
<p>ALL RETURN AIR DUCT DROPS TO INCLUDE A MANUAL DAMPER</p>		<p>ALL RETURN AIR DUCT DROPS TO INCLUDE A MANUAL DAMPER</p>																																																																																																																																																																																																																																											
		<p>THERMOSTAT TEMPERATURE SENSOR TEMPERATURE OVERRIDE SENSOR/SWITCH</p>																																																																																																																																																																																																																																											
		<p>FIRE DAMPER W/ ACCESSIBLE DUCT ACCESS DOOR FIRE/SMOKE DAMPER W/ ACCESSIBLE DUCT ACCESS DOOR</p>																																																																																																																																																																																																																																											
		<p>FLOW DIRECTION</p>																																																																																																																																																																																																																																											
		<p>PIPE DROP</p>																																																																																																																																																																																																																																											
		<p>PIPE RISE</p>																																																																																																																																																																																																																																											
		<p>RETURN AIR DUCT RISE/DROP</p>																																																																																																																																																																																																																																											
		<p>SUPPLY AIR DUCT RISE/DROP</p>																																																																																																																																																																																																																																											
		<p>WALL OR FLOOR SLEEVE</p>																																																																																																																																																																																																																																											
		<p>CHILLED WATER SUPPLY/RETURN PIPING</p>																																																																																																																																																																																																																																											
		<p>SQUARE TO ROUND DUCT TRANSITION</p>																																																																																																																																																																																																																																											
<p>MECHANICAL ABBREVIATIONS</p>																																																																																																																																																																																																																																													
<table> <tbody> <tr> <td>A/C</td><td>AIR CONDITIONED</td><td>MAX</td><td>MAXIMUM</td></tr> <tr> <td>AD</td><td>ACCESS DOOR</td><td>MBD</td><td>MANUAL BALANCING DAMPER</td></tr> <tr> <td>AFF</td><td>ABOVE FINISHED FLOOR</td><td>MD</td><td>MOTORIZED DAMPER</td></tr> <tr> <td>AHU</td><td>AIR HANDLING UNIT</td><td>MECH</td><td>MECHANICAL</td></tr> <tr> <td>APPROX</td><td>APPROXIMATE</td><td>MIN</td><td>MINIMUM</td></tr> <tr> <td>ARCH</td><td>ARCHITECTURAL</td><td>MS</td><td>MOTOR STARTER</td></tr> <tr> <td>BDD</td><td>BACK DRAFT DAMPER</td><td>NA</td><td>NOT APPLICABLE</td></tr> <tr> <td>BHP</td><td>BRAKE HORSEPOWER</td><td>NC</td><td>NORMALLY CLOSED</td></tr> <tr> <td>BTU</td><td>BRITISH THERMAL UNIT</td><td>NIC</td><td>NOT IN CONTRACT</td></tr> <tr> <td>CFM</td><td>CUBIC FEET PER MINUTE</td><td>NO</td><td>NORMALLY OPEN</td></tr> <tr> <td>CH</td><td>CHILLER</td><td>NTS</td><td>NOT TO SCALE</td></tr> <tr> <td>CHP</td><td>CHILLED WATER PUMP</td><td>OA</td><td>OUTSIDE AIR</td></tr> <tr> <td>CLG</td><td>CEILING</td><td>OAH</td><td>OUTSIDE AIR INTAKE HOOD</td></tr> <tr> <td>CWP</td><td>CONDENSER WATER PUMP</td><td>OBD</td><td>OPPOSED BLADE DAMPER</td></tr> <tr> <td>CO</td><td>CLEANOUT</td><td>OC</td><td>ON CENTER</td></tr> <tr> <td>CT</td><td>COOLING TOWER</td><td>P</td><td>PUMP</td></tr> <tr> <td>CU</td><td>CONDENSING UNIT</td><td>PBD</td><td>PARALLEL BLADE DAMPER</td></tr> <tr> <td>CW</td><td>COLD WATER</td><td>PP</td><td>PRIMARY CHILLED WATER PUMP</td></tr> <tr> <td>CL</td><td>CENTER LINE</td><td>PRESS</td><td>PRESSURE</td></tr> <tr> <td>DB</td><td>DRY BULB</td><td>PRV</td><td>PRESSURE REDUCING VALVE</td></tr> <tr> <td>DIA</td><td>DIAMETER</td><td>PSIG</td><td>POUNDS PER SQUARE INCH (GAUGE)</td></tr> <tr> <td>DN</td><td>DOWN</td><td>R</td><td>RETURN (AIR DEVICE)</td></tr> <tr> <td>DWG</td><td>DRAWING</td><td>RA</td><td>RETURN AIR</td></tr> <tr> <td>DX</td><td>DIRECT EXPANSION</td><td>RE: 4M7.01</td><td>REFER TO DETAIL 4, SHEET M7.01</td></tr> <tr> <td>EA</td><td>EXHAUST AIR</td><td>RET</td><td>RETURN</td></tr> <tr> <td>EAT</td><td>ENTERING AIR TEMPERATURE</td><td>RH</td><td>RELATIVE HUMIDITY</td></tr> <tr> <td>EDH</td><td>ELECTRIC DUCT HEATER</td><td>RHD</td><td>RELIEF HOOD</td></tr> <tr> <td>EF</td><td>EXHAUST FAN</td><td>RPM</td><td>REVOLUTIONS PER MINUTE</td></tr> <tr> <td>ELEC</td><td>ELECTRICAL</td><td>RTU</td><td>ROOF TOP UNIT</td></tr> <tr> <td>ELEV</td><td>ELEVATION</td><td>S</td><td>SUPPLY (AIR DEVICE)</td></tr> <tr> <td>F</td><td>DEGREES FAHRENHEIT</td><td>SA</td><td>SUPPLY AIR</td></tr> <tr> <td>FC</td><td>FAN COIL</td><td>SCH</td><td>SCHEDULE</td></tr> <tr> <td>FD</td><td>FIRE DAMPER W/ DUCT ACCESS DOOR</td><td>SCHP</td><td>SECONDARY CHILLED WATER PUMP</td></tr> <tr> <td>FLEX</td><td>FLEXIBLE</td><td>SD</td><td>SMOKE DAMPER</td></tr> <tr> <td>FLG</td><td>FLANGE</td><td>SEC</td><td>SECOND</td></tr> <tr> <td>FLR</td><td>FLOOR</td><td>SF</td><td>SUPPLY FAN</td></tr> <tr> <td>FPM</td><td>FEET PER MINUTE</td><td>SMACNA</td><td>SHEET METAL AND AIR CONDITIONING CONTRACTORS NATIONAL ASSOCIATION</td></tr> <tr> <td>FT</td><td>FEET, FOOT</td><td>SP</td><td>STATIC PRESSURE</td></tr> <tr> <td>FS</td><td>FLOW SWITCH</td><td>SPEC</td><td>SPECIFICATION</td></tr> <tr> <td>GAL</td><td>GALLON</td><td>SF</td><td>SQUARE FOOT</td></tr> <tr> <td>GALV</td><td>GALVANIZED</td><td>STD</td><td>STANDARD</td></tr> <tr> <td>GPM</td><td>GALLONS PER MINUTE</td><td>TEMP</td><td>TEMPERATURE</td></tr> <tr> <td>HB</td><td>HOSE BIBB</td><td>T'STAT</td><td>THERMOSTAT</td></tr> <tr> <td>HP</td><td>HORSEPOWER</td><td>TYP</td><td>TYPICAL</td></tr> <tr> <td>HR</td><td>HEAT PUMP (WATER SOURCE)</td><td>UF</td><td>UNDER FLOOR</td></tr> <tr> <td>HR</td><td>HOUR</td><td>UH</td><td>UNIT HEATER</td></tr> <tr> <td>HVAC</td><td>HEATING/VENTILATING/AIR CONDITIONING</td><td>UL</td><td>UNDERWRITERS LABORATORIES</td></tr> <tr> <td>HWP</td><td>HOT WATER PUMP</td><td>VEL</td><td>VELOCITY</td></tr> <tr> <td>HZ</td><td>HERTZ</td><td>VENT</td><td>VENTILATE</td></tr> <tr> <td>ID</td><td>INSIDE DIAMETER</td><td>VF</td><td>VENTILATION FAN</td></tr> <tr> <td>IE</td><td>INVERT ELEVATION (FLOW LINE)</td><td>VOL</td><td>VOLUME</td></tr> <tr> <td>IN</td><td>INCHES</td><td>VOLT</td><td>VOLTAGE</td></tr> <tr> <td>INSUL</td><td>INSULATION</td><td>W</td><td>WIDE, WIDTH</td></tr> <tr> <td>IN WG</td><td>INCHES OF WATER</td><td>W/</td><td>WITH</td></tr> <tr> <td>KW</td><td>KILOWATT(S)</td><td>WB</td><td>WET BULB</td></tr> <tr> <td>LAT</td><td>LEAVING AIR TEMPERATURE</td><td>W/O</td><td>WITHOUT</td></tr> <tr> <td>LB</td><td>POUND</td><td></td><td></td></tr> <tr> <td>L</td><td>LOUVER</td><td></td><td></td></tr> </tbody> </table>						A/C	AIR CONDITIONED	MAX	MAXIMUM	AD	ACCESS DOOR	MBD	MANUAL BALANCING DAMPER	AFF	ABOVE FINISHED FLOOR	MD	MOTORIZED DAMPER	AHU	AIR HANDLING UNIT	MECH	MECHANICAL	APPROX	APPROXIMATE	MIN	MINIMUM	ARCH	ARCHITECTURAL	MS	MOTOR STARTER	BDD	BACK DRAFT DAMPER	NA	NOT APPLICABLE	BHP	BRAKE HORSEPOWER	NC	NORMALLY CLOSED	BTU	BRITISH THERMAL UNIT	NIC	NOT IN CONTRACT	CFM	CUBIC FEET PER MINUTE	NO	NORMALLY OPEN	CH	CHILLER	NTS	NOT TO SCALE	CHP	CHILLED WATER PUMP	OA	OUTSIDE AIR	CLG	CEILING	OAH	OUTSIDE AIR INTAKE HOOD	CWP	CONDENSER WATER PUMP	OBD	OPPOSED BLADE DAMPER	CO	CLEANOUT	OC	ON CENTER	CT	COOLING TOWER	P	PUMP	CU	CONDENSING UNIT	PBD	PARALLEL BLADE DAMPER	CW	COLD WATER	PP	PRIMARY CHILLED WATER PUMP	CL	CENTER LINE	PRESS	PRESSURE	DB	DRY BULB	PRV	PRESSURE REDUCING VALVE	DIA	DIAMETER	PSIG	POUNDS PER SQUARE INCH (GAUGE)	DN	DOWN	R	RETURN (AIR DEVICE)	DWG	DRAWING	RA	RETURN AIR	DX	DIRECT EXPANSION	RE: 4M7.01	REFER TO DETAIL 4, SHEET M7.01	EA	EXHAUST AIR	RET	RETURN	EAT	ENTERING AIR TEMPERATURE	RH	RELATIVE HUMIDITY	EDH	ELECTRIC DUCT HEATER	RHD	RELIEF HOOD	EF	EXHAUST FAN	RPM	REVOLUTIONS PER MINUTE	ELEC	ELECTRICAL	RTU	ROOF TOP UNIT	ELEV	ELEVATION	S	SUPPLY (AIR DEVICE)	F	DEGREES FAHRENHEIT	SA	SUPPLY AIR	FC	FAN COIL	SCH	SCHEDULE	FD	FIRE DAMPER W/ DUCT ACCESS DOOR	SCHP	SECONDARY CHILLED WATER PUMP	FLEX	FLEXIBLE	SD	SMOKE DAMPER	FLG	FLANGE	SEC	SECOND	FLR	FLOOR	SF	SUPPLY FAN	FPM	FEET PER MINUTE	SMACNA	SHEET METAL AND AIR CONDITIONING CONTRACTORS NATIONAL ASSOCIATION	FT	FEET, FOOT	SP	STATIC PRESSURE	FS	FLOW SWITCH	SPEC	SPECIFICATION	GAL	GALLON	SF	SQUARE FOOT	GALV	GALVANIZED	STD	STANDARD	GPM	GALLONS PER MINUTE	TEMP	TEMPERATURE	HB	HOSE BIBB	T'STAT	THERMOSTAT	HP	HORSEPOWER	TYP	TYPICAL	HR	HEAT PUMP (WATER SOURCE)	UF	UNDER FLOOR	HR	HOUR	UH	UNIT HEATER	HVAC	HEATING/VENTILATING/AIR CONDITIONING	UL	UNDERWRITERS LABORATORIES	HWP	HOT WATER PUMP	VEL	VELOCITY	HZ	HERTZ	VENT	VENTILATE	ID	INSIDE DIAMETER	VF	VENTILATION FAN	IE	INVERT ELEVATION (FLOW LINE)	VOL	VOLUME	IN	INCHES	VOLT	VOLTAGE	INSUL	INSULATION	W	WIDE, WIDTH	IN WG	INCHES OF WATER	W/	WITH	KW	KILOWATT(S)	WB	WET BULB	LAT	LEAVING AIR TEMPERATURE	W/O	WITHOUT	LB	POUND			L	LOUVER		
A/C	AIR CONDITIONED	MAX	MAXIMUM																																																																																																																																																																																																																																										
AD	ACCESS DOOR	MBD	MANUAL BALANCING DAMPER																																																																																																																																																																																																																																										
AFF	ABOVE FINISHED FLOOR	MD	MOTORIZED DAMPER																																																																																																																																																																																																																																										
AHU	AIR HANDLING UNIT	MECH	MECHANICAL																																																																																																																																																																																																																																										
APPROX	APPROXIMATE	MIN	MINIMUM																																																																																																																																																																																																																																										
ARCH	ARCHITECTURAL	MS	MOTOR STARTER																																																																																																																																																																																																																																										
BDD	BACK DRAFT DAMPER	NA	NOT APPLICABLE																																																																																																																																																																																																																																										
BHP	BRAKE HORSEPOWER	NC	NORMALLY CLOSED																																																																																																																																																																																																																																										
BTU	BRITISH THERMAL UNIT	NIC	NOT IN CONTRACT																																																																																																																																																																																																																																										
CFM	CUBIC FEET PER MINUTE	NO	NORMALLY OPEN																																																																																																																																																																																																																																										
CH	CHILLER	NTS	NOT TO SCALE																																																																																																																																																																																																																																										
CHP	CHILLED WATER PUMP	OA	OUTSIDE AIR																																																																																																																																																																																																																																										
CLG	CEILING	OAH	OUTSIDE AIR INTAKE HOOD																																																																																																																																																																																																																																										
CWP	CONDENSER WATER PUMP	OBD	OPPOSED BLADE DAMPER																																																																																																																																																																																																																																										
CO	CLEANOUT	OC	ON CENTER																																																																																																																																																																																																																																										
CT	COOLING TOWER	P	PUMP																																																																																																																																																																																																																																										
CU	CONDENSING UNIT	PBD	PARALLEL BLADE DAMPER																																																																																																																																																																																																																																										
CW	COLD WATER	PP	PRIMARY CHILLED WATER PUMP																																																																																																																																																																																																																																										
CL	CENTER LINE	PRESS	PRESSURE																																																																																																																																																																																																																																										
DB	DRY BULB	PRV	PRESSURE REDUCING VALVE																																																																																																																																																																																																																																										
DIA	DIAMETER	PSIG	POUNDS PER SQUARE INCH (GAUGE)																																																																																																																																																																																																																																										
DN	DOWN	R	RETURN (AIR DEVICE)																																																																																																																																																																																																																																										
DWG	DRAWING	RA	RETURN AIR																																																																																																																																																																																																																																										
DX	DIRECT EXPANSION	RE: 4M7.01	REFER TO DETAIL 4, SHEET M7.01																																																																																																																																																																																																																																										
EA	EXHAUST AIR	RET	RETURN																																																																																																																																																																																																																																										
EAT	ENTERING AIR TEMPERATURE	RH	RELATIVE HUMIDITY																																																																																																																																																																																																																																										
EDH	ELECTRIC DUCT HEATER	RHD	RELIEF HOOD																																																																																																																																																																																																																																										
EF	EXHAUST FAN	RPM	REVOLUTIONS PER MINUTE																																																																																																																																																																																																																																										
ELEC	ELECTRICAL	RTU	ROOF TOP UNIT																																																																																																																																																																																																																																										
ELEV	ELEVATION	S	SUPPLY (AIR DEVICE)																																																																																																																																																																																																																																										
F	DEGREES FAHRENHEIT	SA	SUPPLY AIR																																																																																																																																																																																																																																										
FC	FAN COIL	SCH	SCHEDULE																																																																																																																																																																																																																																										
FD	FIRE DAMPER W/ DUCT ACCESS DOOR	SCHP	SECONDARY CHILLED WATER PUMP																																																																																																																																																																																																																																										
FLEX	FLEXIBLE	SD	SMOKE DAMPER																																																																																																																																																																																																																																										
FLG	FLANGE	SEC	SECOND																																																																																																																																																																																																																																										
FLR	FLOOR	SF	SUPPLY FAN																																																																																																																																																																																																																																										
FPM	FEET PER MINUTE	SMACNA	SHEET METAL AND AIR CONDITIONING CONTRACTORS NATIONAL ASSOCIATION																																																																																																																																																																																																																																										
FT	FEET, FOOT	SP	STATIC PRESSURE																																																																																																																																																																																																																																										
FS	FLOW SWITCH	SPEC	SPECIFICATION																																																																																																																																																																																																																																										
GAL	GALLON	SF	SQUARE FOOT																																																																																																																																																																																																																																										
GALV	GALVANIZED	STD	STANDARD																																																																																																																																																																																																																																										
GPM	GALLONS PER MINUTE	TEMP	TEMPERATURE																																																																																																																																																																																																																																										
HB	HOSE BIBB	T'STAT	THERMOSTAT																																																																																																																																																																																																																																										
HP	HORSEPOWER	TYP	TYPICAL																																																																																																																																																																																																																																										
HR	HEAT PUMP (WATER SOURCE)	UF	UNDER FLOOR																																																																																																																																																																																																																																										
HR	HOUR	UH	UNIT HEATER																																																																																																																																																																																																																																										
HVAC	HEATING/VENTILATING/AIR CONDITIONING	UL	UNDERWRITERS LABORATORIES																																																																																																																																																																																																																																										
HWP	HOT WATER PUMP	VEL	VELOCITY																																																																																																																																																																																																																																										
HZ	HERTZ	VENT	VENTILATE																																																																																																																																																																																																																																										
ID	INSIDE DIAMETER	VF	VENTILATION FAN																																																																																																																																																																																																																																										
IE	INVERT ELEVATION (FLOW LINE)	VOL	VOLUME																																																																																																																																																																																																																																										
IN	INCHES	VOLT	VOLTAGE																																																																																																																																																																																																																																										
INSUL	INSULATION	W	WIDE, WIDTH																																																																																																																																																																																																																																										
IN WG	INCHES OF WATER	W/	WITH																																																																																																																																																																																																																																										
KW	KILOWATT(S)	WB	WET BULB																																																																																																																																																																																																																																										
LAT	LEAVING AIR TEMPERATURE	W/O	WITHOUT																																																																																																																																																																																																																																										
LB	POUND																																																																																																																																																																																																																																												
L	LOUVER																																																																																																																																																																																																																																												

APPLICABLE CODES

INDEX OF SHEETS	
MG01	MECHANICAL NOTES & LEGEND
MMDP01	MECHANICAL OVERALL DEMO PLAN
MMDP02	MECHANICAL DEMOLITION ROOF PLAN
MMDP03	MECHANICAL DEMOLITION PLAN
MMDP04	MECHANICAL DEMOLITION PLAN
MMDP05	MECHANICAL DEMOLITION PLAN
MMSP01	MECHANICAL SITE PLAN
MMP01	MECHANICAL OVERALL FLOOR PLAN
MMP02	MECHANICAL ROOF PLAN
MMP03	MECHANICAL FLOOR PLAN
MMP04	MECHANICAL FLOOR PLAN
MMP05	MECHANICAL FLOOR PLAN
MMS01	MECHANICAL SCHEDULES
MMS02	MECHANICAL SCHEDULES
MMS03	MECHANICAL SCHEDULES
MMS04	MECHANICAL SCHEDULES
MMD01	MECHANICAL DETAILS
MMD02	MECHANICAL DETAILS
MMC01	MECHANICAL CONTROLS
MMC02	MECHANICAL CONTROLS
MMC03	MECHANICAL CONTROLS
MMC04	MECHANICAL CONTROLS
MMC05	MECHANICAL CONTROLS
MMC06	MECHANICAL CONTROLS
MMC07	MECHANICAL CONTROLS
MMC08	MECHANICAL CONTROLS



GENERAL DEMOLITION NOTES

- A. THE EXTENT OF DEMOLITION WORK IS INDICATED ON THE ENGINEER DRAWINGS AND BY THE REQUIREMENTS OF THIS SECTION. A VISIT TO THE SITE WILL BE REQUIRED TO PROPERLY BID THE DEMOLITION WORK.
- B. PROVIDE ALL DEMOLITION WORK REQUIRED FOR THE REMOVAL AND/OR RELOCATION OF HVAC FIXTURES AND EQUIPMENTS AND ASSOCIATED SERVICES TO PROVIDE A COMPLETE AND OPERABLE SYSTEM UPON COMPLETION OF THE PROJECT.
- C. MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW THE ENGINEER DOCUMENTS IN ADDITION TO THE DIVISION 15 AND 16 DOCUMENTS TO DETERMINE THE COMPLETE SCOPE OF WORK.
- D. WHERE EQUIPMENT IS INDICATED OR REQUIRED TO BE REMOVED, THE ASSOCIATED SERVICES SHALL BE CAPPED AT A CONCEALED LOCATION.
- E. WHERE SERVICES RUN ABOVE INACCESSIBLE CEILINGS OR IN WALLS WHICH ARE TO REMAIN UNDISTURBED, SERVICES SHALL BE CAPPED AT CONCEALED LOCATION AND ABANDONED
- F. WHERE THE REMOVAL OF EQUIPMENT RENDERS EQUIPMENT DOWNSTREAM INOPERABLE, SERVICES SHALL BE EXTENDED TO THE DOWNSTREAM EQUIPMENT SO THAT THE FIXTURES ARE LEFT IN OPERATING CONDITION.
- G. COORDINATE DEMOLITION OF DIVISION 15 SYSTEMS AS REQUIRED WITH ALL OTHER TRADES.
- H. ALL EXISTING H.V.A.C. AND EQUIPMENT REMOVED DURING CONSTRUCTION THAT ARE NOT TO BE REUSED SHALL BE REMOVED FROM THE JOB SITE AND PROPERLY RETURNED TO THE OWNER, IF DESIRED BY OWNER.
- I. WHERE EXISTING EQUIPMENT IS TO BE RELOCATED, BE CAUTIOUS TO PREVENT DAMAGE DURING THE REMOVAL AND REINSTALLATION. WHERE DAMAGE OCCURS, THE EQUIPMENT SHALL BE REPLACED OR REPAIRED TO THE SATISFACTION AND APPROVAL OF THE ENGINEER AT NO ADDITIONAL COST TO THE OWNER.
- J. EXISTING EQUIPMENT TO BE REUSED SHALL BE CLEANED AND REPAIRED AT THE DISCRETION OF THE ENGINEER WHERE APPLICABLE.
- K. ALL DEVICES ATTACHED TO WALLS OR CEILINGS SHALL BE REMOVED PER DEMOLITION NOTE A - M WHETHER SHOWN ON DRAWINGS OR NOT.
- L. CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE. ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.
- M. REMOVE PARTIAL EXISTING CEILING TILES AND GRID BENEATH DUCT RUNS ONLY. STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE: MEP FOR ADDT. INFO.
- N. ALL EXISTING INDOOR AIR HANDLING UNITS SHALL HAVE THEIR EXISTING CONCRETE PADS DEMOLISHED & DISPOSED OF. ANY/ALL FLOOR DAMAGE UNDER REMOVED CONCRETE PADS TO BE REPAIRED.

KEYED NOTES: MECHANICAL DEMOLITION

- 1 EXISTING FAN TO BE DEMOLISHED AND REPLACED.
- 2 EXISTING AIR HANDLING UNIT/CONDENSER EQUIPMENT TO BE DEMOLISHED AND REPLACED. RETURN COMPONENTS TO OWNER IF OWNER SO DESIRES.
- 3 ALL INDICATED EXISTING OUTSIDE AIR DUCTWORK AND LOUVERS TO BE DEMOLISHED AND REPLACED. PATCH ANY ABANDONED/EXCESS LOUVER OPENINGS W/ CONSTRUCTION MATERIALS TO MATCH EXISTING CONSTRUCTION MATERIALS AND DESIGN. COORDINATE PATCHWORK W/ OWNER THROUGH ENGINEER PRIOR TO COMMENCING WORK AHEAD OF TIME.
- 4 DEMOLISH INDICATED SA/RA DUCTWORK.
- 5 DEMOLISH INDICATED EXISTING MOTORIZED ZONE DAMPER, TO BE REPLACED WITH NEW VAV BOX. REFER TO REMODEL PLAN.
- 6 EXISTING THERMOSTAT/TEMP SENSORS TO BE REPLACED WITH NEW HVAC CONTROLS TEMP/RH%/CO2 SENSOR. RETURN ALL EQUIPMENT TO OWNER.
- 7 CAP, SEAL AND INSULATE BYPASS AIR OPENINGS IN SA/RA DUCTWORK.
- 8 EXISTING OUTSIDE AIR DUCT TO BE DEMOLISHED. CAP, SEAL AND INSULATE OPENING IN DUCTWORK.
- 9 EXISTING INDICATED AIR DEVICE TO BE REPLACED WITH NEW.
- 10 EXISTING DUCTWORK AND AIR DEVICES TO REMAIN.
- 11 EXISTING CONTROLS/ENCLOSURES TO BE REMOVED AND REPLACED WITH NEW HVAC CONTROLS.
- 12 BATTERY BACKUP SYSTEM TO REMAIN.
- 13 INDICATED IT RACK TO BE RELOCATED BY WISD. COORDINATE WITH OWNER.
- 14 INDICATED IT RACK TO REMAIN, COORDINATE W/ OWNER. INDICATED CONTROLS ENCLOSURE & DEVICES TO BE RETURNED TO OWNER IN CONDITION IT WAS FOUND IN PRIOR TO DEMOLITION
- 15 EXISTING HOODS TO REMAIN.
- 16 EXISTING REFRIGERATION CONDENSERS TO REMAIN.
- 17 NEW GRILLE TO REPLACE EXISTING

1 MECHANICAL OVERALL DEMOLITION PLAN


SCALE: 1" = 30'-0"

GENERAL DEMOLITION NOTES

- A. THE EXTENT OF DEMOLITION WORK IS INDICATED ON THE ENGINEER DRAWINGS AND BY THE REQUIREMENTS OF THIS SECTION. A VISIT TO THE SITE WILL BE REQUIRED TO PROPERLY BID THE DEMOLITION WORK.
- B. PROVIDE ALL DEMOLITION WORK REQUIRED FOR THE REMOVAL AND/OR RELOCATION OF HVAC FIXTURES AND EQUIPMENTS AND ASSOCIATED SERVICES TO PROVIDE A COMPLETE AND OPERABLE SYSTEM UPON COMPLETION OF THE PROJECT.
- C. MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW THE ENGINEER DOCUMENTS IN ADDITION TO THE DIVISION 15 AND 16 DOCUMENTS TO DETERMINE THE COMPLETE SCOPE OF WORK.
- D. WHERE EQUIPMENT IS INDICATED OR REQUIRED TO BE REMOVED, THE ASSOCIATED SERVICES SHALL BE CAPPED AT A CONCEALED LOCATION.
- E. WHERE SERVICES RUN ABOVE INACCESSIBLE CEILINGS OR IN WALLS WHICH ARE TO REMAIN UNDISTURBED, SERVICES SHALL BE CAPPED AT CONCEALED LOCATION AND ABANDONED
- F. WHERE THE REMOVAL OF EQUIPMENT RENDERS EQUIPMENT DOWNSTREAM INOPERABLE, SERVICES SHALL BE EXTENDED TO THE DOWNSTREAM EQUIPMENT SO THAT THE FIXTURES ARE LEFT IN OPERATING CONDITION.
- G. COORDINATE DEMOLITION OF DIVISION 15 SYSTEMS AS REQUIRED WITH ALL OTHER TRADES.
- H. ALL EXISTING H.V.A.C. AND EQUIPMENT REMOVED DURING CONSTRUCTION THAT ARE NOT TO BE REUSED SHALL BE REMOVED FROM THE JOB SITE AND PROPERLY RETURNED TO THE OWNER, IF DESIRED BY OWNER.
- I. WHERE EXISTING EQUIPMENT IS TO BE RELOCATED, BE CAUTIOUS TO PREVENT DAMAGE DURING THE REMOVAL AND REINSTALLATION. WHERE DAMAGE OCCURS, THE EQUIPMENT SHALL BE REPLACED OR REPAIRED TO THE SATISFACTION AND APPROVAL OF THE ENGINEER AT NO ADDITIONAL COST TO THE OWNER.
- J. EXISTING EQUIPMENT TO BE REUSED SHALL BE CLEANED AND REPAIRED AT THE DISCRETION OF THE ENGINEER WHERE APPLICABLE.
- K. ALL DEVICES ATTACHED TO WALLS OR CEILINGS SHALL BE REMOVED PER DEMOLITION NOTE A - M WHETHER SHOWN ON DRAWINGS OR NOT.
- L. CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE. ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.
- M. REMOVE PARTIAL EXISTING CEILING TILES AND GRID BENEATH DUCT RUNS ONLY. STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE: MEP FOR ADDT. INFO.
- N. ALL EXISTING INDOOR AIR HANDLING UNITS SHALL HAVE THEIR EXISTING CONCRETE PADS DEMOLISHED & DISPOSED OF. ANY/ALL FLOOR DAMAGE UNDER REMOVED CONCRETE PADS TO BE REPAIRED.


KEYED NOTES: MECHANICAL DEMOLITION

- 1 EXISTING FAN TO BE DEMOLISHED AND REPLACED.
- 2 EXISTING AIR HANDLING UNIT/CONDENSER EQUIPMENT TO BE DEMOLISHED AND REPLACED. RETURN COMPONENTS TO OWNER IF OWNER SO DESIRES.
- 3 ALL INDICATED EXISTING OUTSIDE AIR DUCTWORK AND LOUVERS TO BE DEMOLISHED AND REPLACED. PATCH ANY ABANDONED/EXCESS LOUVER OPENINGS W/ CONSTRUCTION MATERIALS TO MATCH EXISTING CONSTRUCTION MATERIALS AND DESIGN. COORDINATE PATCHWORK W/ OWNER THROUGH ENGINEER PRIOR TO COMMENCING WORK AHEAD OF TIME.
- 4 DEMOLISH INDICATED SA/RA DUCTWORK.
- 5 DEMOLISH INDICATED EXISTING MOTORIZED ZONE DAMPER, TO BE REPLACED WITH NEW VAV BOX. REFER TO REMODEL PLAN.
- 6 EXISTING THERMOSTAT/TEMP SENSORS TO BE REPLACED WITH NEW HVAC CONTROLS TEMP/RH%/CO2 SENSOR. RETURN ALL EQUIPMENT TO OWNER.
- 7 CAP, SEAL AND INSULATE BYPASS AIR OPENINGS IN SA/RA DUCTWORK.
- 8 EXISTING OUTSIDE AIR DUCT TO BE DEMOLISHED. CAP, SEAL AND INSULATE OPENING IN DUCTWORK.
- 9 EXISTING INDICATED AIR DEVICE TO BE REPLACED WITH NEW.
- 10 EXISTING DUCTWORK AND AIR DEVICES TO REMAIN.
- 11 EXISTING CONTROLS/ENCLOSURES TO BE REMOVED AND REPLACED WITH NEW HVAC CONTROLS.
- 12 BATTERY BACKUP SYSTEM TO REMAIN.
- 13 INDICATED IT RACK TO BE RELOCATED BY WISD. COORDINATE WITH OWNER.
- 14 INDICATED IT RACK TO REMAIN, COORDINATE W/ OWNER. INDICATED CONTROLS ENCLOSURE & DEVICES TO BE RETURNED TO OWNER IN CONDITION IT WAS FOUND IN PRIOR TO DEMOLITION
- 15 EXISTING HOODS TO REMAIN.
- 16 EXISTING REFRIGERATION CONDENSERS TO REMAIN.
- 17 NEW GRILLE TO REPLACE EXISTING.




1 MECHANICAL DEMOLITION ROOF PLAN


SCALE: 1" = 30'-0"




MMDP02




2 MECHANICAL ROOM - LIBRARY
SCALE: 3/16" = 1'-0"




3 MECHANICAL ROOM - CAFETERIA
SCALE: 3/16" = 1'-0"




4 ROOF ENLARGED VIEW - LIBRARY/CAFE
SCALE: 3/16" = 1'-0"



5 ROOF ENLARGED VIEW - KITCHEN
SCALE: 3/16" = 1'-0"



1 MECHANICAL DEMOLITION PLAN - LIBRARY & CAFETERIA SECTION
SCALE: 3/32" = 1'-0"




GENERAL DEMOLITION NOTES

- A. THE EXTENT OF DEMOLITION WORK IS INDICATED ON THE ENGINEER DRAWINGS AND BY THE REQUIREMENTS OF THIS SECTION. A VISIT TO THE SITE WILL BE REQUIRED TO PROPERLY BID THE DEMOLITION WORK.
- B. PROVIDE ALL DEMOLITION WORK REQUIRED FOR THE REMOVAL AND/OR RELOCATION OF HVAC FIXTURES AND EQUIPMENT AND ASSOCIATED SERVICES TO PROVIDE A COMPLETE AND OPERABLE SYSTEM UPON COMPLETION OF THE PROJECT.
- C. MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW THE ENGINEER DOCUMENTS IN ADDITION TO THE DIVISION 15 AND 16 DOCUMENTS TO DETERMINE THE COMPLETE SCOPE OF WORK.
- D. WHERE EQUIPMENT IS INDICATED OR REQUIRED TO BE REMOVED, THE ASSOCIATED SERVICES SHALL BE CAPED AT A CONCEALED LOCATION.
- E. WHERE SERVICES RUN ABOVE INACCESSIBLE CEILINGS OR IN WALLS WHICH ARE TO REMAIN UNDISTURBED, SERVICES SHALL BE CAPED AT CONCEALED LOCATION AND ABANDONED.
- F. WHERE THE REMOVAL OF EQUIPMENT renders equipment downstream inoperable, services shall be extended to the downstream equipment so that the fixtures are left in operating condition.
- G. COORDINATE DEMOLITION OF DIVISION 15 SYSTEMS AS REQUIRED WITH ALL OTHER TRADES.
- H. ALL EXISTING H.V.A.C. AND EQUIPMENT REMOVED DURING CONSTRUCTION THAT ARE NOT TO BE REUSED SHALL BE REMOVED FROM THE JOB SITE AND PROPERLY RETURNED TO THE OWNER, IF DESIRED BY OWNER.
- I. WHERE EXISTING EQUIPMENT IS TO BE RELOCATED, BE CAUTIOUS TO PREVENT DAMAGE DURING THE REMOVAL AND REINSTALLATION. WHERE DAMAGE OCCURS, THE EQUIPMENT SHALL BE REPAIRED OR REPAIRED TO THE SATISFACTION AND APPROVAL OF THE ENGINEER AT NO ADDITIONAL COST TO THE OWNER.
- J. EXISTING EQUIPMENT TO BE REUSED SHALL BE CLEANED AND REPAIRED AT THE DISCRETION OF THE ENGINEER WHERE APPLICABLE.
- K. ALL DEVICES ATTACHED TO WALLS OR CEILINGS SHALL BE REMOVED PER DEMOLITION NOTE A - M WHETHER SHOWN ON DRAWINGS OR NOT.
- L. CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE. ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.
- M. REMOVE PARTIAL EXISTING CEILING TILES AND GRID BEHIND DUCT RUNS ONLY. STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE: MEP FOR ADDT. INFO.
- N. ALL EXISTING INDOOR AIR HANDLING UNITS SHALL HAVE THEIR EXISTING CONCRETE PADS DEMOLISHED & DISPOSED OF. ANY/FLOOR DAMAGE UNDER REMOVED CONCRETE PADS TO BE REPAIRED.


KEYED NOTES: MECHANICAL DEMOLITION

- 1 EXISTING FAN TO BE DEMOLISHED AND REPLACED.
- 2 EXISTING AIR HANDLING UNIT/CONDENSER EQUIPMENT TO BE DEMOLISHED AND REPLACED. RETURN COMPONENTS TO OWNER IF OWNER SO DESIRES.
- 3 ALL INDICATED EXISTING OUTSIDE AIR DUCTWORK AND LOUVRES TO BE DEMOLISHED AND REPLACED. PATCH ANY ABANDONED/EXCESS LOUVRE OPENINGS W/ CONSTRUCTION MATERIALS TO MATCH EXISTING CONSTRUCTION MATERIALS AND DESIGN. COORDINATE PATCHWORK W/ OWNER THROUGH ENGINEER PRIOR TO COMMENCING WORK AHEAD OF TIME.
- 4 DEMOLISH INDICATED SA/RA DUCTWORK.
- 5 DEMOLISH INDICATED EXISTING MOTORIZED ZONE DAMPER, TO BE REPLACED WITH NEW VAV BOX. REFER TO REMODEL PLAN.
- 6 EXISTING THERMOSTAT/TEMP SENSORS TO BE REPLACED WITH NEW HVAC CONTROLS TEMP/RH%/CO2 SENSOR. RETURN ALL EQUIPMENT TO OWNER.
- 7 CAP, SEAL AND INSULATE BYPASS AIR OPENINGS IN SA/RA DUCTWORK.
- 8 EXISTING OUTSIDE AIR DUCT TO BE DEMOLISHED. CAP, SEAL AND INSULATE OPENING IN DUCTWORK.
- 9 EXISTING INDICATED AIR DEVICE TO BE REPLACED WITH NEW.
- 10 EXISTING DUCTWORK AND AIR DEVICES TO REMAIN.
- 11 EXISTING CONTROLS/ENCLOSURES TO BE REMOVED AND REPLACED WITH NEW HVAC CONTROLS.
- 12 BATTERY BACKUP SYSTEM TO REMAIN.
- 13 INDICATED IT RACK TO BE RELOCATED BY WISD. COORDINATE WITH OWNER.
- 14 INDICATED IT RACK TO REMAIN. COORDINATE W/ OWNER. INDICATED CONTROLS ENCLOSURE & DEVICES TO BE RETURNED TO OWNER IN CONDITION IT WAS FOUND IN PRIOR TO DEMOLITION.
- 15 EXISTING HOODS TO REMAIN.
- 16 EXISTING REFRIGERATION CONDENSERS TO REMAIN.
- 17 NEW GRILLE TO REPLACE EXISTING.







1 MECHANICAL DEMOLITION PLAN - LEFT WING SECTION
SCALE: 1/16" = 1'-0"




2 MECHANICAL ROOM B
SCALE: 3/16" = 1'-0"



3 MECHANICAL ROOM A
SCALE: 3/16" = 1'-0"



4 MECHANICAL ROOM E
SCALE: 3/16" = 1'-0"



5 ROOF ENLARGED VIEW - MECH B
SCALE: 3/16" = 1'-0"


GENERAL DEMOLITION NOTES

- A. THE EXTENT OF DEMOLITION WORK IS INDICATED ON THE ENGINEER DRAWINGS AND BY THE REQUIREMENTS OF THIS SECTION. A VISIT TO THE SITE WILL BE REQUIRED TO PROPERLY BID THE DEMOLITION WORK.
- B. PROVIDE ALL DEMOLITION WORK REQUIRED FOR THE REMOVAL AND/OR RELOCATION OF HVAC FIXTURES AND EQUIPMENT AND ASSOCIATED SERVICES TO PROVIDE A COMPLETE AND OPERABLE SYSTEM UPON COMPLETION OF THE PROJECT.
- C. MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW THE ENGINEER DOCUMENTS IN ADDITION TO THE DIVISION 15 AND 16 DOCUMENTS TO DETERMINE THE COMPLETE SCOPE OF WORK.
- D. WHERE EQUIPMENT IS INDICATED OR REQUIRED TO BE REMOVED, THE ASSOCIATED SERVICES SHALL BE CAPPED AT A CONCEALED LOCATION.
- E. WHERE SERVICES RUN ABOVE INACCESSIBLE CEILINGS OR IN WALLS WHICH ARE TO REMAIN UNDISTURBED, SERVICES SHALL BE CAPPED AT CONCEALED LOCATION AND ABANDONED.
- F. WHERE THE REMOVAL OF EQUIPMENT renders equipment downstream inoperable, services shall be extended to the downstream equipment so that the fixtures are left in operating condition.
- G. COORDINATE DEMOLITION OF DIVISION 15 SYSTEMS AS REQUIRED WITH ALL OTHER TRADES.
- H. ALL EXISTING H.V.A.C. AND EQUIPMENT REMOVED DURING CONSTRUCTION THAT ARE NOT TO BE REUSED SHALL BE REMOVED FROM THE JOB SITE AND PROPERLY RETURNED TO THE OWNER, IF DESIRED BY OWNER.
- I. WHERE EXISTING EQUIPMENT IS TO BE RELOCATED, BE CAUTIOUS TO PREVENT DAMAGE DURING THE REMOVAL AND REINSTALLATION. WHERE DAMAGE OCCURS, THE EQUIPMENT SHALL BE REPLACED OR REPAIRED TO THE SATISFACTION AND APPROVAL OF THE ENGINEER AT NO ADDITIONAL COST TO THE OWNER.
- J. EXISTING EQUIPMENT TO BE REUSED SHALL BE CLEANED AND REPAIRED AT THE DISCRETION OF THE ENGINEER WHERE APPLICABLE.
- K. ALL DEVICES ATTACHED TO WALLS OR CEILINGS SHALL BE REMOVED PER DEMOLITION NOTE A - M WHETHER SHOWN ON DRAWINGS OR NOT.
- L. CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE. ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.
- M. REMOVE PARTIAL EXISTING CEILING TILES AND GRID BENEATH DUCT RUNS ONLY. STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE: MEP FOR ADDT. INFO.
- N. ALL EXISTING INDOOR AIR HANDLING UNITS SHALL HAVE THEIR EXISTING CONCRETE PADS DEMOLISHED & DISPOSED OF. ANY/ALL FLOOR DAMAGE UNDER REMOVED CONCRETE PADS TO BE REPAIRED.

KEYED NOTES: MECHANICAL DEMOLITION


- 1 EXISTING FAN TO BE DEMOLISHED AND REPLACED.
- 2 EXISTING AIR HANDLING UNIT/CONDENSER EQUIPMENT TO BE DEMOLISHED AND REPLACED. RETURN COMPONENTS TO OWNER IF OWNER SO DESIRES.
- 3 ALL INDICATED EXISTING OUTSIDE AIR DUCTWORK AND LOUVERS TO BE DEMOLISHED AND REPLACED. PATCH ANY ABANDONED/EXCESS LOUVER OPENINGS W/ CONSTRUCTION MATERIALS TO MATCH EXISTING CONSTRUCTION MATERIALS AND DESIGN. COORDINATE PATCHWORK W/ OWNER THROUGH ENGINEER PRIOR TO COMMENCING WORK AHEAD OF TIME.
- 4 DEMOLISH INDICATED SA/RA DUCTWORK.
- 5 DEMOLISH INDICATED EXISTING MOTORIZED ZONE DAMPER, TO BE REPLACED WITH NEW VAV BOX. REFER TO REMODEL PLAN.
- 6 EXISTING THERMOSTAT/TEMP SENSORS TO BE REPLACED WITH NEW HVAC CONTROLS TEMP/RH%/CO2 SENSOR. RETURN ALL EQUIPMENT TO OWNER.
- 7 CAP, SEAL AND INSULATE BYPASS AIR OPENINGS IN SA/RA DUCTWORK.
- 8 EXISTING OUTSIDE AIR DUCT TO BE DEMOLISHED. CAP, SEAL AND INSULATE OPENING IN DUCTWORK.

06/20/2024




MMDP04

1 MECHANICAL DEMOLITION PLAN - RIGHT WING SECTION
SCALE: 1/16" = 1'-0"



6 ROOF ENLARGED VIEW - MECH ROOM C
SCALE: 3/16" = 1'-0"



2 MECHANICAL ROOM TOP D
SCALE: 3/16" = 1'-0"

MECHANICAL ROOM C

SCALE: 3/16" = 1'-0"

MECHANICAL ROOM

SCALE: 3/16" = 1'-0"

GENERAL DEMOLITION NOTES

- A. THE EXTENT OF DEMOLITION WORK IS INDICATED ON THE ENGINEER DRAWINGS AND BY THE REQUIREMENTS OF THIS SECTION. A VISIT TO THE SITE WILL BE REQUIRED TO PROPERLY BID THE DEMOLITION WORK.
- B. PROVIDE ALL DEMOLITION WORK REQUIRED FOR THE REMOVAL AND/OR RELOCATION OF HVAC FIXTURES AND EQUIPMENT AND ASSOCIATED SERVICES TO PROVIDE A COMPLETE AND OPERABLE SYSTEM UPON COMPLETION OF THE PROJECT.
- C. MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW THE ENGINEER DOCUMENTS IN ADDITION TO THE DIVISION 15 AND 14 DOCUMENTS TO DETERMINE THE COMPLETE SCOPE OF WORK.
- D. WHERE EQUIPMENT IS INDICATED OR REQUIRED TO BE REMOVED, THE ASSOCIATED SERVICES SHALL BE CAPPED AT A CONCEALED LOCATION.
- E. WHERE SERVICES RUN ABOVE INACCESSIBLE CEILINGS OR IN WALLS WHICH ARE TO REMAIN UNDISTURBED, SERVICES SHALL BE CAPPED AT CONCEALED LOCATION AND ABANDONED.
- F. WHERE THE REMOVAL OF EQUIPMENT RENDERS EQUIPMENT DOWNSTREAM INOPERABLE, SERVICES SHALL BE EXTENDED TO THE DOWNSTREAM EQUIPMENT SO THAT THE FIXTURES ARE LEFT IN OPERATING CONDITION.
- G. COORDINATE DEMOLITION OF DIVISION 15 SYSTEMS AS REQUIRED WITH ALL OTHER TRADES.
- H. ALL EXISTING H.V.A.C. AND EQUIPMENT REMOVED DURING CONSTRUCTION THAT ARE NOT TO BE REUSED SHALL BE REMOVED FROM THE JOB SITE AND PROPERLY RETURNED TO THE OWNER, IF DESIRED BY OWNER.
- I. WHERE EXISTING EQUIPMENT IS TO BE RELOCATED, BE CAUTIOUS TO PREVENT DAMAGE DURING THE REMOVAL AND REINSTALLATION, WHERE DAMAGE OCCURS, THE EQUIPMENT SHALL BE REPAIRED OR REPAIRED TO THE SATISFACTION AND APPROVAL OF THE ENGINEER AT NO ADDITIONAL COST TO THE OWNER.
- J. EXISTING EQUIPMENT TO BE REUSED SHALL BE CLEANED AND REPAIRED AT THE DISCRETION OF THE ENGINEER WHERE APPLICABLE.
- K. ALL DEVICES ATTACHED TO WALLS OR CEILINGS SHALL BE REMOVED PER DEMOLITION NOTE A - M WHETHER SHOWN ON DRAWINGS OR NOT.
- L. CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE. ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.
- M. REMOVE PARTIAL EXISTING CEILING TILES AND GRID BENEATH DUCT RUNS ONLY, STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE: MEP FOR ADDT. INFO.
- N. ALL EXISTING INDOOR AIR HANDLING UNITS SHALL HAVE THEIR EXISTING CONCRETE PADS DEMOLISHED & DISPOSED OF. ANY/ALL FLOOR DAMAGE UNDER REMOVED CONCRETE PADS TO BE REPAIRED.

KEYED NOTES: MECHANICAL DEMOLITION

- 1 EXISTING FAN TO BE DEMOLISHED AND REPLACED.
- 2 EXISTING AIR HANDLING UNIT/CONDENSER EQUIPMENT TO BE DEMOLISHED AND REPLACED. RETURN COMPONENTS TO OWNER IF OWNER SO DESIRES.
- 3 ALL INDICATED EXISTING OUTSIDE AIR DUCTWORK AND LOUVERS TO BE DEMOLISHED AND REPLACED. PATCH ANY ABANDONED/EXCESS LOUVER OPENINGS W/ CONSTRUCTION MATERIALS TO MATCH EXISTING CONSTRUCTION MATERIALS AND DESIGN. COORDINATE PATCHWORK W/ OWNER THROUGH ENGINEER PRIOR TO COMMENCING WORK AHEAD OF TIME.
- 4 DEMOLISH INDICATED SA/RA DUCTWORK.
- 5 DEMOLISH INDICATED EXISTING MOTORIZED ZONE DAMPER, TO BE REPLACED WITH NEW VAV BOX. REFER TO REMOVAL PLAN.
- 6 EXISTING THERMOSTAT/TEMP SENSORS TO BE REPLACED WITH NEW HVAC CONTROLS TEMP/RH%/CO2 SENSOR. RETURN ALL EQUIPMENT TO OWNER.
- 7 CAP, SEAL AND INSULATE BY/PASS AIR OPENINGS IN SA/RA DUCTWORK.
- 8 EXISTING OUTSIDE AIR DUCT TO BE DEMOLISHED. CAP, SEAL AND INSULATE OPENING IN DUCTWORK.
- 9 EXISTING INDICATED AIR DEVICE TO BE REPLACED WITH NEW.
- 10 EXISTING DUCTWORK AND AIR DEVICES TO REMAIN.
- 11 EXISTING CONTROLS/ENCLOSURES TO BE REMOVED AND REPLACED WITH NEW HVAC CONTROLS.
- 12 BATTERY BACKUP SYSTEM TO REMAIN.
- 13 INDICATED IT RACK TO BE RELOCATED BY WISD. COORDINATE WITH OWNER.
- 14 INDICATED IT RACK TO REMAIN. COORDINATE W/ OWNER. INDICATED CONTROLS ENCLOSURE & DEVICES TO BE RETURNED TO OWNER IN CONDITION IT WAS FOUND IN PRIOR TO DEMOLITION.
- 15 EXISTING HOODS TO REMAIN.
- 16 EXISTING REFRIGERATION CONDENSERS TO REMAIN.
- 17 NEW GRILLE TO REPLACE EXISTING.



06/20/2024
WESLACO
Wilford L. McGee III
3-121833
Project number: 23.1.40


PIPING MATERIAL SCHEDULE

Weight of Chilled Water Piping

<u>Nominal Pipe Size</u>	<u>Weight of Pipe Filled with Water (Lbs./Ft.)</u>
½" in.	2 lbs.
1" in.	3 lbs.
1 ½" in.	5 lbs.
2" in.	6 lbs.
2 ½" in.	9 lbs.
3" in.	12 lbs.
4" in.	17 lbs.
6" in.	33 lbs.
8" in.	55 lbs.

KEYED NOTES: MECHANICAL CHILLER PLANT

- 1 PROVIDE CHILLED WATER SUPPLY AND RETURN LINES W/ BUTTERFLY ISOLATION VALVES AT INDICATED LOCATIONS AT ALL EQUIPMENT.
- 2 RUN CHILLED WATER LINES @ A MINIMUM OF 8' ABOVE FINISHED GRADE.
- 3 PROVIDE PIPE SUPPORT @ EVERY 8'. LINES TO RUN @ MIN 8' ABOVE FINISHED GRADE.
- 4 CHILLER TO BE MOUNTED ON A 4" THICK BY 18" WIDE CONCRETE PAD. COORDINATE WITH CHILLER ACTUAL DIMENSIONS FOR PROPER PAD LOCATION. COORDINATE W/ STRUCTURAL PLANS.
- 5 MOTORIZED BUTTERFLY ISOLATION VALVE AT THIS LOCATION. TYPICAL FOR ALL CHILLERS.
- 6 4" CHILLED WATER BYPASS LINE. REFERENCE DETAIL 02 ON THIS SHEET FOR ALL GAGES, POTS, AND SENSORS REQUIRED.
- 7 MOUNT MAKE UP WATER LINE VALVES AND BACKFLOW ON THIS WALL. COORDINATE EXACT PLACEMENT WITH DIVISION 16. REF. DETAIL ON DETAIL SHEET CM5.2.
- 8 PLACE CHEMICAL POT FEEDER IN THIS LOCATION. REFERENCE DETAIL ON DETAIL SHEET FOR ALL VALVE AND LINE SIZES.
- 9 PLACE CONTROLS CONTROLLER ENCLOSURE IN THIS LOCATION.
- 10 MOUNT VFD AT THIS LOCATION.
- 11 PROVIDE TEMPERATURE AND PRESSURE GAUGES AT SUPPLY AND RETURN LINES.
- 12 MOUNT EQUIPMENT ON 4" CONCRETE HOUSEKEEPING PAD.
- 13 INSULATE MAKE-UP WATER LINES.
- 14 PROVIDE HOSE BIB.
- 15 PROVIDE WITH 6' CHAINLINK FENCE AROUND CHILLER YARD ANCHORED TO STRUCTURAL FOUNDATION.



2 ENLARGED CHILLED WATER PLANT

SCALE: 1/8" = 1'-0"

GENERAL NOTES - MECHANICAL:


- (1) PROVIDE HYDROSTATIC TEST BEFORE INSULATING ANY PIPE. CONTACT ENGINEER TO PROVIDE INSPECTION DURING HYDROSTATIC TEST.
- (2) ALL CHILLED WATER PIPING TO BE FLUSHED BEFORE FINAL CONNECTION TO A/C EQUIPMENT.
- (3) COORDINATE WITH DIVISION 16 FOR ALL LOCATIONS OF VFD'S AND ELECTRICAL DISCONNECTS.
- (4) PROVIDE ALL HYDRONIC EQUIPMENT W/ BUTTERFLY ISOLATION VALVES IMMEDIATELY UPSTREAM & DOWNSTREAM OF EQUIPMENT. TYPICAL OF ALL EQUIPMENT PART OF CHILLED WATER SYSTEM.
- (5) EXISTING ROOF IS STILL UNDER WARRANTY BY MANUFACTURER. ALL ROOF PENETRATIONS SHALL BE PROVIDED BY APPROVED VENDOR IN ORDER FOR ROOF WARRANTY TO BE MAINTAINED.

AMERICAN CONTRACTING USA, INC
1606 S. REYNOLDS RIO HONDO, TX 78583

- (6) ALL WORK ON ROOF SHALL NEED TO BE DONE OVER A WORKING MAT. ABSOLUTELY NO THREADING OR WELDING WILL BE ALLOWED ON ROOF. ROOF DAMAGES WILL NEED TO BE REPAIRED BY CONTRACTOR AT CONTRACTOR'S EXPENSE.


AT CONTRACTOR'S EXPENSE.

- 1 RUN CHILLED WATER LINES AT 10' ABOVE FINISHED GRADE. PROVIDE PIPE SUPPORT AS SHOWN OR AT LEAST EVERY 8'.
- 2 ANCHOR CHILLED WATER LINES TO EXISTING STEEL RAILS.
- 3 PROVIDE DIFFERENTIAL PRESSURE SENSOR AT THS LOCATION
- 4 PROVIDE 3/4" WATER LINE FROM WALL MOUNTED HOSE BIB TO CHILLER YARD FOR MAKEUP WATER.
- 5 PROVIDE ROOF CURB MOUNTED PITCH PAN, REF. DETAIL 03 ON SHEET MD02, IN WHICH TO RUN LINES AND SEAL ALL OPENINGS WATER TIGHT. RUN CHILLED WATER LINES FROM ROOF TO EACH AIR HANDLER.
- 6 PROVIDE BUTTERFLY CHILLED WATER ISOLATION VALVES @ THIS LOCATION.
- 7 PROVIDE CHILLED WATER PIPE SUPPORTS @ EVERY 10'. SUPPORT MANUFACTURER SHALL BE MIRO OR EQUAL. PROVIDE ADDITIONAL ROOFING PADS UNDER SUPPORT FOOTLEGS.
- 8 PROVIDE UNDERGROUND PRE-INSULATED CHILLED WATER LINES W/ HDPE JACKET 4' BELOW BUILDING GRADE, EQUAL TO FERRO-THERM MANUFACTURED BY THERMACOR.



MECHANICAL CHILLED WATER PIPING SITE PLAN


SCALE: 1" = 30'-0"

**GENERAL NOTES:**

- (1) CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE, ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.
- (2) REMOVE PARTIAL EXISTING CEILING TILES AND GRID BEHIND DUCT RUNS ONLY. STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE-MEP FOR ADDT. INFO.
- (3) NEW AIR HANDLING UNITS TO BE MOUNTED/INSTALLED IN MECHANICAL SPACE APPROXIMATELY WHERE EXISTING ONE WAS REMOVED. VENDOR TO MEASURE ALL ROOM DIMENSIONS AND EGRESS DIMENSIONS PRIOR TO SUBMITTALS TO VERIFY EASE OF INSTALLATION. RECONNECT TO EXISTING DUCTWORKS, PIPING AND WIRING.
- (4) PROVIDE ADEQUATE CLEARANCES TO SERVICE BOTH CONDENSERS AND AIR HANDLERS FOR ALL UNITS.
- (5) WHERE ADDITIONAL EQUIPMENT/TEMPERATURE CONTROLLED DAMPERS ARE DISCOVERED, COORDINATE WITH DESIGN TEAM TO PROVIDE ADDITIONAL REPLACEMENT EQUIPMENT/VAV BOXES.
- (6) ALL CONDENSING UNITS SHALL BE PROVIDED W/ 2 NEW STRUCTURAL SUPPORTS FOR EVERY ROW OF CONDENSERS IN CONDENSER ENCLOSURE. SUPPORTS SHALL BE OF GALVANIZED STEEL CHANNEL SUPPORTED AND WELDED ACROSS TO ENCLOSURE SCREENING STRUCTURE.

KEYED NOTES: MECHANICAL

- 1 PROVIDE NEW CONTROLS TRIPLE COMBO T-STAT (TEMPERATURE/HUMIDITY/CO2) WITH OCCUPANCY SENSOR FOR UNOCCUPIED SETPOINT SETBACKS.
- 2 PROVIDE W/ MOTORIZED DAMPER W/ OPEN/CLOSE OPERATION. DAMPER TO BE ACTUATED TO MAX ONLY WHEN HEATER IS ENERGIZED & ACTUATED TO THE CLOSED POSITION @ ALL OTHER TIMES. PROVIDE W/ ADDITIONAL MANUAL BALANCING DAMPER TO BALANCE CFM AMOUNTS OF OUTSIDE AIR. MECHANICAL CONTRACTOR TO PROVIDE W/ ANY ELECTRICAL HARDWARE TO POWER DAMPER.
- 3 PROVIDE ALUMINUM PIPING SUPPORTS AT EVERY 4' FEET. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.
- 4 COORDINATE LOCATION/HEIGHT OF LOUVERS/WALLCAPS TO NOT CONFLICT WITH CONTROL JOINTS AND DOWNSPOUTS. FIELD COORDINATE LOCATIONS OF EXISTING CONDUITS/PIPE TO PLACE LOUVERS & COORDINATE W/ ENGINEER TO RERUN LIMITED QTY OF CONDUIT/CIRCUITS.
- 5 ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF VIA A "ROOF PENETRATION HOUSING" EQUAL TO "MEDIUM VAULT" FROM "ROOFPENETRATIONHOUSING.COM" ROUTE REFRIGERANT LINES TO RESPECTIVE AIR HANDLER. ANCHOR LINES TO STRUCTURE AND SEAL ALL PENETRATIONS WATER TIGHT. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.
- 6 ALTERNATE #01 TIE IN NEW FAN TO EXISTING EXHAUST TERMINATION.
- 7 PROVIDE WITH NEW VAV BOX TO REPLACE MOTORIZED DAMPER. RE-CONNECT TO EXISTING SA DUCTWORK INLET AND OUTLET. PROVIDE WITH NEW DUCT CONNECTIONS/EXTENSIONS WHERE REQUIRED. RE-INSULATE AS PER SPECS.
- 8 NEW SA DEVICE AND ASSOCIATED DUCTWORK TO TIE INTO EXISTING SA DUCTWORK.
- 9 TIE IN NEW SA/RA DUCTS INTO EXISTING DUCTWORK.
- 10 TRIPLE COMBO TEMPERATURE SENSORS BY CONTROLS CONTRACTOR. TO BE MOUNTED IN EXISTING SENSOR J-BOXES.
- 11 UNIT TO BE MOUNTED ON A 24" HIGH PLATFORM CONSTRUCTED OF 1-1/2" ANGLE IRON/1" SQUARE METAL TUBING. WRAP PLATFORM IN GALVANIZED SHEET METAL. LINE INTERIOR OF PLATFORM W/ 1" DUCT BOARD. W/ FOIL FACING AIRSTREAM. COAT INSIDE W/ MASTIC (TO FACILITATE CLEANING) & SEAL AIR TIGHT.
- 12 ALTERNATE #01 HOOD BELOW. RECONNECT NEW HOOD VENTILATION EQUIPMENT TO EXISTING EXHAUST/MAKEUP DUCTWORK.
- 13 NEW MINISPLIT SYSTEM TO REPLACE EXISTING SYSTEM.
- 14 WRAP GREASE DUCT & TOP OF HOOD ABOVE CEILING W/ TWO LAYERS OF 3M FIRE BARRIER DUCT WRAP 615+ OR EQUAL FROM HOOD COLLAR TO FAN ON ROOF.
- 15 PROVIDE WITH ELECTRIC DUCT HEATER IN SUPPLY AIR DUCT.
- 16 HVAC CONTROLS ENCLOSURE FOR AHUs.
- 17 HVAC CONTROLS ENCLOSURE FOR CU's.
- 18 ALTERNATE #01 NEW KITCHEN VENTILATION EXHAUST FANS & TEMPERED MAKEUP AIR UNITS TO MATCH EXISTING EQUIPMENT AIR VOLUMES. PROVIDE W/ NEW KITCHEN CONTROLLER & BAS CONTROL STATUS POINTS ON ALL NEW EQUIPMENT.
- 19 NEW VFD W/ MANUAL BYPASS AS PER SCHEDULES.
- 20 COORDINATE LOCATIONS OF ALL IT RACKS W/ DISTRICT PRIOR TO COMMENCEMENT OF WORK.
- 21 OA DUCT DOWN FROM NEW ROOF CAP ON ROOF.
- 22 PROVIDE OUTSIDE AIR TO NEW UNIT FROM NEW ROOF CAP. PROVIDE 12" ROUND DUCT DOWN FROM ROOF CAP TO RETURN AIR PLENUM OF UNIT.
- 23 REMOTE H2 SENSOR LOCATED WITHIN SPACE, EQUAL TO "ACME GAS MONITOR" SENSOR, UN-ECHT. INSTALL AS PER MANUFACTURER'S INSTRUCTIONS. CONTROLS WIRING, RELAYS, & STARTERS BY ELECTRICAL CONTRACTOR.
- 24 ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF VIA A "ROOF PENETRATION HOUSING" EQUAL TO "SMALL VAULT" FROM "ROOFPENETRATIONHOUSING.COM" ROUTE REFRIGERANT LINES TO RESPECTIVE AIR HANDLER. ANCHOR LINES TO STRUCTURE AND SEAL ALL PENETRATIONS WATER TIGHT. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.
- 25 MOUNT NEW CONDENSING UNIT ON EXISTING STRUCTURAL SUPPORTS. MECHANICALLY FASTEN UNIT TO CURB.
- 26 PROVIDE WITH DRYER VENT EXHAUST THRU WALL CAP. TO BE CONSTRUCTED OF KB DUCT "CLAMP TOGETHER" STYLE DUCT (OR EQUAL). DUCT TO BE SIZED ACCORDING TO DRYER MANUFACTURERS REQUIREMENTS, AND TO COMPLY WITH SECTION 504 OF THE IBC. DUCT TO BE WRAPPED IN 3M FIRE BARRIER DUCT WRAP 615+ OR EQUAL FROM DRYER VENT TO WALL CAP. REFER TO DRYER DUCT FITTINGS EQUIVALENT LENGTHS CHART.
- 27 PROVIDE WITH IN-WALL DRYER VENT BOX STYLE CONNECTION EQUAL TO THE DRYERBOX DB-480.
- 28 BAROMETRIC RELIEF DAMPER SET TO OPEN AT +0.05 W.C. OF POSITIVE BUILDING PRESSURE.
- 29 MOUNT UNIT OVER A 4' CONCRETE HOUSEKEEPING PAD.
- 30 PROVIDE W/ REFRIGERANT LINE WALL PENETRATION HOUSING/PANEL EQUAL TO "TGS SERIES PRO SYSTEM KIT" MADE BY "AIREX MANUFACTURING INC". WALL PANEL TO BE SIZED TO ACCOMMODATE REFRIGERANT LINES. COORDINATE W/ ARCH FOR COLOR. SECURE WITH LOCK-TYPE TAMPER-RESISTANT FASTENERS TO PREVENT UNAUTHORIZED ACCESS. PROVIDE WITH UV/WEATHER RESISTANT INSULATION PROTECTOR (E-FLEX GUARD). PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING. MOUNT AT 24" A.F.F.
- 31 CW SUPPLY/RETURN LINES FROM ABOVE ROOF.
- 32 DROPS CONNECT TO CW COIL INLET AND OUTLETS. PROVIDE WITH COIL VALVE PACKAGE.



1 MECHANICAL ROOF PLAN
SCALE: 1" = 30'-0"

GENERAL NOTES:

- (1) CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE, ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.
- (2) REMOVE PARTIAL EXISTING CEILING TILES AND GRID BEHIND DUCT RUNS ONLY. STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE-MEP FOR ADDT. INFO.
- (3) NEW AIR HANDLING UNITS TO BE MOUNTED/INSTALLED IN MECHANICAL SPACE APPROXIMATELY WHERE EXISTING ONE WAS REMOVED. VENDOR TO MEASURE ALL ROOM DIMENSIONS AND EGRESS DIMENSIONS PRIOR TO SUBMITTALS TO VERIFY EASE OF INSTALLATION. RECONNECT TO EXISTING DUCTWORK, PIPING AND WIRING.
- (4) PROVIDE ADEQUATE CLEARANCES TO SERVICE BOTH CONDENSERS AND AIR HANDLERS FOR ALL UNITS.
- (5) WHERE ADDITIONAL EQUIPMENT/TEMPERATURE CONTROLLED DAMPERS ARE DISCOVERED, COORDINATE WITH DESIGN TEAM TO PROVIDE ADDITIONAL REPLACEMENT EQUIPMENT/VAV BOXES.
- (6) ALL CONDENSING UNITS SHALL BE PROVIDED W/ 2 NEW STRUCTURAL SUPPORTS FOR EVERY ROW OF CONDENSERS IN CONDENSER ENCLOSURE. SUPPORTS SHALL BE OF GALVANIZED STEEL CHANNEL SUPPORTED AND WELDED ACROSS TO ENCLOSURE SCREENING STRUCTURE.

KEYED NOTES: MECHANICAL

- ① PROVIDE NEW CONTROLS TRIPLE COMBO T-STAT (TEMPERATURE/HUMIDITY/CO2) WITH OCCUPANCY SENSOR FOR UNOCCUPIED SETPOINT SETBACKS.
- ② PROVIDE W/ MOTORIZED DAMPER W/ OPEN/CLOSE OPERATION. DAMPER TO BE ACTUATED TO MAX ONLY WHEN HEATER IS ENERGIZED & ACTUATED TO THE CLOSED POSITION @ ALL OTHER TIMES. PROVIDE W/ ADDITIONAL MANUAL BALANCING DAMPER TO BALANCE CFM AMOUNTS OF OUTSIDE AIR. MECHANICAL CONTRACTOR TO PROVIDE W/ ANY ELECTRICAL HARDWARE TO POWER DAMPER.
- ③ PROVIDE ALUMINUM PIPING SUPPORTS AT EVERY 4' FEET. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.
- ④ COORDINATE LOCATION/HEIGHT OF LOUVERS/WALLCAPS TO NOT CONFLICT WITH CONTROL JOINTS AND DOWNSPOUTS. FIELD COORDINATE LOCATIONS OF EXISTING CONDUITS/PIPE TO PLACE LOUVERS & COORDINATE W/ ENGINEER TO RERUN LIMITED QTY OF CONDUIT/CIRCUITS.
- ⑤ ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF VIA A "ROOF PENETRATION HOUSING" EQUAL TO "MEDIUM VAULT" FROM "ROOFPENETRATIONHOUSING.COM" ROUTE REFRIGERANT LINES TO RESPECTIVE AIR HANDLER. ANCHOR LINES TO STRUCTURE AND SEAL ALL PENETRATIONS WATER TIGHT. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.
- ⑥ ALTERNATE #01 TIE IN NEW FAN TO EXISTING EXHAUST TERMINATION.
- ⑦ PROVIDE WITH NEW VAV BOX TO REPLACE MOTORIZED DAMPER. RE-CONNECT TO EXISTING SA DUCTWORK INLET AND OUTLET. PROVIDE WITH NEW DUCT CONNECTIONS/EXTENSIONS WHERE REQUIRED. RE-INSULATE AS PER SPECS.
- ⑧ NEW SA DEVICE AND ASSOCIATED DUCTWORK TO TIE INTO EXISTING SA DUCTWORK.
- ⑨ TIE IN NEW SA/RA DUCTS INTO EXISTING DUCTWORK.
- ⑩ TRIPLE COMBO TEMPERATURE SENSORS BY CONTROLS CONTRACTOR. TO BE MOUNTED IN EXISTING SENSOR J-BOXES.
- ⑪ UNIT TO BE MOUNTED ON A 24" HIGH PLATFORM CONSTRUCTED OF 1-1/2" ANGLE IRON/1" SQUARE METAL TUBING. WRAP PLATFORM IN GALVANIZED SHEET METAL. LINE INTERIOR OF PLATFORM W/ 1" DUCT BOARD. W/ FOIL FACING AIRSTREAM. COAT INSIDE W/ MASTIC (TO FACILITATE CLEANING) & SEAL AIR TIGHT.
- ⑫ ALTERNATE #01 HOOD BELOW. RECONNECT NEW HOOD VENTILATION EQUIPMENT TO EXISTING EXHAUST/MAKEUP DUCTWORK.
- ⑬ NEW MINISPLIT SYSTEM TO REPLACE EXISTING SYSTEM.
- ⑭ WRAP GREASE DUCT & TOP OF HOOD ABOVE CEILING W/ TWO LAYERS OF 3M FIRE BARRIER DUCT WRAP 615+ OR EQUAL FROM HOOD COLLAR TO FAN ON ROOF.
- ⑮ PROVIDE WITH ELECTRIC DUCT HEATER IN SUPPLY AIR DUCT.
- ⑯ HVAC CONTROLS ENCLOSURE FOR AHUs.
- ⑰ HVAC CONTROLS ENCLOSURE FOR CUs.
- ⑱ ALTERNATE #01 NEW KITCHEN VENTILATION EXHAUST FANS & TEMPERED MAKEUP AIR UNITS TO MATCH EXISTING EQUIPMENT AIR VOLUMES. PROVIDE W/ NEW KITCHEN CONTROLLER & BAS CONTROL STATUS POINTS ON ALL NEW EQUIPMENT.
- ⑲ NEW VFD W/ MANUAL BYPASS AS PER SCHEDULES.
- ⑳ COORDINATE LOCATIONS OF ALL IT RACKS W/ DISTRICT PRIOR TO COMMENCEMENT OF WORK.
- ㉑ OA DUCT DOWN FROM NEW ROOF CAP ON ROOF.
- ㉒ PROVIDE OUTSIDE AIR TO NEW UNIT FROM NEW ROOF CAP. PROVIDE 12" ROUND DUCT DOWN FROM ROOF CAP TO RETURN AIR PLENUM OF UNIT.
- ㉓ REMOTE H2 SENSOR LOCATED WITHIN SPACE. EQUAL TO "ACME GAS MONITOR" SENSOR, UN-ECHT. INSTALL AS PER MANUFACTURER'S INSTRUCTIONS. CONTROLS WIRING, RELAYS, & STARTERS BY ELECTRICAL CONTRACTOR.
- ㉔ ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF VIA A "ROOF PENETRATION HOUSING" EQUAL TO "SMALL VAULT" FROM "ROOFPENETRATIONHOUSING.COM" ROUTE REFRIGERANT LINES TO RESPECTIVE AIR HANDLER. ANCHOR LINES TO STRUCTURE AND SEAL ALL PENETRATIONS WATER TIGHT. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.
- ㉕ MOUNT NEW CONDENSING UNIT ON EXISTING STRUCTURAL SUPPORTS. MECHANICALLY FASTEN UNIT TO CURB.
- ㉖ PROVIDE WITH DRYER VENT EXHAUST THRU WALL CAP. TO BE CONSTRUCTED OF KB DUCT "CLAMP TOGETHER" STYLE DUCT (OR EQUAL). DUCT TO BE SIZED ACCORDING TO DRYER MANUFACTURERS REQUIREMENTS, AND TO COMPLY WITH SECTION 504 OF THE 2018 IBC. DUCT TO BE WRAPPED IN 3M FIRE BARRIER DUCT WRAP 615+ OR EQUAL FROM DRYER VENT TO WALL CAP. REFER TO DRYER DUCT FITTINGS EQUIVALENT LENGTHS CHART.
- ㉗ PROVIDE WITH IN-WALL DRYER VENT BOX STYLE CONNECTION EQUAL TO THE DRYERBOX DB-480.
- ㉘ BAROMETRIC RELIEF DAMPER SET TO OPEN AT +0.05 W.C OF POSITIVE BUILDING PRESSURE.
- ㉙ MOUNT UNIT OVER A 4' CONCRETE HOUSEKEEPING PAD.
- ㉚ PROVIDE W/ REFRIGERANT LINE WALL PENETRATION HOUSING/PANEL EQUAL TO "TGS SERIES PRO SYSTEM KIT" MADE BY "AIREX MANUFACTURING INC". WALL PANEL TO BE SIZED TO ACCOMMODATE REFRIGERANT LINES. COORDINATE W/ ARCH FOR COLOR. SECURE WITH LOCK-TYPE TAMPER-RESISTANT FASTENERS TO PREVENT UNAUTHORIZED ACCESS. PROVIDE WITH UV/WEATHER RESISTANT INSULATION PROTECTOR (E-FLEX GUARD). PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING. MOUNT AT 24" A.F.F.
- ㉛ CW SUPPLY/RETURN LINES FROM ABOVE ROOF.
- ㉜ DROPS CONNECT TO CW COIL INLET AND OUTLETS. PROVIDE WITH COIL VALVE PACKAGE.

GENERAL NOTES:

(1) CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE, ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.

(2) REMOVE PARTIAL EXISTING CEILING TILES AND GRID BEHIND DUCT RUNS ONLY. STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE-MEP FOR ADDT. INFO.

(3) NEW AIR HANDLING UNITS TO BE MOUNTED/INSTALLED IN MECHANICAL SPACE APPROXIMATELY WHERE EXISTING ONE WAS REMOVED. VENDOR TO MEASURE ALL ROOM DIMENSIONS AND EGRESS DIMENSIONS PRIOR TO SUBMTTS TO VERIFY EASE OF INSTALLATION. RECONNECT TO EXISTING DUCTWORKS, PIPING AND WIRING.

(4) PROVIDE ADEQUATE CLEARANCES TO SERVICE BOTH CONDENSERS AND AIR HANDLERS FOR ALL UNITS.

(5) WHERE ADDITIONAL EQUIPMENT/TEMPERATURE CONTROLLED DAMPERS ARE DISCOVERED, COORDINATE WITH DESIGN TEAM TO PROVIDE ADDITIONAL REPLACEMENT EQUIPMENT/VAV BOXES.

(6) ALL CONDENSING UNITS SHALL BE PROVIDED W/ 2 NEW STRUCTURAL SUPPORTS FOR EVERY ROW OF CONDENSERS IN CONDENSER ENCLURE. SUPPORTS SHALL BE 4" GALVANIZED STEEL CHANNEL SUPPORTED AND WELDED ACROSS TO ENCLURE SCREENING STRUCTURE.

KEYED NOTES: MECHANICAL

(1) PROVIDE NEW CONTROLS TRIPLE COMBO T-STAT (TEMPERATURE/HUMIDITY/CO₂) WITH OCCUPANCY SENSOR FOR UNOCCUPIED SETPOINT SETBACKS.

(2) PROVIDE W/ MOTORIZED DAMPER W/ OPEN/CLOSE OPERATION. DAMPER TO BE ACTUATED TO MAX ONLY WHEN HEATER IS ENERGIZED & ACTUATED TO THE CLOSED POSITION @ ALL OTHER TIMES. PROVIDE W/ ADDITIONAL MANUAL BALANCING DAMPER TO BALANCE CFM AMOUNTS OF OUTSIDE AIR. MECHANICAL CONTRACTOR TO PROVIDE W/ ANY ELECTRICAL HARDWARE TO POWER DAMPER.

(3) PROVIDE ALUMINUM PIPING SUPPORTS AT EVERY 4' FEET. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.

(4) COORDINATE LOCATION/HEIGHT OF LOUVERS/WALLCAPS TO NOT CONFLICT WITH CONTROL JOINTS AND DOWNSPOUTS. FIELD COORDINATE LOCATIONS OF EXISTING CONDUITS/PIPE TO PLACE LOUVERS & COORDINATE W/ ENGINEER TO RERUN LIMITED QTY OF CONDUIT/CIRCUITS.

(5) ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF VIA A "ROOF PENETRATION HOUSING" EQUAL TO "MEDIUM VAULT" FROM "ROOFPENETRATIONHOUSING.COM" ROUTE REFRIGERANT LINES TO RESPECTIVE AIR HANDLER. ANCHOR LINES TO STRUCTURE AND SEAL ALL PENETRATIONS WATER TIGHT. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.

(6) ALTERNATE #01 TIE IN NEW FAN TO EXISTING EXHAUST TERMINATION.

(7) PROVIDE WITH NEW VAV BOX TO REPLACE MOTORIZED DAMPER. RE-CONNECT TO EXISTING SA DUCTWORK INLET AND OUTLET. PROVIDE WITH NEW DUCT CONNECTIONS/EXTENSIONS WHERE REQUIRED. RE-INSULATE AS PER SPECS.

(8) NEW SA DEVICE AND ASSOCIATED DUCTWORK TO TIE INTO EXISTING SA DUCTWORK.

(9) TIE IN NEW SA/RA DUCTS INTO EXISTING DUCTWORK.

(10) TRIPLE COMBO TEMPERATURE SENSORS BY CONTROLS CONTRACTOR. TO BE MOUNTED IN EXISTING SENSOR J-BOXES.

(11) UNIT TO BE MOUNTED ON A 24" HIGH PLATFORM CONSTRUCTED OF 1-1/2" ANGLE IRON/1" SQUARE METAL TUBING. WRAP PLATFORM IN GALVANIZED SHEET METAL. INTERIOR OF PLATFORM W/ 1" DUCT BOARD. W/ FOIL FACING AIRSTREAM. COAT INSIDE W/ TAIC (TO FACILITATE CLEANING) & SEAL AIR TIGHT.

(12) ALTERNATE #01 HOOD BELOW, RECONNECT NEW HOOD VENTILATION EQUIPMENT TO EXISTING EXHAUST/MAKEUP DUCTWORK.

(13) NEW MINISPLIT SYSTEM TO REPLACE EXISTING SYSTEM.

(14) WRAP GREASE DUCT & TOP OF HOOD ABOVE CEILING W/ TWO LAYERS OF 3M FIRE BARRIER DUCT WRAP 615+ OR EQUAL FROM HOOD COLLAR TO FAN ON ROOF.

(15) PROVIDE WITH ELECTRIC DUCT HEATER IN SUPPLY AIR DUCT.

(16) HVAC CONTROLS ENCLOSURE FOR AHUs.

(17) HVAC CONTROLS ENCLOSURE FOR CUs.

(18) ALTERNATE #01 NEW KITCHEN VENTILATION EXHAUST FANS & TEMPERED MAKEUP AIR UNITS TO MATCH EXISTING EQUIPMENT AIR VOLUMES. PROVIDE W/ NEW KITCHEN CONTROLLER & BAS CONTROL STATUS POINTS ON ALL NEW EQUIPMENT.

(19) NEW VFD W/ MANUAL BYPASS AS PER SCHEDULES.

(20) COORDINATE LOCATIONS OF ALL IT RACKS W/ DISTRICT PRIOR TO COMMENCEMENT OF WORK.

(21) OA DUCT DOWN FROM NEW ROOF CAP ON ROOF.

(22) PROVIDE OUTSIDE AIR TO NEW UNIT FROM NEW ROOF CAP. PROVIDE 12" ROUND DUCT DOWN FROM ROOF CAP TO RETURN AIR PLENUM OF UNIT.

(23) REMOTE B SENSOR LOCATED WITHIN SPACE. EQUAL TO "ACME GAS MONITOR" SENSOR, UN-ECHT. INSTALLED AS PER MANUFACTURER'S INSTRUCTIONS. CONTROLS WIRING, RELAYS, & STARTERS BY ELECTRICAL CONTRACTOR.

(24) ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF VIA A "ROOF PENETRATION HOUSING" EQUAL TO "SMALL VAULT" FROM "ROOFPENETRATIONHOUSING.COM" ROUTE REFRIGERANT LINES TO RESPECTIVE AIR HANDLER. ANCHOR LINES TO STRUCTURE AND SEAL ALL PENETRATIONS WATER TIGHT. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.

(25) MOUNT NEW CONDENSING UNIT ON EXISTING STRUCTURAL SUPPORTS. MECHANICALLY FASTEN UNIT TO CURB.

(26) PROVIDE WITH DRYER VENT EXHAUST THRU WALL CAP. TO BE CONSTRUCTED OF KB DUCT "CLAMP TOGETHER" STYLE DUCT (OR EQUAL). DUCT TO BE SIZED ACCORDING TO DRYER MANUFACTURERS REQUIREMENTS, AND TO COMPLY WITH SECTION 504 OF THE IBC. WRAP DUCT IN 3M FIRE BARRIER DUCT WRAP 615+ OR EQUAL FROM DRYER VENT TO WALL CAP. REFER TO DRYER DUCT FITTINGS EQUIVALENT LENGTHS CHART.

(27) PROVIDE WITH IN-WALL DRYER VENT BOX STYLE CONNECTION EQUAL TO THE DRYERBOX DB-480.


(28) BAROMETRIC RELIEF DAMPER SET TO OPEN AT +0.05 W.C. OF POSITIVE BUILDING PRESSURE.

(29) MOUNT UNIT OVER A 4' CONCRETE HOUSEKEEPING PAD.

(30) PROVIDE W/ REFRIGERANT LINE WALL PENETRATION HOUSING/PANEL EQUAL TO "TGS SERIES PRO SYSTEM KIT" MADE BY "AIREX MANUFACTURING INC" WALL PANEL TO BE SIZED TO ACCOMMODATE REFRIGERANT LINES. COORDINATE W/ ARCH FOR COLOR. SECURE WITH LOCK-TYPE TAMPER-RESISTANT FASTENERS TO PREVENT UNAUTHORIZED ACCESS. PROVIDE WITH UV/WEATHER RESISTANT INSULATION PROTECTOR (E-FLEX GUARD). PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING. MOUNT AT 24" A.F.F.


(31) CW SUPPLY/RETURN LINES FROM ABOVE ROOF.

(32) DROPS CONNECT TO CW COIL INLET AND OUTLETS. PROVIDE WITH COIL VALVE PACKAGE.




2 MECHANICAL ROOM - LIBRARY

SCALE: 3/16" = 1'-0"




3 MECHANICAL ROOM - CAFETERIA

SCALE: 3/16" = 1'-0"





4 ALTERNATE #1 ROOF ENLARGED VIEW - KITCHEN


SCALE: 3/16" = 1'-0"



1 MECHANICAL FLOOR PLAN - LIBRARY & CAFETERIA SECTION

SCALE: 3/32" = 1'-0"






1 MECHANICAL FLOOR PLAN - LEFT WING SECTION
SCALE: 1/16" = 1'-0"

GENERAL NOTES:

- CONTRACTOR TO REUSE AS MUCH EXISTING CEILING TILES AS POSSIBLE. ONLY DAMAGED CLG. TILES AND GRID DAMAGED BY THE SUB/CONTRACTOR WILL BE REPLACED WITH NEW.
- REMOVE PARTIAL EXISTING CEILING TILES AND GRID BEHIND DUCT RUNS ONLY. STORE, PROTECT & REUSE TILES. RE: MEP ALL OTHER CEILING MOUNTED SYSTEMS (FIRE SPRINKLER HEADS, DIFFUSERS, LIGHT FIXTURES, ALARMS, STROBES, ETC.) SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. RE: JMEP FOR ADDT. INFO.
- NEW AIR HANDLING UNITS TO BE MOUNTED/INSTALLED IN MECHANICAL SPACE APPROXIMATELY WHERE EXISTING ONE WAS REMOVED. VENDOR TO MEASURE ALL ROOM DIMENSIONS AND EGRESS DIMENSIONS PRIOR TO SUBMITTALS TO VERIFY EASE OF INSTALLATION. RECONNECT TO EXISTING DUCTWORKS, PIPING AND WIRING.
- PROVIDE ADEQUATE CLEARANCES TO SERVICE BOTH CONDENSERS AND AIR HANDLERS FOR ALL UNITS.
- WHERE ADDITIONAL EQUIPMENT/TEMPERATURE CONTROLLED DAMPERS ARE DISCOVERED, COORDINATE WITH DESIGN TEAM TO PROVIDE ADDITIONAL REPLACEMENT EQUIPMENT/VAV BOXES.
- ALL CONDENSING UNITS SHALL BE PROVIDED W/ 2 NEW STRUCTURAL SUPPORTS FOR EVERY ROW OF CONDENSER IN CONDENSER ENCLOSURE. SUPPORTS SHALL BE 6" GALVANIZED STEEL CHANNEL SUPPORTED AND WELDED ACROSS TO ENCLOSURE SCREENING STRUCTURE.

KEYED NOTES: MECHANICAL

- PROVIDE NEW CONTROLS TRIPLE COMBO T-STAT [TEMPERATURE/HUMIDITY/CO2] WITH OCCUPANCY SENSOR FOR UNOCCUPIED SETPOINT SETBACKS.
- PROVIDE W/ MOTORIZED DAMPER W/ OPEN/CLOSE OPERATION. DAMPER TO BE ACTUATED TO MAX ONLY WHEN HEATER IS ENERGIZED & ACTUATED TO THE CLOSED POSITION @ ALL OTHER TIMES. PROVIDE W/ ADDITIONAL MANUAL BALANCING DAMPER TO BALANCE CFM AMOUNTS OF OUTSIDE AIR. MECHANICAL CONTRACTOR TO PROVIDE W/ ANY ELECTRICAL HARDWARE TO POWER DAMPER.
- PROVIDE ALUMINUM PIPING SUPPORTS AT EVERY 4' FEET. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.
- COORDINATE LOCATION/HEIGHT OF LOUVERS/WALLCAPS TO NOT CONFLICT WITH CONTROL JOINTS AND DOWNSPOUTS. FIELD COORDINATE LOCATIONS OF EXISTING CONDUITS/PIPE TO PLACE LOUVERS & COORDINATE W/ ENGINEER TO RERUN LIMITED QTY OF CONDUIT/CIRCUITS.
- ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF LINE. PROVIDE CONDUIT TO TIE IN NEW FAN TO NEW ROOF CAP. COORDINATE LOCATIONS OF ALL IT RACKS W/ DISTRICT PRIOR TO COMMENCEMENT OF WORK.
- ALTERNATE #01 TIE IN NEW FAN TO EXISTING EXHAUST TERMINATION.
- PROVIDE WITH NEW VAV BOX TO REPLACE MOTORIZED DAMPER. RE-CONNECT TO EXISTING SA DUCTWORK INLET AND OUTLET. PROVIDE WITH NEW DUCT CONNECTIONS/EXTENSIONS WHERE REQUIRED. RE-INSULATE AS PER SPECS.
- NEW SA DEVICE AND ASSOCIATED DUCTWORK TO TIE INTO EXISTING SA DUCTWORK.
- IEE TIE IN NEW SA/RA DUCTS INTO EXISTING DUCTWORK.
- TRIPLE COMBO TEMPERATURE SENSORS BY CONTROLS CONTRACTOR. TO BE MOUNTED IN EXISTING SENSOR J-BOXES.
- UNIT TO BE MOUNTED ON A 24" HIGH PLATFORM CONSTRUCTED OF 1-1/2" ANGLE IRON/1" SQUARE METAL TUBING. WRAP PLATFORM IN GALVANIZED SHEET METAL. LINE INTERIOR OF PLATFORM W/ 1" DUCT BOARD, W/ FOIL FACING AIRSTREAM. COAT INSIDE W/ MASTIC (TO FACILITATE CLEANING) & SEAL AIR TIGHT.
- ALTERNATE #01 HOOD BELOW. RECONNECT NEW HOOD VENTILATION EQUIPMENT TO EXISTING EXHAUST/MAKEUP DUCTWORK.
- NEW MINISPLIT SYSTEM TO REPLACE EXISTING SYSTEM.
- WRAP GREASE DUCT & TOP OF HOOD ABOVE CEILING W/ TWO LAYERS OF 3M FIRE BARRIER DUCT WRAP 615+ OR EQUAL FROM HOOD COLLAR TO FAN ON ROOF.
- PROVIDE WITH ELECTRIC DUCT HEATER IN SUPPLY AIR DUCT.
- HVAC CONTROLS ENCLOSURE FOR AHUs.
- HVAC CONTROLS ENCLOSURE FOR CUs.
- ALTERNATE #01 NEW KITCHEN VENTILATION EXHAUST FANS & TEMPERED MAKEUP AIR UNITS TO MATCH EXISTING EQUIPMENT AIR VOLUMES. PROVIDE W/ NEW KITCHEN CONTROLLER & BAS CONTROL STATUS POINTS ON ALL NEW EQUIPMENT.
- NEW VFD w/ MANUAL BYPASS AS PER SCHEDULES.
- COORDINATE LOCATIONS OF ALL IT RACKS W/ DISTRICT PRIOR TO COMMENCEMENT OF WORK.
- IEE DUCT DOWN FROM NEW ROOF CAP ON ROOF.
- PROVIDE OUTSIDE AIR TO NEW UNIT FROM NEW ROOF CAP. PROVIDE 12" ROUND DUCT DOWN FROM ROOF CAP TO RETURN AIR PLenum OF UNIT.
- REMOTE H2 SENSOR LOCATED WITHIN SPACE. EQUAL TO "ACME GAS MONITOR" SENSOR. UN-ECH INSTALL AS PER MANUFACTURER'S INSTRUCTIONS. CONTROLS WIRING, RELAY & STABILIZER BY ELECTRICAL CONTRACTOR.
- ROUTE REFRIGERANT LINES AND DUCTS AND COORDINATE LOCATIONS OF CONDUIT BELOW ROOF LINE. PROVIDE CONDUIT TO TIE IN NEW FAN TO NEW ROOF CAP. COORDINATE LOCATIONS OF ALL IT RACKS W/ DISTRICT PRIOR TO COMMENCEMENT OF WORK.
- PROVIDE WITH DRYER VENT EXHAUST THRU WALL CAP. TO BE CONSTRUCTED OF K8 DUCT "CLAMP TOGETHER" STYLE DUCT (OR EQUAL). DUCT TO BE SIZED ACCORDING TO DRYER MANUFACTURERS REQUIREMENTS, AND TO COMPLY WITH SECTION 504 OF THE INTERNATIONAL MECHANICAL CODE. PROVIDE WITH ONE LAYER OF 3M FIRE BARRIER DUCT WRAP 615+ OR EQUAL FROM DRYER VENT TO WALL CAP. REFER TO DRYER DUCT FITTINGS EQUIVALENT LENGTHS CHART.
- PROVIDE WITH IN-WALL DRYER VENT BOX STYLE CONNECTION EQUAL TO THE DRYERBOX DB-480.
- ALTERNATE RELIEF DAMPER SET TO OPEN AT +0.05 W.C. OF POSITIVE BUILDING PRESSURE.
- MOUNT UNIT OVER A 4' CONCRETE HOUSEKEEPING PAD.
- PROVIDE W/ REFRIGERANT LINE WALL PENETRATION HOUSING/PANEL EQUAL TO TGS SERIES PRO SYSTEM KIT MADE BY "AIREX MANUFACTURING INC.". WALL PANEL FOR COLOR. SECURE WITH LOCK-TYPE TAMPER-RESISTANT FASTENERS TO PREVENT UNAUTHORIZED ACCESS. PROVIDE WITH UV/ WEATHER RESISTANT INSULATION PROTECTOR (E-FLY GUARD). PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING. MOUNT AT 24" A.F.F.



1 MECHANICAL FLOOR PLAN - RIGHT WING SECTION
SCALE: 1/16" = 1' 0"

SCALE: 1/16" = 1'-0"



5 ROOF ENLARGED VIEW - MECH ROOM D
SCALE: 3/16" = 1' 0"

6 ROOF ENLARGED VIEW - MECH ROOM C
SCALE: 3/16" = 1' 0"

KEYED NOTES: MECHANICAL

1 PROVIDE NEW CONTROLS TRIPLE COMBO T-STAT (TEMPERATURE/HUMIDITY/CO2) WITH OCCUPANCY SENSOR FOR UNOCCUPIED SETPOINT SETBACKS.

2 PROVIDE W/ MOTORIZED DAMPER W/ OPEN/CLOSE OPERATION. DAMPER TO BE ACTUATED TO MAX ONLY WHEN HEATER IS ENERGIZED & ACTUATED TO THE CLOSED POSITION @ ALL OTHER TIMES. PROVIDE W/ ADDITIONAL MANUAL BALANCING DAMPER TO BALANCE CFM AMOUNTS OF OUTSIDE AIR. MECHANICAL CONTRACTOR TO PROVIDE W/ ANY ELECTRICAL HARDWARE TO POWER DAMPER.

3 PROVIDE ALUMINUM PIPING SUPPORTS AT EVERY 4' FEET. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.

4 COORDINATE LOCATION/HEIGHT OF LOUVERS/WALLCAPS TO NOT CONFLICT WITH CONTROL JOINTS AND DOWNSPOUTS. FIELD COORDINATE LOCATIONS OF EXISTING CONDUITS/PIPE TO PLACE LOUVERS & COORDINATE W/ ENGINEER TO RERUN LIMITED QTY OF CONDUIT/CIRCUITS.

5 ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF VIA A "ROOF PENETRATION HOUSING" EQUAL TO "MEDIUM VAULT" FROM 'ROOFPENETRATIONHOUSING.COM' ROUTE REFRIGERANT LINES TO RESPECTIVE AIR HANDLER, ANCHOR LINES TO STRUCTURE AND SEAL ALL PENETRATIONS WATER TIGHT. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.

6 **ALTERNATE #01** TIE IN NEW FAN TO EXISTING EXHAUST TERMINATION.

7 PROVIDE WITH NEW VAV BOX TO REPLACE MOTORIZED DAMPER. RE-CONNECT TO EXISTING SA DUCTWORK INLET AND OUTLET. PROVIDE WITH NEW DUCT CONNECTIONS/EXTENSIONS WHERE REQUIRED. RE-INSULATE AS PER SPECS.

8 NEW SA DEVICE AND ASSOCIATED DUCTWORK TO TIE INTO EXISTING SA DUCTWORK.

9 TIE IN NEW SA/RA DUCTS INTO EXISTING DUCTWORK.

10 TRIPLE COMBO TEMPERATURE SENSORS BY CONTROLS CONTRACTOR. TO BE MOUNTED IN EXISTING SENSOR J-BOXES

11 UNIT TO BE MOUNTED ON A 24" HIGH PLATFORM CONSTRUCTED OF 1-1/2" ANGLE IRON/1" SQUARE METAL TUBING. WRAP PLATFORM IN GALVANIZED SHEET METAL. LINE INTERIOR OF PLATFORM W/ 1" DUCT BOARD, W/ FOIL FACING AIRSTREAM. COAT INSIDE W/ MASTIC (TO FACILITATE CLEANING) & SEAL AIR TIGHT.

12 **ALTERNATE #01** HOOD BELOW, RECONNECT NEW HOOD VENTILATION EQUIPMENT TO EXISTING EXHAUST/MAKEUP DUCTWORK.

13 NEW MINISPLIT SYSTEM TO REPLACE EXISTING SYSTEM.

15 PROVIDE WITH ELECTRIC DUCT HEATER IN SUPPLY AIR DUCT.

16 HVAC CONTROLS ENCLOSURE FOR AHU'S.

17 HVAC CONTROLS ENCLOSURE FOR CU'S.

18 **ALTERNATE #01** NEW KITCHEN VENTILATION EXHAUST FANS & TEMPERED MAKEUP AIR UNITS TO MATCH EXISTING EQUIPMENT AIR VOLUMES. PROVIDE W/ NEW KITCHEN CONTROLLER & BAS CONTROL STATUS POINTS ON ALL NEW EQUIPMENT.

19 NEW VFD W/ MANUAL BYPASS AS PER SCHEDULES.

20 COORDINATE LOCATIONS OF ALL IT RACKS W/ DISTRICT PRIOR TO COMMENCEMENT OF WORK.

21 OA DUCT DOWN FROM NEW ROOF CAP ON ROOF.

22 PROVIDE OUTSIDE AIR TO NEW UNIT FROM NEW ROOF CAP. PROVIDE 12" ROUND DUCT DOWN FROM ROOF CAP TO RETURN AIR PLENUM OF UNIT.

23 REMOTE H2 SENSOR LOCATED WITHIN SPACE, EQUAL TO "ACME GAS MONITOR" SENSOR, "UN-ECH". INSTALL AS PER MANUFACTURER'S INSTRUCTIONS. CONTROLS WIRING, RELAYS, & STARTERS BY ELECTRICAL CONTRACTOR.

24 ROUTE REFRIGERANT LINES AND CONDENSER ELECTRICAL CONDUIT BELOW ROOF VIA A "ROOF PENETRATION HOUSING" EQUAL TO "SMALL VAULT" FROM 'ROOFPENETRATIONHOUSING.COM' ROUTE REFRIGERANT LINES TO RESPECTIVE AIR HANDLER, ANCHOR LINES TO STRUCTURE AND SEAL ALL PENETRATIONS WATER TIGHT. PROVIDE ALUMINUM JACKETING ON ALL LINES EXTERIOR TO THE BUILDING.

25 MOUNT NEW CONDENSING UNIT ON EXISTING STRUCTURAL SUPPORTS. MECHANICALLY FASTEN UNIT TO CURB.

26 PROVIDE WITH DRYER VENT EXHAUST THRU WALL CAP. TO BE CONSTRUCTED OF KB DUCT "CLAMP TOGETHER" STYLE DUCT (OR EQUAL). DUCT TO BE SIZED ACCORDING TO DRYER MANUFACTURERS REQUIREMENTS, AND TO COMPLY WITH SECTION 504 OF THE INTERNATIONAL MECHANICAL CODE. PROVIDE WITH ONE LAYER OF '3M FIRE BARRIER DUCT WRAP 615+' OR EQUAL FROM DRYER VENT TO WALL CAP. REFER TO DRYER DUCT FITTINGS EQUIVALENT LENGTHS CHART.

27 PROVIDE WITH IN-WALL DRYER VENT BOX STYLE CONNECTION EQUAL TO THE DRYERBOX DB-480.

28 BAROMETRIC RELIEF DAMPER SET TO OPEN AT +0.05 W.C OF POSITIVE BUILDING PRESSURE.

29 MOUNT UNIT OVER A 4" CONCRETE HOUSEKEEPING PAD.

31 CW SUPPLY/RETURN LINES FROM ABOVE ROOF.

32 DROPS CONNECT TO CW COIL INLET AND OUTLETS. PROVIDE WITH COIL VALVE PACKAGE.

6/20/2024

STATE OF TEXAS
Wilford L. McGee III
121939
PROFESSIONAL ENGINEER

TRINITY
M E P E N G I N E E R I N G

3533 Moreland Dr. Ste A | Weslaco, Tx 78596
p:956.973.0500 | f:956-351-5750
www.trinitymep.com | Copyright 2022
Texas Registered Engineering Firm - F10362
Project number: 23.1.40

MMP05

GENERAL NOTES:

(1.) CONTRACTOR SHALL INCLUDE ALL COST IN BID TO COMPLETE PROJECT BY AUGUST 2025.
(2.) INCLUDE ALL COST TO EXPEDITE ALL HVAC EQUIPMENT FOR A DELIVERY TIME OF 30 WEEKS.

AIR HANDLING UNIT SCHEDULE														CHILLER SCHEDULE				PUMPS SCHEDULE			
TAG	AHU-1	AHU-2	AHU-3	AHU-4	AHU-5,13	AHU-6,7,14,15	AHU-8,9	AHU-10	AHU-11	AHU-12	AHU-16,17	AHU-18	AHU-19	TAG	CH-1,2	TAG	PP-1,2,3	SP-1,2			
	TYPE	MULT ZN VAV	MULT ZN VAV	MULT ZN VAV	MULT ZN VAV	MULT ZN VAV	MULT ZN VAV	SCROLL	LOCATION	CHILLER YARD	CHILLER YARD										
FLOW CONFIGURATION	VERTICAL	VERTICAL	VERTICAL	VERTICAL	VERTICAL	VERTICAL	PHYSICAL PARAMETERS		SERVICE	CWAHU'S											
AREA SERVED	LIBRARY	CAFETERIA	KITCHEN	ADMIN	SPECIAL NEEDS	SPECIAL NEEDS	CLASSROOMS	CLASSROOMS	CLASSROOMS	CLASSROOMS	CLASSROOMS	CLASSROOMS	CLASSROOMS	NOMINAL CAPACITY (TONS)	180	TYPE	END SUCTION	END SUCTION			
SINGLE/DUAL PATH	DUAL	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	CAPACITY AT DESIGN CONDITIONS (TONS)	157	PUMP DETAILS AND ACCESSORIES											
AHU CONSTRUCTION	2" DOUBLE WALL	2" DOUBLE WALL	1" DOUBLE WALL	2" DOUBLE WALL	1" DOUBLE WALL	2" DOUBLE WALL	2" DOUBLE WALL	1" DOUBLE WALL	2" DOUBLE WALL	2" DOUBLE WALL	2" DOUBLE WALL	2" DOUBLE WALL	2" DOUBLE WALL	ENTERING WATER TEMP (DEG F)	56	FLOW (GPM)	320	640			
INDOOR UNIT FAN														LEAVING WATER TEMP (DEG F)	44	DESIGN HEAD (FT.)	35	100			
SUPPLY CFM	6000	8000	3500	5500	1000	500	8400	8400	2200	3500	6000	13500	6400	FOULING FACTOR	0.0001	PUMP EFF. (%)	83%	81%			
MIN. OUTSIDE AIR (CFM)	2000	3000	600	900	350	175	3250	3250	800	400	1750	3850	2000	EVAP CONFIG	2 PASS	MOTOR TYPE	NEMA PREMIUM	NEMA PREMIUM			
EXT. STATIC INCHES WC	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	DESIGN FLOW RATE (GPM)	313	MOTOR HOUSING	TEFC	TEFC			
SINGLE/DUAL PATH	DUAL	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	MIN WATER FLOW RATE (GPM)	245	HP	5	25									
MIN FAN POWER	10 HP	6 HP X 2	5 HP	6 HP	1 HP	0.5 HP	7.5 HP	7.5 HP X 2	1.5 HP	3 HP	7.5 HP	4 HP X 5	4 HP X 2	DESIGN PRESS. DROP FT. WATER	9	RPM	1760	1760			
MIN FAN QUANTITY	1	2	1	1	1	1	1	2	1	1	1	5	2	IMPELLER DIA. (IN.)	6.5"	10.4"					
FAN TYPE	DIRECT DRIVE	BELT DRIVE	DIRECT DRIVE PLenum	DIRECT DRIVE	DIRECT DRIVE	BELT	DIRECT DRIVE	DIRECT DRIVE	DETAILS AND ACCESSORIES		AMBIENT DB (°F)	105									
MOTOR TYPE	VFD	ECM	ECM	ECM	ECM	ECM	VFD	VFD	ECM	ECM	VFD	ECM	ECM	KW INPUT (MAX)	211.5	SUCTION SIZE (IN.)	4	5			
RETURN AIR COOLING COIL														DISCHARGE (IN.)	3	4					
ENTERING AIR DB/WB (°F)	73/61	84.8/70.6	78.27/65.57	77.96/65.32	83.85/69.97	83.85/69.97	73/61	73/61	84.16/70.20	76.41/64.01	73/61	73/61	73/61	VOLTS / PHASE	480/3	VOLTS/PHASE	480/3	480/3			
LEAVING AIR DB/WB (°F)	55/54.1	53.8/53.3	53.9/52.3	53.9/52.6	54.8/53.6	54.2/52.7	55/53.7	54.3/53.3	54.3/53.7	52.5/51.6	55/53.6	55/53.3	55/53.3	POWER CONNECTION	SINGLE POINT						
MIN. TOTAL/SENSIBLE CAPACITY (MBH)	78.9/76.9	441.6/274.3	138.1/69.3.5	207.3/150.2	51.85/32.1	29.4/17.2	106.9/101.7	106.9/101.7	118.2/72.5	114.1/85.2	112.5/95.8	202.2/190.6	96.3/86.9	CKT 1 MCA/MCOP	379/450+	MANUFACTURER	TACO	TACO			
ENTERING/LEAVING WATER TEMP (°F)	44/56	44/56	44/56	44/56	44/56	44/56	44/56	44/56	44/56	44/56	44/56	44/56	44/56	CKT 2 MCA/MCOP	-	MODEL	FI 3007D	FI 4011C			
GPM/PRESSURE DROP	13.1/2.4	73/11	25/8.3	34/4.7	8.9/6	5.1/5	17.8/2	17.8/2	20.3/5	20.3/6	18.7/2.5	33.6/4	12.8/7	MIN. FULL LOAD EFFICIENCY @ ARI (EER)	8.9	NOTES	ALL	ALL			
DESIGN RETURN AIR DB/WB (°F)	73/61	73/61	73/61	73/61	73/61	73/61	73/61	73/61	73/61	73/61	73/61	73/61	73/61	MIN. PART LOAD EFFICIENCY @ API (IPV)	14.8						
OUTSIDE AIR COOLING COIL														NOTES:							
ENTERING AIR DB/WB (°F)	104/83	-	-	-	-	-	104/83	104/83	-	-	104/83	104/83	104/83	MANUFACTURER	TRANE						
LEAVING AIR DB/WB (°F)	54/53.9	-	-	-	-	-	52/51.9	52/51.9	-	-	53/52.9	55/54.57	55/54.45	MODEL	ACSA180						
MIN. TOTAL/SENSIBLE CAPACITY (MBH)	217.8/111.9	-	-	-	-	-	371.3/189.2	362.7/185.5	-	-	195.4/99.9	409/211.1	213/109	MAX OPER. WEIGHT	9600 LBS						
ENTERING/LEAVING WATER TEMP (°F)	44/56	-	-	-	-	-	44/56	44/56	-	-	44/56	44/56	44/56	NOTES	ALL						
GPM/PRESSURE DROP	36.2/8.1	-	-	-	-	-	61.7/12	60.2/12	-	-	32.5/11	54/10	35.4/9	01. SINGLE POINT POWER OF CONNECTION WITH FACTORY CIRCUIT BREAKER.							
DESIGN OUTSIDE AIR DB/WB (°F)	104/83	-	-	-	-	-	104/83	104/83	-	-	104/83	104/83	104/83	02. PROVIDE COMPLETE CONDENSER COIL COATING WITH MINIMUM 5,000 HR							
DETAILS AND ACCESSORIES														SALT SPRAY RATING PER ASMB117. COATING TO BE UV RESISTANT.							
VOLTAGE/PHASE	208/3	208/3	208/3	208/3	208/3	208/3	208/3	208/3	208/3	208/3	208/3	208/3	208/3	03. PROVIDE BACNET OR LONWORKS COMMUNICATION INTERFACE CARD -							
MCA/MCOP	37/60	25.2/35	19.7/35	14.7/25	5.75/15	3/15	31.75/50	29.1/50 x2	9.5/1.5	14/25	31.7/50	11.63/20 X4	11/15 x2	COORDINATE REQUIREMENTS WITH SUCCESSFUL CONTROLS CONTRACTOR							
MANUFACTURER	TRANE	TRANE	TRANE	TRANE	TRANE	TRANE	04. PROVIDE 120V CONVENIENCE OUTLET. UNIT 20A RATED.														
MODEL	PCC	PCC	BCVE090	PCC	BCVE036	BCVE024	PCC	BCVE090	BCVE120	PCC	PCC	BCVE120	PCC	05. PROVIDE 5-YR ENTIRE UNIT PARTS, LABOR AND REFRIGERANT WARRANTY.							
MAX LENGTH/WIDTH/HEIGHT (INCH)	126X51X70	77X9X72	31x48x67	68X71X71	23x30x50	62x30x17	108x71x84	136x67x83	31x48x67	108x71x81	125x80x94	125x67x81	2300 lbs	06. PROVIDE WITH HUMAN INTERFACE PANEL.							
MAX WEIGHT (lbs)	1880 LBS	1500 LBS	500 lbs	1200 lbs	250 lbs	2200 lbs	2500 lbs	500 lbs	2300 lbs	3100 lbs	2100 lbs			07. PROVIDE WITH FULL ARCHITECTURAL LOUVERS ON COILS AND BASE FRAME							
NOTES	1-7	1-7	1-7	1-7	1-7	1-7	1-7	1-7	1-7	1-7	1-7	1-7	1-7	08. PROVIDE W/ FACTORY EC MOTOR FANS							

LOUVER SCHEDULE										ROOF CAP SCHEDULE							
TAG	L-1	L-2	L-3	L-4	L-5	L-6	L-7,8	L-9-13	TAG	RC-1	RC-2	RC-3,6	RC-4,5,7,8	TAG	INTAKE	INTAKE	INTAKE
TYPE	INTAKE	INTAKE	INTAKE	INTAKE	INTAKE	EXHAUST	EXHAUST	SERVES	INTAKE	INTAKE	INTAKE	INTAKE	LOCATION	ROOF	ROOF	ROOF	

<tbl_r cells="16" ix="4" maxcspan="

TERMINAL UNIT SCHEDULE - D (AHU-8)

NOTES
01. PROVIDE A MATTE FACE INTERIOR LINE
02. FACTORY INSTALLED 3RD PARTY CONT.

TERMINAL UNIT SCHEDULE - E (AHU-9)

NOTES

01. PROVIDE A MATTE FACE INTERIOR LINER.
02. FACTORY INSTALLED 3RD PARTY CONTROLS. TERMINAL UNIT MFGR. SHALL PROVIDE CONTROLS TRANSFORMER.
03. PROVIDE POWER FOR TRANSFORMERS

TERMINAL UNIT SCHEDULE - F (AHU-10)

NOTES

01. PROVIDE A MATTE FACE INTERIOR LINER.
02. FACTORY INSTALLED 3RD PARTY CONTROLS. TERMINAL UNIT MFGR. SHALL PROVIDE CONTROLS TRANSFORMER.
03. PROVIDE POWER FOR TRANSFORMERS.

TERMINAL UNIT SCHEDULE - G (AHU-11)

TU-F-11	TAG	TU-G-01	TU-G-02
SINGLE DUCT	TYPE	SINGLE DUCT	SINGLE DUCT
CORRIDOR	AREA SERVED	RM 100	RM 101
	LOCATION		
AIR FLOW CHARACTERISTICS			
N/A	FAN FLOW (CFM)	N/A	N/A
100/50	MAX/MIN PRIMARY (CFM)	1100/400	1100/400
N/A	MAX/MIN REHEAT (CFM)	N/A	N/A
0.25	MAX AIR PRESSURE DROP (in.wg)	0.25	0.25
HEATING COIL PERFORMANCE			
NONE	HEAT TYPE	NONE	NONE
-	ENTERING/LEAVING AIR TEMP. (F°)	-	-
120/1	VOLTS/PHASE	120/1	120/1
-/-	HEAT INPUT/STAGES	-	-
-	MCA/MOCP	-	-
PHYSICAL PROPERTIES & ACCESSORIES			
N/A	FAN MOTOR VOLTAGE/PHASE	N/A	N/A
4"Ø	INLET SIZE	12"Ø	12"Ø
12"x8"	OUTLET SIZE	16"x16"	16"x16"
-- NC	MAX RADIATED NOISE	-- NC	-- NC
75 lbs	MAX WEIGHT	100 lbs	100 lbs
PRICE	MANUFACTURER	PRICE	PRICE
SDV5	MODEL	SDV5	SDV5
4	MODEL SIZE	12	12
1-3	NOTES	12.3	12.3

NOTES

01. PROVIDE A MATTE FACE INTERIOR LINER.
02. FACTORY INSTALLED 3RD PARTY CONTROLS. TERMINAL UNIT MFGR. SHALL PROVIDE CONTROLS TRANSFORMER.
03. PROVIDE POWER FOR TRANSFORMERS.

TERMINAL UNIT SCHEDULE - H (AHU-12)

TAG	TU-H-01	TU-H-02	TU-H-03	TU-H-04	TU-H-05	TU-H-06	TU-H-07	TAG
	TYPE	SINGLE DUCT	SINGLE DUCT	SINGLE DUCT	SINGLE DUCT	SINGLE DUCT	SINGLE DUCT	
AREA SERVED	GENERAL OFFICE	ASST PRINCIPAL	NURSE	LOUNGE	LOUNGE	RRs	TEACHER WORK	
LOCATION			NURSE					
AIR FLOW CHARACTERISTICS								AIR FLOW CHARACTERISTICS
FAN FLOW (CFM)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	F.
MAX/MIN PRIMARY (CFM)	525/125	300/75	325/75	300/75	850/200	250/50	850/200	MAX/MIN
MAX/MIN REHEAT (CFM)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	MAX/MIN
MAX AIR PRESSURE DROP (in.wg)	0.25	0.25	0.25	0.25	0.25	0.25	0.25	MAX AIR PRESSURE
HEATING COIL PERFORMANCE								HEATING COIL PERFORMANCE
HEAT TYPE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	
ENTERING/LEAVING AIR TEMP. (F°)	-	-	-	-	-	-	-	ENTERING/LEAVING
VOLTS/PHASE	120/1	120/1	120/1	120/1	120/1	120/1	120/1	
HEAT INPUT/STAGES	-/-	-/-	-/-	-/-	-/-	-/-	-/-	HEAT
MCA/MOCP	-	-	-	-	-	-	-	
PHYSICAL PROPERTIES & ACCESSORIES								PHYSICAL PROPERTIES & ACCESSORIES
FAN MOTOR VOLTAGE/PHASE	N/A	N/A	N/A	N/A	N/A	N/A	N/A	FAN MOTOR V
INLET SIZE	8"Ø	6"Ø	6"Ø	6"Ø	10"Ø	6"Ø	10"Ø	
OUTLET SIZE	12"x10"	12"x8"	12"x8"	12"x8"	14"x12"	12"x8"	14"x12"	
MAX RADIATED NOISE	-- NC	-- NC	-- NC	-- NC	-- NC	-- NC	-- NC	MAX R
MAX WEIGHT	75 lbs	75 lbs	75 lbs	75 lbs	75 lbs	75 lbs	75 lbs	
MANUFACTURER	PRICE	PRICE	PRICE	PRICE	PRICE	PRICE	PRICE	
MODEL	SDV5	SDV5	SDV5	SDV5	SDV5	SDV5	SDV5	M
MODEL SIZE	8	6	6	6	10	6	10	

NOTES

01. PROVIDE A MATTE FACE INTERIOR LINER.
02. FACTORY INSTALLED 3RD PARTY CONTROLS. TERMINAL UNIT MFGR. SHALL PROVIDE CONTROLS TRANSFORMER
03. PROVIDE POWER FOR TRANSFORMERS

TERMINAL UNIT SCHEDULE - I (AHU-19)

TERMINAL UNIT SCHEDULE - 1 (AIRC 17)								
'ICT ORK	TAG	TU-I-01	TU-I-02	TU-I-03	TU-I-04	TU-I-05	TU-I-06	TU-I-07
	TYPE	SINGLE DUCT						
	AREA SERVED	RM 131/HALL	RM 132	RM 158	TESTING	CONFERENCE	RM 157/HALL	RM 155
LOCATION								
AIR FLOW CHARACTERISTICS								
0	FAN FLOW (CFM)	N/A						
	MAX/MIN PRIMARY (CFM)	1150/350	1050/350	1200/350	300/75	300/75	1200/350	1200/350
	MAX/MIN REHEAT (CFM)	N/A						
MAX AIR PRESSURE DROP (in.wg)								
HEATING COIL PERFORMANCE								
	HEAT TYPE	NONE						
	ENTERING/LEAVING AIR TEMP. (F°)	-	-	-	-	-	-	-
	VOLTS/PHASE	120/1	120/1	120/1	120/1	120/1	120/1	120/1
	HEAT INPUT/STAGES	-/-	-/-	-/-	-/-	-/-	-/-	-/-
	MCA/MOCP	-	-	-	-	-	-	-
	PHYSICAL PROPERTIES & ACCESSORIES							
	FAN MOTOR VOLTAGE/PHASE	N/A						
	INLET SIZE	12"Ø	12"Ø	12"Ø	6"Ø	6"Ø	12"Ø	12"Ø
	OUTLET SIZE	16"x16"	16"x16"	16"x16"	12"x8"	12"x8"	16"x16"	16"x16"
	MAX RADIATED NOISE	-- NC						
	MAX WEIGHT	75 lbs						
	MANUFACTURER							
	PRICE	PRICE	PRICE	PRICE	PRICE	PRICE	PRICE	
	MODEL	SDV5	SDV5	SDV5	SDV5	SDV5	SDV5	
	MODEL SIZE	12	12	12	6	6	12	12

NOTES
01. PROVIDE A MATTE FACE INTERIOR LINER.
02. FACTORY INSTALLED 3RD PARTY CONTROLS. TERMINAL UNIT MFGR. SHALL PROVIDE CONTROLS TRANSFORMER.

TERMINAL UNIT SCHEDULE - J (AHU-18)

TAG	TU-J-01	TU-J-02	TU-J-03	TU-J-04	TU-J-05	TU-J-06	TU-J-07	TU-J-08	TU-J-09	TU-J-10	TU-J-11	TU-J-12	TU-J-13
TYPE	SINGLE DUCT												
AREA SERVED	BOOK RM	RM 133	RM 139	RM 135/HALL	RM 136	RM 137	RM 138	RM 139/HALL	RM 141/HALL	RM 140	RM 142	RM 143	RR
LOCATION													
AIR FLOW CHARACTERISTICS													
FAN FLOW (CFM)	N/A												
MAX/MIN PRIMARY (CFM)	300/75	1200/350	1100/350	1300/400	1300/400	1200/350	1300/400	1300/400	1200/350	1100/350	200/50		
MAX/MIN REHEAT (CFM)	N/A												
MAX AIR PRESSURE DROP (in.wg)	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
HEATING COIL PERFORMANCE													
HEAT TYPE	NONE												
ENTERING/LEAVING AIR TEMP. (°F)	-	-	-	-	-	-	-	-	-	-	-	-	-
VOLTS/PHASE	120/1	120/1	120/1	120/1	120/1	120/1	120/1	120/1	120/1	120/1	120/1	120/1	120/1
HEAT INPUT/STAGES	-/-	-/-	-/-	-/-	-/-	-/-	-/-	-/-	-/-	-/-	-/-	-/-	-/-
MCA/MOPC	-	-	-	-	-	-	-	-	-	-	-	-	-
PHYSICAL PROPERTIES & ACCESSORIES													
FAN MOTOR VOLTAGE/PHASE	N/A												
INLET SIZE	6"Ø	12"Ø	4"Ø										
OUTLET SIZE	12"X8"	16"X16"	12"X8"										
MAX RADIATED NOISE	-- NC												
MAX WEIGHT	75 lbs												
MANUFACTURER	PRICE												
MODEL	SDV5												
MODEL SIZE	6	12	12	12	12	12	12	12	12	12	12	12	4
NOTES	1-3	1-3	1-3	1-3	1-3	1-3	1-3	1-3	1-3	1-3	1-3	1-3	1-3

NOTES
01. PROVIDE A MATTE FACE INTERIOR LINER.
02. FACTORY INSTALLED 3RD PARTY CONTROLS. TERMINAL UNIT MFGR. SHALL PROVIDE CONTROLS TRANSFORMER.
03. PROVIDE POWER FOR TRANSFORMERS.


TERMINAL UNIT SCHEDULE - K (AHU-17)


TAG	TU-K-01	TU-K-02	TU-K-03	TU-K-04	TU-K-05	TU-K-06
TYPE	SINGLE DUCT					
AREA SERVED	BOOK RM	RM 133	RM 139	RM 135/HALL	RM 136	RM 137
LOCATION						
AIR FLOW CHARACTERISTICS						
FAN FLOW (CFM)	N/A	N/A	N/A	N/A	N/A	N/A
MAX/MIN PRIMARY (CFM)	1200/350	1300/400	1200/350	1200/350	1100/350	200/50
MAX/MIN REHEAT (CFM)	N/A	N/A	N/A	N/A	N/A	N/A
MAX AIR PRESSURE DROP (in.wg)	0.25	0.25	0.25	0.25	0.25	0.25
HEATING COIL PERFORMANCE						
HEAT TYPE	NONE	NONE	NONE	NONE	NONE	NONE
ENTERING/LEAVING AIR TEMP. (°F)	-	-	-	-	-	-
VOLTS/PHASE	120/1	120/1	120/1	120/1	120/1	120/1
HEAT INPUT/STAGES	-/-	-/-	-/-	-/-	-/-	-/-
MCA/MOPC	-	-	-	-	-	-
PHYSICAL PROPERTIES & ACCESSORIES						
FAN MOTOR VOLTAGE/PHASE	N/A	N/A	N/A	N/A	N/A	N/A
INLET SIZE	12"Ø	12"Ø	12"Ø	12"Ø	12"Ø	4"Ø
OUTLET SIZE	16"X16"	16"X16"	16"X16"	16"X16"	16"X16"	16"X16"
MAX RADIATED NOISE	-- NC					
MAX WEIGHT	75 lbs					
MANUFACTURER	PRICE	PRICE	PRICE	PRICE	PRICE	PRICE
MODEL	SDV5	SDV5	SDV5	SDV5	SDV5	SDV5
MODEL SIZE	12	12	12	12	12	4
NOTES	1-3	1-3	1-3	1-3	1-3	1-3

NOTES
01. PROVIDE A MATTE FACE INTERIOR LINER.
02. FACTORY INSTALLED 3RD PARTY CONTROLS. TERMINAL UNIT MFGR. SHALL PROVIDE CONTROLS TRANSFORMER.
03. PROVIDE POWER FOR TRANSFORMERS.


FAN SCHEDULE


TAG	EF-1,2,5,16	EF-3,4,11	EF-6	EF-7,17	EF-8,10,15,18-20	EF-12	EF-13	EF-14	EF-21	EF-22	TAG	TU-L-01	TU-L-02	TU-L-03	TU-L-04	TU-L-05
SERVICE	RRs	RRs	RRs	SPEC NEEDS HALL	RRs	BREAK ROOM	RR	NURSE	STORAGE/MDF	CUSTODIAL	TYPE	SINGLE DUCT				
LOCATION	CEILING	CEILING	CEILING	ROOF	CEILING	ROOF	ROOF	CEILING	CEILING	CEILING	AREA SERVED	RM 150/RR	RM 149	RM 151	RM 152	RM 153
UNIT TYPE	Cooling Only	Heat Pump	Cooling Only	Heat Pump							LOCATION					
FAN PROPERTIES											AIR FLOW CHARACTERISTICS					
CFM	150	300	100	200	350	200	350	200	200	200	FAN FLOW (CFM)	N/A	N/A	N/A	N/A	N/A
FAN RPM	1020	1544	838	1616	1488	1508	1616	838	838	838	INLET SIZE	12"Ø	12"Ø	12"Ø	12"Ø	12"Ø
EXT SP (IN WG)	0.2	0.5	0.2	0.25	0.5	0.5	0.5	0.25	0.25	0.25	OUTLET SIZE	16"X16"	16"X16"	16"X16"	16"X16"	16"X16"
FAN MOTOR SIZE	128 W	1/6 HP	80 W	43 W	1/10 HP ECM	1/4 HP - ECM	1/10 HP - ECM	43 W	43 W	43 W	MAX RADIATED NOISE	-- NC				
ENTERING AIR (DB/WB)	74/62	74/62	74/62	74/62	120/1	120/1	120/1	120/1	120/1	120/1	MAX AIR PRESSURE DROP (in.wg)	0.25	0.25	0.25	0.25	0.25
TOTAL CAPACITY (BTUH)	9,000	12,000	12,000	9,000	12,000	12,000	12,000	12,000	12,000	12,000	HEATING COIL PERFORMANCE					
HEATING CAPACITY (BTUH)	0	12,000	0	9,000							HEAT TYPE	NONE	NONE	NONE	NONE	NONE
UNIT DETAILS											ENTERING/LEAVING AIR TEMP. (°F)	-	-	-	-	-
VOLTAGE/PHASE	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	VOLTS/PHASE	120/1	120/1	120/1	120/1	120/1
MANUFACTURER	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	HEAT INPUT/STAGES	-/-	-/-	-/-	-/-	-/-



TRINITY
M E P ENGINEERING

3533 Moreland Dr. Ste. A, Weslaco, Tx 78596
p: 956.973.0600 | f: 956.351.5760
www.trinitymep.com | Copyright 2022
Texas Registered Engineering Firm - F10362
Project number: 23.1.40





DUAL PATH CW MULTI-ZONE VARIABLE AIR VOLUME AIR HANDLING UNIT (TYPICAL)

THE AHU SHALL RUN BASED ON A USER DEFINED OCCUPANCY SCHEDULE OR WHEN REQUESTED FOR HEATING OR COOLING DURING UNOCCUPIED MODE. TO PREVENT SHORT CYCLING, THE SUPPLY FAN SHALL HAVE A USER DEFINABLE (ADJ.) MINIMUM RUNTIME.

THE UNIT SHALL SHUT DOWN AND GENERATE AN ALARM ON ANY OF THE FOLLOWING CONDITIONS:

- FREEZE PROTECTION STATUS IN ALARM
- SUPPLY AIR HIGH STATIC
- SMOKE DETECTOR STATUS IN ALARM
- AHU OPTIMAL START SHALL START PRIOR TO SCHEDULED OCCUPANCY BASED ON THE TIME NECESSARY FOR THE ZONES TO REACH THEIR OCCUPIED SETPOINTS. THE START TIME SHALL AUTOMATICALLY ADJUST BASED ON CHANGES IN OUTSIDE AIR TEMPERATURE AND ZONE TEMPERATURES.

MINIMUM OUTSIDE AIR VENTILATION:

MINIMUM OUTSIDE AIR VENTILATION - CARBON DIOXIDE (CO2) CONTROL:

THE OUTSIDE AIR DAMPERS WILL MAINTAIN A MINIMUM POSITION OF 10% (ADJ.) OPEN WHENEVER OCCUPIED. WHEN IN THE OCCUPIED MODE, THE CONTROLLER WILL MEASURE THE RETURN AIR CO2 CONCENTRATION AND MODULATE THE OUTSIDE AIR DAMPERS OPEN (AND IF NEEDED START MODULATING DOWN THE RA DAMPERS) ON RISING CO2 CONCENTRATIONS, OVERRIDE NORMAL DAMPER OPERATIONS TO MAINTAIN A CO2 SETPOINT OF 800 PPM TO 1000 PPM (ADJ.).

RETURN AIR CARBON DIOXIDE (CO2) CONCENTRATION MONITORING & DEMAND CONTROL VENTILATION (DCV):

THE CONTROLLER SHALL MEASURE THE RETURN AIR CO2 CONCENTRATION. VARIABLE OUTSIDE AIR DAMPERS (& RETURN AIR DAMPERS IF REQUIRED) SHALL MODULATE TO MAINTAIN CO2 CONCENTRATIONS BETWEEN 800-1100 PPM (ADJ.). OPEN/CLOSED OA DAMPERS SHALL OPEN WHEN CO2 CONCENTRATION REACHES 1100 PPM (ADJ.) OR HIGHER AND SHALL CLOSE WHEN CO2 CONCENTRATION REACHES 800 PPM (ADJ.) OR LOWER.

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH RETURN AIR CARBON DIOXIDE CONCENTRATION: IF THE RETURN AIR CO2 CONCENTRATION IS GREATER THAN 1200PPM (ADJ.) WHEN IN THE UNIT IS RUNNING.

OUTSIDE AIR COOLING/HEATING STAGES:

THE CONTROLLER SHALL MEASURE THE OUTSIDE AIR SUPPLY AIR TEMPERATURE AND MODULATED COOL/HEAT TO MAINTAIN OUTSIDE SUPPLY AIR SETPOINT, INITIALLY SET AT 52°F (ADJ.).

THE COOLING SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS GREATER THAN 54°F (ADJ.)
- AND THE SUPPLY FAN STATUS IS ON
- AND THE OUTSIDE AIR DAMPER IS OPEN

THE HEATING SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS LESS THAN 50°F (ADJ.)
- AND THE SUPPLY FAN STATUS IS ON
- AND THE OUTSIDE AIR DAMPER IS OPEN

SUPPLY AIR DUCT STATIC PRESSURE CONTROL:

THE CONTROLLER SHALL MEASURE DUCT STATIC PRESSURE AND MODULATE THE SUPPLY FAN VFD SPEED TO MAINTAIN A DUCT STATIC PRESSURE SETPOINT. THE SPEED SHALL NOT DROP BELOW 10% (ADJ.).

THE STATIC PRESSURE SETPOINT SHALL BE RESET BASED UPON THE POSITION OF THE ZONE DAMPERS, WITH A GOAL OF REDUCING THE STATIC PRESSURE UNTIL AT LEAST ONE ZONE DAMPER IS NEARLY WIDE OPEN. THE INITIAL DUCT STATIC PRESSURE SETPOINT SHALL BE 2.0IN H2O (ADJ.). IF NO ZONE DAMPER IS NEARLY WIDE OPEN, THE SETPOINT SHALL INCREMENTALLY RESET DOWN TO A MINIMUM OF 1.25IN H2O (ADJ.). AS ONE OR MORE DAMPERS NEARS THE WIDE OPEN POSITION, THE SETPOINT SHALL INCREMENTALLY RESET UP TO A MAXIMUM OF 1.8IN H2O (ADJ.).

THE OUTSIDE AIR IS DRAWN THROUGH ITS OWN COOLING COIL TO DEHUMIDIFY IT, WHICH THEN MIXES WITH THE AIR DRAWN THROUGH THE RETURN COOLING COIL. UNDER PART LOAD CONDITIONS, THIS ALLOWS SUPPLY AIR TO RESET TO HIGHER DRY BULB TEMPERATURES WHILE STILL MAINTAINING LOW WET BULB CONDITIONS.

SUPPLY AIR TEMPERATURE SETPOINT - OPTIMIZED:

THE CONTROLLER SHALL MONITOR THE SUPPLY AIR TEMPERATURE AND SHALL MAINTAIN A SUPPLY AIR TEMPERATURE SETPOINT RESET BASED ON ZONE COOLING AND HEATING REQUIREMENTS.

THE SUPPLY AIR TEMPERATURE SETPOINT SHALL BE RESET FOR COOLING BASED ON ZONE COOLING REQUIREMENTS AS FOLLOWS:

THE INITIAL SUPPLY AIR TEMPERATURE SETPOINT SHALL BE 55°F (ADJ.). AS COOLING DEMAND INCREASES, THE SETPOINT SHALL INCREMENTALLY RESET DOWN TO A MINIMUM OF 53°F (ADJ.). AS COOLING DEMAND DECREASES, THE SETPOINT SHALL INCREMENTALLY RESET UP TO A MAXIMUM OF 60°F (ADJ.).

IF MORE ZONES NEED HEATING THAN COOLING (HEAT MODE), THEN THE SUPPLY AIR TEMPERATURE SETPOINT SHALL BE RESET FOR HEATING AS FOLLOWS: THE INITIAL SUPPLY AIR TEMPERATURE SETPOINT SHALL BE 80°F (ADJ.). AS HEATING DEMAND INCREASES, THE SETPOINT SHALL INCREMENTALLY RESET UP TO A MAXIMUM OF 85°F (ADJ.). AS HEATING DEMAND DECREASES, THE SETPOINT SHALL INCREMENTALLY RESET DOWN TO A MINIMUM OF 72°F (ADJ.).

RETURN AIR COOLING/HEATING STAGES:

THE CONTROLLER SHALL MEASURE THE SUPPLY AIR TEMPERATURE AND MODULATED CHILLED WATER VALVES TO MAINTAIN SUPPLY AIR COOLING SETPOINT.

THE COOLING SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS GREATER THAN 60°F (ADJ.)
- AND THE SUPPLY FAN STATUS IS ON
- AND THE OUTSIDE AIR DAMPER IS OPEN

THE HEATING SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS LESS THAN 55°F (ADJ.)
- AND THE SUPPLY FAN STATUS IS ON
- AND THE OUTSIDE AIR DAMPER IS OPEN

ELECTRIC HEATING WITH SCR:

THE CONTROLLER SHALL MEASURE THE SUPPLY AIR TEMPERATURE AND MODULATE THE HEATING TO MAINTAIN ITS SUPPLY AIR TEMPERATURE SETPOINT.

THE HEATING WILL BE ENABLED WHENEVER:

- THE AHU IS IN HEAT MODE
- AND THE SUPPLY AIR TEMPERATURE IS BELOW SUPPLY AIR TEMPERATURE SETPOINT
- AND THE FAN IS ON.

DEHUMIDIFICATION (DURING COOLING):

WHEN RA RH% REACHES OR EXCEEDS 60% (ADJ.), BAS SHALL MODULATE CW VALVE ON OA COIL, TO RESET COIL LAT TO 50°F (ADJ.) AND RA COIL TO RESET TO 60°F (ADJ.). AFTER 15 MINUTES (ADJ.), IF RH IS NOT BELOW 55% (ADJ.), RA COIL LAT MAY CONTINUE TO RESET UP TO 65°F (ADJ.) BASED ON SA TEMP RESET SEQUENCE DURING DEHUMIDIFICATION. WHEN RA RH% DROPS BELOW 55% (ADJ.), SYSTEM TO REVERT BACK TO NORMAL COOLING AFTER AN ADDITIONAL 15 MINUTE (ADJ.) TIMER EXPIRES OR RH DROPS BELOW 50% (ADJ.), WHICHEVER COMES FIRST.

PREFILTER STATUS:

THE CONTROLLER SHALL MONITOR THE PREFILTER STATUS.

THE CONTROLLER SHALL MONITOR:

- RETURN AIR HUMIDITY.
- RETURN AIR TEMPERATURE.
- SUPPLY AIR HUMIDITY.
- SUPPLY AIR TEMPERATURE.


ALARMS SHALL BE PROVIDED AS FOLLOWS:

- SUPPLY FAN FAILURE: COMMANDED ON, BUT THE STATUS IS OFF.
- SUPPLY FAN IN HAND: COMMANDED OFF, BUT THE STATUS IS ON.
- HIGH SUPPLY AIR STATIC PRESSURE: IF THE SUPPLY AIR STATIC PRESSURE IS 25% (ADJ.) GREATER THAN SETPOINT.
- LOW SUPPLY AIR STATIC PRESSURE: IF THE SUPPLY AIR STATIC PRESSURE IS 25% (ADJ.) LESS THAN SETPOINT.
- SUPPLY FAN VFD FAULT.
- FREEZE STAT TRIPPED ALARM
- HIGH SUPPLY AIR TEMP: IF THE SUPPLY AIR TEMPERATURE IS 5°F (ADJ.) GREATER THAN SETPOINT.
- LOW SUPPLY AIR TEMP: IF THE SUPPLY AIR TEMPERATURE IS 5°F (ADJ.) LESS THAN SETPOINT.
- PREFILTER CHANGE REQUIRED: PREFILTER DIFFERENTIAL PRESSURE EXCEEDS A USER DEFINABLE LIMIT (ADJ.).
- FINAL FILTER CHANGE REQUIRED: FINAL FILTER DIFFERENTIAL PRESSURE EXCEEDS A USER DEFINABLE LIMIT (ADJ.).
- HIGH RETURN AIR HUMIDITY: IF THE RETURN AIR HUMIDITY IS GREATER THAN 70% (ADJ.).
- LOW RETURN AIR HUMIDITY: IF THE RETURN AIR HUMIDITY IS LESS THAN 35% (ADJ.).
- HIGH SUPPLY AIR TEMP: IF THE SUPPLY AIR TEMPERATURE IS GREATER THAN 120°F (ADJ.).
- LOW SUPPLY AIR TEMP: IF THE SUPPLY AIR TEMPERATURE IS LESS THAN 45°F (ADJ.).



06/20/2024
Wilford L. McGee III
121833
Project number: 23.1.40

MMC01

**SINGLE PATH CW SINGLE ZONE VAV****RUN CONDITIONS - REQUESTED:**

- SCHEDULED OCCUPIED
- UNOCCUPIED BEYOND SETPOINT

FREEZE PROTECTION:
A HARDWIRED, LOW LIMIT TEMPERATURE SWITCH SHALL BE ELECTRICALLY INTERLOCKED WITH THE VARIABLE SPEED DRIVE. IF THE LOW LIMIT TEMPERATURE SWITCH IS TRIPPED 38F, THE OUTSIDE AIR DAMPER SHALL CLOSE, AND THE UNIT SHALL SHUT DOWN AND GENERATE AN ALARM UPON RECEIVING A FREEZESTAT STATUS. A MANUAL RESET OF THE LOW LIMIT TEMPERATURE SWITCH SHALL BE REQUIRED TO RESTART THE FAN.

HIGH STATIC SHUTDOWN:
THE UNIT SHALL SHUT DOWN AND GENERATE AN ALARM UPON RECEIVING AN HIGH STATIC SHUTDOWN SIGNAL.

SMOKE DETECTION SHUTDOWN:
IF THE BUILDING DOES NOT HAVE A FIRE ALARM SYSTEM, THE UNIT SHALL SHUT DOWN AND GENERATE AN ALARM TO THE BAS UPON RECEIVING A SUPPLY OR RETURN AIR SMOKE DETECTOR ALARM STATUS. IF THE BUILDING HAS A FIRE ALARM SYSTEM, THE BUILDING FIRE ALARM SYSTEM SHALL PROVIDE AN AIR HANDLER SHUTDOWN SIGNAL TO EACH AIR HANDLER. THE BUILDING FIRE ALARM SYSTEM SHALL PROVIDE ONE DIGITAL OUTPUT TO THE BAS TO INDICATE AN ALARM CONDITION. WIRING FOR THIS ALARM POINT SHALL BE PROVIDED BY THE BAS PROVIDER THROUGH COORDINATION WITH THE FIRE ALARM SYSTEM PROVIDER.

AHU OPTIMAL START:
THE UNIT SHALL START PRIOR TO SCHEDULED OCCUPANCY BASED ON THE TIME NECESSARY FOR THE ZONES TO REACH THEIR OCCUPIED SETPOINTS. THE START TIME SHALL AUTOMATICALLY ADJUST BASED ON CHANGES IN OUTSIDE AIR TEMPERATURE AND ZONE TEMPERATURES.

SUPPLY FAN:
THE SUPPLY FAN SHALL RUN ANYTIME THE UNIT IS COMMANDED TO RUN, UNLESS SHUTDOWN ON SAFETIES. TO PREVENT SHORT CYCLING, THE SUPPLY FAN SHALL HAVE A USER DEFINABLE (ADJ.) MINIMUM RUNTIME.

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- SUPPLY FAN FAILURE: COMMANDED ON, BUT THE STATUS IS OFF.
- SUPPLY FAN IN HAN: COMMANDED OFF, BUT THE STATUS IS ON.

SUPPLY AIR TEMPERATURE SETPOINT - OPTIMIZED:
THE CONTROLLER SHALL MONITOR THE SUPPLY AIR TEMPERATURE AND SHALL MAINTAIN A SUPPLY AIR TEMPERATURE SETPOINT RESET BASED ON ZONE COOLING AND HEATING REQUIREMENTS. THE SUPPLY AIR TEMPERATURE SETPOINT SHALL BE RESET FOR COOLING BASED ON ZONE COOLING REQUIREMENTS AS FOLLOWS:

- THE INITIAL SUPPLY AIR TEMPERATURE SETPOINT SHALL BE 55°F (ADJ.).
- AS COOLING DEMAND INCREASES, THE SETPOINT SHALL INCREMENTALLY RESET DOWN TO A MINIMUM OF 53°F (ADJ.).
- AS COOLING DEMAND DECREASES, THE SETPOINT SHALL INCREMENTALLY RESET UP TO A MAXIMUM OF 65°F (ADJ.).

IF MORE ZONES NEED HEATING THAN COOLING, THEN THE SUPPLY AIR TEMPERATURE SETPOINT SHALL BE RESET FOR HEATING AS FOLLOWS:

- THE INITIAL SUPPLY AIR TEMPERATURE SETPOINT SHALL BE 82°F (ADJ.).
- AS HEATING DEMAND INCREASES, THE SETPOINT SHALL INCREMENTALLY RESET UP TO A MAXIMUM OF 85°F (ADJ.).
- AS HEATING DEMAND DECREASES, THE SETPOINT SHALL INCREMENTALLY RESET DOWN TO A MINIMUM OF 72°F (ADJ.).

COOLING/HEATING STAGES:
THE CONTROLLER SHALL MEASURE THE SUPPLY AIR TEMPERATURE AND STAGE THE COMPRESSORS TO MAINTAIN SUPPLY AIR COOLING SETPOINT.

THE COOLING SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS GREATER THAN 60°F (ADJ.)
- AND THE SUPPLY FAN STATUS IS ON
- AND THE AHU IS NOT IN HEAT MODE

THE HEATING SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS LESS THAN 55°F (ADJ.)
- AND THE SUPPLY FAN STATUS IS ON
- AND THE AHU IS IN HEAT MODE

LOW SUPPLY AIR TEMPERATURE ALARM:
THE CONTROLLER SHALL ALARM IF THE SUPPLY AIR TEMPERATURE IS LESS THAN 45°F (ADJ.).

ECONOMIZER:
THE CONTROLLER SHALL MEASURE THE MIXED AIR TEMPERATURE AND MODULATE THE ECONOMIZER DAMPERS IN SEQUENCE TO MAINTAIN A SETPOINT 2°F (ADJ.) LESS THAN THE SUPPLY AIR TEMPERATURE SETPOINT. THE OUTSIDE AIR DAMPERS SHALL MAINTAIN A MINIMUM ADJUSTABLE POSITION OF 20% (ADJ.) OPEN WHENEVER OCCUPIED.

THE ECONOMIZER SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS LESS THAN 65°F (ADJ.).
- AND THE OUTSIDE AIR ENTHALPY IS LESS THAN THE RETURN AIR ENTHALPY.
- AND THE SUPPLY FAN STATUS IS ON.

THE ECONOMIZER SHALL CLOSE WHENEVER:

- MIXED AIR TEMPERATURE DROPS FROM 40°F TO 35°F (ADJ.)
- OR THE FREEZESTAT (IF PRESENT) IS ON.
- OR ON LOSS OF SUPPLY FAN STATUS.

THE OUTSIDE AIR DAMPERS SHALL CLOSE AND THE RETURN AIR DAMPER SHALL OPEN WHEN THE UNIT IS OFF. IF OPTIMAL START UP IS AVAILABLE THE MIXED AIR DAMPER SHALL OPERATE AS DESCRIBED IN THE OCCUPIED MODE EXCEPT THAT THE OUTSIDE AIR DAMPER SHALL MODULATE TO FULLY CLOSED.

MINIMUM OUTSIDE AIR VENTILATION - FIXED PERCENTAGE:
THE OUTSIDE AIR DAMPERS SHALL MAINTAIN A MINIMUM ADJUSTABLE POSITION DURING BUILDING OCCUPIED HOURS AND BE CLOSED DURING UNOCCUPIED HOURS.

FILTER STATUS:
THE CONTROLLER SHALL MONITOR THE FILTER STATUS AND GENERATE AN ALARM AT THE BAS WHEN DIFFERENTIAL PRESSURE IS EXCEEDED.

MIXED AIR TEMPERATURE:
THE CONTROLLER SHALL MONITOR THE MIXED AIR TEMPERATURE AND USE AS REQUIRED FOR ECONOMIZER CONTROL (IF PRESENT) OR PREHEATING CONTROL (IF PRESENT). ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH MIXED AIR TEMP: IF THE MIXED AIR TEMPERATURE IS GREATER THAN 90°F (ADJ.).
- LOW MIXED AIR TEMP: IF THE MIXED AIR TEMPERATURE IS LESS THAN 45°F (ADJ.).

RETURN AIR CARBON DIOXIDE (CO₂) CONCENTRATION MONITORING & DEMAND CONTROL VENTILATION (DCV):

THE CONTROLLER SHALL MEASURE THE RETURN AIR CO₂ CONCENTRATION. VARIABLE OUTSIDE AIR DAMPERS & RETURN AIR DAMPERS (IF REQUIRED) SHALL MODULATE TO MAINTAIN CO₂ CONCENTRATIONS BETWEEN 800-1100 PPM (ADJ.). OPEN/CLOSED OA DAMPERS SHALL OPEN WHEN CO₂ CONCENTRATION REACHES 1100 PPM (ADJ.) OR HIGHER AND SHALL CLOSE WHEN CO₂ CONCENTRATION REACHES 800 PPM (ADJ.) OR LOWER.

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH RETURN AIR CARBON DIOXIDE CONCENTRATION: IF THE RETURN AIR CO₂ CONCENTRATION IS GREATER THAN 1200PPM (ADJ.) WHEN IN THE UNIT IS RUNNING.

RETURN AIR HUMIDITY:
THE CONTROLLER SHALL MONITOR THE RETURN AIR HUMIDITY AND USE AS REQUIRED FOR ECONOMIZER CONTROL (IF PRESENT) OR HUMIDITY CONTROL (IF PRESENT).

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH RETURN AIR HUMIDITY: IF THE RETURN AIR HUMIDITY IS GREATER THAN 70% (ADJ.).
- LOW RETURN AIR HUMIDITY: IF THE RETURN AIR HUMIDITY IS LESS THAN 35% (ADJ.).

RETURN AIR TEMPERATURE:
THE CONTROLLER SHALL MONITOR THE RETURN AIR TEMPERATURE AND USE AS REQUIRED FOR SETPOINT CONTROL OR ECONOMIZER CONTROL (IF PRESENT).

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH RETURN AIR TEMP: IF THE RETURN AIR TEMPERATURE IS GREATER THAN 90°F (ADJ.).
- LOW RETURN AIR TEMP: IF THE RETURN AIR TEMPERATURE IS LESS THAN 45°F (ADJ.).

SUPPLY AIR TEMPERATURE:

THE CONTROLLER SHALL MONITOR THE SUPPLY AIR TEMPERATURE.

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH SUPPLY AIR TEMP: IF THE SUPPLY AIR TEMPERATURE IS GREATER THAN 120°F (ADJ.).
- LOW SUPPLY AIR TEMP: IF THE SUPPLY AIR TEMPERATURE IS LESS THAN 45°F (ADJ.).


ELECTRIC HEATING WITH SCR:

THE CONTROLLER SHALL MEASURE THE SUPPLY AIR TEMPERATURE AND MODULATE THE HEATING TO MAINTAIN ITS SUPPLY AIR TEMPERATURE SETPOINT AT 80°F (ADJ.). THE HEATING WILL BE ENABLED WHENEVER:

- THE AHU IS IN HEAT MODE
- AND THE SUPPLY AIR TEMPERATURE IS BELOW SUPPLY AIR TEMPERATURE SETPOINT
- AND THE FAN IS ON.

HEAT/COOL UNOCCUPIED SETBACK:

DURING SCHEDULED HOURS OF OPERATION, IF OCCUPANCY SENSORS (ALL) DETECT SPACE IS UNOCCUPIED FOR 15 MINS, SPACE TEMPERATURE SETPOINT SHALL RESET TO 76°F (COOLING) AND 66°F (HEATING) AND OA DAMPERS SHALL RESET TO 5% (ADJ.).




TRINITY

M E P ENGINEERING

3533 Moreland Dr. Ste A | Weslaco, Tx 78596
p:956.732.0800 | f:956.351.5760
www.trinityep.com | Copyright 2022
Texas Registered Engineering Firm - F10362
Project number: 23.1.40

MMC02



SINGLE ZONE CW SPLIT SYSTEM FC (TYPICAL)

RUN CONDITIONS - SCHEDULED:

THE UNIT SHALL RUN ACCORDING TO A USER DEFINABLE TIME SCHEDULE IN THE FOLLOWING MODES:
OCCUPIED MODE: THE UNIT SHALL MAINTAIN

- A 74°F (ADJ.) COOLING SETPOINT
- A 70°F (ADJ.) HEATING SETPOINT.

UNOCCUPIED MODE (NIGHT SETBACK): THE UNIT SHALL MAINTAIN

- A 80°F (ADJ.) COOLING SETPOINT.
- A 60°F (ADJ.) HEATING SETPOINT.

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH ZONE TEMP: IF THE ZONE TEMPERATURE IS GREATER THAN THE COOLING SETPOINT BY A USER DEFINABLE AMOUNT (ADJ.).
- LOW ZONE TEMP: IF THE ZONE TEMPERATURE IS LESS THAN THE HEATING SETPOINT BY A USER DEFINABLE AMOUNT (ADJ.).

ZONE SETPOINT ADJUST:

THE OCCUPANT SHALL BE ABLE TO ADJUST THE ZONE TEMPERATURE HEATING AND COOLING SETPOINTS AT THE ZONE SENSOR.

ZONE OPTIMAL START:

THE UNIT SHALL USE AN OPTIMAL START ALGORITHM FOR MORNING START-UP. THIS ALGORITHM SHALL MINIMIZE THE UNOCCUPIED WARM-UP OR COOL-DOWN PERIOD WHILE STILL ACHIEVING COMFORT CONDITIONS BY THE START OF SCHEDULED OCCUPIED PERIOD.

ZONE UNOCCUPIED OVERRIDE:

A TIMED LOCAL OVERRIDE CONTROL SHALL ALLOW AN OCCUPANT TO OVERRIDE THE SCHEDULE AND PLACE THE UNIT INTO AN OCCUPIED MODE FOR AN ADJUSTABLE PERIOD OF TIME. AT THE EXPIRATION OF THIS TIME, CONTROL OF THE UNIT SHALL AUTOMATICALLY RETURN TO THE SCHEDULE.

FAN:

THE FAN SHALL RUN ANYTIME THE UNIT IS COMMANDED TO RUN, UNLESS SHUTDOWN ON SAFETIES.

COOLING STAGE:

THE CONTROLLER SHALL MEASURE THE ZONE TEMPERATURE AND STAGE THE COOLING TO MAINTAIN ITS COOLING SETPOINT.

THE COOLING SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS GREATER THAN 60°F (ADJ.)
- AND THE ZONE TEMPERATURE IS ABOVE COOLING SETPOINT.
- AND THE FAN IS ON.

ELECTRIC HEATING STAGE:

THE CONTROLLER SHALL MEASURE THE ZONE TEMPERATURE AND STAGE THE HEATING TO MAINTAIN ITS HEATING SETPOINT.

THE HEATING SHALL BE ENABLED WHENEVER:

- OUTSIDE AIR TEMPERATURE IS LESS THAN 65°F (ADJ.).
- AND THE ZONE TEMPERATURE IS BELOW HEATING SETPOINT.
- AND THE FAN IS ON.

FILTER STATUS:

THE CONTROLLER SHALL MONITOR THE FILTER STATUS AND GENERATE AN ALARM AT THE BAS WHEN DIFFERENTIAL PRESSURE IS EXCEEDED.

DISCHARGE AIR TEMPERATURE:

THE CONTROLLER SHALL MONITOR THE DISCHARGE AIR TEMPERATURE.

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH DISCHARGE AIR TEMP: IF THE DISCHARGE AIR TEMPERATURE IS GREATER THAN 100°F (ADJ.).
- LOW DISCHARGE AIR TEMP: IF THE DISCHARGE AIR TEMPERATURE IS LESS THAN 40°F (ADJ.).

FAN STATUS:

THE CONTROLLER SHALL MONITOR THE FAN STATUS.

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- FAN FAILURE: COMMANDED ON, BUT THE STATUS IS OFF.
- FAN IN HAND: COMMANDED OFF, BUT THE STATUS IS ON.

ELECTRIC HEATING WITH SCR:

THE CONTROLLER SHALL MEASURE THE SUPPLY AIR TEMPERATURE AND MODULATE THE HEATING TO MAINTAIN ITS SUPPLY AIR TEMPERATURE SETPOINT.

THE HEATING WILL BE ENABLED WHENEVER:

- THE AHU IS IN HEAT MODE
- AND THE SUPPLY AIR TEMPERATURE IS BELOW SUPPLY AIR TEMPERATURE SETPOINT
- AND THE FAN IS ON.

RETURN AIR CARBON DIOXIDE (CO2) CONCENTRATION MONITORING & DEMAND CONTROL VENTILATION (DCV):

THE CONTROLLER SHALL MEASURE THE RETURN AIR CO2 CONCENTRATION. VARIABLE OUTSIDE AIR DAMPERS & RETURN AIR DAMPERS IF REQUIRED SHALL MODULATE TO MAINTAIN CO2 CONCENTRATIONS BETWEEN 800-1100 PPM (ADJ.). OPEN/CLOSED OA DAMPERS SHALL OPEN WHEN CO2 CONCENTRATION REACHES 1100 PPM (ADJ) OR HIGHER AND SHALL CLOSE WHEN CO2 CONCENTRATION REACHES 800 PPM (ADJ) OR LOWER.

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH RETURN AIR CARBON DIOXIDE CONCENTRATION: IF THE RETURN AIR CO2 CONCENTRATION IS GREATER THAN 1200PPM (ADJ.) WHEN IN THE UNIT IS RUNNING.


DEHUMIDIFICATION:

IF RETURN AIR RELATIVE HUMIDITY (RH) EXCEEDS 65% (ADJ) WHILE UNIT IS RUNNING, SUPPLY AIR TEMPERATURE SHALL RESET DOWN TO 50 DEGREES (ADJ) AND DISCHARGE SUPPLEMENTAL HEATER SHALL ENERGIZE AND MODULATE TO DISCHARGE 65 DEGREE (ADJ) AIR DOWN STREAM. WHEN HUMIDITY SENSORS ARE AT 50% (ADJ) RELATIVE HUMIDITY OR BELOW, DEHUMIDIFICATION TO BE DISENGAGED.

HEAT/COOL UNOCCUPIED SETBACK:

DURING SCHEDULED HOURS OF OPERATION, IF OCCUPANCY SENSORS (ALL) DETECT SPACE IS UNOCCUPIED FOR 15 MINS, SPACE TEMPERATURE SETPOINT SHALL RESET TO 76°F (COOLING) AND 66°F (HEATING) AND OA DAMPERS SHALL RESET TO 5% (ADJ.).

MMC04



MMC04

06/20/2024

Wilford L. McGee III

121833


HVAC LOAD SHEDDING SEQUENCES:

COOLING:

DURING COOLING, IF THE BUILDING CURRENT LOAD (AMPS) MEETS/EXCEEDS 95% (ADJ.), THE COLDEST REPORTING ZONE SHALL HAVE IT'S TEMPERATURE SETPOINT (T-STAT) INCREASED BY 1°F (ADJ.). IF AFTER 1 MIN. (ADJ.) THE CONNECTED LOAD DOES NOT DROP BELOW 90% (ADJ.) OF MAX, REPEAT SEQUENCE.


HEATING:

THE WARMEST REPORTING ZONE SHALL HAVE IT'S TEMPERATURE SETPOINT (T-STAT) DECREASED BY 1°F (ADJ.) AND THE ASSOCIATED UNIT SA DISCHARGE SETPOINT DECREASED BY 1°F.



GENERAL NOTES (EXTERIOR LIGHTING):

NEW HVAC CONTROLS TO TIE INTO EXISTING
EXTERIOR LIGHTING CONTACTOR.



VARIABLE AIR VOLUME TERMINAL UNIT (TYPICAL)

RUN CONDITIONS - SCHEDULED:

THE UNIT SHALL RUN ACCORDING TO A USER DEFINABLE TIME SCHEDULE IN THE FOLLOWING MODES:

OCCUPIED MODE: THE UNIT SHALL MAINTAIN

- A 74°F (ADJ.) COOLING SETPOINT
- A 70°F (ADJ.) HEATING SETPOINT

UNOCCUPIED MODE (NIGHT SETBACK): THE UNIT SHALL MAINTAIN

- A 68°F (ADJ.) COOLING SETPOINT
- A 60°F (ADJ.) HEATING SETPOINT

ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH ZONE TEMP: IF THE ZONE TEMPERATURE IS GREATER THAN THE COOLING SETPOINT BY A USER DEFINABLE AMOUNT (ADJ.).
- LOW ZONE TEMP: IF THE ZONE TEMPERATURE IS LESS THAN THE HEATING SETPOINT BY A USER DEFINABLE AMOUNT (ADJ.).

ZONE SETPOINT ADJUST:

THE OCCUPANT SHALL BE ABLE TO ADJUST THE ZONE TEMPERATURE HEATING AND COOLING SETPOINTS AT THE ZONE SENSOR.

ZONE OPTIMAL START:

THE UNIT SHALL USE AN OPTIMAL START ALGORITHM FOR MORNING START-UP. THIS ALGORITHM SHALL MINIMIZE THE UNOCCUPIED WARM-UP OR COOL-DOWN PERIOD WHILE STILL ACHIEVING COMFORT CONDITIONS BY THE START OF SCHEDULED OCCUPIED PERIOD.

ZONE UNOCCUPIED OVERRIDE:

A TIMED LOCAL OVERRIDE CONTROL SHALL ALLOW AN OCCUPANT TO OVERRIDE THE SCHEDULE AND PLACE THE UNIT INTO AN OCCUPIED MODE FOR AN ADJUSTABLE PERIOD OF TIME. AT THE EXPIRATION OF THIS TIME, CONTROL OF THE UNIT SHALL AUTOMATICALLY RETURN TO THE SCHEDULE.

REVERSING VARIABLE VOLUME TERMINAL UNIT - FLOW CONTROL:
THE UNIT SHALL MAINTAIN ZONE SETPOINTS BY CONTROLLING THE AIRFLOW THROUGH ONE OF THE FOLLOWING:

OCCUPIED:

- WHEN ZONE TEMPERATURE IS GREATER THAN ITS COOLING SETPOINT, THE ZONE DAMPER SHALL MODULATE BETWEEN THE MINIMUM OCCUPIED AIRFLOW (ADJ.) AND THE MAXIMUM COOLING AIRFLOW (ADJ.) UNTIL THE ZONE IS SATISFIED.
- WHEN THE ZONE TEMPERATURE IS BETWEEN THE COOLING SETPOINT AND THE HEATING SETPOINT, THE ZONE DAMPER SHALL MAINTAIN THE MINIMUM REQUIRED ZONE VENTILATION (ADJ.).
- WHEN ZONE TEMPERATURE IS LESS THAN ITS HEATING SETPOINT, THE CONTROLLER SHALL ENABLE HEATING TO MAINTAIN THE ZONE TEMPERATURE AT ITS HEATING SETPOINT. ADDITIONALLY, IF WARM AIR IS AVAILABLE FROM THE AHU, THE ZONE DAMPER SHALL MODULATE BETWEEN THE MINIMUM OCCUPIED AIRFLOW (ADJ.) AND THE MAXIMUM HEATING AIRFLOW (ADJ.) UNTIL THE ZONE IS SATISFIED.

UNOCCUPIED:

- WHEN THE ZONE IS UNOCCUPIED THE ZONE DAMPER SHALL CONTROL TO ITS MINIMUM UNOCCUPIED AIRFLOW (ADJ.).
- WHEN THE ZONE TEMPERATURE IS GREATER THAN ITS COOLING SETPOINT, THE ZONE DAMPER SHALL MODULATE BETWEEN THE MINIMUM UNOCCUPIED AIRFLOW (ADJ.) AND THE MAXIMUM COOLING AIRFLOW (ADJ.) UNTIL THE ZONE IS SATISFIED.
- WHEN ZONE TEMPERATURE IS LESS THAN ITS UNOCCUPIED HEATING SETPOINT, THE CONTROLLER SHALL ENABLE HEATING TO MAINTAIN THE ZONE TEMPERATURE AT THE SETPOINT. ADDITIONALLY, IF WARM AIR IS AVAILABLE FROM THE AHU, THE ZONE DAMPER SHALL MODULATE BETWEEN THE MINIMUM UNOCCUPIED AIRFLOW (ADJ.) AND THE AUXILIARY HEATING AIRFLOW (ADJ.) UNTIL THE ZONE IS SATISFIED.


DISCHARGE AIR TEMPERATURE:

THE CONTROLLER SHALL MONITOR THE DISCHARGE AIR TEMPERATURE.


ALARMS SHALL BE PROVIDED AS FOLLOWS:

- HIGH DISCHARGE AIR TEMP: IF THE DISCHARGE AIR TEMPERATURE IS GREATER THAN 120°F (ADJ.).
- LOW DISCHARGE AIR TEMP: IF THE DISCHARGE AIR TEMPERATURE IS LESS THAN 40°F (ADJ.).

MMC07



06/20/2024
TRINITY
M E P E N G I N E E R I N G
3533 Moreland Dr. Ste A | Weslaco, Tx 78596
p:956.973.0800 | f:956.351.5760
www.trinityep.com | Copyright 2022
Texas Registered Engineering Firm - F10362
Project number: 23.1.40




REVISION:

TEXAS

WISD MEMORIAL ELEMENTARY SCHOOL
HVAC REPLACEMENT


WESLACO

ELECTRICAL LEGEND-LIGHTING		ELECTRICAL LEGEND-FIRE ALARM		ELECTRICAL ABBREVIATIONS:		GENERAL ELECTRICAL NOTES	
---ALL SYMBOLS SHOWN MAY NOT APPEAR IN ALL DRAWINGS. SYMBOLS ARE SHOWN SCHEMATIC AND MAY NOT BE SCALE.		---ALL SYMBOLS SHOWN MAY NOT APPEAR IN ALL DRAWINGS. SYMBOLS ARE SHOWN SCHEMATIC AND MAY NOT BE SCALE.		ABBV: DESCRIPTION ABBV: DESCRIPTION		1. ALL SYMBOLS AND ABBREVIATIONS SHOWN ON THIS LEGEND MAY NOT APPEAR ON THIS SET OF DRAWINGS. 2. USE DIRECTIONAL ARROW ON EXIT SIGNS AS REQUIRED. 3. IEEE STANDARD C37.2-1991, ELECTRICAL POWER SYSTEM DEVICE FUNCTION NUMBERS. 4. CONTRACTOR SHALL NOT INSTALL MORE THAN THREE CURRENT CARRYING CONDUCTORS IN A COMMON RACEWAY. IF CONTRACTOR IS PLANNING ON GROUPING MULTIPLE CIRCUITS IN A SINGLE RACEWAY, THE CONTRACTOR MUST SUBMIT ALL DERATING CALCULATIONS FOR THE PROPOSED INSTALLED CIRCUITS TO THE STATE OF TEXAS, SECTION 310.16 (12) FOR APPROVAL. PRIOR TO INSTALLATION, NON APPROVED INSTALLATIONS WILL BE REMOVED AND REINSTALLED BY THE CONTRACTOR IN ACCORDANCE WITH THE NEC AT NO ADDITIONAL COST TO THE OWNER. 5. THERE SHALL NOT BE MORE THAN THE EQUIVALENT OF THREE 90° BENDS (70 DEGREES TOTAL) BETWEEN PULL POINTS. WHERE THERE ARE MORE THAN THREE QUARTER BENDS, CONTRACTOR SHALL PROVIDE PULL BOXES AS SPECIFIED AND SIZED IN ACCORDANCE WITH NEC. 6. COMPLY WITH NEC REQUIREMENTS FOR ELECTRICAL INSTALLATIONS. ALL ELECTRICAL EQUIPMENT AND MATERIAL TO BE APPROVED, LISTED, LABELED, IDENTIFIED AND INSTALLED PER RECOGNIZED ELECTRICAL TESTING LABORATORY. 7. ALL RECEPTACLES, SWITCHES AND JUNCTION BOXES SERVED BY EMERGENCY BRANCH CIRCUITS SHALL BE RED IN COLOR. COVERPLATES SHALL BE LABELED IN ACCORDANCE WITH SPECIFICATIONS TO INDICATE PANELBOARD AND CIRCUIT NO. (IE: ET-LA-3).	
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		AFF: ABOVE FINISHED FLOOR MFR: MANUFACTURER BFC: BELOW FINISHED CEILING (S.C.) SHARE CIRCUIT C: CONDUIT QRCPT(S) QUAD RECEPTACLE(S) CB: CIRCUIT BREAKER RCP(S) DUPLEX RECEPTACLE(S) EC: EMPTY CONDUIT QCRCP(S) I.G. RECEPTACLE(S) EX: EXISTING PNL PANEL F: FUSE SO (S.O.) SPACE ONLY G: GROUND (EQUIPMENT) SP SPARE GFI: GROUND FAULT INTERRUPTER ST (S.T.) SHUNT TRIP MFD: MOUNT OR MOUNTED SW SWITCH NF: NONFUSED UF UNDERFLOOR NIC: NOT IN CONTRACT UG UNDERGROUND H.D: HEAVY DUTY NL NIGHT LIGHT UNO(U.N.O.) UNLESS NOTED OTHERWISE NL: NIGHT LIGHT UNO(U.N.O.) UNLESS NOTED OTHERWISE AC: ABOVE COUNTER WG WIRE GUARD HT: HEIGHT WP WEATHERPROOF MFD: MOUNTING XFMR TRANSFORMER CKT: CIRCUIT MB MAIN BREAKER LTG: LIGHTING MLO MAIN LUGS ONLY LC: LIGHTING CONTACTOR RMC RIGID METAL CONDUIT IG: ISOLATED GROUND RNC RIGID NONMETALLIC CONDUIT EA: EACH EMT ELECTRICAL METALLIC N1: NEMA-1 TUBING CONDUIT N3: NEMA-38 SOLID NEUTRAL N4: NEMA-4X AC ABOVE COUNTER AHU AUTHORITY HAVING SS: STAINLESS STEEL T JURISDICTION TAMPER PROOF			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		NOTES: 1. J 48" AFF INDICATES TO TOP OF DEVICE; 15" AFF INDICATES TO BOTTOM OF DEVICE; ALL OTHER MOUNTING HEIGHTS REFER TO CENTERLINE OF DEVICE. AC INDICATES 6" ABOVE COUNTER TO BOTTOM OF DEVICE.			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		ELECTRICAL LEGEND - WIRING DEVICES			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		---ALL SYMBOLS SHOWN MAY NOT APPEAR IN ALL DRAWINGS. SYMBOLS ARE SHOWN SCHEMATIC AND MAY NOT BE SCALE.			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		---ALL SYMBOLS SHOWN MAY NOT APPEAR IN ALL DRAWINGS. SYMBOLS ARE SHOWN SCHEMATIC AND MAY NOT BE SCALE.			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION		SYMBOL DESCRIPTION		SYMBOL DESCRIPTION			
SYMBOL DESCRIPTION							



1 ELECTRICAL OVERALL DEMOLITION PLAN
SCALE: 1" = 30'-0"

2 ENLARGED VIEW -
ELECTRICAL EQUIPMENT YARD
SCALE: 1/8" = 1'-0"



GENERAL DEMOLITION NOTES: (TO ALL SHEETS)

- A. THE EXTENT OF DEMOLITION WORK IS INDICATED ON THE HVAC DRAWINGS AND BY THE REQUIREMENTS OF THIS SECTION. A VISIT TO THE SITE WILL BE REQUIRED TO PROPERLY BID THE DEMOLITION WORK.
- B. PROVIDE ALL DEMOLITION WORK REQUIRED FOR THE REMOVAL AND/OR RELOCATION OF ELECTRICAL EQUIPMENT AND ASSOCIATED CONDUITS, CONDUIT BOXES, ETC. TO PROVIDE A COMPLETE AND OPERABLE SYSTEM UPON COMPLETION OF THE PROJECT.
- C. ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW THE HVAC DOCUMENTS IN ADDITION TO THE DIVISION 23 AND 26 DOCUMENTS TO DETERMINE THE COMPLETE SCOPE OF WORK.
- D. WHERE DEVICES OR EQUIPMENT ARE INDICATED OR REQUIRED TO BE REMOVED, THE ASSOCIATED BOXES, CONDUIT, AND CONDUCTORS SHALL BE REMOVED BACK TO THEIR SOURCE.
- E. WHERE DEVICES OR EQUIPMENT ARE INDICATED OR REQUIRED TO BE RELOCATED, THE ASSOCIATED BOXES, CONDUIT, AND CONDUCTORS SHALL BE REMOVED BACK TO A CONCEALED JUNCTION BOX AND NEW PRODUCTS SHALL BE USED TO EXTEND THE SERVICE TO THE NEW LOCATION.
- F. WHERE CONDUITS RUN ABOVE INACCESSIBLE CEILINGS OR IN WALLS WHICH ARE NOT PART OF DEMOLITION ARE TO REMAIN UNDISTURBED. CONDUCTORS SHALL BE REMOVED AND THE CONDUITS CAPPED AND ABANDONED.
- G. WHERE THE REMOVAL OF DEVICES OR EQUIPMENT RENDERS EQUIPMENT DOWNSTREAM INOPERABLE, SERVICE SHALL BE EXTENDED TO THE DOWNSTREAM DEVICE OR EQUIPMENT SO THAT THE DEVICE OR EQUIPMENT IS LEFT IN OPERATING CONDITION.
- H. COORDINATE DEMOLITION OF DIVISION 24 SYSTEMS AS REQUIRED WITH ALL OTHER TRADES.
- I. ALL EXISTING ELECTRICAL EQUIPMENT, CONDUIT AND WIRING REMOVED DURING CONSTRUCTION NO LONGER REQUIRED AS PART OF AN ACTIVE SYSTEM AND NOT TO BE REUSED SHALL BE REMOVED FROM THE JOB SITE AND PROPERLY RETURNED TO THE OWNER, IF DESIRED BY OWNER.
- J. WHERE EXISTING EQUIPMENT IS TO BE RELOCATED, EXTREME CARE SHALL BE TAKEN TO PREVENT DAMAGE DURING THE REMOVAL AND REINSTALLATION, WHERE DAMAGE OCCURS, THE EQUIPMENT SHALL BE REPLACED OR REPAIRED TO THE SATISFACTION AND APPROVAL OF THE ARCHITECT AT NO ADDITIONAL COST TO THE OWNER.
- K. EXISTING DEVICES AND/OR EQUIPMENT TO BE REUSED SHALL BE CLEANED AND REPAIRED AT THE DISCRETION OF THE OWNER WHERE APPLICABLE.
- L. ALL DEVICES WITH AN "EX" SYMBOL ARE EXISTING TO REMAIN.
- M. ALL DEVICES ATTACHED TO WALLS OR CEILINGS SHALL BE REMOVED PER DEMOLITION NOTE A - L WHETHER SHOWN ON DRAWINGS OR NOT.

KEYED NOTES: DEMOLITION

- 1 EXISTING POWER COMPANY PAD MOUNT TRANSFORMER 120/208V, 30, 4W TO REMAIN. FIELD VERIFY EXISTING CONDITIONS.
- 2 EXISTING 120/208V, 30, 4W 1200AMP, MFR. GE, N3R, MAIN SWITCH DISCONNECT TO REMAIN. **ALTERNATE#2** REPLACE EXISTING ELECTRICAL SERVICE EQUIPMENT, REFER TO ALTERNATE#2 RISER DIAGRAM.
- 3 EXISTING 120/208V, 30, 4W 1600AMP, MFR. GE, N3R, MAIN SWITCH DISCONNECT TO REMAIN. **ALTERNATE#2** REPLACE EXISTING ELECTRICAL SERVICE EQUIPMENT, REFER TO ALTERNATE#2 RISER DIAGRAM.
- 4 EXISTING ELECTRICAL SERVICE METER TO REMAIN. FIELD VERIFY EXISTING CONDITIONS. **ALTERNATE#2** REPLACE EXISTING ELECTRICAL SERVICE EQUIPMENT, REFER TO ALTERNATE#2 RISER DIAGRAM.
- 5 EXISTING 600AMP, 120/208V, 30, 4W, DISCONNECT TO BE REMAIN. FIELD VERIFY EXISTING CONDITIONS. **ALTERNATE#2** REPLACE EXISTING ELECTRICAL SERVICE EQUIPMENT, REFER TO ALTERNATE#2 RISER DIAGRAM.
- 6 EXISTING ABANDONED GENERATOR TO REMOVED AND DISPOSED.

06/20/2024











TRINITY
M E P E N G I N E E R I N G
3533 Moreland Dr. Ste A 1 Weslaco, Tx 78596
p:956.973.0800 | f:956.351.5760
www.trinitymep.com | Copyright 2022
Texas Registered Engineering Firm - F10362
Project number: 23.1.40

MEDP01


WISD MEMORIAL ELEMENTARY SCHOOL
HVAC REPLACEMENT

WESLACO





2 MECHANICAL ROOM - CAFETERIA
SCALE: 3/16" = 1'-0"




3 MECHANICAL ROOM - CAFETERIA
SCALE: 3/16" = 1'-0"

GENERAL NOTES:


- A. CONTRACTOR SHALL COORDINATE WITH ALL TRADES AND OWNER PRIOR TO ANY REMOVAL OF ANY EQUIPMENT.
- B. ANY ELECTRICAL SHUT DOWN REQUIRED SHALL BE COORDINATE WITH OWNER 5 DAYS PRIOR TO A BID DATE.
- C. CONTRACTOR SHALL COORDINATE WITH OWNER/ROOF MANUFACTURER TO SEAL ANY EXISTING OPENINGS PRIOR TO ANY WORK.
- D. MANDATORY FOR THE CONTRACTOR TO VISIT THE SITE EXISTING CONDITIONS PRIOR TO BID DATE AND INCLUDE ALL COST TO COMPLETE AN OPERABLE CODE COMPLIANT ELECTRICAL SYSTEM IN BID.
- E. EXISTING FIRE ALARM SYSTEM HVAC DUCT SMOKE DETECTORS SHALL REUSE. CONTRACTOR SHALL CLEAN DEVICE AND SHALL BE PROTECTED TO BE USE WHEN NEW HVAC UNIT IS INSTALLED.

ELECTRICAL KEYED NOTES: DEMOLITION

- 1 ALTERNATE #01. EXISTING FAN TO BE DEMOLISHED AND REPLACED. REFER TO ELECTRICAL REMODEL PLANS FOR EXISTING/NEW CIRCUIT REQUIREMENTS.
- 2 EXISTING AIR HANDLING UNIT/CONDENSER EQUIPMENT TO BE DEMOLISHED AND REPLACED. REMOVE ALL ASSOCIATED CONDUIT, WIRING, ELECTRICAL DEVICES. REFER TO ELECTRICAL REMODEL PLANS FOR EXISTING/NEW CIRCUIT REQUIREMENTS.
- 3 REMOVE INDICATED EXISTING MOTORIZED ZONE DAMPER. TO BE REPLACED WITH NEW VAV BOX. REFER TO REMODEL PLAN.
- 4 INDICATED CONTROLS TO BE REMOVED AND RETURNED TO OWNER.
- 5 EXISTING ELECTRICAL EQUIPMENT TO REMAIN.
- 6 ALL EXISTING ELECTRICAL EQUIPMENT TO REMAIN UNLESS OTHERWISE NOTED.
- 7 EXISTING HVAC CONTROLS TO BE REMOVED. FIELD VERIFY EXISTING CONDITIONS.
- 8 EXISTING MINI SPLIT EQUIPMENT TO BE DEMOLISHED AND REPLACED. REMOVE ALL ASSOCIATED CONDUIT, WIRING, ELECTRICAL DEVICES. REFER TO ELECTRICAL REMODEL PLANS FOR EXISTING/NEW CIRCUIT REQUIREMENTS.
- 9 INDICATED IT RACK/CONTROLS TO REMAIN.
- 10 EXISTING EMERGENCY BATTERY BACKUP CABINET TO REMAIN.




1 ELECTRICAL DEMOLITION PLAN - LIBRARY & CAFETERIA SECTION
SCALE: 3/32" = 1'-0"



WISD MEMORIAL ELEMENTARY SCHOOL
HVAC REPLACEMENT

WESLACO



GENERAL NOTES:

- A. CONTRACTOR SHALL COORDINATE WITH ALL TRADES AND OWNER PRIOR TO ANY REMOVAL OF ANY EQUIPMENT.
- B. ANY ELECTRICAL SHUT DOWN REQUIRED SHALL BE COORDINATE WITH OWNER 5 DAYS PRIOR TO ANY WORK.
- C. CONTRACTOR SHALL COORDINATE WITH OWNER/ROOF MANUFACTURER TO SEAL ANY EXISTING OPENINGS PRIOR TO ANY WORK.
- D. MANUFACTURER FOR CONTRACTOR TO VISIT THE SITE EXISTING CONDITIONS PRIOR TO BID DATE. THIS INCLUDES ALL COST TO COMPLETE AN OPERABLE CODE COMPLIANT ELECTRICAL SYSTEM IN BID.
- E. EXISTING FIRE ALARM SYSTEM/HVAC DUCT SMOKE DETECTORS SHALL REUSE. CONTRACTOR SHALL CLEAN DEVICE AND SHALL BE PROTECTED TO BE USED WHEN NEW HVAC UNIT IS INSTALLED.
- F. ALL EXISTING HVAC SENSORS/THERMOSTATS TO BE REPLACE WITH NEW AT EXISTING LOCATIONS. REFER TO MECHANICAL DOCUMENTS.

ELECTRICAL KEYED NOTES: DEMOLITION

- ① ALTERNATE #01: EXISTING FAN TO BE DEMOLISHED AND REPLACED. REFER TO ELECTRICAL REMODEL PLANS FOR EXISTING/NEW CIRCUIT REQUIREMENTS.
- ② EXISTING AIR HANDLING UNIT/CONDENSER EQUIPMENT TO BE DEMOLISHED AND REPLACED. REMOVE ALL ASSOCIATED CONDUIT, WIRING, ELECTRICAL DEVICES. REFER TO ELECTRICAL REMODEL PLANS FOR EXISTING/NEW CIRCUIT REQUIREMENTS.
- ③ REMOVE INDICATED EXISTING MOTORIZED ZONE DAMPER, TO BE REPLACED WITH NEW VAV BOX. REFER TO REMODEL PLAN.
- ④ ALL EXISTING ELECTRICAL EQUIPMENT TO REMAIN UNLESS OTHERWISE NOTED.
- ⑤ EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED. REFER TO ELECTRICAL REMODEL PLANS.
- ⑥ EXISTING IT EQUIPMENT TO BE RELOCATED BY WISD. COORDINATE FINAL LOCATION WITH OWNER AND REMODEL PLANS.
- ⑦ EXISTING HVAC CONTROLS TO BE REMOVED. FIELD VERIFY EXISTING CONDITIONS.




1 ELECTRICAL DEMOLITION PLAN - RIGHT WING SECTION
SCALE: 1/16" = 1'-0"

SCALE: 1/16" = 1'-0"




4 MECHANICAL ROOM

SCALE: 3/16" = 1'-0"



2 MECHANICAL ROOM D

SCALE: 3/16" = 1'



3 MECHANICAL ROOM C

SCALE: 3/16" = 1'

GENERAL NOTES:

- A. CONTRACTOR SHALL COORDINATE WITH ALL TRADES AND OWNER PRIOR TO ANY REMOVAL OF ANY EQUIPMENT.
- B. ANY ELECTRICAL SHUT DOWN REQUIRED SHALL BE COORDINATE WITH OWNER 5 DAYS PRIOR TO ANY WORK.
- C. CONTRACTOR SHALL COORDINATE WITH OWNER/ROOF MANUFACUTURER TO SEAL ANY EXISTING OPENINGS PRIOR TO ANY WORK.
- D. MANDATORY FOR THE CONTRACTOR TO VISIT THE SITE EXISTING CONDITIONS PRIOR TO BID DATE AND INCLUDE ALL COST TO COMPLETE AN OPERABLE CODE COMPLIANT ELECTRICAL SYSTEM IN BID.
- E. EXISTING FIRE ALARM SYSTEM HVAC DUCT SMOKE DETECTORS SHALL REUSE. CONTRACTOR SHALL CLEAN DEVICE AND SHALL BE PROTECTED TO BE USE WHEN NEW HVAC UNIT IS INSTALLED.
- F. ALL EXISTING HVAC SENSORS/ THERMOSTATS TO BE REPLACE WITH NEW AT EXISTING LOCATIONS. REFER TO MECHANICAL DOCUMENTS.

ELECTRICAL KEYED NOTES: DEMOLITION

1 **ALTERNATE #01.** EXISTING FAN TO BE DEMOLISHED AND REPLACED. REFER TO ELECTRICAL REMODEL PLANS FOR EXISTING/NEW CIRCUIT REQUIREMENTS.

2 EXISTING AIR HANDLING UNIT/CONDENSER EQUIPMENT TO BE DEMOLISHED AND REPLACED. REMOVE ALL ASSOCIATED CONDUIT, WIRING, ELECTRICAL DEVICES. REFER TO ELECTRICAL REMODEL PLANS FOR EXISTING/NEW CIRCUIT REQUIREMENTS.

3 REMOVE INDICATED EXISTING MOTORIZED ZONE DAMPER, TO BE REPLACED WITH NEW VAV BOX. REFER TO REMODEL PLAN.

4 ALL EXISTING ELECTRICAL EQUIPMENT TO REMAIN UNLESS OTHERWISE NOTED.


5 EXISTING ELECTRICAL EQUIPMENT TO BE DEMOLISHED AND REPLACED. REFER TO ELECTRICAL REMODEL PLANS.

6 EXISTING IT EQUIPMENT TO BE RELOCATED BY WISD. COORDINATE FINAL LOCATION WITH OWNER AND REMODEL PLANS.

7 EXISTING HVAC CONTROLS TO BE REMOVED. FIELD VERIFY EXISTING CONDITIONS.

8 INDICATED IT RACK TO REMAIN. NO WORK.

9 EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED. REFER TO ELECTRICAL REMODEL PLANS.



1 ELECTRICAL SITE PLAN
SCALE: 1" = 50'-0"

GENERAL NOTES - ELECTRICAL SITE

A. CONTRACTOR TO VERIFY ALL EXISTING AND NEW MAIN POWER SERVICES AND COORDINATE WITH POWER COMPANY FOR ALL NEW REQUIREMENTS AND ALL COST ASSOCIATED. CONTRACTOR SHALL INCLUDE ANY COST FOR THE NEW TRANSFORMER AND OTHER ASSOCIATED FEES IN BID. CONTRACTOR IS RESPONSIBLE TO VERIFY ALL FEES WITH POWER COMPANY AND TO INCLUDE IN BID. CONTRACTOR IS RESPONSIBLE TO COORDINATE WITH POWER COMPANY AS SOON THE CONTRACT IS AWARDED TO ORDER TRANSFORMER AND THE RELATED ELECTRICAL SERVICE EQUIPMENT AS SOON AS POSSIBLE.

B. CONTRACTOR IS RESPONSIBLE FOR ALL EXCAVATION, TRENCHING AND BACKFILLING. COORDINATE WITH ALL UTILITIES PRIOR TO EXCAVATION.

C. ALL ELECTRICAL EQUIPMENT OUTDOORS SHALL BE RATED TYPE NEMA 3R UNLESS OTHERWISE NOTED.

D. CONTRACTOR SHALL HAVE A WORKING KNOWLEDGE OF LOCAL CODES AND ORDINANCES. ALL WORK SHALL CONFORM TO NATIONAL ELECTRICAL CODE AND ALL OTHER AUTHORITY HAVING JURISDICTION. OBTAIN PERMITS AND PAY ALL FEES, PERIODICALLY, AS REQUIRED TO MEET CODE AND ORDINANCE REQUIREMENTS AT NO ADDITIONAL COST TO OWNER, OR ENGINEER. VERIFY PRIOR TO BID DATE.

E. VERIFY AT JOB SITE THE EXACT LOCATIONS OF STRUCTURAL MEMBERS SUCH AS BEAMS, COLUMNS, ETC. TO LOCATE EQUIPMENT CONDUIT, PANELS AND DEVICES. IF DEVIATIONS FROM THE DRAWING ARE NECESSARY TO MEET STRUCTURAL CONDITIONS MAKE DEVIATIONS WITHOUT ADDITIONAL COST TO OWNER OR ENGINEER.

F. IN COOPERATION WITH OTHER CONTRACTORS, DETERMINE THE EXACT LOCATION OF EQUIPMENT AND DEVICES AND CONNECTIONS THERETO BY REFERENCE TO THE SUBMITTALS AND ROUGH-IN DRAWINGS, AND BY MEASUREMENTS AT THE SITE. REFER TO ALL OTHER TRADES SUBMITTAL FOR ELECTRICAL INFORMATION.

G. GROUND ENTIRE ELECTRICAL SYSTEM IN STRICT ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE.

I. VERIFY AT JOB SITE GENERAL WORK TO BE DONE AS SPECIFIED, AS NOTED, OR AS REQUIRED FOR INSTALLATION ELECTRICAL SYSTEMS PRIOR TO SUBMISSION OF BIDS.

H. CONTRACTOR SHALL FIELD VERIFY EXISTING CONDITIONS AND EQUIPMENT TO BE REMOVED AND REPLACED BEFORE SUBMITTING HIS BID.

I. ELECTRICAL DRAWINGS ARE DIAGRAMMATIC AND SMALL SCALE ONLY. THEY CONVEY THE INTENT OF THE WORK BUT DO NOT SHOW DETAIL SUCH AS JUNCTION AND PULL BOXES REQUIRED BY THE SPECIFICATIONS AND THE NATIONAL ELECTRICAL CODE(NEC). PROVIDE ALL MATERIALS AND METHODS CALLED FOR IN THE SPECIFICATIONS AND AS REQUIRED IN THE NEC TO PROVIDE A COMPLETE INSTALLATION OF ALL WORK.

J. ALL WIRING SHALL BE COPPER.

K. ALL SLEEVES, PENETRATIONS, ETC. SHALL BE SEALED SOLID NON-SHRINKING MATERIAL IMMEDIATELY UPON FILLING OF THE OPENING WITH PIPE OR CONDUIT.

L. ARRANGE FOR SOURCES OF TEMPORARY CONSTRUCTION SERVICES. SUCH SERVICES SHALL BE NOMINALLY 120/240V, 1-PHASE, 3-WIRE FROM WHICH A COMPLETE SYSTEM OF TEMPORARY POWER AND LIGHTING SHALL BE PROVIDED FOR ALL CONSTRUCTION NEEDS.

ELECTRICAL KEYED NOTES: POWER

1 NEW POWER COMPANY POWER POLE. COORDINATE WITH UTILITY COMPANY PRIOR TO ANY WORK.

2 PROVIDE WEATHER PROOF JBOX FOR MOTORIZED BUTTERFLY ISOLATION VALVE POWER. COORDINATE EXACT LOCATION PRIOR TO ANY WORK.

3 PROVIDE WEATHER PROOF JBOX FOR CONTROLLER POWER. COORDINATE EXACT LOCATION PRIOR TO ANY WORK.

4 NEW VFD FOR CHILLED WATER EQUIPMENT VFD BY DIVISION 23 INSTALLED BY DIVISION 26. COORDINATE EXACT LOCATION PRIOR TO ANY WORK.

5 3' GALVANIZED PIPE WITH UNISTRUT STAND FOR ELECTRICAL SERVICE EQUIPMENT. COORDINATE WITH UTILITY COMPANY PRIOR TO ANY WORK.

6 NEW POWER COMPANY POWER POLE WITH RISER DIP POLE. FIELD COORDINATE EXACT LOCATION WITH POWER COMPANY PRIOR TO ANY WORK.

7 CONTRACTOR TO PROVIDE AND INSTALL (1)-4" PVC CONDUIT FROM PROPOSED NEW UTILITY COMPANY POWER POLE WITH RISER DIP POLE TO NEW PAD MOUNT TRANSFORMER VIA PULLBOXES. ALL UNDERGROUND WORK SHALL BE ACCORDING TO POWER COMPANY STANDARDS. VERIFY ALL REQUIREMENTS WITH THE POWER COMPANY BEFORE ANY ROUGH-IN. COORDINATE LOCATION, COST, AND INSTALLATION WITH POWER COMPANY PRIOR TO BID.


8 J-BOX FOR H.V.A.C. CONTROLS COORDINATE EXACT LOCATION AND ELECTRICAL REQUIREMENTS WITH EQUIPMENT SUPPLIER PRIOR TO COMMENCING ANY WORK.

9 PROVIDE 1-RUN OF 1" C WITH PULL STRING TO EACH UNIT FOR HVAC CONTROLS.

10 NEW POWER COMPANY PAD MOUNTED TRANSFORMER. PROVIDE CONCRETE PAD PER POWER COMPANY STANDARDS. COORDINATE COST AND INSTALLATION WITH POWER COMPANY PRIOR TO BID DATE. COORDINATE EXACT LOCATION WITH POWER COMPANY PRIOR TO ANY ROUGH-IN.

11 NEW 480/277V, 30, 4W, ELECTRICAL SERVICE METER, ON A GALVANIZED UNISTRUT PIPE STAND.


12 CONTRACTOR TO PROVIDE AND INSTALL PVC CONDUIT FROM NEW UTILITY TRANSFORMER TO NEW ELECTRICAL DISCONNECT EQUIPMENT. VERIFY ALL REQUIREMENTS PRIOR TO ANY ROUGH-IN. REFER TO ELECTRICAL RISER DIAGRAM.



2 ENLARGED CHILLED WATER PLANT
SCALE: 1/8" = 1'-0"



06/20/2024



GENERAL NOTES: POWER

- A. CONTRACTOR SHALL REFER TO EQUIPMENT SUBMITTAL FOR ALL ELECTRICAL REQUIREMENTS PRIOR TO COMMENCING ANY WORK.
- B. ELECTRICAL CONTRACTOR SHALL MAKE FINAL CONNECTION TO H.V.A.C EQUIPMENT, PLUMBING AND MECHANICAL CONTRACTOR SHALL REFER TO PANEL SCHEDULE FOR WIRE SIZE.
- C. ELECTRICAL CONTRACTOR SHALL PROVIDE STARTERS, RELAYS, CONTACTORS AND THE REQUIRED ELECTRICAL ACCESSORIES FOR MECHANICAL SYSTEM AS REQUIRED.
- D. COORDINATE EXACT LOCATION OF ALL MECHANICAL EQUIPMENT IN ACCORDANCE W/MECHANICAL DRAWINGS TO MEET ELECTRICAL AND MECHANICAL REQUIRED CLEARANCE BY THE LATEST CODE.
- E. NEMA RATED OUTLETS, REFER TO BREAKER SIZE AND COORDINATE WITH EQUIPMENT REQUIREMENTS PRIOR TO BID.
- F. ELECTRICAL CONTRACTOR PROVIDE NEW H.V.A.C. CONTROLS/THERMOSTATS AT EXISTING LOCATIONS. REFER TO MECHANICAL DOCUMENTS.
- G. CONTRACTOR IS RESPONSIBLE TO REPLACE ANY DAMAGE CEILING TILES WITH NEW ONES TO MATCH EXISTING. CONTRACTOR SHALL INCLUDE AN ALLOWANCE OF 500 CEILING TILES PER SCHOOL IN BASE BID.
- H. ALL EXISTING DUCT SMOKE DETECTOR SHALL BE REUSE. PROVIDE 5 CONVENTIONAL DUCT SMOKE DETECTOR, AND A ADDRESSABLE MONITOR MODULE ADDITIONAL WITH 100' OF WIRING/LABOR FOR THE 5 ADDITIONAL IN BID.

ELECTRICAL KEYED NOTES: POWER

- 1 ROOF PENETRATION HOUSING, COORDINATED WITH MECHANICAL DOCUMENTS PRIOR TO ANY WORK.
- 2 CONDENSER ELECTRICAL CONDUIT TO ENTER BUILDING VIA ROOF PENETRATION HOUSING, COORDINATE EXACT ROUTE WITH REFRIGERANT LINES PRIOR TO ANY WORK. PROVIDE CONDUIT ROOF SUPPORTS AT EVERY 10'. ROOF SUPPORTS SHALL BE MFR. MIRO INDUSTRIES STAINLESS STEEL #12-BASE-12.
- 3 ALTERNATE #01. PROVIDE WEATHER PROOF JBOX WITH 1-1/2" C WITH PULLSTRING, ROUTE TO KITCHEN VENTILATION CONTROL PANEL SYSTEM, COORDINATE WITH EQUIPMENT SUPPLIER AND MECHANICAL DOCUMENTS PRIOR TO COMMENCING ANY WORK. REFER TO MECHANICAL DOCUMENTS FOR WIRING DIAGRAMS AND DETAILS.
- 4 ALTERNATE #01. NEW KITCHEN HVAC EQUIPMENT, EXISTING ELECTRICAL CIRCUIT TO BE REUSED, FIELD VERIFY EXISTING CONDITIONS.
- 5 NEW HVAC EQUIPMENT, INTERLOCK FCCU_ WITH FC_- H.V.A.C. EQUIPMENT. WIRING SHALL BE 3#10, 1#10G, 3/4"IC.






GENERAL NOTES: POWER

- A. CONTRACTOR SHALL REFER TO EQUIPMENT SUBMITTAL FOR ALL ELECTRICAL REQUIREMENTS PRIOR TO COMMENCING ANY WORK.
- B. ELECTRICAL CONTRACTOR SHALL MAKE FINAL CONNECTION TO H.V.A.C EQUIPMENT, PLUMBING EQUIPMENT, REFER TO PANEL SCHEDULE FOR WIRE SIZE.
- C. ELECTRICAL CONTRACTOR SHALL PROVIDE STARTERS, RELAYS, CONTACTORS AND THE REQUIRED ELECTRICAL ACCESSORIES FOR MECHANICAL SYSTEM AS REQUIRED.
- D. COORDINATE EXACT LOCATION OF ALL MECHANICAL EQUIPMENT IN ACCORDANCE W/MECHANICAL DRAWINGS TO MEET ELECTRICAL AND MECHANICAL REQUIRED CLEARANCE BY THE LATEST CODE.
- E. NEMA RATED OUTLETS, REFER TO BREAKER SIZE AND COORDINATE WITH EQUIPMENT REQUIREMENTS PRIOR TO BID.
- F. ELECTRICAL CONTRACTOR PROVIDE NEW H.V.A.C. CONTROLS/ THERMOSTATS AT EXISTING LOCATIONS. REFER TO MECHANICAL DOCUMENTS.
- G. CONTRACTOR IS RESPONSIBLE TO REPLACE ANY DAMAGE CEILING TILES WITH NEW ONES TO MATCH EXISTING. CONTRACTOR SHALL INCLUDE AN ALLOWANCE OF 500 CEILING TILES PER SCHOOL IN BASE BID.
- H. ALL EXISTING DUCT SMOKE DETECTOR SHALL BE REUSE. PROVIDE 5 CONVENTIONAL DUCT SMOKE DETECTOR, AND ADDRESSABLE MONITOR MODULE ADDITIONAL WITH 100' OF WIRING/LABOR FOR THE 5 ADDITIONAL IN BID.

ELECTRICAL KEYED NOTES: POWER

- 1 NEW HVAC EQUIPMENT, INTERLOCK FCCU_ WITH FC_ H.V.A.C. EQUIPMENT, WIRING SHALL BE 3#10, 1#10G, 3/4" C.
- 2 NEW EXHAUST FAN TO TIE INTO ROOMS LIGHTING CIRCUIT AND INTERLOCK FAN WITH ROOMS LIGHTS. WIRING SHALL BE 2#10, 1#10G, 3/4" C.
- 3 NEW ELECTRICAL EQUIPMENT, FIELD COORDINATE EXACT LOCATION WITH EXISTING CONDITIONS.
- 4 PROVIDE DISCONNECT ABOVE CEILING FOR NEW MECHANICAL EQUIPMENT, FIELD COORDINATE EXACT LOCATION WITH EXISTING CONDITIONS.
- 5 REUSE EXISTING FIRE ALARM DUCT SMOKE DETECTOR, TIE INTO EXISTING FIRE ALARM SYSTEM. INCLUDE ALL COST IN BID FOR A COMPLETE OPERABLE AND CODE COMPLIANT SYSTEM.
- 6 PROVIDE J-BOX FOR HVAC MOTORIZED DAMPER. COORDINATE EXACT LOCATION WITH MECHANICAL DOCUMENTS.
- 7 PROVIDE J-BOX FOR NEW HVAC CONTROLS ENCLOSURE. REFER TO MECHANICAL DOCUMENTS.
- 8 ALTERNATE #2. NEW SWITCHBOARD DISTRIBUTION PANELBOARD. FIELD COORDINATE EXACT LOCATION. REFER TO SHEET MER03, MER04.
- 9 NEW MDF ROOM HVAC EQUIPMENT, INTERLOCK FCCU_ WITH FC_ H.V.A.C. EQUIPMENT, WIRING SHALL BE 3#10, 1#10G, 3/4" C.
- 10 EXISTING IT RACK TO BE RELOCATED BY OWNER. FIELD COORDINATE FINAL LOCATION WITH EXISTING CONDITIONS.
- 11 PROVIDE J-BOX FOR H2 SENSOR. REFER TO MECHANICAL DOCUMENTS.
- 12 NEW EXHAUST FAN TO TIE INTO ROOMS LIGHTING CIRCUIT WITH 2#10, 1#10G, 3/4" C. SHALL BE CONTROLLED VIA H2 SENSOR. REFER TO MECHANICAL DOCUMENTS.
- 13 PROVIDE J-BOX GAS DETECTION SYSTEM. REFER TO MECHANICAL DOCUMENTS.
- 14 EXISTING ELECTRICAL SERVICE METER. FIELD VERIFY EXISTING CONDITIONS.
- 15 EXISTING POWER COMPANY PAD MOUNT TRANSFORMER 120/208V, 30, 4W.



**GENERAL NOTES: POWER**

- A. CONTRACTOR SHALL REFER TO EQUIPMENT SUBMITTAL FOR ALL ELECTRICAL REQUIREMENTS PRIOR TO COMMENCING ANY WORK.
- B. ELECTRICAL CONTRACTOR SHALL MAKE FINAL CONNECTION TO H.V.A.C EQUIPMENT, PLUMBING EQUIPMENT, REFER TO PANEL SCHEDULE FOR WIRE SIZE.
- C. ELECTRICAL CONTRACTOR SHALL PROVIDE STARTERS, RELAYS, CONTACTORS AND THE REQUIRED ELECTRICAL ACCESSORIES FOR MECHANICAL SYSTEM AS REQUIRED.
- D. CONTRACTOR SHALL PROVIDE APPROXIMATE LOCATION OF ALL MECHANICAL EQUIPMENT IN ACCORDANCE W/MECHANICAL DRAWINGS TO MEET ELECTRICAL AND MECHANICAL REQUIRED CLEARANCE BY THE LATEST CODE.
- E. NEMA RATED OUTLETS, REFER TO BREAKER SIZE AND COORDINATE WITH EQUIPMENT REQUIREMENTS PRIOR TO BID.
- F. ELECTRICAL CONTRACTOR PROVIDE NEW H.V.A.C. CONTROLS/ THERMOSTATS AT EXISTING LOCATIONS. REFER TO MECHANICAL DOCUMENTS.
- G. CONTRACTOR IS RESPONSIBLE TO REPLACE ANY DAMAGE CEILING TILES WITH NEW ONES TO MATCH EXISTING. CONTRACTOR SHALL INCLUDE AN ALLOWANCE OF 500 CEILING TILES PER SCHOOL IN BASE BID.
- H. ALL EXISTING DUCT SMOKE DETECTOR SHALL BE REUSE. PROVIDE 5 CONVENTIONAL DUCT SMOKE DETECTOR, AND ADDRESSABLE MONITOR MODULE ADDITIONAL WITH 100' OF WIRING/LABOR FOR THE 5 ADDITIONAL IN BID.


ELECTRICAL KEYED NOTES: POWER

- 1 PROVIDE DISCONNECT ABOVE CEILING FOR NEW MECHANICAL EQUIPMENT. FIELD COORDINATE EXACT LOCATION WITH EXISTING CONDITIONS.
- 2 NEW EXHAUST FAN TO TIE INTO ROOMS LIGHTING CIRCUIT AND INTERLOCK FAN WITH ROOMS LIGHTS. WIRING SHALL BE 2#10, 1#10G, 3/4".
- 3 NEW ELECTRICAL EQUIPMENT. FIELD COORDINATE EXACT LOCATION WITH EXISTING CONDITIONS.
- 4 ALTERNATE #01. NEW EXHAUST FAN TO BE OPERATED AND MONITORED BY BAS. TIE INTO EXISTING EXHAUST FAN CIRCUIT.
- 5 REUSE EXISTING FIRE ALARM DUCT SMOKE DETECTOR. TIE INTO EXISTING FIRE ALARM SYSTEM. INCLUDE ALL COST IN BID FOR A COMPLETE OPERABLE AND CODE COMPLIANT SYSTEM.
- 6 APPROXIMATE LOCATION OF EXISTING MFR. SILENT NIGHT #SK-5208 FIRE ALARM CONTROL PANEL. FIELD VERIFY EXACT LOCATION AND EXISTING CONDITIONS.
- 7 PROVIDE J-BOX FOR HVAC MOTORIZED DAMPER. COORDINATE EXACT LOCATION WITH MECHANICAL DOCUMENTS.
- 8 PROVIDE JBOX FOR NEW HVAC CONTROLS ENCLOSURE. REFER TO MECHANICAL DOCUMENTS.
- 9 COORDINATE RELOCATION OF ALL IT RACKS WITH DISTRICT PRIOR TO COMMENCEMENT OF WORK.
- 10 NEW HVAC EQUIPMENT, INTERLOCK FCCU- WITH FC- H.V.A.C. EQUIPMENT. WIRING SHALL BE 3#10, 1#10G, 3/4".




ELECTRICAL FLOOR PLAN - RIGHT WING


1 SCALE: 1/16" = 1'-0"



MECHANICAL ROOM



MECHANICAL ROOM D



MECHANICAL ROOM C

3

GENERAL NOTES: POWER

CONTRACTOR SHALL REFER TO EQUIPMENT SUBMITTAL FOR ALL ELECTRICAL REQUIREMENTS OR TO COMMENCING ANY WORK.

ELECTRICAL CONTRACTOR SHALL MAKE FINAL CONNECTION TO H.V.A.C EQUIPMENT, PLUMBING EQUIPMENT, REFER TO PANEL SCHEDULE FOR WIRE SIZE.

ELECTRICAL CONTRACTOR SHALL PROVIDE STARTERS, RELAYS, CONTACTORS AND THE REQUIRED ELECTRICAL ACCESSORIES FOR MECHANICAL SYSTEM AS REQUIRED.

COORDINATE EXACT LOCATION OF ALL MECHANICAL EQUIPMENT IN ACCORDANCE MECHANICAL DRAWINGS TO MEET ELECTRICAL AND MECHANICAL REQUIRED CLEARANCE BY THE LATEST CODE.

AMPERE RATED OUTLETS, REFER TO BREAKER SIZE AND COORDINATE WITH EQUIPMENT REQUIREMENTS PRIOR TO BID.

ELECTRICAL CONTRACTOR PROVIDE NEW H.V.A.C. CONTROLS/ THERMOSTATS AT EXISTING LOCATIONS. REFER TO MECHANICAL DOCUMENTS.

CONTRACTOR IS RESPONSIBLE TO REPLACE ANY DAMAGE CEILING TILES WITH NEW ONES TO MATCH EXISTING. CONTRACTOR SHALL INCLUDE AN ALLOWANCE OF 500 CEILING TILES PER SCHOOL IN THE BID.

EXISTING DUCT SMOKE DETECTOR SHALL BE REUSE. PROVIDE 5 CONVENTIONAL DUCT SMOKE DETECTOR, AND ADDRESSABLE MONITOR MODULE ADDITIONAL WITH 100'

ELECTRICAL KEYED NOTES: POWER

PROVIDE DISCONNECT ABOVE CEILING FOR NEW MECHANICAL EQUIPMENT. FIELD COORDINATE EXACT LOCATION WITH EXISTING CONDITIONS.

ERNATE #01. NEW EXHAUST FAN TO TIE INTO ROOMS LIGHTING CIRCUIT AND INTERLOCK FAN WITH ROOMS LIGHTS. WIRING SHALL BE 2#10, 1#10G, 3/4"C.

PROVIDE ELECTRICAL EQUIPMENT. FIELD COORDINATE EXACT LOCATION WITH EXISTING CONDITIONS.

ERNATE #01. NEW EXHAUST FAN TO BE OPERATED AND MONITORED BY BAS. TIE TO EXISTING EXHAUST FAN CIRCUIT.

USE EXISTING FIRE ALARM DUCT SMOKE DETECTOR. TIE INTO EXISTING FIRE ALARM SYSTEM. INCLUDE ALL COST IN BID FOR A COMPLETE OPERABLE AND CODE COMPLIANT SYSTEM.

COORDINATE RELOCATION OF ALL IT RACKS WITH DISTRICT PRIOR TO COMMENCEMENT WORK.

PROVIDE JBOX FOR NEW HVAC CONTROLS ENCLOSURE. REFER TO MECHANICAL DOCUMENTS.

PROVIDE J-BOX FOR HVAC MOTORIZED DAMPER. COORDINATE EXACT LOCATION WITH MECHANICAL DOCUMENTS.

PROVIDE HVAC EQUIPMENT INTERLOCK FCCU- WITH FC- H.V.A.C. EQUIPMENT. WIRING

DUCT HEATER DISCONNECT SCHEDULE	
EDH-1	200AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-2	400AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-3	60AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-4	200AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-5	60AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-6	30AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-7	30AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-8	400AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-9	400AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-10	400AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-11	100AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-12	100AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-13	60AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-14	30AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-15	30AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-16	200AMP, 3PH, 4W, N1, 208V, S/N, H.D. FUSED DISCONNECT, FUSED AT 150 AMPS
EDH-17	200AMP, 3PH, 4W, N1, 208V, S/N, H.D. FUSED DISCONNECT, FUSED AT 150 AMPS
EDH-18	400AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT
EDH-19	200AMP, 3PH, 4W, 208V, NEMA-1, HD, NF DISCONNECT

NOTE:
1.) COORDINATE EXACT LOCATION WITH MECHANICAL CONTRACTOR.
2.) COORDINATE WITH EQUIPMENT SUBMITTAL PRIOR TO ANY WORK.
3.) REFER TO ALL DOCUMENTS.
4.) REFER TO MECHANICAL DRAWINGS FOR QUANTITIES.

DISCONNECT SCHEDULE	
FC-1 THRU 9	30AMP, 1Ø, 3W, N3R, 208V, S/N, H.D. FUSED DISCONNECT

NOTE: 1. REFER TO BREAKER SIZE FOR FUSE SIZE.
2. REFER TO PANELBOARD FOR DISCONNECT PHASES AND VOLTAGE.
3. PROVIDE SOLID STATE PHASE LOSS PROTECTION FOR ALL STARTER AND COMBOS.
4. REFER TO MECHANICAL DRAWINGS FOR QUANTITIES.

DISCONNECT SCHEDULE	
AHU-1a,1b	3 HP VFD PROVIDED BY MECHANICAL CONTRACTOR, INSTALLED BY ELECTRICAL CONTRACTOR
AHU-2	60AMP, 3PH, 4W, N1, 208V, S/N, H.D. FUSED DISCONNECT, FUSED AT 35AMPS
AHU-3	60AMP, 3PH, 4W, N1, 208V, S/N, H.D. FUSED DISCONNECT, FUSED AT 35AMPS
AHU-4,5,6,7	30AMP, 3PH, 4W, N1, 208V, S/N, N.F., H.D. DISCONNECT
AHU-8,9,10a,10b	7.5 HP VFD PROVIDED BY MECHANICAL CONTRACTOR, INSTALLED BY ELECTRICAL CONTRACTOR
AHU-11,12,13,14,15	30AMP, 3PH, 4W, N1, 208V, S/N, N.F., H.D. DISCONNECT
AHU-16	7.5 HP VFD PROVIDED BY MECHANICAL CONTRACTOR, INSTALLED BY ELECTRICAL CONTRACTOR
AHU-17	30AMP, 3PH, 4W, N1, 208V, S/N, N.F., H.D. DISCONNECT
AHU-18	30AMP, 3PH, 4W, N1, 208V, S/N, N.F., H.D. DISCONNECT
AHU-19	30AMP, 3PH, 4W, N1, 208V, S/N, N.F., H.D. DISCONNECT

NOTE:
1.) COORDINATE EXACT LOCATION WITH MECHANICAL CONTRACTOR.
2.) COORDINATE WITH EQUIPMENT SUBMITTAL PRIOR TO ANY WORK.
3.) REFER TO ALL DOCUMENTS.
4.) REFER TO MECHANICAL DRAWINGS FOR QUANTITIES.

TERMINAL UNITS DISCONNECT SCHEDULE	
TU UNIT	DISCONNECT SIZE
TU-A-01 THRU TU-A-10	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-B-01 THRU TU-B-05	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-C-01 THRU TU-C-14	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-D-01 THRU TU-D-09	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-E-01 THRU TU-E-09	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-F-01 THRU TU-F-10	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-G-01 THRU TU-G-02	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-H-01 THRU TU-H-08	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-I-01 THRU TU-I-07	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-J-01 THRU TU-J-12	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-K-01 THRU TU-K-06	30AMP, 1PH, 3W, 120V, NEMA-1, HD
TU-L-01 THRU TU-L-05	30AMP, 1PH, 3W, 120V, NEMA-1, HD


NOTE:
1.) COORDINATE EXACT LOCATION WITH MECHANICAL CONTRACTOR.
2.) COORDINATE WITH EQUIPMENT SUBMITTAL PRIOR TO ANY WORK.
3.) REFER TO ALL DOCUMENTS.
4.) REFER TO MECHANICAL DRAWINGS FOR QUANTITIES.

GENERAL NOTES:

- A. ALL EXISTING PANELBOARDS TO REMAIN. EXISTING MANUFACTURER GENERAL ELECTRIC. PROVIDE NEW BREAKERS FOR NEW HVAC EQUIPMENT AS NOTED ON THE PANEL SCHEDULES. EXISTING BREAKERS TO BE REMOVED AND PROVIDE BLANK SPACES AS NEEDED.
- B. EXISTING BREAKERS NOT USED BE RETURNED TO OWNER IF DESIRED. PROVIDE BLANK SPACES TO PROVIDE NEW CIRCUIT OF INDEX.
- C. ALL NEW BREAKERS SHALL MATCH EXISTING PANELBOARD AIC RATING.

ELECTRICAL RISER
DIAGRAM KEYED NOTES:

- ① EXISTING ELECTRICAL EQUIPMENT TO REMAIN UNLESS OTHERWISE NOTED. FIELD VERIFY EXISTING CONDITIONS PRIOR TO COMMENCING ANY WORK.
- ② EXISTING 1600AMP, 120/208V, 3Ø, 4W, MAIN SERVICE DISCONNECT REMAIN.
- ③ EXISTING POWER COMPANY PAD MOUNT TRANSFORMER 120/208V, 3Ø, 4W TO REMAIN.
- ④ EXISTING, 1600AMP, 120/208V, 3Ø, 4W, PANEL-PDP TO REMAIN.
- ⑤ EXISTING, 400AMP, 120/208V, 3Ø, 4W, PANEL-1P TO BE REPLACED BY NEW PANEL WITH SIMILAR PHYSICAL CHARACTERISTICS.
- ⑥ EXISTING, 400AMP, 120/208V, 3Ø, 4W, PANEL-2P TO BE REPLACED BY NEW PANEL WITH SIMILAR PHYSICAL CHARACTERISTICS.
- ⑦ EXISTING, 800AMP, 120/208V, 3Ø, 4W, PANEL-3P TO BE REPLACED BY NEW PANEL WITH SIMILAR PHYSICAL CHARACTERISTICS.
- ⑧ EXISTING, 600AMP, 120/208V, 3Ø, 4W, PANEL-4P TO REMAIN.
- ⑨ EXISTING, 1200AMP, 120/208V, 3Ø, 4W, DISCONNECT TO REMAIN.
- ⑩ EXISTING, 600AMP, 120/208V, 3Ø, 4W, DISCONNECT TO REMAIN.
- ⑪ EXISTING ELECTRICAL METER TO REMAIN. FIELD VERIFY EXISTING CONDITIONS.
- ⑫ EXISTING ELECTRODE TO REMAIN.
- ⑬ EXISTING CONDUITS TO REMAIN.



DRY-TYPE TRANSFORMER SCHEDULE			
LABEL	TRANSFORMER DESCRIPTION	PRIMARY VOLTAGE FEEDER -	SECONDARY VOLTAGE FEEDER -
TX-CL	TYPE-DT-3: GENERAL, 15KVA, COPPER WINDINGS,1-PHASE, (P)480V-(S)240/120V,115°RISE,NEMA-3R	480V, 1Ø 3#8, 1#10G IN 1.25°C	120/240V, 1Ø, 3W 3#8, 1#10G IN 1.25°C

NOTE: ALL DRY-TYPE TRANSFORMER SHALL BE ENERGY EFFICIENT MODELS AND MEET 2016 ENERGY EFFICIENT REQUIREMENTS..


ELECTRICAL RISER
DIAGRAM KEYED NOTES:

- 1 NEW POWER COMPANY POLE WITH RISER DIP POLE. COORDINATE WITH POWER COMPANY FOR ALL REQUIREMENTS.
- 2 NEW ELECTRICAL SERVICE METER 480/277V, 3Ø, 4W. CONTRACTOR SHALL PROVIDE METER BASE. VERIFY WITH POWER FOR METER BASE REQUIREMENTS PRIOR TO BID DATE. INCLUDE ALL COST IN BID. COORDINATE ALLOCATION OF METER SOCKET AND WIRING WITH POWER COMPANY.
- 3 NEW POWER COMPANY PAD MOUNT TRANSFORMER 480/277V, 3Ø, 4W. PROVIDE CONCRETE PAD AS PER POWER COMPANY REQUIREMENTS.
- 4 FURNISH AND INSTALL 1"xC FOR UTILITY PRIMARY RACEWAY TO POWER SOURCE AS DIRECTED BY UTILITY COMPANY. PROVIDE WARNING RIBBON 12' ABOVE CONDUIT.
- 5 1#3/0G IN 1", 3/4"X10' COPPER CLAD RODS. PROVIDE GROUNING AS PER NEC REQUIREMENTS.
- 6 PROVIDE 2 RUNS EACH 4#4/0, 1#2G, 2.5°C.
- 7 PROVIDE 1-2'C WITH PULLSTRING.
- 8 PROVIDE 600AMP, 480V, 3Ø, 4W, S/N, N1, HEAVY DUTY FUSED AT 450AMPS.
- 9 PROVIDE 4#3/0, 2'C.
- 10 CHILLER HEATER CIRCUIT, FIELD COORDINATE EXACT LOCATION AND REQUIREMENTS.
- 11 1#8G, GROUND ELECTRODE CONDUCTOR.
- 12 3" GALVANIZED PIPE WITH UNISTRUT STAND FOR ELECTRICAL SERVICE EQUIPMENT. COORDINATE WITH UTILITY COMPANY PRIOR TO ANY WORK.
- 13 NEW POWER COMPANY POLE. COORDINATE WITH POWER COMPANY FOR ALL REQUIREMENTS.

GENERAL NOTES:


- A. PROVIDE GROUND / BONDING AS INDICATED ON THE NATIONAL ELECTRICAL CODE.
- B. NAME PLATES SHALL BE PROVIDED FOR ALL ELECTRICAL SWITCH GEAR, PANEL BOARDS, LIGHTING CONTACTORS, LIGHTING CONTROL PANELS, ETC., BY ELECTRICAL CONTRACTOR.
- C. NEW ELECTRICAL METERING AND SERVICE EQUIPMENT SHALL BE PROVIDED AND INSTALLED ACCORDING TO THE LOCAL POWER UTILITY CO. AND CITY REQUIREMENTS. VERIFY AND COORDINATE WITH POWER UTILITY CO. AND AHJ BEFORE BID AND INSTALLATION.
- D. COMPLY WITH NFPA 70E SAFETY REQUIREMENTS.
- E. PANELBOARDS WITH MORE THAN 42 CIRCUITS SHALL BE IN ONE CABINET ENCLOSURE, UNLESS OTHERWISE NOTED.
- F. PROVIDE 4" CONCRETE PAD FOR ALL DRY-TYPE TRANSFORMERS.
- G. ALL TWO SECTION PANELBOARDS SHALL BE FEED THRU LUGS.
- H. CONTRACTOR SHALL BE RESPONSIBLE FOR DELIVERY OF ELECTRICAL SERVICE TO THE NEW BUILDING WITHIN PROJECT SCHEDULE. COORDINATE ALL COST FOR LABOR AND MATERIALS WITH LOCAL ELECTRICAL UTILITY COMPANY PRIOR TO BID. ALL COST ASSOCIATED WITH THE DELIVERY OF ELECTRICAL SERVICE INCLUDING ALL MATERIALS SHALL BE INCLUDED IN BID. TRANSITION OF NEW ELECTRICAL SERVICE SHALL PROCEED IN WEEKENDS OR HOLIDAYS. INCLUDE ALL COST IN BID FOR OVERTIME FROM ELECTRIC UTILITY COMPANY. NO ADDITIONAL PAYMENT WILL BE MADE FOR SERVICE DELIVERY COSTS AFTER CONTRACT HAS BEEN AWARDED.
- I. THE CONTRACTOR SHALL FURNISH AN ARC FLASH HAZARD ANALYSIS STUDY PER NFPA 70E STANDARD FOR ELECTRICAL SAFETY IN THE WORKPLACE. REFERENCE ARTICLE 130.3 AND ANEX D.
- J. CONTRACTOR SHALL INCLUDE ALL COST TO PROVIDE SHORT CIRCUIT AND PROTECTIVE DEVICE STUDY. THE SHORT CIRCUIT STUDY REPORT AND CIRCUIT BREAKER SELECTIONS SHALL BE SUBMITTED TO THE DESIGN ENGINEER PRIOR TO RECEIVING FINAL APPROVAL OF THE DISTRIBUTION EQUIPMENT SHOP DRAWINGS AND/OR PRIOR TO RELEASE OF EQUIPMENT DRAWINGS FOR MANUFACTURING. APPROVAL FROM THE ENGINEER MAY BE OBTAINED FOR PRELIMINARILY SUBMITTAL OF SUFFICIENT STUDY DATA. TO ENSURE THAT THE SELECTION OF DEVICE AND CHARACTERISTICS WILL BE SATISFACTORY.

480/277V, 3Ø, 4W ELECTRICAL LOAD ANALYSIS	
DESCRIPTION	TOTAL KVA
CHILLER #1	379
CHILLERS #2	379
PANEL-CH	90
 TOTAL WATTS:	848 KVA
TOTAL AMPS:	1020 AMPS




1 CHILL WATER PLANT
ELECTRICAL SCHEMATIC DIAGRAM
SCALE: NTS





PANEL-MDPM MEMORIAL	AMP	LUGS	NEMA	V(LU)	(P)	(W)	FEEDER/BRANCH CIRCUIT SIZE	POLE SIZE	V(LN)	MNT	KAIC	FDR
	3000	MB	3R	208	3	4						
LOAD SERVED	CKT	LOAD	BKR	POLE	FEEDER/BRANCH CIRCUIT SIZE	POLE SIZE	LOAD SERVED	CKT	LOAD SERVED			
1) EXISTING PANEL-PDP	1	183	1400	3	4-RUNS 4#600KCMIL, 1#4/0G, 4C	3	1200	75	2	1) EXISTING PANEL-MDP1		
"	3	183			"		"		75	4		
"	5	183			"		"		75	6		
1) EXISTING PANEL-K1	7	45	600	3	2-RUNS 4#350KCMIL, 1#1G, 4C	400	8			SPARE		
"	9	45			"		"		10			
"	11	45			"		"		12			
SPARE	13	400	3		4#10, 1#10G, 3/4C	30	14			2) SPD		
"	15				"		"		16			
"	17				"		"		18			
LOADS	-	(KVA)			303 303 303	(KVA)	-	DESCRITIVE LOADS				
CONNECTED LOAD	-	909				KVA/PHASE		0 - EXISTING PANELS				
RESERVE	0	0						0 - RECIPIECLES				
TOTAL LOAD	-	1000						0 - COOLING				
TOTAL AMPS	-	2776						0 - HEATING				
								909 - PANELS				

NOTES:
1) 100% RATED SOLID STATE BREAKER
2) INTEGRAL SURGE PROTECTION DEVICE 160KVA WITH MEAN DISCONNECT
3) MAIN BREAKER SHALL BE 100% RATED SOLID STATE
4) 5)



ELECTRICAL RISER
DIAGRAM KEYED NOTES:

- 1) EXISTING ELECTRICAL EQUIPMENT TO REMAIN. FIELD VERIFY EXISTING CONDITIONS PRIOR TO COMMENCING ANY WORK.
- 2) NEW SWITCHBOARD DISTRIBUTION PANELBOARD. REFER TO PANEL SCHEDULES. FIELD COORDINATE EXACT LOCATION.
- 3) EXISTING POWER COMPANY PAD MOUNT TRANSFORMER 120/208V, 30. 4W.
- 4) 3" GALVANIZED PIPE WITH UNISTRUT STAND FOR NEW ELECTRICAL CONDUITS. PROVIDE 4" CONCRETE PAD. SECURE TO EXISTING WALL. COORDINATE WITH EXISTING CONDITIONS.
- 5) EXISTING POWER COMPANY PAD MOUNT TRANSFORMER 120/208V, 30. 4W TO REMAIN. INCLUDE ALL COST IN BID FOR NEW SECONDARY WIRING CONNECTIONS.
- 6) 1#3/0G IN 1", 3/4"X10' COPPER CLAD RODS. PROVIDE GROUNDING AS PER NEC REQUIREMENTS.
- 7) PROVIDE WEATHER PROOF J-BOX FOR NEW CONDUITS. FIELD COORDINATE EXACT LOCATION.
- 8) PROVIDE NEW CONDUIT/WIRE TO CONNECT TO EXISTING PANEL-MDPA FEEDER WITH 3-RUNS EACH 4#600KCMIL, 1#3/0G, 4C. INCLUDE POLARIS CONNECTORS IN A JUNCTION BOX. SIZE BOX AS REQUIRED, AND PROVIDE 8" CONCRETE PAD FOR BOX TO SIT ON.
- 9) PROVIDE NEW CONDUIT/WIRE TO CONNECT TO EXISTING PANEL-1K FEEDER WITH 2-RUNS EACH 4#350KCMIL, 1#1G, 4C. INCLUDE POLARIS CONNECTORS IN A JUNCTION BOX. SIZE BOX AS REQUIRED, AND PROVIDE 8" CONCRETE PAD FOR BOX TO SIT ON.
- 10) PROVIDE 4-RUNS EACH, 4#600KCMIL, 4C FROM EXISTING TRANSFORMER TO NEW ELECTRICAL GEAR. INCLUDE ALL COST IN BID FOR TRENCHING / BACKFILLING AND ANY COST ASSOCIATED WITH AEP FOR NEW INSTALLATION.
- 11) PROVIDE 6" CONCRETE PAD FOR NEW GEAR.
- 12) ALL NEW CONDUITS SHALL BE SIDE/ BACK MOUNT, NO TOP FEED. FIELD VERIFY SPACE REQUIRED FOR A COMPLETE INSTALLATION. PROVIDE NEW GALVANIZED UNISTRUT STANDS/ SUPPORTS.
- 13) PROVIDE NEW CONDUIT/WIRE TO CONNECT TO EXISTING PANEL-PDP FEEDER WITH 3-RUNS EACH 4#600KCMIL, 1#3/0G, 4C. INCLUDE POLARIS CONNECTORS IN A JUNCTION BOX. SIZE BOX AS REQUIRED, AND PROVIDE 8" CONCRETE PAD FOR BOX TO SIT ON.

GENERAL NOTES:

- A. PROVIDE GROUND /BONDING AS INDICATED ON THE NATIONAL ELECTRICAL CODE.
- B. NAME PLATES SHALL BE PROVIDED FOR ALL ELECTRICAL SWITCH GEAR, PANEL BOARDS, LIGHTING CONTACTORS, LIGHTING CONTROL PANELS, ETC. BY ELECTRICAL CONTRACTOR.
- C. NEW ELECTRICAL METERING AND SERVICE EQUIPMENT SHALL BE PROVIDED AND INSTALLED ACCORDING TO THE LOCAL POWER UTILITY CO. AND CITY REQUIREMENTS. VERIFY AND COORDINATE WITH POWER UTILITY CO. AND AHU BEFORE BID AND INSTALLATION.
- D. COMPLY WITH NFPA 70E SAFETY REQUIREMENTS.
- E. PANELBOARDS WITH MORE THAN 42 CIRCUITS SHALL BE IN ONE CABINET ENCLOSURE, UNLESS OTHERWISE NOTED.
- F. PROVIDE 4" CONCRETE PAD FOR ALL DRY-TYPE TRANSFORMERS.
- G. ALL TWO SECTION PANELBOARDS SHALL BE FEED THRU LUGS.
- H. CONTRACTOR SHALL BE RESPONSIBLE FOR DELIVERY OF ELECTRICAL SERVICE TO THE NEW BUILDING WITHIN PROJECT SCHEDULE. COORDINATE ALL COST FOR LABOR AND MATERIALS WITH LOCAL ELECTRICAL UTILITY COMPANY PRIOR TO BID. ALL COST ASSOCIATED WITH THE DELIVERY OF ELECTRICAL SERVICE INCLUDING ALL MATERIALS SHALL BE INCLUDED IN BID. TRANSITION OF NEW ELECTRICAL SERVICE SHALL PROCEED IN WEEKENDS OR HOLIDAYS. INCLUDE ALL COST IN BID FOR OVERTIME FROM ELECTRIC UTILITY COMPANY. NO ADDITIONAL PAYMENT WILL BE MADE FOR SERVICE DELIVERY COSTS AFTER CONTRACT HAS BEEN AWARDED.
- I. PROVIDE TRENCHING AND BACKFILLING FOR ALL UNDERGROUND CONDUITS FOR REGULAR NON-ASPHALT/CONCRETE SURFACE.
- J. PROVIDE SAWCUT AND PATCHING FOR ALL UNDERGROUND CONDUITS FOR REGULAR ASPHALT OR CONCRETE SURFACE. INCLUDE ALL COST TO PATCH SURFACE TO MATCH EXISTING FINISH.
- K. PROVIDE CONCRETE PAD FOR ALL ELECTRICAL GEAR AND CONDUITS SUPPORTS.
- L. ALL EXTERIOR J-BOXES SHALL BE GALVANIZED AND SIZED AS REQUIRED BY CODE.
- M. THE CONTRACTOR SHALL FURNISH AN ARC FLASH HAZARD ANALYSIS STUDY PER NFPA 70E- STANDARD FOR ELECTRICAL SAFETY IN THE WORKPLACE. REFERENCE ARTICLE I3.0.3 AND ANEX D.
- N. CONTRACTOR SHALL INCLUDE ALL COST TO PROVIDE SHORT CIRCUIT AND PROTECTIVE DEVICE. THE SHORT CIRCUIT AND PROTECTIVE DEVICE CORRELATIVE STUDIES SHALL BE SUBMITTED TO THE LOCAL ENGINEER FOR REVIEW AND APPROVAL. A COPY OF THE DISTRIBUTION EQUIPMENT SHOP DRAWINGS AND/OR PRIOR TO RELEASE OF EQUIPMENT DRAWINGS FOR MANUFACTURING. APPROVAL FROM THE ENGINEER MAY BE OBTAINED FOR PRELIMINARLY SUBMITTING OF SUFFICIENT STUDY DATA. TO ENSURE THAT THE SELECTION OF DEVICE AND CHARACTERISTICS WILL BE SATISFACTORY.

REVISION:

TEXAS

WISD MEMORIAL ELEMENTARY SCHOOL
HVAC REPLACEMENT

WESLACO



TRINITY
MEP ENGINEERING

3533 Moreland Dr. Ste A | Weslaco, Tx 78596
p:956.972.0800 | f:956.561.5760
www.trinitymep.com | Copyright 2022
Texas Registered Engineering Firm - F10362
Project number: 23.1.40

MEPS01

NEW PNL-1P	AMP	LUGS	NEMA	V(L)	(P)	(W)	V(L)	(P)	(W)	V(L)	MNT	KAIC	FDR	LOAD
LOAD SERVED	CKT #	LOAD KVA	SIZE	POLE	FEEDER/BRANCH CIRCUIT	POLE	FEEDER/BRANCH CIRCUIT	POLE	FEEDER/BRANCH CIRCUIT	POLE	SIZE	KVA	CKT #	SERVED
AHU-5	1	0.7	15	3	4#10, 1#10G,3/4'C	3	4#2, 1#6G,2'C	3	110	10	2	EDH-4 (30KW)		
"	3	0.7			"		"		"			10	4	
"	5	0.7			"		"		"			10	6	
EDH-5 (9KW)	7	3	35	3	4#8, 1#10G,3/4'C	3	4#10, 1#10G,3/4'C	3	15	1.1	8	AHU-11(9.5/15)		
"	9	3			"		"		"			1.1	10	
"	11	3			"		"		"			1.1	12	
AHU-10b	13	3.5	50	3	4#6, 1#10G,1'C	3	4#4, 1#8G,1 1/2'C	3	70	1.3	14	EDH-11(17.5KW)		
"	15	3.5			"		"		"			1.3	16	
"	17	3.5			"		"		"			1.3	18	
AHU-10a	19	3.5	50	3	4#6, 1#10G,1'C	3	4#10, 1#10G,3/4'C	3	25	1.8	20	AHU-4 (14.75/25)		
"	21	3.5			"		"		"			1.8	22	
"	23	3.5			"		"		"			1.8	24	
EDH-10 (50KW)	25	16.6	175	3	4#3/0, 1#6G,2'C	3	3#2, 1#8G,1 1/2'C	2	100	4	26	NEW PANEL-1P1		
"	27	16.6			"		"		"			3	28	
"	29	16.6			"		"		"			2	30	
LOADS	-	(KVA)			46	44	44		(KVA)	-	DESCRIPTIVE LOADS			
CONNECTED LOAD	-	134			KVA/PHASE				0	-	LIGHTING			
RESERVE	0	0							0	-	RECEPTACLES			
TOTAL LOAD	-	134							32	-	COOLING			
TOTAL AMPS	-	371							93	-	HEATING			
									9	-	OTHER			

NEW PNL-2P	AMP	LUGS	NEMA	V(L)	(P)	(W)	V(L)	(P)	(W)	V(L)	MNT	KAIC	FDR	LOAD
LOAD SERVED	CKT #	LOAD KVA	SIZE	POLE	FEEDER/BRANCH CIRCUIT	POLE	FEEDER/BRANCH CIRCUIT	POLE	FEEDER/BRANCH CIRCUIT	POLE	SIZE	KVA	CKT #	SERVED
EDH-7 (4.5)	1	1.5	20	3	4#10, 1#10G,3/4'C	3	4#10, 1#10G,3/4'C	3	20	1.5	2	EDH-6 (4.5W)		
"	3	1.5			"		"		"			1.5	4	
"	5	1.5			"		"		"			1.5	6	
AHU-7 (3/15)	7	0.4	15	3	4#10, 1#10G,3/4'C	3	4#10, 1#10G,3/4'C	3	15	0.4	8	AHU-6 (3/15)		
"	9	0.4			"		"		"			0.4	10	
"	11	0.4			"		"		"			0.4	12	
AHU-9 (31.75/50)	13	3.8	50	3	4#6, 1#10G,1'C	3	4#6, 1#10G,1'C	3	50	3.8	14	AHU-8 (31.75/50)		
"	15	3.8			"		"		"			3.8	16	
"	17	3.8			"		"		"			3.8	18	
EDH-9 (43KW)	19	14.3	150	3	4#2/0, 1#6G,2'C	3	4#2/0, 1#6G,2'C	3	150	14.3	20	EDH-8 (43KW)		
"	21	14.3			"		"		"			14.3	22	
"	23	14.3			"		"		"			14.3	24	
LOADS	-	(KVA)			40	40	40		(KVA)	-	DESCRIPTIVE LOADS			
CONNECTED LOAD	-	120			KVA/PHASE				0	-	LIGHTING			
RESERVE	0	0							0	-	RECEPTACLES			
TOTAL LOAD	-	120							25	-	COOLING			
TOTAL AMPS	-	333							95	-	HEATING			
									0	-	OTHER			

EXISTING PNL-4P	AMP	LUGS	NEMA	V(L)	(P)	(W)	V(L)	(P)	(W)	V(L)	MNT	KAIC	FDR	LOAD
LOAD SERVED	CKT #	LOAD KVA	SIZE	POLE	FEEDER/BRANCH CIRCUIT	POLE	FEEDER/BRANCH CIRCUIT	POLE	FEEDER/BRANCH CIRCUIT	POLE	SIZE	KVA	CKT #	SERVED
1) AHU-16 (31.7/50)	1	3.8	50	3	4#6, 1#10G,1'C	3	4#4, 1#8G,1 1/2'C	3	70	4	2	1) NEW PANEL-4P1		
"	3	3.8			"		"		"			3	4	
"	5	3.8			"		"		"			2	6	
1) AHU-17 (31.7/50)	7	3.8	50	3	4#6, 1#10G,1'C	3	4#4, 1#8G,1 1/2'C	3	70	1.8	8	3) EXISTING		
"	9	3.8			"		"		"			10		
"	11	3.8			"		"		"			12		
1.) EXISTING	13	20	1		"		"		"			14	14	3) EXISTING
SPACE	15				"		"		"			16		
SPACE	17				"		"		"			18		
SPACE	19				"		"		"			20		3) EXISTING
SPACE	21				"		"		"			22		
SPACE	23				"		"		"			24		
SPACE	25				"		"		"			26		
SPACE	27				"		"		"			28		
SPACE	29				"		"		"			30		
4) EDH-16(43KW)	14.3	175	3		4#3/0, 1#6G,2'C	3	4#3/0, 1#6G,2'C	3	175	14.3		4) EDH-17(43KW)		
"	14.3				"		"		"			14.3		
"	14.3				"		"	</						

WISD MEMORIAL ELEMENTARY SCHOOL HVAC REPLACEMENT

NESLACO

NEW PANEL-1P1	AMP 100	LUGS MB	NEMA 1	V(LL) 208	(P) 3	(W) 4	V(LN) 120	MNT SUR.	KAIC 10	FDR		
LOAD SERVED	CKT #	LOAD KVA	BKR SIZE	POLE	FEEDER/BRANCH CIRCUIT SIZE	A	B	FEEDER/BRANCH CIRCUIT SIZE	POLE BKR SIZE	LOAD KVA #	LOAD SERVED	
FCCU-7	1	1	15	2	3#10, 1#10G,3/4"C	*	*	3#10, 1#10G,3/4"C	2	15	1 2	FCCU-8
"	3	1			-	*	*	-		1	4	"
FCCU-9	5	1	15	2	3#10, 1#10G,3/4"C		*	2#10, 1#10G,3/4"C	1	20	1.2 6	TU-E, TU-D
"	7	1			-	*	*	2#10, 1#10G,3/4"C	1	20	1.2 8	TU-F, TU-G TU-C
MOTORIZED DAMPERS	9	0.2	20	1	2#10, 1#10G,3/4"C	*	*	2#10, 1#10G,3/4"C	1	20	0.6 10	NEW HVAC CONTROLS
SPACE	11				-		*	-			12	SPACE
SPACE	13				-	*	*	-			14	SPACE
SPARE	15		20	1	-	*	*	-	1	20	16	SPARE
SPARE	17		20	1	-		*	-	1	20	18	SPARE
SPARE	19		20	1	-	*	*	-	1	20	20	SPARE
<u>LOADS</u>	-	(KVA)				4	3	2	(KVA)	-	<u>DESCRIPTIVE LOADS</u>	
CONNECTED LOAD	-	13								0	- LIGHTING	
RESERVE	0	0								3	- RECEPTACLES	
TOTAL LOAD	-	13								6	- COOLING	
TOTAL AMPS	-	37								0	- HEATING	
										0	- OTHER	
										0	- OTHER-A	
										0	- OTHER-B	
										4	- OTHER-C	

NEW PANEL-4P1	AMP 100	LUGS MLO	NEMA 1	V(LL) 208	(P) 3	(W) 4		V(LN) 120	MNT SUR.	KAIC 10	FDR		
LOAD SERVED	CKT #	LOAD KVA	BKR SIZE	POLE SIZE	FEEDER/BRANCH CIRCUIT		FEEDER/BRANCH CIRCUIT	POLE SIZE	BKR SIZE	LOAD KVA	CKT #	LOAD SERVED	
FCCU-4	1	1.4	15	2	3#10, 1#10G,3/4"C	*		3#10, 1#10G,3/4"C	2	15	1.4	2	FCCU-5
"	3	1.4			-	*		-			1.4	4	"
FCCU-6	5	1.4	15	2	3#10, 1#10G,3/4"C		*	2#10, 1#10G,3/4"C	1	20	1.2	6	TU-K, TU-J
"	7	1.4			-	*		2#10, 1#10G,3/4"C	1	20	1.2	8	TU-H, TU-I, TU-L
MOTORIZED DAMPERS	9	0.2	20	1	2#10, 1#10G,3/4"C	*		2#10, 1#10G,3/4"C	1	20	0.6	10	NEW HVAC CONTROLS
EF-14,15	11	0.2	20	1	2#10, 1#10G,3/4"C		*	-				12	SPACE
SPACE	13				-	*		-				14	SPACE
SPARE	15		20	1	-	*		-	1	20		16	SPARE
SPARE	17		20	1	-		*	-	1	20		18	SPARE
SPARE	19		20	1	-	*		-	1	20		20	SPARE
<u>LOADS</u>	-	(KVA)				5	4	3			(KVA)	-	<u>DESCRIPTIVE LOADS</u>
CONNECTED LOAD	-	17				KVA/PHASE					0	-	LIGHTING
RESERVE	0	0									3	-	RECEPTACLES
TOTAL LOAD	-	17									8	-	COOLING
TOTAL AMPS	-	48									0	-	HEATING
											0	-	OTHER
											0	-	OTHER-A
											0	-	OTHER-B
											6	-	OTHER-C

NEW PANEL-PDP1	AMP 100	LUGS MLO	NEMA 1	V(LL) 208		(P) 3		(W) 4		V(LN) 120	MNT SUR.	KAIC 10	FDR	
LOAD SERVED	CKT #	LOAD KVA	BKR SIZE	POLE	FEEDER/BRANCH CIRCUIT SIZE	A	B	C	FEEDER/BRANCH CIRCUIT SIZE	POLE	BKR SIZE	LOAD KVA	CKT #	LOAD SERVED
FCCU-2	1	1.4	15	2	3#8, 1#10G,3/4"C	*			3#8, 1#10G,3/4"C	2	15	1.4	2	FCCU-3
"	3	1.4			-		*		-			1.4	4	"
FCCU-1	5	1.4	15	2	3#8, 1#10G,3/4"C			*	2#10, 1#10G,3/4"C	1	20	1.2	6	TU-A, TU-B
"	7	1.4			-		*		2#10, 1#10G,3/4"C	1	20	0.2	8	EF-21,22
MOTORIZED DAMPERS	9	0.2	20	1	2#10, 1#10G,3/4"C		*		2#10, 1#10G,3/4"C	1	20	0.6	10	NEW HVAC CONTROLS
GAS DETECTION	11	0.2	20	1	2#10, 1#10G,3/4"C			*	-				12	SPACE
SPACE	13				-		*		-				14	SPACE
1) EDH-3(12.5KW)	15	4	50	3	4#6, 1#10G,1"C		*		-	1	20		16	SPARE
"	17	4			-			*	-	1	20		18	SPARE
"	19	4			-		*		-	1	20		20	SPARE
<u>LOADS</u>	-	(KVA)				8	8	7			(KVA)	-		<u>DESCRIPTIVE LOADS</u>
CONNECTED LOAD	-	23										0	-	LIGHTING
RESERVE	0	0										2	-	RECEPTACLES
TOTAL LOAD	-	23										8	-	COOLING
TOTAL AMPS	-	63										0	-	HEATING
												12	-	OTHER

