



**Date:** 12/16/24

Performed by: Andrew Tinklenberg

**Location:** Whittier School – 315 West 26<sup>th</sup> Street, Minneapolis, MN 55404

**RE:** Radon Testing

#### **INTRODUCTION**

From December 9–12, 2024, radon testing was performed within Whittier School located at 315 West 26<sup>th</sup> Street, Minneapolis, MN. The testing was performed to ensure that radon gas concentrations within the building are below the established regulatory limits. Testing was conducted under normal occupied building conditions in frequently-occupied ground contact rooms and other areas in accordance with ANSI/AARST Protocol for Conducting Measurements of Radon and Radon Decay Products in Multifamily, School, Commercial and Mixed-Use Buildings (MA-MFLB 2023) and Minnesota Department of Health (MDH) guidelines.

#### **SUMMARY OF FINDINGS**

All of the areas that were tested were found to have radon gas levels below 4.0 picocuries per liter of air (pCi/L), which is the EPA and MDH action level. (Note: Spike sampling is performed in conjunction with this testing, Duplicate (side-by-side) sampling was conducted in select areas at a rate of 10% of areas tested, and "Room A" was the blank sample.)

The radon test kits were submitted to and analyzed by AirChek, Inc., 1936 Butler Bridge Rd, Mills River, NC 28759 (MN License #RL-00003). Please refer to the attached AirChek radon testing report and sample diagrams for further information concerning the radon testing, areas that were tested, and the radon levels that were found to be present. Per MDH requirements, this information will be shared with the local regulatory agency (MDH - <a href="health.indoorair@state.mn.us">health.indoorair@state.mn.us</a>, Phone # 651-201-4601) and incorporated in an MPS' board meeting. The information will also be posted on the <a href="health.sep">EH&S webpage</a> available through the main MPS website and maintained on file by EH&S.

#### **REMARKS**

Every effort was made to maintain closed building conditions and HVAC systems are monitored and controlled remotely by MPS Direct Digital Control (DDC) personnel. Any deviation in building conditions or sampling protocol which could have an impact on the testing and test results is described in the summary above. If any unoccupied areas that were not tested are planned for future occupancy, contact EH&S so that the areas can be tested. Unless specified, all QA/QC measurements were within the required limits. Radon testing is to be performed in MPS District buildings every 5 years or any time major renovation activities take place which have the potential to impact the building's foundation or HVAC systems. Refer to the attached test condition summary and ANSI/AARST advisories for additional information concerning the radon testing.

If you have any questions regarding this information, please feel free to contact me. Thank you,

al Sing

Andrew Tinklenberg MDH RMEA-00426 NRPP ID# 111389 RMP



Safety Specialist - Environmental Health & Safety Minneapolis Public Schools
Environmental Health & Safety - Facilities Dept.
1225 N. 7<sup>th</sup> Street, Minneapolis, MN 55411
andrew.tinklenberg@mpls.k12.mn.us
612-668-0306 Phone
612-668-0310 EH & S General Office
612-668-0275 Fax







## **Attachments**

Radon Testing Results
Floor Plans
Notification & Communication Documents
Test Condition Summary
ANSI/AARST Advisory Statements

## 15554 / ANDREW TINKLENBERG / MINNEAPOLIS PUBLIC SCHOOLS

11810909 20	2024-12-09 2024-12-09	7:00 am			Temp.	Facility	Building	Room	Project ID	Floor	Result
	2024-12-09		2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CUSTODIAN 007	WHITTIER	0	< 0.3
11810910 20	2024-12-07	7:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CUSTODIAN 007	WHITTIER	0	< 0.3
	2024-12-09	7:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CUSTODIAN BREAK ROOM	WHITTIER	0	0.5
11810911 20	2024-12-09	7:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	GYM OFFICE 004	WHITTIER	0	0.8
11810912 20	2024-12-09	7:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	OFFICE 115	WHITTIER	1	< 0.3
11810913 20	2024-12-09	7:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	OFFICE 115B	WHITTIER	1	< 0.3
11810914 20	2024-12-09	7:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	MULTI-PURPOSE 106	WHITTIER	1	< 0.3
11810915 20	2024-12-09	7:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CAFETERIA 107	WHITTIER	1	< 0.3
11810916 20	2024-12-09	7:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CAFETERIA OFFICE 108A	WHITTIER	1	< 0.3
11810917 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 175	WHITTIER	1	< 0.3
11810918 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 174	WHITTIER	1	< 0.3
11810919 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 135B	WHITTIER	1	< 0.3
11810920 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 131	WHITTIER	1	< 0.3
11810921 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	OFFICE 156	WHITTIER	1	< 0.3
11810922 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 176	WHITTIER	1	< 0.3
11810923 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 166	WHITTIER	1	< 0.3
11810924 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 213	WHITTIER	2	< 0.3
11810925 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 221	WHITTIER	2	< 0.3
11810926 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 221	WHITTIER	2	< 0.3
11810927 20	2024-12-09	8:00 am	2024-12-12	2:00 pm	70	MPS WHITTIER	MPS WHITTIER	CLASSROOM 248	WHITTIER	2	< 0.3
11810928 20	2024-12-09	8:00 am	2024-12-12	3:00 pm	70	MPS WHITTIER	MPS WHITTIER	ROOM A	WHITTIER	2	< 0.3

Air Chek 1936 Butler Bridge Rd, Mills River, NC 28759-3892 Phone: (828) 684-0893 Fax: (828) 684-8498



**Environmental Health & Safety** 

Office: (612) 668-0310 Direct: (612) 668-0306 Andrew Tinklenberg Safety Specialist Environmental Health & Safety

## **RADON TESTING NOTIFICATION (2024)**

## **Whittier School**

The District will be conducting short-term radon testing at Whittier School. Radon is a naturally occurring radioactive gas that is created from the breakdown of Radium that is naturally present in soil. Radon can enter buildings from the soil through gaps, cracks and holes in the foundation. Radon testing is performed periodically and is being performed based on Minnesota Department of Health recommendations and protocols. As per the recommendations, frequently occupied, ground level or ground contact areas will be the focus of the testing. Sampling locations will be selected that provide the best representation of these areas.

If your room is selected for testing, please do your part by ensuring that the devices are not removed or tampered with in any way. The devices are small, rectangular envelopes, approximately 4 by 6 inches and will typically be hung from the ceiling or an interior wall. The short-term radon detectors are planned to be placed and collected December 9 - 12, 2024. When available, sample results will be shared with your principal and placed on the EH&S webpage available through the main MPS website.

An example of the detector is pictured below:



Thank you very much for your cooperation. If you have questions, please contact me at 612-668-0306 or andrew.tinklenberg@mpls.k12.mn.us



# **Notice of Inspection for Facilitating Staff**

## A radon test is scheduled for:

Building:	
Test Start Date:	Test End Date:

## Please help to maintain the required test conditions throughout the building:

- 1. All windows and exterior doors must be kept closed (aside for momentary entry or exit) for 12 hours before and during the test.
- 2. Heating and cooling systems must be set to normal occupied operating temperatures.
- 3. Test devices are not to be disturbed.

Further guidance on required building conditions are found on the next page.

Test kits are not dangerous in any way. The type of devices used for this testing may include:

- **Short-term test kits**: It's important these devices are fully open and not covered. They will be analyzed by a laboratory.
- Continuous radon monitors: These are electronic monitors that record hourly radon readings.
- Long-term test kits: It is important that these devices are not covered. They will be analyzed by a laboratory.

## **Declaration of Observed Compliance:**

Failure to reasonably maintain test conditions can lead to unnecessary expense, disruptions, and unreliable data. Disturbing test devices can also cause unreliable or invalid test results.

- Please report in a timely manner if required test conditions are not maintained.
- Please sign and return this form once the rest is complete.

To the best of my knowledge, the required conditions were maintained during the test.

Yes	No			
Name:				
Signatı	ure: Al-	5-	Date:	

## NOTICE OF INSPECTION FOR FACILITATING STAFF

## **Required Closed Building Conditions for Radon Testing**

Building Component	Action Required	
Windows	Keep Closed, Seal broken windows closed	
External doors (except for normal entry or exit)	Keep Closed	
Heating & Cooling Systems	Set to normal operating conditions	
Bathroom fans	Operate normally	
Fireplaces (including gas)	Do not operate	
Auxiliary or temporary systems that bring air into the building	Do not operate, unless an integral part of HVAC or supplies make-up air for combustion appliances	
Exhaust systems (ex. from shops, laundries, kitchens)	Avoid excessive operation	
Interior doors, Stairwells, Fire Doors	Operate Normally	
Garage doors	Operate normally	
Ceiling Fans, Portable Fans	Do not blow directly on the test device	
Window AC Units	Operate in recirculation mode only	
Window Fans	Do not operate. Seal shut or remove.	
Humidifiers, Dehumidifiers, Portable Air Cleaners	Operate Normally	
Central Vacuum Cleaner Systems	Operate Normally	
Passive crawl space vents	Operate normally	
Crawlspace exhaust systems for humidity control	Operate normally	
Passive Vents for Combustion Make-Up Air	Leave Open	

#### NOTICE OF INSPECTION FOR FACILITATING STAFF

Building Component	Action Required
Combustion Appliance Vents	Operate Normally
Passive Solar Systems	Operate Normally
Attic Vent Fans	Operate Normally
<b>Evaporative Cooling Systems</b>	Do not operate

## **Radon Test Device Placement Requirements**

Place detectors within the general breathing zone. Locate detectors no less than:

- 3 feet from exterior doors, windows, other openings to outdoors,
- 20 inches above the floor,
- · 4 inches from other test devices and objects, and
- 1 foot from ceilings.

Place detectors where they are not easily disturbed.

Place detectors where they are not influenced by other factors:

- Do not place in closets, crawlspaces, cupboards, sumps, or nooks within building foundation,
- Do not place devices in areas with high air movement (ex. mechanical areas, furnace closets),
- Do not place devices in areas with high humidity (ex. kitchens, bathrooms, laundry rooms),
- Do not place devices near drafts from HVAC systems or fans,
- Do not place test devices near heat sources (ex. appliances, radiators, fireplaces, direct sun), and
- Do not place detectors on devices that produce radiation (ex. natural stone counters, pool tables, rock collections)

## For more information regarding on-site activities, contact:

Licensed measurement p	professional:	

Minnesota Department of Health, Indoor Air Unit, PO Box 64975, St. Paul, MN 55164 651-201-4601, health.indoorair@state.mn.us, mn.gov/radon

8/17/2023, To obtain this information in a different format, call: 651-201-4601.



# **Notice of Inspection for Building Occupants**

#### A radon test is scheduled for:

Building:		
Test Start Date:	Test End Date:	

An important step is being taken to ensure a safe and healthy building. Testing for radon is recommended for all homes and schools.

Radon is a naturally occurring radioactive gas that can be present in some buildings at concentrations greater than recommended. In the United States, radon exposure is the second leading cause of lung cancer, and it is the leading cause of lung cancer in nonsmokers.

Please help to maintain the required test conditions throughout the building.

- 1. All windows and exterior doors must be kept closed (aside from momentary entry or exit) for 12 hours before and during the test.
- 2. Heating and cooling systems must be set to normal occupied operating temperatures.
- 3. Test devices are not to be disturbed.

The test devices are not dangerous in any way and a sample device is available to view upon request.

More information about radon in Minnesota can be found online at mn.gov/radon.

If you have any questions or concerns, please contact:



# **Client Authorizations & Communications**

Client and Facilitating Staff Memb	er Contact Information
Client/Authorized Agent	phone
Onsite Supervisor	phone
Building/Dwelling Access	phone
HVAC Operations	phone
Other Contact/Title	phone
Radon Testing Professional Conta	ct Information
Scheduling/Logistics	phone
Onsite Supervisor	phone
Field Technician	phone
Field Technician	phone
Staff authorized for responding to	occupant and public inquiries:
Name/Title	phone
Name/Title	phone
Person(s) authorized to receive re	port data and incremental reports:
Name/Title	phone
Name/Title	phone
Frequency of Reports	
	se of testing when testing is complete

Minnesota Department of Health | Indoor Air Unit | PO Box 64975 | St. Paul, MN 55164 | 651-201-4601 health.indoorair@state.mn.us | www.health.state.mn.us | mngov/radon

08/17/2023 | To obtain this information in a different format, call: 651-201-4601.



# **Client Commitment to Compliance**

## **Management Commitment:**

	ctent reasonably possible, I, on beh		e radon tests are met, a	, commit to sportrayed herein.
Client/A	uthorized Agent:			
, Signatur	$AI \subset AI$		Date:	
Buildin	g On-Site Supervisor Commit	ment:		
	ctent reasonably possible, I commi adon tests are met, as portrayed h	· -	=	
	rior Notifications: Notices will be outlined with the control of t		and non-tested dwellin	gs and posted in
lo	ccess: Access will be provided to e ocations on the same day for both etrieving test devices.	_		
On-Site S	Supervisor:			
Signatur	all Si		Date:	
Buildin	g Operations Staff Commitme	ent:		
	ctent reasonably possible, I commi adon tests are met, as portrayed h	. •	•	
	uilding Preparation: I accept responded	=		
	ompliance Verification: I accept re VAC units and repairs where comp	-		=
HVAC O	erations Supervisor:			
Signatur	Me S-		Date:	

Minnesota Department of Health, Indoor Air Unit, PO Box 64975, St. Paul, MN 55164 651-201-4601, <a href="https://health.indoorair@state.mn.us">health.indoorair@state.mn.us</a>, mn.gov/radon



## **Whittier Test Condition Summary**

### December 9-12, 2024 - Minneapolis, MN (Climate Zone 6)

	Annually	During the Test	
Outdoor Temperatures	Average = 46° F	Max. = 37° F	
		Min. = -8° F	
		Average = 15° F	
Prevailing Operating Condition	Heating – 50%	Heating – 100%	
(Heating/Cooling)	Cooling – 25%	Cooling – 0%	
	Mixed – 25%	Mixed – 0%	
Air Distribution Systems	Intermittent during summer	Active	

<sup>\* -</sup> Note: No rain or snowfall was recorded during the testing period and winds were light to moderate.

## **Informative Advisories**

- 1. Fluctuations in radon concentrations are usually caused by either:
  - changes in the strength of indoor air pressures that draw soil gas into a building; or
  - changes in the volume of outside air entering a building.
- 2. Clear characterization of a radon hazard is more likely to occur when:
  - Outdoor temperatures extend below 65°F (18°C), at least intermittently, which causes natural indoor air pressures that draw radon laden soil gas into a building; and
  - Heating or cooling distribution fans are at least intermittently active during a test.
- 3. Measurements more likely to reflect an occupant's exposure to radon are measurements conducted under conditions that most closely align to the building operating conditions that prevail during the greatest amount of time each year.

<sup>\* -</sup> Above advisory information is taken from page 33 of the ANSI/AARST MA-MFLB-2023 Standard, "Protocol for Conducting Measurements of Radon and Radon Decay Products in Multifamily, School, Commercial and Mixed-Use Buildings." Additional advisory notes/information will be added when necessary. Weather information was collected from timeanddate.com/weather/usa/minneapolis.

## **ANSI/AARST ADVISORY STATEMENTS**

### **Table 8-A Reporting Low Radon Concentrations**

Consider fixing the building if test results indicate radon concentrations greater than half the action level, (e.g., between 2 and 4 pCi/L). Responsible care requires repeating initial testing procedures for all building(s) at least every 5 years and in conjunction with any sale of a building. Radon testing should also be conducted when any of the following circumstances occur:

- a new addition is constructed or alterations for building reconfiguration or rehabilitation occur;
- a ground contact area not previously tested is occupied, or a building is newly occupied;
- heating or cooling systems are significantly altered, resulting in changes to air pressures or pressure relationships;
- ventilation is significantly altered by extensive weatherization, changes to mechanical systems or comparable procedures;
- significant openings to soil occur due to:
  - o groundwater or slab surface water control systems that are altered or added (e.g., sumps, perimeter drain tile, shower/tub retrofits, etc.) or,
  - o natural settlement causing major cracks to develop;
- earthquakes or construction blasting, fracking or formation of sink holes nearby; or
- a mitigation system is altered, modified or repaired.

Should testing indicate concentrations that meet or exceed the action level, conduct evaluations, corrections and further testing until radon concentrations have been mitigated to below the action level.

#### Table 8-B Reporting Elevated Radon Concentrations

Fix the building. Test results indicate occupants may be exposed to radon concentrations that meet or exceed the action level. Efforts to reduce radon concentrations are not complete until retests provide evidence of effectiveness. The initial retest should be conducted within 30 days after mitigation efforts and system installations.

Post-mitigation clearance testing to confirm each building is fixed requires testing all buildings that demonstrated elevated radon concentrations:

- 1) in all ground-contact rooms and dwellings,
- 2) in not less than 10% of non-residential rooms and dwellings on each upper floor.

Should testing indicate concentrations that meet or exceed the action level, conduct evaluations, corrections and further testing until radon concentrations have been mitigated to below the action level.

<sup>\* -</sup> Above advisory information is taken from pages 29-30 of the ANSI/AARST MA-MFLB-2023 Standard, "Protocol for Conducting Measurements of Radon and Radon Decay Products in Multifamily, School, Commercial and Mixed-Use Buildings." Additional advisory notes/information will be added when necessary.