Shawnee Mission School District
Bid 25-005 – Food Services Equipment - Dishwashers
April 22, 2025

Addendum No. 1

REVISED SPECIFICATIONS: The District has become aware that the current dishwashers have **drain tempering assemblies**; this accessory was not listed in the specifications. Revised specifications for both machines are provided below; these revised specifications now include the drain tempering assemblies:

ITEM 1 - DISHWASHER, CONVEYOR TYPE (1 REQ'D)
Hobart Model CL44-BAS+BUILDUP Dimensions: 68.5(h) x 44.75(w) x 31.25(d)

Conveyor Dishwasher, single tank, (202) racks/hour, insulated hinged doors, .45 gallon/rack, Complete Delime with Booster Guard, Touch Screen Controls with diagnostics, troubleshooting, and SmartConnect App, capless wash arms, NSF Pot & Pan mode, cULus, NSF, ENERGY STAR®, Factory Startup - Free for installations within 100 miles (accessible by public roadway) of a Hobart Service Office during normal business hours with appropriate notice; Installation beyond 100 miles or those not accessible by public roadway will be quoted by Service.

1 ea	Oversized units with crated shipping dimensions greater or equal to 72" in length and/or 90" in height. If delivery is to a facility without a standard height dock, additional shipping charges will apply depending on the service requested. consult Factory.
1 ea	Standard warranty - 1-Year parts, labor & travel time during normal working hours within the USA
1 ea	Model CL44BAS-ELE0CD 480v/60/3-ph Single point connection standard (field convertible to dual point)
1 ea	Model CL44BAS-HGTHTS Higher than Standard 24”H x22”W opening, fits large oval trays, tall drink dispensers
1 ea	Model CL44BAS-HTE15K Electric tank heat 15kW
1 ea	Model CL44BAS-ERH18K With 18 kW Booster (default)
1 ea	Model CL44BAS-DIR0RL Right to left operation
1 ea	NOTE: For water of 3-grains of hardness or more, Hobart suggests adding a water softener.
1 ea	Model DWT-CL Drain water tempering kit for CL models
2 ea	Model SHTHD/E-ADJ E-series vent hood short (adjustable)
1 ea	Model CL44EN-BASFETSTD Standard feet

ITEM 2 - DISHWASHER, CONVEYOR TYPE (1 REQ'D)
Hobart Model CL44-BAS+BUILDUP Dimensions: 68.5(h) x 44.75(w) x 31.25(d)

Conveyor Dishwasher, single tank, (202) racks/hour, insulated hinged doors, .45 gallon/rack, Complete Delime with Booster Guard, Touch Screen Controls with diagnostics, troubleshooting, and SmartConnect App, capless wash arms, NSF Pot & Pan mode, cULus, NSF, ENERGY STAR®, Factory Startup - Free for installations within 100 miles (accessible by public roadway) of a Hobart Service Office during normal business hours with appropriate notice; Installation beyond 100 miles or those not accessible by public roadway will be quoted by Service.

1 ea	Oversized units with crated shipping dimensions greater or equal to 72" in length and/or 90" in height. If delivery is to a facility without a standard height dock, additional shipping charges will apply depending on the service requested. consult Factory.
1 ea	Standard warranty - 1-Year parts, labor & travel time during normal working hours within the USA
1 ea	Model CL44BAS-ELE0CD 480v/60/3-ph Single point connection standard (field convertible to dual point)
1 ea	Model CL44BAS-HGTHTS Higher than Standard 24”H x22”W opening, fits large oval trays, tall drink dispensers
1 ea	Model CL44BAS-HTE15K Electric tank heat 15kW
1 ea	Model CL44BAS-ERH18K With 18 kW Booster (default)
1 ea	Model CL44BAS-DIR0LR Left to right operation
1 ea	NOTE: For water of 3-grains of hardness or more, Hobart suggests adding a water softener.
1 ea	Model DWT-CL Drain water tempering kit for CL models
2 ea	Model SHTHD/E-ADJ E-series vent hood short (adjustable)
1 ea	Model CL44EN-BASFETSTD Standard feet