



ADDENDUM

Addendum #: 2
Date: May 12, 2025
Project #: 2024-0014
Project Name: MOTF - Reroof

BIDS DUE: Prior to 2:00 p.m., Thursday, May 15, 2025
(*unchanged*) Longview School District, MOTF Office
2080 38TH Avenue
Longview, WA 98632

The work stated and described in this addendum shall become a part of the Contract Documents for this project.

SPECIFICATIONS:

- See revised Specification section **00 41 00 – Bid Form** which includes a section on unit pricing.
- See added Specification section **01 22 00 – Unit Prices**
- See revised Specification section **06 10 00 – Rough Carpentry**

ADDITIONAL INFORMATION:

- Monday, May 12, 2025 @ 5 p.m. is the last day for questions to be submitted.

END OF ADDENDUM # 2

Attachments:

- Revised 00 41 00-Bid Form
- Added 01 22 00-Unit Prices
- Revised 06 10 00-Rough Carpentry

BID FORM

To be submitted no later than 2:00 p.m. on the bid submittal date indicated in Section 00 11 13.

TO: Longview School District No. 122
MOTF Office
2080 38th Avenue
Longview, Washington 98632

The undersigned Bidder acknowledges receipt of and familiarization with the Bidding Documents, the Project Manual, the Drawings, the Specifications, the Contract Documents, and the following Addenda:

Addendum No.:	Date	Pages	Initials of Bidder Representative
1			
2			
3			
4			

BASE BID:

Pursuant to and in compliance with the Contract Documents, including the Advertisement for Bids and Instructions to Bidders, the Bidder hereby certifies that it has carefully examined the Bidding Documents, the Contract Documents, and the conditions affecting the Work, and being familiar with the site, and having made the necessary examinations, proposes to furnish all labor, materials, equipment, and services necessary to complete the Work in strict accordance with the Contract Documents for the above-named Project for the following sum, which is hereby designated as the Base Bid:

_____ Dollars (\$ _____).

(Show amount in words and figures. This amount does not include state/local sales tax.)

ALTERNATE BIDS:

See Section 01 23 00, Alternates, for full description.

No.:	Description of Alternate Bids	Type	Alternate Bid Amount (Words)	Alternate Bid Amount (Figures)
1.	Remove and replace Roof Hatch.	Additive		\$

REINSTATEMENT OF ALTERNATE BIDS:

The undersigned Bidder agrees that the Owner has the right, for a period of forty-five (45) days following the bid submittal deadline, to initiate or rescind acceptance of any Alternate Bid in the amount(s) quoted above.

UNIT PRICES:

See Section 01 22 00, Unit Prices, for full description.

No.:	Description of Unit Prices	Unit	Unit Price Amount (Words)	Unit Price Amount (Figures)
1.	T&G roof decking.	Per 10 Lineal Ft.		\$

SALES TAX:

None of the sums stated in the foregoing includes Washington State or local sales tax.

TIME OF COMPLETION AND LIQUIDATED DAMAGES:

The undersigned Bidder agrees, if awarded the Contract, to achieve Substantial Completion of the Work of the Contract within the period specified in AIA Document A101-2017, as modified by Owner, and also agrees to the amounts specified in the Contract Documents for Liquidated Damages. It is further agreed that the time for completion of the Work described herein is a reasonable time considering the average climatic range and usual industrial conditions prevailing in the locality.

TRENCH EXCAVATION SAFETY PROVISIONS:

If the Contract Documents contain any work that requires trenching exceeding a depth of four (4) feet, all costs for adequate trench safety systems must be identified as a separate bid item in compliance with Chapter 39.04 RCW and WAC 296-155-650. The purpose of this provision is to ensure that the Bidder agrees to comply with all the relevant trench safety requirements of Chapter 49.17 RCW. This bid amount will be considered as part of the Base Bid set forth above. Bidder must include a lump-sum dollar amount in the blank below (even if the value is \$0.00) to be responsive.

Trench Excavation Safety Provisions Only: _____ Dollars
(\$_____).

CONTRACT AND BONDS:

If the Owner awards a contract based on this Bid within forty-five (45) days of the bid submittal deadline, the Bidder agrees to execute a contract for the above work, for compensation computed from the above-stated sums, on the form of contract provided in the Bidding Documents, and to furnish Payment and Performance Bonds and acceptable evidence of insurance as required by the Contract Documents.

BID GUARANTEE:

Pursuant to the Instruction to Bidders, Section 00 21 13, Bidder hereby certifies that it has furnished a bid guarantee for no less than five (5) percent of the Base Bid, and that such guarantee accompanies this Bid Form.

Within twenty-four (24) hours after the issuance of the Owner's notice of intent to award the Contract, the successful bidder must furnish evidence satisfactory to the Owner of its ability to obtain statutory bonds pursuant to Chapter 39.08 RCW. Additionally, the successful bidder must submit the Payment and Performance Bonds and other documents required by the Contract Documents (including, but not limited to, certificates of insurance) to the Owner no later than seven (7) days after the date of execution of the Contract. The successful bidder must also submit within forty-eight (48) hours of the Owner's request a complete Apprenticeship Utilization Plan and such other information as specified in Paragraph 1.06 ("Post-Bid Information") of the Instructions to Bidders, Section 00 21 13.

If the successful bidder, upon award of the Contract by the Owner, fails to execute the Contract or submit the Payment and Performance Bonds or other information required by the Instructions to Bidders as required within the time specified, the Owner may revoke the award. Should the successful bidder fail to enter into the Contract with Owner, the bid guarantee may be retained by Owner as liquidated damages, not as a penalty.

If a contract is not awarded within forty-five (45) days after the bid submittal deadline, or if the Bidder delivers an executed Contract, executed Payment and Performance Bonds, and such other information required by the Instructions to Bidders, Section 00 21 13, then the certified or bank cashier's check submitted as the bid guarantee will be returned to the bidder, or the Bid Bond will become void.

RESPONSIBILITY CRITERIA:

The undersigned hereby verifies under penalty of perjury, in accordance with RCW 9A.72.085, that Bidder is in compliance with the responsible bidder criteria requirements of RCW 39.04.350(1)(g).

BIDDER'S INFORMATION:

Bidder's Business Name:		
Type of Business: ☐ Sole Proprietorship ☐ Partnership ☐ Corporation (State of Incorporation:____) ☐ Other		
Physical Business Address (Must not be a P.O. Box):		
City:	State:	Zip Code:
Business Telephone Number:	Business Fax Number:	Business Email Address:
State of Washington numbers for the following:		
Contractor Registration No.:	UBI No.:	Employment Security Dept. No.:

OFFICIAL AUTHORIZED TO SIGN FOR BIDDER:

"I certify (or declare) under penalty of perjury under the laws of the State of Washington that the foregoing is true and correct":	
Signature:	Date:
Print Name and Title	Location or Place Executed: (City, State)

END OF SECTION

**SECTION 01 22 00
UNIT PRICES**

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. List of unit prices, for use in preparing Bids.
- B. Measurement and payment criteria applicable to Work performed under a unit price payment method.

1.02 COSTS INCLUDED

- A. Unit Prices included on the Bid Form to include full compensation for all required labor, products, tools, equipment, plant, transportation, services and incidentals; erection, application or installation of an item of the Work; overhead and profit.

1.03 UNIT QUANTITIES SPECIFIED

- A. Quantities indicated in the Bid Form are for bidding and contract purposes only. Quantities and measurements of actual Work will determine the payment amount.

1.04 MEASUREMENT OF QUANTITIES

- A. Measurement methods delineated in the individual specification sections complement the criteria of this section. In the event of conflict, the requirements of the individual specification section govern.
- B. Contractor to report actual quantities of material added or subtracted.
- C. Assist by providing necessary equipment, workers, and survey personnel as required.
- D. Measurement Devices:
 - 1. Weigh Scales: Inspected, tested and certified by the applicable state Weights and Measures department within the past year.
 - 2. Platform Scales: Of sufficient size and capacity to accommodate the conveying vehicle.
 - 3. Metering Devices: Inspected, tested and certified by the applicable state department within the past year.
- E. Measurement by Weight: Concrete reinforcing steel, rolled or formed steel or other metal shapes will be measured by handbook weights. Welded assemblies will be measured by handbook or scale weight.
- F. Measurement by Volume: Measured by cubic dimension using mean length, width and height or thickness.
- G. Measurement by Area: Measured by square dimension using mean length and width or radius.
- H. Linear Measurement: Measured by linear dimension, at the item centerline or mean chord.
- I. Stipulated Price Measurement: Items measured by weight, volume, area, or linear means or combination, as appropriate, as a completed item or unit of the Work.
- J. Perform surveys required to determine quantities, including control surveys to establish measurement reference lines. Notify Architect prior to starting work.
- K. Contractor's Engineer Responsibilities: Sign surveyor's field notes or keep duplicate field notes, calculate and certify quantities for payment purposes.
- L. The Owner reserves the right to reject the Contractor's measurement of Work-in-place that involves use of established unit prices and to have this work measured, at the Owner's expense, by an independent surveyor acceptable to the Contractor.

1.05 PAYMENT

- A. Payment for Work governed by unit prices will be made on the basis of the actual measurements and quantities of Work that is incorporated in or made necessary by the Work

and accepted by the Architect, multiplied by the unit price. Contract Sum will be adjusted by Change Order.

- B. Payment will not be made for any of the following:
1. Products wasted or disposed of in a manner that is not acceptable.
 2. Products determined as unacceptable before or after placement.
 3. Products not completely unloaded from the transporting vehicle.
 4. Products placed beyond the lines and levels of the required Work.
 5. Products remaining on hand after completion of the Work.
 6. Loading, hauling, and disposing of rejected Products.

1.06 SCHEDULE OF UNIT PRICES

- A. Item 1: T&G Roof Decking, per 10 lineal feet; Section 06 10 00.
1. Existing roof decking that is damaged or unsuitable for reuse to be replaced with new.

PART 2 PRODUCTS - NOT USED

PART 3 EXECUTION - NOT USED

END OF SECTION

**SECTION 06 10 00
ROUGH CARPENTRY**

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. Tongue and groove decking.

1.02 REFERENCE STANDARDS

- A. ASTM A153/A153M - Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware.
- B. AWPA U1 - Use Category System: User Specification for Treated Wood.
- C. PS 1 - Structural Plywood.
- D. PS 2 - Performance Standard for Wood Structural Panels.
- E. PS 20 - American Softwood Lumber Standard.
- F. WCLIB (GR) - WCLB Standard Grading Rules for West Coast & Imported Softwood Lumber No.18.

1.03 SUBMITTALS

- A. See Section 01 30 00 - Administrative Requirements for submittal procedures.
- B. Product Data: Provide technical data on insulated sheathing, wood preservative materials, and application instructions.
- C. Manufacturer's Certificate: Certify that wood products supplied for rough carpentry meet or exceed specified requirements.

1.04 QUALITY ASSURANCE

- A. In the event of conflicting requirements between applicable codes, regulations, structural notes and the requirements in this Specification, the most stringent requirements apply.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. General: Cover wood products to protect against moisture. Support stacked products to prevent deformation and to allow air circulation.
 - 1. Underlayment: Store in clean, dry, indoor area.

PART 2 PRODUCTS

2.01 GENERAL REQUIREMENTS

- A. Dimension Lumber: Comply with PS 20 and requirements of specified grading agencies.
 - 1. Species: Douglas Fir-Larch, unless otherwise indicated.
 - 2. If no species is specified, provide species graded by the agency specified; if no grading agency is specified, provide lumber graded by grading agency meeting the specified requirements.
 - 3. Grading Agency: Grading agency whose rules are approved by the Board of Review, American Lumber Standard Committee at www.alsc.org, and who provides grading service for the species and grade specified; provide lumber stamped with grade mark unless otherwise indicated.

2.02 EXPOSED BOARDS

- A. Submit manufacturer's certificate that products meet or exceed specified requirements, in lieu of grade stamping.
- B. Lumber Decking, For Replacement of Damaged Roof Decking: See Section 01 22 00 - Unit Prices.
 - 1. Fabricated to AITC 212.
 - 2. Moisture Content: Kiln-dry (15 percent maximum).

3. Species: Douglas Fir-Larch, graded under SPIB (GR) rules.
4. Size: 3 x 6 inches, nominal.
5. Edge: Tongue and groove.

2.03 ACCESSORIES

- A. Fasteners and Anchors:
 1. Metal and Finish: Hot-dipped galvanized steel complying with ASTM A153/A153M for high humidity and preservative-treated wood locations, unfinished steel elsewhere, unless noted otherwise.

2.04 FACTORY WOOD TREATMENT

- A. Treated Lumber and Plywood: Comply with requirements of AWP A U1 - Use Category System for wood treatments determined by use categories, expected service conditions, and specific applications.
 1. Preservative-Treated Wood: Provide lumber and plywood marked or stamped by an ALSC-accredited testing agency, certifying level and type of treatment in accordance with AWP A standards.
- B. Preservative Treatment:
 1. Products:
 - a. Koppers Performance Chemicals, Inc:
www.koppersperformancechemicals.com/#sle.
 - b. Viance, LLC; Preserve ACQ: www.treatedwood.com/#sle.
 - c. Substitutions: See Section 01 60 00 - Product Requirements.
 2. Preservative Pressure Treatment of Lumber Above Grade: AWP A U1, Use Category UC3B, Commodity Specification A using waterborne preservative.
 - a. Kiln dry lumber after treatment to maximum moisture content of 19 percent.
 - b. Treat lumber in contact with roofing, flashing, or waterproofing.
 - c. Treat lumber in contact with concrete.

PART 3 EXECUTION

3.01 INSTALLATION - GENERAL

- A. Select material sizes to minimize waste.
- B. Where treated wood is used on interior, provide temporary ventilation during and immediately after installation sufficient to remove indoor air contaminants.

3.02 FRAMING INSTALLATION

- A. Set structural members level, plumb, and true to line. Discard pieces with defects that would lower required strength or result in unacceptable appearance of exposed members.
- B. Make provisions for temporary construction loads, and provide temporary bracing sufficient to maintain structure in true alignment and safe condition until completion of erection and installation of permanent bracing.
- C. Install structural members full length without splices unless otherwise specifically detailed.
- D. Comply with member sizes, spacing, and configurations indicated, and fastener size and spacing indicated, but not less than required by applicable codes and AWC (WFCM) Wood Frame Construction Manual, whichever is most stringent.

3.03 TOLERANCES

- A. Framing Members: 1/4 inch from true position, maximum.
- B. Variation from Plane, Other than Floors: 1/4 inch in 10 feet maximum, and 1/4 inch in 30 feet maximum.

3.04 FIELD QUALITY CONTROL

- A. See Section 01 40 00 - Quality Requirements for additional requirements.

3.05 CLEANING

- A. Waste Disposal:
 - 1. Comply with applicable regulations.
 - 2. Do not burn scrap on project site.
 - 3. Do not burn scraps that have been pressure treated.
 - 4. Do not send materials treated with pentachlorophenol, CCA, or ACA to co-generation facilities or "waste-to-energy" facilities.
- B. Do not leave wood, shavings, sawdust, etc. on the ground or buried in fill.
- C. Prevent sawdust and wood shavings from entering the storm drainage system.

END OF SECTION