HOT WORK PERMIT

Seek an alternative/safer method if possible!

Before initiating hot work, ensure precautions are in place as required by NFPA 51B and ANSI Z49.1. Make sure an appropriate fire extinguisher is readily available.

This Hot Work Permit is required for any operation involving open flame or producing heat and/or sparks. This work includes, but is not limited to, welding, brazing, cutting, grinding, soldering, thawing pipe, torch-applied roofing, or chemical welding.

Date	Hot work by □ employee □ contractor
Location/Building and floor	Name (print) and signature of person doing hot work
Work to be done Time started Time completed	I verify that the above location has been examined, the precautions marked on the checklist below have been taken, and permission is granted for this work. Name (print) and signature of permit-authorizing individual (PAI)
THIS PERMIT IS GOOD FOR DATE/TIME ABOVE	
Available sprinklers, hose streams, and extinguishers are in service.	rice and operable.
☐ Hot work equipment is in good working condition in accordance w	with manufacturer's specifications.
☐ Special permission obtained to conduct hot work on metal vessels or piping lined with rubber or plastic.	
□ Flammable liquid, dust, lint, and oily deposits removed. □ Explosive atmosphere in area eliminated. □ Floors swept clean and trash removed. □ Combustible floors wet down or covered with damp sand or fire relation of the personnel protected from electrical shock when floors are wet. □ Othercombustible storage material removed or covered with listed fire resistive tarpaulins), metal shields, or noncombustible material all wall and floor openings covered. □ Ducts and conveyors that might carry sparks to distant combustion of the personnel of th	or approved materials (welding pads, blankets, or curtains; rials. ible material covered, protected, or shut down.
Requirements for hot work on enclosed equipment □ Enclosed equipment is cleaned of all combustibles. □ Containers are purged of flammable liquid/vapor. □ Pressurized vessels, piping, and equipment removed from service Requirements for hot work fire watch and fire monitoring □ Fire watch is provided by	and for a minimum of 1 hour after hot work, including any break activity. ractical, a charged small hose.
© 2018 National Fire Protection Association	NFPA 51B

