



Business Office

Post Office Box 2338 - Jackson, Mississippi 39225-2338
rfp@jackson.k12.ms.us or (601) 973-8582

Addendum # 1

DATE: 10/15/2025

FORMAL BID NUMBER/TITLE: Bid 26-3275 Powell Middle School Cafeteria Serving Equipment

BID OPENING DATE/TIME: Tuesday, October 28, 2025 @ 10:00 A.M.

The purpose of this addendum is to inform you of: **Please see updated specifications below.**

JACKSON PUBLIC SCHOOLS: POWELL MIDDLE SCHOOL

ITEM 1 - KOLPAK WALK-IN COOLER/FREEZER (1 REQ'D)

Kolpak Model CUSTOM
Walk-In Cooler/Freezer

ARCHITECTURAL SPECIFICATIONS: KOLPAK WALK-IN COOLER/FREEZER

OVERALL SIZE: 16' 4 1/2" length x 8' 8 1/2" width x 8' 6 1/4" height
Interior dimensions of cooler: 7' 2 1/2" deep by 8' 0 1/2" wide by 7' 10 5/8" high.
Interior dimensions of freezer: 8' 2" deep by 8' 0 1/2" wide by 7' 10 5/8" high.
DOORS CENTERED IN 8' 8 1/2" SIDES. PARTITION TO BE 8' 8 1/2".

UNIT TO BE OUTDOORS, WITH NOMINAL 9' SIDE UP AGAINST OPENING IN BUILDING WALL: TO REPLACE EXISTING WALK-IN IN SAME LOCATION

GENERAL:

Walk-in cooler/freezer provided shall be prefabricated of modular design and construction to allow convenient and accurate field assembly.

PANEL CONSTRUCTION:

Standard wall, ceiling and floor panels shall be 11-1/2", 23", 34-1/2", and 46" in width. corner panels shall be 90 degree angles with actual 12" exterior horizontal measurements.

Panels shall consist of foamed-in-place urethane insulation, sandwiched between interior and exterior metal surfaces, which has been die-formed and gauged for uniformity in size. slab urethane, high density rails or wood shall not be acceptable in any door, wall, or ceiling panel.

Edges of panels shall be foamed-in-place "tongue and groove" with "Posi-Loc" locking assemblies foamed-in-place at time of fabrication.

INSULATION:

Each panel shall be filled with rigid "foamed-in-place" urethane. insulation shall have a 97% closed cell structure, average in-place density of 2.2 lbs. per cubic foot, and compression strength at yield point of 19 lbs. per square inch. Overall thickness shall be 4".

RATINGS AND APPROVALS:

Each 4" panel shall have a thermal conductivity (k factor) of 0.133 btu/hr/sq. Ft. Per degrees Fahrenheit per inch; and an overall coefficient of heat transfer (u factor) of not more than 0.03. The "R" factor shall be 34.

Fire hazard classification according to ASTM E-84 (UL723) shall be a flame spread rating of 25 or less with a certifying

Underwriters Laboratory label attached to every panel showing the meeting of the fire code.

Smoke development rating to be 450 or less; Factory Mutual approved; N.S.F. Listed; and toxicity rated and approved by U.S. Testing.

METAL FINISHES:

Interior ceilings and walls 26 gauge pre-painted white galvalume.

Exterior to be 26 gauge stucco aluminum.

Floors to be .100 smooth aluminum, with 3/16" tread plate in aisle areas

PANEL LOCKING ASSEMBLIES:

Assembly of walk-ins shall be accomplished by "Posi-Loc" locking assemblies, which shall be foamed-in-place and activated by a hex wrench provided by the manufacturer. Access ports shall be on interior to allow assembly of walk-in from the inside and shall be covered by snap caps.

PANEL GASKETS:

Flexible vinyl gaskets shall be foamed-in-place on the interior and exterior edge of the "tongue" rail.

Gaskets shall be impervious to stains, greases, oils and mildew.

ROOF CAP:

Provide and install Durolast vinyl roof cap with all trim to waterproof/weatherproof seal roof cap to walk-in and building wall. Provide sloped foam roof.

DOOR CONSTRUCTION:

The doors shall be flush (in-fitting) type, self-closing with cam-lift hinges and posi-seal (hydraulic, not spring) door closures.

Door hardware shall consist of magnetic gasket, "Posi-Seal" door closure, brushed chrome latch and strap-type, cam-lift hinges. Door latches shall lock and have a safety release to prevent entrapment. One quarter turn of the release handle unlocks the door from the inside. **Three hinges to be provided per door and frame.**

The door jamb frames shall be made of durable fiberglass reinforced plastic (FRP).

The freezer door shall be provided with an isolated, low wattage (5 watts/ft.) Heater wire covered by magnetically attracting stainless steel, fitted onto this jamb and beneath the threshold. This shall provide perfect sealing of magnetic gasket and prevent frost and condensation buildup.

Entrance door sections shall be provided with LED Lamp & Globe 11806LEDGU24KT vapor-proof light, pilot light switch and conduit between switch box and outlet box. Concealed wiring shall be standard on each entrance door section.

Door sizes to be: 34" x 78"

PARTITION:

Fabrication and finish of partition walls shall be the same as the walk-in walls and shall lock into wall, ceiling, and floor panels with "Posi-Loc" locking assemblies. Tongue and groove foam surfaces shall provide the thermal break between cooler and freezer compartments. Wall tee panels shall be 23" x 12" symmetrical tee.

EXTERIOR AND INTERIOR KICKPLATE:

Doors to be provided with 1/8" aluminum diamond treadplate kickplate 36" high on both sides of all doors and door sections.

FLOOR CONSTRUCTION:

Floor skin to be .100 smooth aluminum. Floor panels to be foamed in place, in similar manner to other panels. In addition, floor panels shall contain foamed in place ERA anti delamination brackets. Floor skins are riveted to internal anti delamination brackets, thus providing protection against floor delamination. ERA floor to be rated at 1,000 pounds per square foot uniform load.

TREADPLATE OVERLAY:

Provide 3/16" thick aluminum diamond treadplate in aisles only. Cooler/Freezer to require 46 square feet. Tread Plate to be 3' wide by total of 14' 4" long, through center of walk-in

PRESSURE RELIEF PORT:

A tri-action air vent shall be provided for freezers to equalize pressure between the interior and exterior of the walk-in caused by sudden temperature changes, due to door openings and evaporator defrosting. The vent shall be heated to prevent moisture and/or frost accumulation.

LIGHTING:

Provide, install, and wire a total of one (1) each Light Fixture, Kason 1810LX 48" LED (with Diode Strips) light fixtures in cooler ceiling. Provide, install, and wire a total of two (2) each Light Fixture, Kason 1810LX 48" LED (with Diode Strips) in freezer ceiling.

REFRIGERATION EQUIPMENT:

Condensing units shall be **Kolpak** 120 systems, pre-charged, pre-assembled remote, (UL listed) with 52% larger condenser and oversized receiver for **high efficiency performance**, rated up to 120 degree ambient temperature. All components factory installed including thermostatic expansion valves, solenoid valves, temperature controls, sight glasses, filter driers, and pressure controls. Refrigeration systems to be supplied with crankcase heaters, low ambient controls and weather proof housings. Condensing unit shall be air cooled. Components to be mounted on a heavy gauge steel base.

Evaporator assemblies shall be made of plate type aluminum fins with copper tubes. Fan motors and coil to be housed in a heavy gauge aluminum enclosure. Evaporators to have drain pan with suitable drainpipe fitting. Cooler evaporator to be air defrost. Freezer evaporator shall have an automatic electric defrost system including heaters, time clock, fan delay control and heated drain pan. Defrost shall be time initiated and temperature terminated with built-in fail-safe control.

1 ea KPC225ALZOP-2S

PC225ALZOP-2S, 208-230/60/1, 2-1/4HP, R454A, Pre-Charged, AirCooled, Scroll Low Temp Standard Compressor Unit, Amps: 13.7, Ambient Temperature: 100 Includes Fan Cycle Controls, Amps: 13.7, Ambient Temperature: 100 1 ea KEL26-079-2EC-PR-A EL26-079-2EC-PR-A, 208-230/60/1, R454A, Low Temp, Electric Defrost, Low Profile Unit Cooler, Amps: 14.1

FREEZER:

CONDENSING UNIT:

1 ea KPC225ALZOP-2S

PC225ALZOP-2S, 208-230/60/1, 2-1/4HP, R454A, Pre-Charged, AirCooled, Scroll Low Temp Standard Compressor Unit, Amps: 13.7, Ambient Temperature: 100 Includes Fan Cycle Controls, Ambient Temperature: 100 F

EVAPORATOR COIL:

1 ea KEL26-079-2EC-PR-A

EL26-079-2EC-PR-A, 208-230/60/1, R454A, Low Temp, Electric Defrost, Low Profile Unit Cooler, Amps: 14.0

COOLER:

CONDENSING UNIT:

1 ea KPC50AMZOP-2S

PC50AMZOP-2S, 208-230/60/1, 1/2HP, R454A, Pre-Charged, AirCooled, Scroll Medium Temp Standard Compressor Unit, Amps: 6, Ambient Temperature: 100 Includes Fan Cycle Controls, Ambient Temperature: 100 F

EVAPORATOR COIL:

1 ea KAM16-081-1EC-PR-A

AM16-081-1EC-PR-A, 115/60/1, R454A, Medium Temp, Air Defrost, Low Profile Unit Cooler, Amps: 2.0

VERIFY VOLTAGE, PHASE, AND AMPERAGE ON ALL SYSTEMS WITH OWNER

Cooler to operate at minimum 35 degrees Fahrenheit.

Freezer to operate at minimum of -10 degrees Fahrenheit.

Electrical: VERIFY WITH OWNER

WARRANTIES: EXTENDED PARTS AND LABOR WARRANTY AT NO EXTRA CHARGE:

Panels to be free from defects in material and workmanship under normal use and service for a period of ten years from the date of installation.

Hardware and electrical components are warranted against defects in workmanship under normal use and service for a period of one year from date of installation.

Refrigeration systems to be free from defects in material and workmanship under normal use and service for a period of two years from date on installation to be provided by the manufacturer. An additional 3 year compressor warranty shall be provided.

LABOR:

Two years warranty from installation, to be provided by successful bidder.

INSTALLATION:

Successful bidder to be responsible for installation which shall consist of erecting and leveling of walk-in, piping, charging and testing of refrigeration system.

Successful bidder to be responsible for removal and disposal of all cartons and job associated debris.

All piping of refrigeration systems and coil drain lines to be done in hard drawn copper. All evaporator coils to include "p" trap and risers on suction line. All drain lines in freezer to include heaters. Drain lines to be a minimum of 3/4" o.d. all drain lines to have "p" traps. All refrigerant lines subject to sweating shall be insulated with 3/4" elastomeric thermal insulation. **All panel joints to be caulked and weather sealed inside and out with high grade, non hardening butyl caulk. Walk in floor to be sealed to concrete slab in like manner.**

Owner to provide area outside of building on which to erect walk-in. **Condensing units to be located on top of walk-in, in similar manner, as existing condensing units. Provide rubber isolation pads to prevent damage to roof cap.**

NOTE: Owner may allow condensing units to be on ground level in close proximity to walk-in. VERIFY WITH OWNER.

Owner will also provide necessary power to disconnects within 8 feet of condensing units. Successful bidder to be responsible for electrical work from disconnects to condensing units, control wiring, lighting, etc.

It is the responsibility of all bidders, prior to submitting bid, to visit job site making themselves aware of all job conditions, physical dimensions and verify voltage / phase of electrical.

Successful bidder to be responsible for all field dimensioning of walk-in, refrigeration line runs, etc. in accordance with best practices.

QUANTUM COOLER/FREEZER SHELVING/DUNNAGE PACKAGE (1 REQ'D)

TO CONSIST OF:

COOLER SHELVING/DUNNAGE RACKS

1-ea DUNNAGE RACK, VENTED

Quantum Model QFSD-2248 Dimensions: 12(h) x 48(w) x 22(d)

Dunnage Rack, polymer, ventilated top, 48"W x 22"D x 12"H, 4,000 lb. capacity, plastic

1 ea Lifetime warranty

1-ea SHELVING UNIT, PLASTIC WITH METAL POSTS

Quantum Model WR74-2448WPM Dimensions: 74(h) x 48(w) x 24(d)

Wire Plastic Mat Shelving Unit, stationary, 4-tier, 48"W x 24"D x 74"H overall size, 600-800 lb. max weight, includes, (4) plastic wire mats, (4) wire frames, (4) posts, & packs of split sleeves, green epoxy antimicrobial coating, NSF, KD

2-ea SHELVING UNIT, PLASTIC WITH METAL POSTS

Quantum Model WR74-2436WPM Dimensions: 74(h) x 36(w) x 24(d)

Wire Plastic Mat Shelving Unit, stationary, 4-tier, 36"W x 24"D x 74"H overall size, 600-800 lb. max weight, includes, (4) plastic wire mats, (4) wire frames, (4) posts, & packs of split sleeves, green epoxy antimicrobial coating, NSF, KD

FREEZER SHELVING/DUNNAGE RACKS

3-ea DUNNAGE RACK, VENTED

Quantum Model QFSD-2248 Dimensions: 12(h) x 48(w) x 22(d)

Dunnage Rack, polymer, ventilated top, 48"W x 22"D x 12"H, 4,000 lb. capacity, plastic

1 ea Lifetime warranty

2-ea SHELVING UNIT, PLASTIC WITH METAL POSTS (6 kt REQ'D)

Quantum Model WR74-2448 WPM Dimensions: 74(h) x 48(w) x 24(d)

Wire Plastic Mat Shelving Unit, stationary, 4-tier, 48"W x 24"D x 74"H overall size, 600-800 lb. max weight, includes, (4) plastic wire mats, (4) wire frames, (4) posts, & packs of split sleeves, green epoxy antimicrobial coating, NSF, KD

ERECT AND PLACE ALL SHELVING/DUNNAGE IN COOLER AND FREEZER PER OWNER'S INSTRUCTIONS.

ITEM 2 - QUANTUM DRY STORAGE SHELVING/DUNNAGE PACKAGE (1 REQ'D)

TO CONSIST OF:

SHELVING UNIT, PLASTIC WITH METAL POSTS (5 kt REQ'D)

Quantum Model WR74-2460WPM Dimensions: 74(h) x 60(w) x 24(d)

Wire Plastic Mat Shelving Unit, stationary, 4-tier, 60"W x 24"D x 74"H overall size, 600-800 lb. max weight, includes, (4) plastic wire mats, (4) wire frames, (4) posts, & packs of split sleeves, green epoxy antimicrobial coating, NSF, KD

SHELVING UNIT, PLASTIC WITH METAL POSTS (3 kt REQ'D)

Quantum Model WR74-2448WPM Dimensions: 74(h) x 48(w) x 24(d)

Wire Plastic Mat Shelving Unit, stationary, 4-tier, 48"W x 24"D x 74"H overall size, 600-800 lb. max weight, includes, (4) plastic wire mats, (4) wire frames, (4) posts, & packs of split sleeves, green epoxy antimicrobial coating, NSF, KD

SHELVING UNIT, PLASTIC WITH METAL POSTS (1 kt REQ'D)

Quantum Model WR74-2436WPM Dimensions: 74(h) x 36(w) x 24(d)

Wire Plastic Mat Shelving Unit, stationary, 4-tier, 36"W x 24"D x 74"H overall size, 600-800 lb. max weight, includes, (4) plastic wire mats, (4) wire frames, (4) posts, & packs of split sleeves, green epoxy antimicrobial coating, NSF, KD

SHELVING UNIT, PLASTIC WITH METAL POSTS (2 kt REQ'D)

Quantum Model WR74-2454WPM Dimensions: 74(h) x 54(w) x 24(d)

Wire Plastic Mat Shelving Unit, stationary, 4-tier, 54"W x 24"D x 74"H overall size, 600-800 lb. max weight, includes, (4) plastic wire mats, (4) wire frames, (4) posts, & packs of split sleeves, green epoxy antimicrobial coating, NSF, KD

SHELVING UNIT, PLASTIC WITH METAL POSTS (1 kt REQ'D)

Quantum Model WR74-2442WPM Dimensions: 74(h) x 42(w) x 24(d)

Wire Plastic Mat Shelving Unit, stationary, 4-tier, 42"W x 24"D x 74"H overall size, 600-800 lb. max weight, includes, (4) plastic wire mats, (4) wire frames, (4) posts, & packs of split sleeves, green epoxy antimicrobial coating, NSF, KD

DUNNAGE RACK, VENTED (6 REQ'D)

Quantum Model QFSD-2248 Dimensions: 12(h) x 48(w) x 22(d)

Dunnage Rack, polymer, ventilated top, 48"W x 22"D x 12"H, 4,000 lb. capacity, plastic
6 ea Lifetime warranty

ERECT AND PLACE ALL SHELVING/DUNNAGE IN COOLER AND FREEZER PER OWNER'S INSTRUCTIONS.

ITEM 3 - NUGGET ICE MAKER (1 REQ'D)

Ice-O-Matic Model GEM0450A Dimensions: 32(h) x 24(w) x 27(d)

Pearl Ice® Maker, soft, chewable ice crystals, air-cooled, self-contained condenser, approximately 464 lb/210 kg production/24 hours, durable stainless finish, cULus, NSF, CE

ICE BIN (1 REQ'D)

Ice-O-Matic Model B40PS Dimensions: 39(h) x 33(w) x 34(d)

Ice Bin, 344 lb storage capacity, 30"W x 31"D x 37-1/2"H, top-hinged, slope front door, for top-mounted ice maker, polyethylene interior, durable aluminum exterior, 6" legs, NSF

WATER FILTRATION SYSTEM (1 REQ'D)

Ice-O-Matic Model IFQ1 Dimensions: 15(h) x 6(w) x 4(d)

Water Filter Manifold, single filter designed for ice makers producing up to 800 lbs. (363.6 Kg.) of ice per day, 1.5 gpm maximum flow rate, IsoNet® scale inhibitor, .5 micron particle reduction, quick connect fittings (water filters must be changed every 180 days (6 months), at a minimum)

ITEM 4 - PLANETARY MIXER (1 REQ'D)

Hobart Model HL200-1

100-120/50/60/1; Bench type mixer; without attachments; US/EXP configuration - Legacy Planetary Mixer - Unit Only, Bench, 20 quart, (3) fixed speeds plus stir speed, gear-driven transmission, 15-minute SmartTimer™, #12 taper hub, manual bowl lift, stainless steel bowl guard, 1/2 hp, cord with plug

- | | |
|------|--|
| 1 ea | Standard warranty - 1-Year parts, labor & travel time during normal working hours within the USA |
| 1 ea | Model BOWL-HL20P Legacy® Mixer Bowl, 20 quart, stainless steel |
| 1 ea | Model BBEATER-HL20 Legacy® Mixer 20 quart,"B" flat beater, aluminum |
| 1 ea | Model DWHIP-HL20 Legacy® Mixer 20 quart "D" wire whip, stainless steel |
| 1 ea | Model EDDOUGH-HL20 Legacy® Mixer 20 qt. "ED" dough arm, aluminum |

ITEM 5 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)

AERO Manufacturing Model 2TSBX-30120

Dimensions: 39(h) x 120(w) x 30(d)

Premium Work Table, 120"W x 30"D x 39"H, 14/304 stainless steel top reinforced with (3) galvanized steel box channels, 4"H backsplash, sound deadened underside, galvanized steel gussets, 16/304 stainless steel legs with side & rear cross bracing, adjustable white metal feet, Aero Hemmed Safety Edge™, shipped KD, NSF

- | | |
|------|--|
| 2 ea | Model T-118 Delux™ drawers, stainless steel face & pan, 15" x 20", roller bearing slides (drawer pan is not removable) |
| 1 ea | Model CUSTOM Undershelf installed under the left side of the table |

ITEM 6 - INGREDIENT BIN (3 REQ'D)

Cambro Model IBS27148 Dimensions: 28(h) x 16.31(w) x 29.63(d)

Ingredient Bin, mobile, 27 gallon capacity, 1-pc seamless polyethylene bin, 2-pc sliding polycarbonate lid, scoop holder included (scoop sold separately), (4) 3" heavy duty casters (2 front swivel, 2 fixed), white with clear cover, NSF, Made in USA

ITEM 7 - SHELVING, WALL MOUNTED (1 REQ'D)

AERO Manufacturing Model 2W-1896 Dimensions: 1.5(h) x 96(w) x 18(d)

Aerospec™ Shelf, wall-mounted, 96"W x 18"D x 12-1/2"H, 14/304 stainless steel construction, 1-1/2" lip on sides & rear, 3/4" radius rolled front edge, stainless steel brackets, Aero Hemmed Safety Edge™, NSF, KD

ITEM 8 - HAND SINK (1 REQ'D)

AERO Manufacturing Model HSB Dimension: 17(w) x 15(d)

Hand Sink, wall mount, 14" wide x 10" front-to-back x 5" deep, stainless steel construction, 8" splash on back, pedestal base with foot pedals, gooseneck splash mount spout, basket, NSF

ITEM 9 - CAN OPENER (1 REQ'D)

Edlund Model S-11

Can Opener, manual, 16" bar length, dishwasher safe, rust proof, stainless steel, with cast stainless steel base, NSF certified

ITEM 10 - SPARE NUMBER

ITEM 11 - CAN OPENER (1 REQ'D)

Edlund Model 266/115V

Can Opener, electric, single speed, recommended usage is up to 75 cans per day, 115v/60/1-ph, 4 AMPS

1 ea 1 year limited warranty, standard

1 ea New Age Model 1331 Bun Pan Rack, mobile, full height, end loading, open sides, accommodates (20) 18" x 26" pans, slides on 3" centers, all welded aluminum construction, (4) 5" platform casters, NSF, Made in USA, (standard factory lead time)

1 ea New Age Lifetime warranty against rust & corrosion, 5 year workmanship and material defects warranty, standard

1 ea New Age 5" platform type casters, std.

ITEM 12 - SHELVING, WALL MOUNTED (1 REQ'D)

AERO Manufacturing Model 2W-18120 Dimensions: 1.5(h) x 120(w) x 18(d)

Aerospec™ Shelf, wall-mounted, 120"W x 18"D x 12-1/2"H, 14/304 stainless steel construction, 1-1/2" lip on sides & rear, 3/4" radius rolled front edge, stainless steel brackets, Aero Hemmed Safety Edge™, NSF, KD

ITEM 13 - FOOD PROCESSOR, BENCHTOP / COUNTERTOP (1 REQ'D)

Edlund Model VARICUT Dimensions: 26.44(h) x 14.87(w) x 10.94(d)

Edlund Varicut VC-500 ADJ DISC Continuous Feed Food Processor, 7 in one adjustable blade, 5/32" grating/shredding disc, 3/8" dicing kit with cleaning tool, and 1/4" julienne disc. 120 V , 6 AMPS

ITEM 14 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)

AERO Manufacturing Model 2TSB-30120 Dimensions: 39(h) x 120(w) x 30(d)

Premium Work Table, 120"W x 30"D x 39"H, 14/304 stainless steel top reinforced with (3) galvanized steel box channels, 4"H backsplash, sound deadened underside, 18/430 stainless steel adjustable undershelf, galvanized steel gussets, 16/304 stainless steel legs with adjustable white metal feet, Aero Hemmed Safety Edge™, shipped KD, NSF

2 ea Model T-118 Delux™ drawers, stainless steel face & pan, 15" x 20", roller bearing slides (drawer pan is not removable)

WELD-IN SINK (1 REQ'D)

AERO Manufacturing Model T-103 Dimensions: 20(w) x 20(d)

Weld-In Sink, one compartment, 20" x 20" x 14" deep, NSF

1 ea Model T-115 Twist type, 2", lever waste

WALL / SPLASH MOUNT FAUCET (1 REQ'D)

T&S Brass Model B-0231

Sink Mixing Faucet, wall mount, 8" centers, 12" swing nozzle, lever handles, quarter-turn Eterna cartridges, 1/2" NPT female inlets, low lead, ADA Compliant

ITEM 15 - TWO (2) COMPARTMENT SINK (1 REQ'D)

AERO Manufacturing Model 2F2-2020-24LR Dimensions: 42.5(h) x 91(w) x 26(d)

Aerospec™ Sink, two compartment, 91"W x 26"D x 42-1/2"H, 14/304 stainless steel construction, (2) 20" x 20" x 14" deep fabricated compartments, 24" drainboards on left & right, 10"H backsplash, 8" OC splash mount faucet holes, raised rolled edges on front & sides, fully welded stainless steel gussets, 16/304 stainless steel legs with front & side cross bracing, adjustable stainless steel feet, Aero Hemmed Safety Edge™, KD, NSF

2 ea Model S-20 2" Twist type lever waste

WALL / SPLASH MOUNT FAUCET (1 REQ'D)

T&S Brass Model B-0231

Sink Mixing Faucet, wall mount, 8" centers, 12" swing nozzle, lever handles, quarter-turn Eterna cartridges, 1/2" NPT female inlets, low lead, ADA Compliant

ITEM 16 - SHELVING, WALL MOUNTED (1 REQ'D)

AERO Manufacturing Model 2W-1884 Dimensions: 1.5(h) x 84(w) x 18(d)

Aerospec™ Shelf, wall-mounted, 84"W x 18"D x 12-1/2"H, 14/304 stainless steel construction, 1-1/2" lip on sides & rear, 3/4" radius rolled front edge, stainless steel brackets, Aero Hemmed Safety Edge™, NSF, KD

ITEM 17 - BUN / SHEET PAN RACK (6 REQ'D)

New Age Model 1331 Dimensions: 69.75(h) x 20.38(w) x 26(d)

Bun Pan Rack, mobile, full height, end loading, open sides, accommodates (20) 18" x 26" pans, slides on 3" centers, all welded aluminum construction, (4) 5" platform casters, NSF, Made in USA, (standard factory lead time)

ITEM 18 - WORK TABLE (2 REQ'D)

AERO Manufacturing Model 2TSS-2496 Dimensions: 37.75(h) x 96(w) x 24(d)

Premium Work Table, 96"W x 24"D x 37-3/4"H, 14/304 stainless steel top reinforced with (2) galvanized steel box channels, 2-3/4"H backsplash, sound deadened underside, 18/430 stainless steel adjustable undershelf, galvanized steel gussets, 16/304 stainless steel legs with adjustable white metal feet, Aero Hemmed Safety Edge™, shipped KD, NSF

4 ea Model T-118 Delux™ drawers, stainless steel face & pan, 15" x 20", roller bearing slides (drawer pan is not removable)

ITEM 19 - SHELVING, WALL MOUNTED (2 REQ'D)

AERO Manufacturing Model 2W-1896 Dimensions: 1.5(h) x 96(w) x 18(d)

Aerospec™ Shelf, wall-mounted, 96"W x 18"D x 12-1/2"H, 14/304 stainless steel construction, 1-1/2" lip on sides & rear, 3/4" radius rolled front edge, stainless steel brackets, Aero Hemmed Safety Edge™, NSF, KD

ITEM 20 - SPARE NUMBER

ITEM 21 - HD RANGE, 34", 6 OPEN BURNERS (1 REQ'D)

Garland Model M43S Dimensions: 34(w) x 38(d)

Master Series Heavy Duty Range, gas, 34", (6) 24,000 BTU two-piece Starfire burners, removable heads, storage base, drip tray, aluminized steel interior, stainless steel front & sides, 6" chrome steel adjustable legs, 144,000 BTU, CSA Flame, CSA Star, NSF (Garland)

1 ea Two year limited parts and labor warranty, covers products purchased and installed in the USA only, standard

1 ea Master Series Single High Shelf, 22-1/2" H, 34" W, stainless steel

1 ea Natural gas, specify elevation if over 2,000 ft

- 1 ea 3/4" Rear gas connection, including "Tee" in manifold, end cap & cover (Consult spec sheet and specify)
- 1 kt Dormont Model 1675KIT48 Dormont Blue Hose™ Moveable Gas Connector Kit, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) full port valve, (2) 90° elbows, coiled restraining cable with hardware, 180,000 BTU/hr minimum flow capacity, limited lifetime warranty
- 1 ea Model M17SD Master Series Single High Shelf, 22-1/2" H, 17" W, stainless steel (Garland)

ITEM 22 - GAS FLOOR FRYER (1 REQ'D)

Frymaster/Dean Model 11814GF Dimensions: 47.75(h) x 20(w) x 33.13(d)

Frymaster® Fryer, gas, floor model, 63 lb. oil capacity, 18" x 14" cooking area, filtration system, oil conserving, tube-type design, electronic ignition, includes: rack-type basket supports, basket hangers, (3) twin baskets, stainless steel frypot, door & cabinet sides, 119,000 BTU, cCSAus, CSA Flame, CSA Star, CE, NSF, ENERGY STAR®

- 1 ea Digital Timer controller
- 1 ea 120v/60/1-ph, 9 amps (controller/filter), plug & cord
- 1 ea External oil discharge (front option), available on built-in filter batteries of two more frypots or a frypot/spreader, front connection comes with 5' washdown hose
- 1 bx Model 8030002 Frymaster®/Dean® Filter Powder, box of 80, 1 ounce packs
- 1 bx Model 8030289 Frymaster®/Dean® Filter Paper, 22" x 34", for 50/60UFF equipped, box of 100 sheets
- 1 ea 6" casters (set of 4), standard
- 1 kt Dormont Model 1675KIT48 Dormont Blue Hose™ Moveable Gas Connector Kit, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) full port valve, (2) 90° elbows, coiled restraining cable with hardware, 180,000 BTU/hr minimum flow capacity, limited lifetime warranty

ITEM 23 - MOBILE HEATED CABINET (2 REQ'D)

FWE / Food Warming Equipment Co., Inc. Model UHS-12 Dimensions: 69.5(h) x 32.75(w) x 33.5(d)

Quick Ship - Heated Cabinet, mobile, (12) universal tray slides, (12) 18" x 26" or (24) 12" x 20" pan capacity, 4-1/2" OC, adjustable on 1-1/2" increments, Humi-temp heat & humidity system, adjustable thermostat, individual controls, insulated, removable humidifier pan, (1) flush mounted door, edgemount door latch, push bar handles, wraparound bumper, stainless steel interior & exterior, 5" casters (2) rigid & (2) swivel with brakes, NSF, cULus, UL, IPX4, ENERGY STAR®

- 2 ea Two year limited parts & one year labor warranty, standard
- 2 ea 120v/50/60/1-ph, 11.0 amps, 1315 watts, NEMA 5-15P, standard (US)
- 2 ea Manual Control, standard

ITEM 24 - CONVECTION OVEN, GAS (2 REQ'D)

Garland Model MCO-GD-10-S Dimensions: 57.5(h) x 38(w) x 44.5(d)

Master Series Convection Oven, gas, single-deck, deep depth 43", (2) speed fan, Master 200 solid state controls with 1 hour timer, electric ignition, (2) speed fan, dependent 60/40 doors with windows, stainless steel front, sides & top, porcelain cavity, 24" cooking cavity height, with (6) chrome plated oven racks on 13-position rack guides, 25-1/2" legs, 80,000 BTU (Garland), UL, cUL, NSF

- 2 ea (2) year limited parts & (1) year labor warranty, Door warranty (5) year limited parts except window, covers products purchased and installed in the USA & Canada only, standard
- 2 ea Natural gas
- 2 ea Upgrade to 80,000 BTU
- 2 ea 120v/60/1-ph, 9.8 amps each, NEMA 5-15P (3/4 HP motor), standard
- 2 ea Stainless steel removable drip pan, one per deck
- 2 ea Stainless steel enclosed back, standard
- 2 kt Dormont Model 1675KIT48 Dormont Blue Hose™ Moveable Gas Connector Kit, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) full port valve, (2) 90° elbows, coiled restraining cable with hardware, 180,000 BTU/hr minimum flow capacity, limited lifetime warranty

ITEM 25 - CONVECTION STEAMER, GAS, BOILERLESS (1 REQ'D)**Cleveland Range Model (2) 22CGT66.1** Dimensions: 74.31(h) x 25.5(w) x 38.93(d)

SteamChef™ 6 Convection Steamer, Gas, boilerless, double stacked, on equipment stand 113130GC, (6) full size pan capacity per compartment, SureCook controls, easyTimer 90-minute timer with dial and LED digital readout in minutes and seconds, includes SureCook load compensating thermostat, manual cooking mode and descale indicator, left-hand hinged door, controls on right, automatic drain & water level controls, KleanShield™ interior, standard treated & tap water connection, stainless steel exterior, 4" adjustable legs with flanged feet, (2) 32,000 BTU, UL, NSF, ENERGY STAR®

- 1 ea Extended warranty, not to exceed 24 months from date of installation (for K-12 schools only)
- 2 ea 3 year Convection Steamer Door Warranty, standard
- 1 ea Low Stand for stacking
- 1 ea Performance start-up included at customer request after equipment is installed (Free Water Quality Check included) (contact Cleveland Sales Representative for details)
- 1 ea Natural Gas
- 2 ea (2) 120v/60/1-ph, 4.0 amps each, standard
- 1 kt Model FLT0040-KIT Water Treatment Filtration Kit, with cartridge replacements - Includes: (1) FLT0040 Water Filter System with (3) FLT0014 Cartridges & (3) FLT0018 Cartridges
- 1 ea Second year limited warranty on water related parts only when purchasing a steamer and filter from Cleveland. Must include a completed Performance Start-Up (See Cleveland warranty statement for details)
- 2 kt Dormont Model 1675KIT48 Dormont Blue Hose™ Moveable Gas Connector Kit, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) full port valve, (2) 90° elbows, coiled restraining cable with hardware, 180,000 BTU/hr minimum flow capacity, limited lifetime warranty

ITEM 26 - TILTING SKILLET BRAISING PAN, GAS (1 REQ'D)**Cleveland Range Model SGL40TR** Dimensions: 42(h) x 48(w) x 40(d)

DuraPan™ Tilting Skillet, gas, 40-gallon capacity, modular open base, standard with hydraulic hand tilt with quick lowering feature, stainless steel construction, includes spring-assisted cover, gallon markings and electronic spark ignition, stainless steel level adjustable feet, 130,000 BTU, CE, NSF, IPX6

- 1 ea Extended Warranty, not to exceed 36 months from date of installation (K-12 Schools only)
- 1 ea 10 Year Pan warranty (K-12 Schools only)
- 1 ea Performance start-up included at customer request after equipment is installed (Free Water Quality Check included) (contact Cleveland Sales Representative for details)
- 1 ea Natural Gas
- 1 ea 120v/60/1-ph, 1.8 amps NEMA 5-15P, standard
- 1 ea Model TD2SK 2" tangent draw-off valve, front mounted left side (Note: May require additional lead time, contact factory)
- 1 ea Model PCS Pan Carrier, for floor models
- 1 ea Model DKFS Double Pantry Skillet Filler, with 60" hose
- 1 ea Model FBSTR Faucet Bracket for R series floor model skillets
- 1 kt Dormont Model 1675KIT48 Dormont Blue Hose™ Moveable Gas Connector Kit, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) full port valve, (2) 90° elbows, coiled restraining cable with hardware, 180,000 BTU/hr minimum flow capacity, limited lifetime warranty

ITEM 27 - COMMERCIAL WASTE CONTAINER (6 REQ'D)**Quantum Model CTC-44**

Crusader Round Heavy-duty Utility Container, 44 Gallon, 24" Dia. x 31-1/2" H, Polyethylene, NSF, Made in USA

- 3 ea Model CTC-L44 Crusader Round Heavy-duty Utility Container Lid, 24" Dia., for 44 Gallon trash can, Polyethylene, NSF, Made in USA
- 1 ea Model CTC-DLY Crusader Quiet Dolly, 1,000 lb. load capacity, contains 5 swivel 3" x 1" thermoplastic rubber casters

ITEM 28 - HAND SINK (2 REQ'D)

BY OWNER, NO BID

ITEM 29 - SHELVING UNIT (3 REQ'D)

Quantum Model WR74-2448WPM
Shelving Unit

ITEM 30 - SPARE NUMBER

ITEM 31 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)

AERO Manufacturing Model 2TSB-3048 Dimensions: 39(h) x 48(w) x 30(d)

Premium Work Table, 48"W x 30"D x 39"H, 14/304 stainless steel top reinforced with (3) galvanized steel box channels, 4"H backsplash, sound deadened underside, 18/430 stainless steel adjustable undershelf, galvanized steel gussets, 16/304 stainless steel legs with adjustable white metal feet, Aero Hemmed Safety Edge™, shipped KD, NSF

ITEM 32 - REACH-IN REFRIGERATOR (1 REQ'D)

Delfield Model DSLR2-G Dimensions: 83.85(h) x 51.89(w) x 33.42(d)

DSL Refrigerator, Reach-In, two-section, 44.57 cubic feet capacity, top-mounted self-contained refrigeration system, (2) full-height hinged glass doors (locking), (6) adjustable wire shelves, 4.3" easyTouch® screen temperature display/control with remote monitoring, LED interior lighting, pilaster with shelf clips, stainless steel exterior front, sides & interior, (4) 6" adjustable stainless steel legs, R290 Hydrocarbon refrigerant, 1/3 HP, 115v/60/1-ph, 6.5 amps, NEMA 5-15P, UL, UL Sanitation

6-ea Additional shelves, three per section

ITEM 33 - REACH-IN HEATED CABINET (1 REQ'D)

Delfield Model DSLH2-G Dimensions: 83.85(h) x 51.89(w) x 33.42(d)

DSL Heated Cabinet, Reach-In, two-section, 46.5 cubic feet capacity, (2) full-height hinged glass doors (locking), (6) adjustable wire shelves, 4.3" easytouch® screen temperature display/control with remote monitoring, stainless steel exterior front, sides & interior, (4) 6" adjustable stainless steel legs, 208-240v/60/1-ph, 13 amps, NEMA 6-20P, UL, UL Sanitation

6-ea Additional shelves, three per section

ITEM 34 - MILK COOLER (1 REQ'D)

True Mfg. - General Foodservice Model TMC-34-S-DS-SS-HC dimensions: 41.63(h) x 34(w) x 33(d)

mobile milk cooler, forced-air, (8) 13" x 13" x 11-1/8" crate capacity, dual sided stainless steel drop front/hold-open flip-up lids with locks, 33 - 38°F temperature range, (2) heavy-duty floor racks, digital thermometer, stainless exterior, stainless steel interior & floor, 4" castors, r290 hydrocarbon refrigerant, 1/5 hp, 115v/60/1-ph, 2.7 amps, nema 5-15p, culus, ul eph classified, made in usa, energy star®

1 ea 7 year compressor warranty, 7 years parts warranty, 7 year labor warranty, standard.

1 ea self-contained refrigeration standard

1 ea 4" casters, standard

ITEM 35 - DELFIELD MODEL SH-3-NU (1 REQ'D)

Shelley Custom Fabrication Sh-3-Nu Custom Length Three Well Hot Food Counter, 36 Inches High, 51" Long, 51" S/S V-Tray Slide 12" Wide With 3 Ribs, Located On Customer Side, Mounted 34" High, 51" S/S Workshelf 8" Wide, Located On Operator Side, Mounted 36" High, 50" Recessed Wells For 18x26" Sheet Pans, Line-Up Interlock, Laminate Finish, Verify Color, Flexishield Factory Installed To Base, Sg23 Stainless Steel Toe Plates, On Customer Side Only
Provide Open Rear Under storage. Supply Counter with NEMA 14-20p Cord and Plug. 14.4 Amps

1-ea

Model 000-Cca13xre6 Shelley Custom Fabrication Glass Front Food Flexishield, Single Tier With Glass Shelf, Single Service 50 Inches Long X 16 Inches Wide With Glass Shelf, With Led Light On First Tier. DCSFSF Three Way Style.

ITEM 36 - DELFIELD MODEL SCSC-50-NUP (1 REQ'D)

Shelley Custom Fabrication Scsc-50-Nup Custom Length 46" Cold Pan Counter, 7" Deep Cold

Pan, R290 36 Inches High, 46" S/S V-Tray Slide 12" Wide With 3 Ribs, Located On Customer Side, Mounted 34" High, 46" S/S Workshelf 8" Wide, Located On Operator Side, Mounted 36" High, Line-Up Interlock, Laminate Finish , Verify Color, Flexishield Factory Installed To Base, Sg23 Stainless Steel Toe Plates, On Customer Side Only , Sg33g, Recessed Wells For 18x26" Sheet Pans. Modify 7" Cold Pan To Be Recessed For Sheet Pans With 1" Indention, 35.25" By 25.12", Exact Dimensions , To Hold Exactly Two Each 18 By 26 Sheet Pans.

Rated At 120v/60/1-Ph, 7.0 Amps, Cord With Nema 5-15p Plug.

Provide Open Rear Under storage.

- 1 ea. Model w00007an 7 Year Compressor Warranty, Standard
- 1 ea Model 0550000n Warranty, 2yr, S/L, No Charge
- 1 ea Model 000-Cca13xre5 Shelley Custom Fabrication Double Tier, Fixed Sneeze Guard Front, Single Service
47.378 Inches Display Long X 14 Inches Wide With Glass Shelves,
With Led Light On Both Tiers, DCSFH Fixed Glass Two Tier Style

ITEM 37 - DELFIELD MODEL SC-60-NU, (1 REQ'D)

Shelley Custom Fabrication, Sc-60-Nu, All Purpose Counter, 36 Inches High, 60" S/S V-Tray Slide 12" Wide With 3 Ribs, Located On Customer Side, Mounted 34" High, 60" S/S Workshelf 8" Wide, Located On Operator Side, Mounted 36" High, Line-Up Interlock, Laminate Finish , Verify Color, Sg23 Stainless Steel Toe Plates, On Customer Side Only, Provide Open Rear Under storage.

- 2 Ea Provide Two Ea Grommated Holes In Countertop Per Owner's
Instruction For Cord Passages
- 2-Ea Outlets In Side Of Understorage Area
To Accommodate Items 5a And 6a
- 1-Ea NEMA 14-20 Cord And Plug Interwired To Outlets To Accommodate Electrical Requirements For
Items 39 And 41

ITEM 38 - MERCHANDISER, HEATED, FOR MULTI-PRODUCT (1 REQ'D)

Hatco Model Grsds-30d dimensions: 32.4(h) x 30 w) x 24.29(d)

Glo-ray® merchandising warmer, countertop, 30" long, (12) rods, pass thru design, with (2) shelves, forward-slanted shelves, pre-focused infrared top heat, tempered glass sides, stainless steel & aluminum construction, 4" legs, 1530 watts, cULus, UL EPH classified, made in usa

- 1 ea one year on-site parts & labor warranty, plus one additional year parts only warranty on
all glo-ray metal sheathed elements
- 1 ea **120v/60/1-ph, 1530 watts, 12.8 amps, NEMA 5-15p cord and plug**
- 1 ea model black designer housing color
- 1 ea open customer side, upper, standard
- 1 ea open customer side, lower, standard

ITEM 38 TO SIT ON ITEM 37

ITEM 39 TO BE BY OWNER

ITEM 39 FROZEN DRINK MACHINE, NON-CARBONATED, BOWL TYPE (1 REQ'D)

Bunn Model 58000.0010 Dimensions: 32.4(H) X 16.6(W) X 26.4(D)

58000.0000 Ultra® Nx Frozen Beverage Dispenser, Countertop, Pull & Hold Dispense, (2) 3 Gallon (11.4 Liter) Bowls, Led Lighted Hopper Lids, Independently Controlled Rotating Augers, Low Product Alert, Quick Defrost Feature, Bunnlink Compatible, R290 Hydrocarbon Refrigerant, Black Finish, 120v/60/1-Ph, 12 Amps, Cord, Nema 5-15p, Etlus, Nsf

ITEM 39 TO SIT ON ITEM 37

ITEM 40 - SPARE NUMBER

ITEM 41 - DELFIELD MODEL SCS-30 , CASHIER'S COUNTER (1 REQ'D)

Shelley Custom Fabrication SCS-30 , Cashier's Counter, 48"Custom Length 36 Inches High, 48" S/S V-Tray Slide 12" Wide With 3 Ribs Located On Customer Side 34" High, Line-Up Interlock, Laminate Finish Verify Color, Sg23 Stainless Steel Toe Plates, On Customer Side Only. 18" Top Extension. Provide 120 V, 15amp Duplex Outlet With 10 Amp Breaker.

ITEM 42 - ICE CREAM NOVELTY MERCHANDISER (1 REQ'D)

Excelence Model Vb-2hc Dimensions: 28 ½ W X 27 3/8 D X 33 ½ H

Novelty Case, 6.02 Cu. Ft. Capacity, Angled Top Design, (2) Removable Glass Lids, Lid Locks & Keys, (2) Removable Baskets, Adjustable Thermostat Control, Integrated Tag Molding, Led Lighting, Drain Plug, Maintenance-Free Condenser, Pre-Painted White Steel Cabinet Finish, 2" Casters, R290 Hydrocarbon Refrigerant, 1/5 Hp, Etl-Sanitation, Cetlus

1 Ea 1 Year Parts & Labor And 5 Years On Leaks And Compressor Warranty 1 Ea 120v/60/1-Ph, 3.0 Amps, Cord With Nema 5-15p Cord And Plug

TO SIT BESIDE CASHIER STAND ITEM 41

ITEM 43 - HAND SINK (1 REQ'D)

AERO Manufacturing Model HSB Dimension: 17(w) x 15(d)

Hand Sink, wall mount, 14" wide x 10" front-to-back x 5" deep, stainless steel construction, 8" splash on back, pedestal base with foot pedals, gooseneck splash mount spout, basket, NSF

ITEM 44 - VORTEX WASH SYSTEM (1 REQ'D)

Champion Model L-R 48W

Vortex Wash System

Dish Room Area - VORTEX POWER WASH SINK SYSTEM (1 REQUIRED)

Bi-Line Systems, Inc Model VWS180LR. Dimensions: 45(h) x 216(w) x 34.75(d)

Vortex Power Wash Sink System, 9 1/2"H x 2-1/2"D backsplash or 1 1/2" rolled edge where indicated, twist handle drains on wash, rinse & sanitizer tanks, rear discharge with removable strainer plates, inherent motor overload protection with manual reset, low water protection for wash pump motor, (1) stainless steel 3 hp wash pump motor with sealed bearings & impeller, 5000 watt tank heater, 14/304 polished stainless steel construction, stainless steel legs with cross rails & adjustable bullet feet, NSF, cETLus (consult factory for price)

1 ea 1 year parts & labor warranty on pump, heater and controls, standard

1 ea Left-to-Right operation

1 ea Voltage to be 208 V, three phase, rated at 23 amps

1 ea 1-1/2" Rolled edge on edges not against walls

1 ea 48" Scrap/Soiled Table

1 ea 24" Scrap sink

2 ea Scrap Baskets

1 ea 13" Control apron

1 ea 48" Wash tank with maintenance heater

1 ea 24" Rinse sink with cover

1 ea 24" Sanitizer sink with cover

3 ea Wall / Splash Mount Faucet T&S Brass Model B-0291

1 ea 1/2" pre-rinse sprayer

1 ea (3) Twist lever drains

1 ea Utensil basket (0710179)
1 ea Sheet pan racking system (339718)
1 ea 36" Clean drain board

ITEM 45 - DRYING RACKS (2 REQ'D)
Quantum Model M2448W46DR Drying Racks

ITEM 46 - SHELVING, WALL MOUNTED (1 REQ'D)

AERO Manufacturing Model 2W-1884 Dimensions: 1.5(h) x 84(w) x 18(d)
Aerospec™ Shelf, wall-mounted, 84"W x 18"D x 12-1/2"H, 14/304 stainless steel construction, 1-1/2" lip on sides & rear, 3/4" radius rolled front edge, stainless steel brackets, Aero Hemmed Safety Edge™, NSF, KD

ITEM 47 - THREE (3) COMPARTMENT SINK (1 REQ'D)

AERO Manufacturing Model 2F3-2418-18LR Dimensions: 42.5(h) x 93(w) x 30(d)
Aerospec™ Sink, three compartment, 93"W x 30"D x 42-1/2"H, 14/304 stainless steel construction, (3) 18"W x 24" front-to-back x 14" deep fabricated compartments, 18" drainboards on left & right, 10"H backsplash, 8" OC splash mount faucet holes, raised rolled edges on front & sides, fully welded stainless steel gussets, 16/304 stainless steel legs with front & side cross bracing, adjustable stainless steel feet, Aero Hemmed Safety Edge™, KD, NSF

PRE-RINSE FAUCET ASSEMBLY, WITH ADD ON FAUCET (1 REQ'D)

T&S Brass Model B-0133-01

EasyInstall Pre-Rinse Unit, mixing faucet, 8" wall mount, 14" add-on 063X swing nozzle, 18" riser, overhead spring, lever handles, 56" flex hose, Eterna cartridges, spray valve (B-0107), 9" wall support (B-0109-02), 1/2" male NPT, EPAct2005 Compliant

WALL / SPLASH MOUNT FAUCET (1 REQ'D)

T&S Brass Model B-0291

Kettle & Pot Sink Faucet, Big-Flo, wall mounted 8" centers, 3/4" IPS model LL street EL inlets with locknuts, 18" swing nozzle, 175°F four arm handles, 1-1/4" dia. holes required in backsplash

ITEM 48 - DRYING RACKS (2 REQ'D)
Quantum Model M2448W46DR Drying Racks

ITEM 49 - CART, BUSSING UTILITY TRANSPORT, PLASTIC (4 REQ'D)

Quantum Model PFTC4026-33-3 Dimensions: 32.5(h) x 40(w) x 26(d)
Utility Cart, (3) shelves, 40"W x 26"D x 32-1/2"H, flat top, 550 lb. capacity, push handle, (4) 5" casters: (2) rigid & (2) swivel, polymer, gray, shipped KD

ITEM 50 - SPARE NUMBER

ITEM 51 - WORK TABLE, STAINLESS STEEL TOP (2 REQ'D)

AERO Manufacturing Model 2TSB-3048 Dimensions: 39(h) x 48(w) x 30(d)
Premium Work Table, 48"W x 30"D x 39"H, 14/304 stainless steel top reinforced with (3) galvanized steel box channels, 4"H backsplash, sound deadened underside, 18/430 stainless steel adjustable undershelf, galvanized steel gussets, 16/304 stainless steel legs with adjustable white metal feet, Aero Hemmed Safety Edge™, shipped KD, NSF

2 ea Model T-118 Delux™ drawers, stainless steel face & pan, 15" x 20", roller bearing slides
(drawer pan is not removable)

ITEM 52 - REACH-IN REFRIGERATOR (1 REQ'D)

Delfield Model DSLR2-G Dimensions: 83.85(h) x 51.89(w) x 33.42(d)

DSL Refrigerator, Reach-In, two-section, 44.57 cubic feet capacity, top-mounted self-contained refrigeration system, (2) full-height hinged glass doors (locking), (6) adjustable wire shelves, 4.3" easyTouch® screen temperature display/control with remote monitoring, LED interior lighting, pilaster with shelf clips, stainless steel exterior front, sides & interior, (4) 6" adjustable stainless steel legs, R290 Hydrocarbon refrigerant, 1/3 HP, 115v/60/1-ph, 6.5 amps, NEMA 5-15P, UL, UL Sanitation

6-ea Additional shelves, three per section

ITEM 53 - REACH-IN HEATED CABINET (1 REQ'D)

Delfield Model DSLH2-G Dimensions: 83.85(h) x 51.89(w) x 33.42(d)

DSL Heated Cabinet, Reach-In, two-section, 46.5 cubic feet capacity, (2) full-height hinged glass doors (locking), (6) adjustable wire shelves, 4.3" easyTouch® screen temperature display/control with remote monitoring, stainless steel exterior front, sides & interior, (4) 6" adjustable stainless steel legs, 208-240v/60/1-ph, 13 amps, NEMA 6-20P, UL, UL Sanitation

6-ea Additional shelves, three per section

ITEM 54 - HAND SINK (1 REQ'D)

BY OWNER, NO BID

*****END SPECIFICATIONS*****

JACKSON PUBLIC SCHOOL DISTRICT

JOBSITE VISITATION FORM

This form is to certify that prospective bidders on project of installation of specified new equipment, including all related work, have visited the jobsite, **and are aware of all existing conditions.**

Owner will provide electrical and disconnects to within six feet of required new equipment.

Successful bidder to supply and wire all new equipment.

Successful bidder shall render "turn key" installation.

Prospective bidders should call Mr. Marc Rowe or Mr. Alvin Edney at 601-960-5328 to make an appointment to visit the jobsite.

POWELL MIDDLE SCHOOL

DATE JOBSITE VISITED: _____

JPSD FACILITIES REPRESENTATIVE

PROSPECTIVE BIDDER'S REPRESENTATIVE

This signed form ***must*** be included in submitted bid package.

End of Addendum #1

The vendor shall acknowledge Addendum No. 1 on the original "Proposal Form".

All other sections of this proposal shall remain the same.



Michele Mays

Purchasing Coordinator | Office of Finance and Operations

662 S. President Street | Jackson | Mississippi 39201

Post Office Box 2338 | Jackson | MS 39225

Office: (601) 973-8582 | Fax: (601) 960-8967

mmays@jackson.k12.ms.us | Web: www.jackson.k12.ms.us

Facebook: <https://www.facebook.com/JacksonPublicSchools> |

YouTube: <http://www.youtube.com/jpsity>