799273
01/25/08

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: ACETONE
PRODUCT CODE: 799273

HMIS CODES: H F R P
2 3 0 H

========== SECTION I - MANUFACTURER IDENTIFICATION ==========

MANUFACTURER'S NAME: RODDA PAINT COMPANY
ADDRESS : 6123 N MARINE DRIVE
PORTLAND, OR 97203

EMERGENCY PHONE : (800) 424-9300
INFORMATION PHONE : (503) 521-4300

DATE PRINTED : 01/25/08
NAME OF PREPARER : Rick Barnard

==== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MM HG @ TEMP	WEIGHT PERCENT
ACETONE	67-64-1	181.7 20C	90 - 100

OSHA TWA- 1000ppm 2400mg/m3
NIOSH TWA- 250ppm 590mg/m3
ACGIH TWA- 500ppm 1188mg/m3 STEL- 750ppm 1782mg/m3

This product is believed not to contain toxic materials subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.
This product is believed not to contain materials listed as carcinogens by NTP, IARC, or OSHA.
The above chemical(s) meet the criteria as defined under 29 CFR 1910 for toxic a hazardous substances.
This product may contain small amounts of materials known to the State of California to cause cancer and reproductive harm.
This product is believed not to contain materials listed in Section 112(b) of the Clean Air Act.

======== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ========

BOILING RANGE: 133F
SPECIFIC GRAVITY (H2O=1): 0.79
VAPOR DENSITY: Heavier than air.
EVAPORATION RATE: Faster than Butyl Acetate.
COATING V.O.C.: N/A
MATERIAL V.O.C.: 0.00 lb/gl
SOLUBILITY IN WATER: None
APPEARANCE AND ODOR: Clear liquid, strong solvent odor.

========= SECTION IV - FIRE AND EXPLOSION HAZARD DATA =========

FLASH POINT: -1.0F
METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6
UPPER: 12.8

EXTINGUISHING MEDIA: FOAM. Blanket fire with this extinguishing media.

SPECIAL FIREFIGHTING PROCEDURES:
For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode to protect against the hazardous effects of normal products of combustion o xygen deficiency.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting