

Blending Quiz

Name _____ Date _____ Session _____

1.) Under certain automotive OEM repair warranties in no clean “break” or body line exists for stopping the application of clear coat, the clear should be extended to the nearest panel edge.

- A. True
- B. False

2.) When preparing an adjacent panel for a basecoat blend, how much of the adjacent panel should be sanded?

- C. Only the area where color is to be applied
- D. 4”-6” into the adjacent panel
- E. 12”-15” into the adjacent panel
- F. The entire adjacent panel

3.) Making a “let down” panel is recommended to achieve a correct color match for any tri-coat repair.

- a. True
- b. False

4.) What is the proper overlap when spraying?

- c. 20-30%
- d. 40-50%
- e. 50-60%
- f. 60-70%

5.) What is the proper gun distance when spraying?

6.) What is the mix ratio for basecoat D.B.C.?

7.) How do you sand a blend panel to get ready to spray?

8.) How long do you wait after applying basecoat before you clear?

9.) What type of respirator should be used while spraying isocynate containing paint products?

- f. Fresh air supplied respirator
- g. Single cartridge charcoal
- h. Dual cartridge charcoal
- i. Paper fiber dust particle

10.) Technician A says that when blending a fender you put color over the whole fender. Technician B says that you should put color on only part of the fender. Who is right?

- j. Technician A
- k. Technician B
- l. Both A and B
- m. Neither A or B