



Residential Roofing Application- Supplemental Information

Proposed Roof Covering Material(s) & areas:

Asphalt shingles Sq. Ft.

Wood Shingle... Sq. Ft.

Membrane / Flat Roof * Sq. Ft.

Metal* / Other* Sq. Ft.

*Manufacturer’s installation instructions are required to be submitted with your permit application

Reroofing Project Type:

- ☐ **Roof Recover-** The installation of a new [roof covering](#) over an existing [roof covering](#) shall be done in accordance with the requirements of the [IRC Chapter 9](#).
- ☐ **Roof Replacement-** [Roof replacement](#) shall include the removal of existing layers of [roof coverings](#) down to the [roof deck](#) and shall be done in accordance with the requirements of [IRC Chapter 9](#).

The permit applicant is required to review and sign this document attesting the proposed work will comply with the requirements of the Connecticut State Building Code, including but not limited to following:

- Roofing covering materials and their method of installation shall be done in compliance with the requirements of the Connecticut State Building Code. There installation shall not cause an existing structure to become less compliant with the provisions of this code than the [existing building](#) or structure was prior to the [addition](#), [alteration](#) or [repair](#) in accordance with [R102.7.1 Additions, Alterations or Repairs](#) .
- [Roof decks](#) shall be covered with [approved roof coverings](#) secured to the building or structure in accordance with the provisions of this chapter. [Roof assemblies](#) shall be designed and installed in accordance with this code and the [approved](#) manufacturer's instructions such that the [roof assembly](#) shall serve to protect the building or structure in accordance with [R903.1 General](#) and [R905.1 Roof Covering Application](#) .
- Flashings shall be installed in a manner that prevents moisture from entering the wall and roof through joints in copings, through moisture permeable materials and at intersections with parapet [walls](#) and other penetrations through the roof plane. Flashings shall be installed at wall and roof intersections, wherever there is a change in roof [slope](#) or direction and around roof openings. **A flashing shall be installed to divert the water away from where the eave of a sloped roof intersects a vertical sidewall** in accordance with [R903.2 Flashing](#) and [R905.2.8 Flashing](#).
- For other than roof recovers, **Ice Barriers, Underlayment which includes taping of decking seams except where roofs are sheathed with lumber having a nominal width of less than 3 feet** in accordance with [R905.1.2 Ice Barriers](#) and [R905.1.1 Underlayment](#).
- Roof ventilation shall not be diminished so as to cause an existing structure to become less compliant with the provisions of this code **and** shall be installed in accordance with all [approved](#) manufacturer's instructions in accordance with [R102.7.1 Additions, Alterations or Repairs](#), [R903.1 General](#) and [R905.1 Roof Covering Application](#) . **Be advised that the installation of ridge vents per the manufacturer’s installation instructions, requires intake vents at the lower side of the roof (i.e. soffits, fascia, or undereave intake vent).**

I certify by signing this document that the information provided is accurate and installation shall be / has been performed in accordance with both the manufacturer’s installation guidelines and the requirements of the Connecticut State Building Code. It shall be the duty of the permit holder / property owner to schedule a final inspection upon completion.

Job Address: _____

Applicant: _____ Signature: _____ Date: _____

Company name: _____ HIC Registration #: _____